





THERMAL PRINTERS

Battery-Operated Micro Thermal Printer

Part Number		FTP-623MCL353, FTP-623DCL001	FTP-623MCL354, FTP-623DCL001
Figure			
Dot structure [dots/line]		384	384
Horizontal dot pitch [dots/mm (dpi)]		8 (203)	8 (203)
Printing speed [dot lines/s]		480	480
Dimensions W x D x H [mm (in.)]	Mechanism	73 x 49 x 20 (2.874 x 1.929 x 0.787)	73 x 49 x 20 (2.874 x 1.929 x 0.787)
	Interface board	108 x 91 x 18 (4.252 x 3.583 x 0.709)	108 x 91 x 18 (4.252 x 3.583 x 0.709)
Weight [g]	Mechanism	80	80
	Interface board	60	60
Power supply voltage [V]		4.2 – 8.5	4.2 – 8.5
Paper width [mm (in.)]		58 (2.283)	58 (2.283)
Remarks		Battery operated is possible. Front paper path. 1 ply, 2 ply. UL recognized.	Battery operated is possible. Rear paper path. Labels or 1 ply, 2 ply. UL recognized.

Part Number		FTP-633MCL353, FTP-623DCL001	FTP-633MCL354, FTP-623DCL001
Figure			
Dot structure [dots/line]		512	512
Horizontal dot pitch [dots/mm (dpi)]		8 (203)	8 (203)
Printing speed [dot lines/s]		480	480
Dimensions W x D x H [mm (in.)]	Mechanism	85 x 49 x 20 (3.346 x 1.929 x 0.787)	85 x 49 x 20 (3.346 x 1.929 x 0.787)
	Interface board	108 x 91 x 18 (4.252 x 3.583 x 0.709)	108 x 91 x 18 (4.252 x 3.583 x 0.709)
Weight [g]	Mechanism	88	88
	Interface board	60	60
Power supply voltage [V]		4.2 – 8.5	4.2 – 8.5
Paper width [mm (in.)]		70 (2.756)	70 (2.756)
Remarks		Battery operated is possible. Front paper path. 1 ply, 2 ply. UL recognized.	Battery operated is possible. Rear paper path. Label paper or 1 ply, 2 ply. UL recognized.