



CG/CE46

0.65 Micron High Performance, Low Power CMOS Gate Arrays

Description

The Fujitsu CG46 is a high performance, 0.65 μm drawn channel length, digital CMOS gate array family. The CE46 is a 0.65 μm drawn channel length, digital CMOS embedded gate array product family. The CE46 offers full support of diffused high speed RAMs, ROMs and embedded megacells. The CE46 series offers density and performance approaching that achievable with standard cell solutions but with the time to market advantage of traditional gate arrays. Both product families feature channelless (Sea-of-Gates) architecture with two layer metal.

A 5.0 volt product, the CG/CE46 features low power and high pin to gate count ratio. These product families are optimized for cost sensitive, high volume applications such as personal computers, workstations and communication systems. A wide variety of high performance and cost effective packages are available including PQFP, CQFP, TQFP, BGA and MCM's. Pin counts of up to 352 are available.

Features

- 0.65 μm drawn channel length
- 5V \pm 5% or 3.3V \pm 0.3V supply voltage
- Channelless, Sea-of-gates Architecture
- Internal gate delay of 300ps, F/O = 2, L = 1mm @ 5.0V
- CE46 RAM compiler supports Single/Dual Port RAM
- Supports JTAG boundary scan, full and partial scan
- PCI buffer available
- Clock net for optimized on-chip clock skew control
- High drive capability: 3.2, 8, or 12 mA in a single I/O slot (24 mA available with double I/O)
- Optimized for 5V \pm 5%, capable of 3.3V \pm 0.3V
- Maximum toggle frequency is 175 MHz, Supports system clock frequencies in excess to 70 MHz
- CE46 Supports mixed 5V and 3.3V I/Os

- Supports all major third party design tools including Cadence, Mentor, Synopsys and Sunrise.
- Higher performance and 30% lower power than 0.8 μm technology
- High pad to gate ratio

CE46 Embedded Gate Array Product Summary

Device Name	Gross Gates	Usable Gates	Max. Pads	Metal Wiring
CE46F10	53,636	28,427	208	2
CE46F20	71,004	36,922	240	2
CE46F30	83,028	42,344	256	2
CE46F40	90,804	45,402	272	2
CE46F50	101,616	49,791	288	2
CE46F60	113,036	54,257	304	2
CE46F70	137,700	64,719	336	2
CE46F80	154,260	70,959	352	2
CE46F90	198,084	89,137	400	2

CG46 Gate Array Product Summary

Device Name	Gross Gates	Usable Gates	Max. Pads	Metal Wiring
CG46533	53,636	28,427	208	2
CG46713	71,004	36,922	240	2
CG46833	83,028	42,344	256	2
CG46104	101,616	49,791	288	2
CG46134	137,700	64,719	336	2
CG46194	198,084	89,137	400	2

DC CHARACTERISTICS

Measuring conditions: $V_{DD} = 5V \pm 5\%$, $V_{SS} = 0V$, $T_a = 70^\circ C$

Parameter	Symbol	Test Conditions		Requirements			Unit
				Min.	Typ.	Max.	
Supply Voltage	I _{DDS}	Standby mode ¹				0.2 ²	mA
High-level input voltage	V _{IH}	CMOS level	Normal cell	V _{DD} ×0.7		V _{DD}	V
			Schmitt trigger	V _{DD} ×0.8		V _{DD}	
		TTL level	Normal cell	2.2		V _{DD}	
			Schmitt trigger	2.4		V _{DD}	
Low-level input voltage	V _{IL}	CMOS level	Normal cell	V _{SS}		V _{DD} ×0.3	V
			Schmitt trigger	V _{SS}		0.6	
		TTL level	Normal cell	V _{SS}		0.8	
			Schmitt trigger	V _{SS}		0.6	
High-level output voltage	V _{OH}	I _{OH} =−2 mA ³		4.0		V _{DD}	V
		I _{OH} =−4 mA					
		I _{OH} =−8 mA					
Low-level output voltage	V _{OL}	I _{OL} =3.2 mA		V _{SS}		0.4	V
		I _{OL} =8 mA					V
		I _{OL} =12 mA					V
		I _{OL} =24 mA				0.5	V
Input leakage current (Three-state pin input) ⁴	I _{LI}	V _I =0 to V _{DD}		−5		5	μA
	I _{LZ}			−5		5	
Input pull-up/pull-down resistors ⁵	R _P	Pull-up V _I = V _{SS}		25	50	100	kΩ
	R _N	Pull-down = V _I = V _{DD}					

NOTES:

- $V_{IH} = V_{DD}$ and $V_{IL} = V_{SS}$, the memory is in the standby mode
- If an input buffer with pull-up/pull-down resistor is used, the supply current may not be assured depending on the circuit configuration.
- The high level output voltage of the $I_{OL}=8\text{mA}$ type output buffer is identical to that ($I_{OH} = 2\text{mA}$) of the $I_{OL} = 3.2\text{mA}$ type output buffer.
- If an input buffer with pull-up/pull-down resistor is used, the input leakage current may exceed the above value.
- Either a buffer without a resistor or with a pull-up/pull-down resistor can be selected from the input and bidirectional buffers.

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Requirements				Unit
Supply Voltage	V _{DD}	V _{SS} ¹ −0.5 to +6.0				V
Input voltage	V _I	V _{SS} ¹ −0.5 to V _{DD} +0.5				V
Output voltage	V _O	V _{SS} ¹ −0.5 to V _{DD} +0.5				°C
Operating temperature	T _a	Plastic −40 to +85				°C
		Ceramic −55 to +125				
Storage temperature	T _{ST}	Plastic −40 to +85				°C
		Ceramic −65 to +150				
		Type/Condition		V _O = V _{DD}	V _O = 0V	
Output current	I _{O3}	Normal Type	O _{IL} =3.2 mA	+40	−40	mA
		Power-type	O _{IL} =8 mA	+80	−40	
		High-power type	O _{IL} =12 mA	+120	−60	
		Double high-power type	O _{IL} =24 mA	+180	−90	
Overshoot	—	V _{SS} ¹ +1.0 V to max. ²				
Undershoot	—	V _{SS} ¹ +1.0 V to max. ²				

NOTES:

1. $V_{SS} = 0V$
2. For 50 ns max.
3. For one second per pin

RECOMMENDED OPERATING CONDITIONS (5.0V)

Parameter		Symbol	Requirements			Unit
			Min.	Typ.	Max.	
Supply Voltage		V_{DD}	4.75	5.0	5.25	V
High-level input voltage	CMOS level	V_{IH}	$V_{DD} \times 0.7$	—	V_{DD}	V
	TTL level		2.2	—	V_{DD}	
Low-level input voltage	CMOS level	V_{IL}	V_{SS}^1	—	$V_{DD} \times 0.3$	V
	TTL level		V_{SS}^1		0.8	
Operating temperature		T_a	0	25	70	°C

NOTES:

1. $V_{SS} = 0V$

RECOMMENDED OPERATING CONDITIONS (3.3 V)

Parameter		Symbol	Requirements			Unit
			Min.	Typ.	Max.	
Supply Voltage		V_{DD}	3.0	3.3	3.6	V
Operating temperature		T_a	0	—	70	°C

INPUT/OUTPUT PIN CAPACITANCE

Parameter		Symbol	Requirements	Unit
Input pin		C_{IN}	Max. 16	pF
Output pin	$I_{OL} = 3.2 \text{ mA}, 8 \text{ mA}, 12 \text{ mA type}$	C_{OUT}	Max. 16	pF
	$I_{OL} = 24 \text{ mA type}$		Max. 18	
I/O pin	$I_{OL} = 3.2 \text{ mA}, 8 \text{ mA}, 12 \text{ mA type}$	C_{VO}	Max. 16	pF
	$I_{OL} = 24 \text{ mA type}$		Max. 18	

Measuring conditions: $T_a = 25^\circ\text{C}$
 $V_{DD} = V_I = OV$, $f = 1 \text{ MHz}$

PACKAGE AVAILABILITY

Package	Array								
CE46 –	F10	F20	F30	F40	F50	F60	F70	F80	F90
CG46 –	533	713	833	—	104	—	134	—	194
QFP100	P	P	P	P	P				
QFP160	P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C
SQFP80	P	P	P						
SQFP100	P	P	P	P					
SQFP144	P	P	P	P	P	P	P	P	
SQFP176	P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C	
SQFP208	P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C
SQFP240		P,C	P,C	P,C	P,C	P,C	P,C	P,C	P,C
SQFP256							P,C	P,C	P,C
TQFP100	P	P	P	P	P	P	P	P	
BGA256(B)			P	P	P	P	P	P	
BGA352(B)								P	P
BGA352(C)						P	P	P	P

NOTES: P: Plastic
 C: Cerquad

DC CHARACTERISTICS at 3.3V Operating Conditions

Measuring conditions: $V_{DD} = 3.3V \pm 0.3V$, $V_{SS} = 0V$, $T_a = 0^\circ$ to $70^\circ C$

Parameter	Symbol	Test Conditions	Requirements			Unit
			Min.	Typ.	Max.	
Supply Current	I_{DDs}	Standby mode *1	—	—	20^2	μA
High-level input voltage	V_{IH}	CMOS level	Normal cell * 3	$V_{DD} \times 0.7$	—	V_{DD}
			Schmitt trigger * 4	$V_{DD} \times 0.8$	—	V_{DD}
Low-level input voltage	V_{IL}	CMOS level	Normal cell * 3	V_{SS}	—	V_{DD}
			Schmitt trigger * 4	V_{SS}	—	V_{DD}
High-level output voltage	V_{OH}	$I_{OH} = -1\text{ mA}^* 5$	$V_{DD} - 0.3$	—	V_{DD}	V
		$I_{OH} = -1\text{ mA}^* 6$				
		$I_{OH} = -2\text{ mA}^* 7$				
		$I_{OH} = -4\text{ mA}^* 8$				
Low-level output voltage	V_{OL}	$I_{OL} = 2\text{ mA}^* 5$	V_{SS}	—	0.4	V
		$I_{OL} = 4\text{ mA}^* 6$				V
		$I_{OL} = 6\text{ mA}^* 7$				V
		$I_{OL} = 12\text{ mA}^* 8$				V
Input pull-up/pull-down resistors *4	R_P	Pull-up $V_I = V_{SS}$	40	150	350	$k\Omega$
	R_N	Pull-down $V_I = V_{DD}$	40	100	200	

NOTES:

*1. $V_{IH} = V_{DD}$ and $V_{IL} = V_{SS}$, the memory is in the standby mode.

*2. If an input buffer with pull-up/pull-down resistor is used, the supply current may not be assured depending on the circuit configuration.

*3. Equivalent to CMOS Input terminal.

*4. Equivalent to CMOS Schmitt Input terminal.

*5. Equivalent to $I_{OL} = 3.2\text{mA}$ output (at $V_{DD} = 5V$).

*6. Equivalent to $I_{OL} = 8\text{mA}$ output (at $V_{DD} = 5V$).

*7. Equivalent to $I_{OL} = 12\text{mA}$ output (at $V_{DD} = 5V$).

*8. Equivalent to $I_{OL} = 24\text{mA}$ output (at $V_{DD} = 5V$).

All Rights Reserved.

Circuit diagrams utilizing Fujitsu products are included as a means of illustrating typical semiconductor applications. Complete information sufficient for construction purposes is not necessarily given.

The information contained in this document has been carefully checked and is believed to be reliable. However, Fujitsu assumes no responsibility for inaccuracies.

The information contained in this document does not convey any license under the copyrights, patent rights or trademarks claimed and owed by Fujitsu.

Fujitsu reserves the right to change products or specifications without notice.

This document contains information on a new product. Specification and information herein are subject to change without notice.

No part of this publication may be copied or reproduced in any form or by any means, or transferred to any third party without prior written consent of Fujitsu.

This device contains circuitry to protect the inputs against damage due to high static voltages or electric fields. However, it is advised that normal precautions be taken to avoid application of any voltage higher than maximum rated voltages to this high impedance circuit.

FUJITSU LIMITED

For further information please contact:

Japan

FUJITSU LIMITED
Electronic Devices International
Sales and Engineering Support Division
1015, Kamikodanaka Nakahara-ku,
Kawasaki 211, Japan
Tel: (044) 754-3753
FAX: (044) 754-3332

North and South America

FUJITSU MICROELECTRONICS, INC.
Logic Products Division
3545 North First Street
San Jose, CA 95134-1804, USA
Tel: 408-922-9000
FAX: 408-432-9044

Europe

FUJITSU MIKROELEKTRONIK GmbH
Am Siebenstein 6-10,
6072 Dreieich-Buchschlag,
Germany
Tel: (06103) 690-0
Telex: 411963
FAX: (06103) 690-122

Asia

FUJITSU MICROELECTRONICS ASIA PTE LIMITED
51 Bras Basah Road,
Plaza By The Park,
#06-04 to #06-07
Singapore 0719
Tel: 336-1600
Telex: 55573
FAX: 336-1609

Sales Offices

California

2880 Lakeside Drive, Suite 250
Santa Clara, CA 95054
(408) 982-1800

Century Center
2603 Main Street, #510
Irvine, CA 92714
(714) 724-8777
©FUJITSU LIMITED 1994

Colorado

12000 North Washington Street, #370
Thornton, CO 80241
(303) 254-9901

Georgia

3500 Parkway Lane, #210
Norcross, GA 30092
(404) 449-8539

Illinois

One Pierce Place, #1245
Itasca, IL 60143-2662
(708) 250-8580

Massachusetts

1000 Winter Street, #2500
Waltham, MA 02154
(617) 487-0029

Minnesota

3800 West 80th Street, #430
Bloomington, MN 55431-4419
(612) 893-5570

New York

898 Veterans Memorial Highway
Building 2, Suite 310
Hauppauge, NY 11788
(516) 582-8700

Oregon

15220 N.W. Greenbrier Parkway, #360
Beaverton, OR 97006
(503) 690-1909

Texas

14785 Preston Rd., #274
Dallas, TX 75240
(214) 233-9394

20515 SH 249, Suite 485
Houston, TX 77070
(713) 379-3030

ASIC-DS-20084-11/95