

Introduction

Lattice Semiconductor's two high-drive "VP" series devices, the GAL16VP8 and GAL20VP8, are based upon the industry standard GAL16V8 and GAL20V8 architectures, adding programmable output configuration for higher drive capability. The "VP" series has programmable output buffers that can be configured to either open-drain or totem-pole outputs. Their output buffers can be independently programmed by setting the appropriate control bits in the architectural array. Additionally, their input buffers contain Schmitt trigger inputs for greater noise immunity and active pull-up resistors on all inputs and I/Os.

The GAL "VP" high drive adds value to the popular GAL16V8 and GAL20V8 product line. The advantages of the "VP" series include:

- **Higher Output Drive Current**
Low-Level Output Current
-I_{ol} = 64 mA vs. 24mA
High Level Output Current
-I_{oh} = -32 mA vs. -3.2mA
- **Schmitt Trigger Input Buffers** – Schmitt trigger input buffers with 200mV of hysteresis between positive and negative input transitions. The Schmitt trigger inputs offer improved noise immunity during switching transitions, especially on the clock input. Hysteresis prevents double clocking when non-monotonic rise and fall times are present.
- **Programmable Output Buffers** – Two independent types of output buffers can be programmed for each OLMC (Output Logic Macro Cell). A combination of open-drain and totem-pole outputs can be used. For example, four totem-pole outputs for interfacing I/O functions and four open-drain outputs for bus interfacing with pull-up resistors. Any mixed combination of output buffers can be used since each output macrocell contains a dedicated fuse to assign the configuration of the output buffer.
 - Totem-pole output for standard high-drive interfacing to external logic systems with heavy capacitive loading. This configuration has V_{ol} and V_{oh} levels that are standard TTL-level data sheet values, V_{ol}=0.5 V max., V_{oh}=2.4 V min.

- Open-drain output for bus interfacing and arbitration circuits. Low logic level V_{ol} has the standard TTL-level data sheet value, V_{ol} = .5 V max. High logic level V_{oh} is set from external pull-up resistors and is a function of the external loading.

These advantages allow the designer greater flexibility when interfacing to bus and memory logic.

The series offers 64mA I_{ol} output drive for driving heavy capacitive loads associated with memory elements, such as those on data buses and back plane type systems.

One of the advantages of using high drive programmable logic for interfacing is that it eliminates the need for 74XX240 type drivers that are used in conjunction with decoding logic as a multiple device solution. In many microprocessor applications, decoding logic is used to decode address space for I/O or memory, then these signals are fed to bus driver components, such as the 74XX240 series, to drive heavy loads on busses or back planes.

Using the Lattice "VP" high drive series allows the designer to accomplish this with a single chip solution. The GAL20VP8 or GAL16VP8 devices are used to decode the address space needed and the appropriate output configuration is chosen to supply the drive capability needed to interface with the system.

Programming the 16/20VP8

Development systems such as ABEL and Synario from Data I/O or CUPL from Logical Devices support both the GAL16VP8 and the GAL20VP8 with compiler support. Logic equations and syntax remain the same as with standard GAL16V8 and GAL20V8 devices. There are three possible modes that are used for different OLMC configurations along with the output drive configuration mode: Registered, Complex and Simple. Each of these modes is set according to the logic functions implemented in the source or design file. The only additional information needed in the source file is the configuration of the output buffers. The output buffer configuration is set with a dedicated architecture fuse for each OLMC, architecture fuse AC2.

- AC2 = 1 Defines totem-pole output.
- AC2 = 0 Defines open-drain output.

The GAL16VP8 and GAL20VP8

Each OLMC has an associated set of architecture fuses; the fuses SYN, AC1, AC0 will be set by the compiler software for the appropriate OLMC mode (Registered, Complex or Simple).

These fuses must be set using the compiler software. The following statements for ABEL and CUPL compilers show how to implement the programmable output buffers.

Each output also contains an AC2 fuse. The following is a list of AC2 fuse locations:

GAL16VP8	GAL20VP8
Output 19 (AC2 = 2194)	Output 22 (AC2 = 2706)
Output 18 (AC2 = 2195)	Output 21 (AC2 = 2707)
Output 17 (AC2 = 2196)	Output 20 (AC2 = 2708)
Output 16 (AC2 = 2197)	Output 19 (AC2 = 2709)
Output 14 (AC2 = 2198)	Output 17 (AC2 = 2710)
Output 13 (AC2 = 2199)	Output 16 (AC2 = 2711)
Output 12 (AC2 = 2200)	Output 15 (AC2 = 2712)
Output 11 (AC2 = 2201)	Output 14 (AC2 = 2713)

Example 1. ABEL Example for the GAL16VP8-15LP (Setting the Output Driver Fuses)

```
Module TEST1
TITLE 'This is an example for the GAL16VP8-15LP that sets the output driver fuses';

TEST1 Device 'P16VP8';
" Note: The GAL16VP8-15LP is a center-pin device. Ground = Pin 15 , Vcc = Pin 5
" Pin Assignments

IN1, IN2, IN3, IN4, IN6, IN7, IN8, IN9      Pin 1,2,3,4,6,7,8,9;
OUT11, OUT12, OUT13, OUT14                 Pin 11,12,13,14;
OUT16, OUT17, OUT18, OUT19                 Pin 16,17,18,19;

" Use the FUSES statement to individually set AC2 fuses for output configurations.

FUSES [2194..2197] = [1,1,1,1];           "Set output pins 19,18,17,16 to totem-pole
FUSES [2198..2201] = [0,0,0,0];           "Set output pins 14,13,12,11 to open-drain

EQUATIONS

OUT19 = IN1 & !IN2 & !IN4;               " Pin 19 configured as totem-pole.
OUT18 = !IN1 & !IN2 & !IN3;             " Pin 18 configured as totem-pole.
OUT17 = IN4 & IN6 & !IN8;               " Pin 17 configured as totem-pole.
OUT16 = IN6 & IN7 & !IN8;               " Pin 16 configured as totem-pole.

OUT14 = !IN3 & !IN8;                     " Pin 14 configured as open-drain.
OUT13 = IN2 & IN7;                       " Pin 13 configured as open-drain.
OUT12 = !IN2 & !IN4 & IN7;             " Pin 12 configured as open-drain.
OUT11 = !IN4 & IN6 & IN8;               " Pin 11 configured as open-drain.

end
```



Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.
Tel.: (503) 681-0118
FAX: (503) 681-3037
<http://www.latticesemi.com>

November 1996
