
Introduction to ispLSI[®] and pLSI[®] 3000 Family

Introduction

Lattice Semiconductor Corporation's (LSC) ispLSI and pLSI families are high-density and high-performance E²C MOS[®] programmable logic devices. They provide design engineers with a superior system solution for integrating high-speed logic on a single chip.

The ispLSI and pLSI 3000 Families are the third generation to combine the performance and ease of use of PLDs with the density and flexibility of FPGAs. This family is ideal for high density designs, where integration of complete logic subsystems into a single device is necessary.

The ispLSI family incorporates Lattice Semiconductor's innovative in-system programmable[™] (ISP[™]) technology. ISP technology allows for real-time programming, less expensive manufacturing and end-user feature reconfiguration.

E²C MOS technology features reprogrammability, the ability to program the device again and again to easily incorporate any design modifications. This same capability allows full parametric testability during manufacturing, which guarantees 100 percent programming and functional yield.

All necessary development tools are available from LSC and third-party vendors. Development tools offered range from LSC's low cost pDS[®] software, featuring Boolean entry in a graphical Windows[™] based environment, to the pDS+[™] family of Fitters that interface with third party development software packages. pDS+ systems support schematic capture, state machine, Boolean, and HDL Design entry. Designs can now be completed in hours as opposed to days or weeks.

ispLSI and pLSI 3000 Family

- ❑ 125 MHz System Performance
- ❑ 7.5 ns Pin-to-Pin Delay
- ❑ Deterministic Performance
- ❑ High Density (7,000 - 14,000 PLD Gates)
- ❑ 160-Pin to 304-Pin Package Options
- ❑ Flexible Easy-to-Use Architecture
- ❑ In-System Programmable (ispLSI)
- ❑ Boundary Scan (IEEE 1149.1)

ispLSI and pLSI Technology

- ❑ UltraMOS E²C MOS — the PLD Technology of Choice
- ❑ Electrically Erasable/Programmable/Reprogrammable
- ❑ 100% Tested During Manufacture
- ❑ 100% Programming Yield
- ❑ Fast Programming

ispLSI and pLSI Development Tools

- ❑ Low Cost, Fully Integrated pDS Design System for the PC
- ❑ HDL, VHDL, Boolean Equation, State Machine and Schematic Capture Entry
- ❑ pDS+ Support for Industry-Standard Third-Party Design Environments and Platforms
- ❑ Timing and Functional Simulation
- ❑ PC and Workstation Platforms

Introduction to ispLSI and pLSI 3000 Family

3000 Family Overview

The ispLSI and pLSI 3000 family of high-density devices address high-performance system logic designs implementing logic functions, ranging from registers, to counters, to multiplexers, to complex state machines.

With up to 14,000 PLD gates density, the ispLSI and pLSI 3000 Family provides a wide range of programmable

logic solutions which meet tomorrow's design requirements today.


Each device contains multiple Generic Logic Blocks (GLBs), which are designed to maximize system flexibility and performance. A balanced ratio of registers and I/O cells provides the optimum combination of internal logic and external connections. A global interconnect scheme ties everything together, enabling utilization of up to 80% of available logic. Table 1 describes the family attributes.

Table 1. ispLSI and pLSI 3000 Family Attributes

Family Member	3160	3192	3256/A	3256E	3320
Density (PLD Gates)	7,000	8,000	11,000	12,000	14,000
Speed: f_{max} (MHz)	125	100	70/90	100	70
Speed: t_{pd} (ns)	7.5	10	15/12	10	15
Macrocells	160	192	256	256	320
Registers	320	384	384	512	480
Inputs + I/O	162	194	130	258	160
Pin/Package	208-pin MQFP	240-pin MQFP	160-pin MQFP 167-pin CPGA	304-pin MQFP	208-pin MQFP

Table 1-0003B/3K

Figure 1. 3000 Family Packages



0288-160C/3K



Copyright © 1996 Lattice Semiconductor Corporation.

E²CMOS, GAL, ispGAL, ispLSI, pLSI, pDS, Silicon Forest, UltraMOS, Lattice Logo, L with Lattice Semiconductor Corp. and L (Stylized) are registered trademarks of Lattice Semiconductor Corporation (LSC). The LSC Logo, Generic Array Logic, In-System Programmability, In-System Programmable, ISP, ispATE, ispCODE, ispDOWNLOAD, ispGDS, ispStarter, ispSTREAM, ispTEST, ispTURBO, Latch-Lock, pDS+, RFT, Total ISP and Twin GLB are trademarks of Lattice Semiconductor Corporation. ISP is a service mark of Lattice Semiconductor Corporation. All brand names or product names mentioned are trademarks or registered trademarks of their respective holders.

Lattice Semiconductor Corporation (LSC) products are made under one or more of the following U.S. and international patents: 4,761,768 US, 4,766,569 US, 4,833,646 US, 4,852,044 US, 4,855,954 US, 4,879,688 US, 4,887,239 US, 4,896,296 US, 5,130,574 US, 5,138,198 US, 5,162,679 US, 5,191,243 US, 5,204,556 US, 5,231,315 US, 5,231,316 US, 5,237,218 US, 5,245,226 US, 5,251,169 US, 5,272,666 US, 5,281,906 US, 5,295,095 US, 5,329,179 US, 5,331,590 US, 5,336,951 US, 5,353,246 US, 5,357,156 US, 5,359,573 US, 5,394,033 US, 5,394,037 US, 5,404,055 US, 5,418,390 US, 5,493,205 US, 0194091 EP, 0196771B1 EP, 0267271 EP, 0196771 UK, 0194091 GB, 0196771 WG, P3686070.0-08 WG. LSC does not represent that products described herein are free from patent infringement or from any third-party right.

The specifications and information herein are subject to change without notice. Lattice Semiconductor Corporation (LSC) reserves the right to discontinue any product or service without notice and assumes no obligation to correct any errors contained herein or to advise any user of this document of any correction if such be made. LSC recommends its customers obtain the latest version of the relevant information to establish, before ordering, that the information being relied upon is current.

LSC warrants performance of its products to current and applicable specifications in accordance with LSC's standard warranty. Testing and other quality control procedures are performed to the extent LSC deems necessary. Specific testing of all parameters of each product is not necessarily performed, unless mandated by government requirements.

LSC assumes no liability for applications assistance, customer's product design, software performance, or infringements of patents or services arising from the use of the products and services described herein.

LSC products are not authorized for use in life-support applications, devices or systems. Inclusion of LSC products in such applications is prohibited.

LATTICE SEMICONDUCTOR CORPORATION

5555 Northeast Moore Court
Hillsboro, Oregon 97124 U.S.A.

Tel.: (503) 681-0118

FAX: (503) 681-3037

<http://www.latticesemi.com>

November 1996
