

PHILIPS

PHILIPS

Data handbook



Electronic
components
and materials

**Components and
materials**

Book C5

1986

Ferroxcube for power, audio/video and accelerators

Ferroxcube for power, audio/video and accelerators

C5

1986

FERROXCUBE FOR POWER, AUDIO/VIDEO AND ACCELERATORS

page

SECTION A

General properties of manganese-zinc and nickel-zinc ferrites

Introduction	3
Applications	4
Symbols, terms, definitions and basic formulae	5
Technical data	9
Characteristic curves	19

SECTION B

Yoke rings for use in deflection coils for picture tubes

Survey of types	53
Device data	54

SECTION C

E/EC/ETD/U/I cores

Introduction	
Core type and material grade selection guide	75
Survey of types	126
Device data	
E-cores	128
EC-cores	197
ETD-systems	241
U/I-cores	262

SECTION D

Materials and cores for magnetic recording

Material data	301
-------------------------	-----

continued overleaf

SECTION E

Small cores and chokes

Iron powder materials	316
Toroids	317
Rods and tubes	319
Ferrite coil formers	325
Beads	327
Beads on wire	330
Multi-hole tubes	331
Screw cores	333
Wound six-hole beads	334

SECTION F

Materials for particle accelerators

Selection guide	339
---------------------------	-----

SECTION G

Ferroxcube for microwave applications	345
--	------------

Index of catalogue numbers to core types/mounting parts	351
--	------------

See Book C4 for Ferroxcube potcores, square cores and cross cores

DATA HANDBOOK SYSTEM

Our Data Handbook System comprises more than 60 books with specifications on electronic components, subassemblies and materials. It is made up of four series of handbooks:

ELECTRON TUBES	BLUE
SEMICONDUCTORS	RED
INTEGRATED CIRCUITS	PURPLE
COMPONENTS AND MATERIALS	GREEN

The contents of each series are listed on pages iv to viii.

The data handbooks contain all pertinent data available at the time of publication, and each is revised and reissued periodically.

When ratings or specifications differ from those published in the preceding edition they are indicated with arrows in the page margin. Where application information is given it is advisory and does not form part of the product specification.

Condensed data on the preferred products of Philips Electronic Components and Materials Division is given in our Preferred Type Range catalogue (issued annually).

Information on current Data Handbooks and on how to obtain a subscription for future issues is available from any of the Organizations listed on the back cover.

Product specialists are at your service and enquiries will be answered promptly.

ELECTRON TUBES (BLUE SERIES)

The blue series of data handbooks comprises:

- T1** Tubes for r.f. heating
- T2a** Transmitting tubes for communications, glass types
- T2b** Transmitting tubes for communications, ceramic types
- T3** Klystrons
- T4** Magnetrons for microwave heating
- T5** Cathode-ray tubes
Instrument tubes, monitor and display tubes, C.R. tubes for special applications
- T6** Geiger-Müller tubes
- T8** Colour display systems
Colour TV picture tubes, colour data graphic display tube assemblies, deflection units
- T9** Photo and electron multipliers
- T10** Plumbicon camera tubes and accessories
- T11** Microwave semiconductors and components
- T12** Vidicon and Newvicon camera tubes
- T13** Image intensifiers and infrared detectors
- T15** Dry reed switches
- T16** Monochrome tubes and deflection units
Black and white TV picture tubes, monochrome data graphic display tubes, deflection units

SEMICONDUCTORS (RED SERIES)

The red series of data handbooks comprises:

- S1 Diodes**
Small-signal silicon diodes, voltage regulator diodes ($< 1,5$ W), voltage reference diodes, tuner diodes, rectifier diodes
- S2a Power diodes**
- S2b Thyristors and triacs**
- S3 Small-signal transistors**
- S4a Low-frequency power transistors and hybrid modules**
- S4b High-voltage and switching power transistors**
- S5 Field-effect transistors**
- S6 R.F. power transistors and modules**
- S7 Surface mounted semiconductors**
- S8a Light-emitting diodes**
- S8b Devices for optoelectronics**
Optocouplers, photosensitive diodes and transistors, infrared light-emitting diodes and infrared sensitive devices, laser and fibre-optic components
- S9 Power MOS transistors**
- S10 Wideband transistors and wideband hybrid IC modules**
- S11 Microwave transistors**
- S12 Surface acoustic wave devices**
- S13 Semiconductor sensors**

INTEGRATED CIRCUITS (PURPLE SERIES)

The purple series of data handbooks comprises:

EXISTING SERIES

Superseded by:

IC1	Bipolar ICs for radio and audio equipment	IC01N
IC2	Bipolar ICs for video equipment	IC02Na and IC02Nb
IC3	ICs for digital systems in radio, audio and video equipment	IC01N, IC02Na and IC02Nb
IC4	Digital integrated circuits CMOS HE4000B family	
IC5	Digital integrated circuits – ECL ECL10 000 (GX family), ECL100 000 (HX family), dedicated designs	IC08N
IC6	Professional analogue integrated circuits	IC03N and Supplement to IC11N
IC7	Signetics bipolar memories	
IC8	Signetics analogue circuits	IC11N
IC9	Signetics TTL logic	IC09N and IC15N
IC10	Signetics Integrated Fuse Logic (IFL)	IC13N
IC11	Microprocessors, microcomputers and peripheral circuitry	IC14N

NEW SERIES

IC01N	Radio, audio and associated systems Bipolar, MOS	(published 1985)
IC02Na	Video and associated systems Bipolar, MOS Types MAB8031AH to TDA1524A	(published 1985)
IC02Nb	Video and associated systems Bipolar, MOS Types TDA2501 to TEA1002	(published 1985)
IC03N	Integrated circuits for telephony	(published 1985)
IC04N	HE4000B logic family CMOS	
IC05N	HE4000B logic family – incased ICs CMOS	(published 1984)
IC06N*	High-speed CMOS; PC74HC/HCT/HCU Logic family	(published 1986)
IC07N	High-speed CMOS; PC54/74HC/HCT/HCU – uncased ICs Logic family	
IC08N	ECL 10K and 100K logic families	(published 1984)
IC09N	TTL logic series	(published 1986)
IC10N	Memories MOS, TTL, ECL	
IC11N	Linear LSI	(published 1985)
Supplement to IC11N	Linear LSI	(published 1986)
IC12N	Semi-custom gate arrays & cell libraries ISL, ECL, CMOS	
IC13N	Semi-custom Integrated Fuse Logic	(published 1985)
IC14N	Microprocessors, microcontrollers & peripherals Bipolar, MOS	(published 1985)
IC15N	FAST TTL logic series	(published 1984)

Note

Books available in the new series are shown with their date of publication.

* Supersedes the IC06N 1985 edition and the Supplement to IC06N issued Autumn 1985.

COMPONENTS AND MATERIALS (GREEN SERIES)

The green series of data handbooks comprises:

- C1 Programmable controller modules**
PLC modules, PC20 modules
- C2 Television tuners, coaxial aerial input assemblies, surface acoustic wave filters**
- C3 Loudspeakers**
- C4 Ferroxcube potcores, square cores and cross cores**
- C5 Ferroxcube for power, audio/video and accelerators**
- C6 Synchronous motors and gearboxes**
- C7 Variable capacitors**
- C8 Variable mains transformers**
- C9 Piezoelectric quartz devices**
- C10 Connectors**
- C11 Varistors, thermistors and sensors**
- C12 Potentiometers, encoders and switches**
- C13 Fixed resistors**
- C14 Electrolytic and solid capacitors**
- C15 Ceramic capacitors**
- C16 Permanent magnet materials**
- C17 Stepping motors and associated electronics**
- C18 Direct current motors**
- C19 Piezoelectric ceramics**
- C20 Wire-wound components for TVs and monitors**
- C21* Assemblies for industrial use**
HNIL FZ/30 series, NORbits 60-, 61-, 90-series, input devices
- C22 Film capacitors**

* To be issued shortly.

SECTION A
GENERAL PROPERTIES OF MANGANESE-ZINC
AND NICKEL-ZINC FERRITES

INTRODUCTION

The Ferroxcube* range of manganese-zinc and nickel-zinc magnetically soft ferrites are intended for use as core material in coils and transformers operating over a wide range of frequencies. Ferroxcube is a ceramic material, manufactured from high-grade raw materials of controlled composition; the composition defines the electrical and mechanical properties.

Ferroxcube products are made by a sequence of ceramic techniques: mixing, pre-firing, milling, drying, shaping by pressing or extruding, sintering and machining. The finished products have a stable structure and high electrical resistivity. This electrical resistivity allows them to be used at high frequencies without the eddy current losses becoming prohibitively high. Ferroxcube is made in a wide range of permeabilities.

Ferroxcube cores are available in convenient shapes such as potcores, square cores, E and I-cores, EC-cores, X-cores, U-cores, toroids, aerial rods, yoke rings, screw cores, rods, tubes, beads, cores for magnetic recording and special materials for proton accelerators.

Potcores, square cores, E and I-cores and X-cores enable well-defined air gaps to be used without introducing appreciable stray fields. In this way the permeability of the material may be reduced to an effective value at which core and copper losses are matched. The dependence of the permeability on temperature and time is furthermore reduced to values that guarantee correct operation of the equipment.

This section contains comprehensive data on manganese-zinc and nickel-zinc ferrites and their various grades.

When ordering cores or associated parts, such as coil formers, adjusters and mounting parts, please quote the 12-digit catalogue number for the product in question given in the device data. Whenever this number ends with 'zero', the actual delivered goods may bear a different figure which is for logistic purposes only.

So if you order e.g. type 4322 021 30180 you may receive 4322 021 30182.

* Our trade name for magnetically soft ferrites.

APPLICATIONS

The various grades of Ferroxcube, the forms in which they are available and their principal applications are listed in the table below.

grade	core shapes and some preferred applications
● 2A2	yoke rings
● 3B	rods and tubes
● 3B7	potcores and square cores
● 3B8	potcores, square cores and cross cores
● 3C2	yoke rings
● 3C6	rods and tubes
● 3C8	E, EC, ETD, U and I cores, square cores
● 3C85	E, ETD, square cores
● 3D3	potcores, square cores, screw cores
● 3E1	E and I cores, toroids, potcores, square cores
● 3E2	H cores and toroids
● 3E4	potcores and square cores
● 3E5	square cores, toroids
● 3F3	ETD, square cores
● 3H1	potcores, square cores, cross cores
● 3H2	tubes, rods, toroids
● 3H3	potcores, square cores
● 4A4	frames for i.f. transformers, rods and tubes
● 4B1	frames for i.f. transformers, rods and tubes
● 4C6	potcores, square cores, toroids, frames for i.f. transformers, rods and tubes
● 4D1, 4D2	frames for i.f. transformers, screw cores, rods and tubes
● 4E1	rods and tubes
3H22, 3F1, 4E2, 4L2, 4M2, 8C11, 8C12	} special-purpose ferrites developed for resonant cavities for particle accelerators. A technical discussion is usually necessary to determine the correct material for this type of application.
8A5, 8C1, 8E1, 8E2, 8E21, 8X1	} cores and structural material for magnetic recording heads.

SYMBOLS, TERMS, DEFINITIONS AND BASIC FORMULAE

This list of symbols is based on the recommendations of IEC Publications 50, 125 and 401. Where symbols or formulae are used in connection with one application, material or core only, they are explained in the relevant section or data sheet.

symbol	units	definition
A_{min}	mm ²	nominal value of the minimum cross-sectional area.
A_e	mm ²	effective cross-sectional area.
$A_{e min}$	mm ²	minimum effective cross-sectional area.
A_L	nH	inductance factor = L/N^2 . Note: unless otherwise stated in this Handbook, A_L is the inductance factor in nH.
AT	A	ampere-turns.
B	T	flux density.
B_s	T	saturation flux density.
B_r	T	remanence: flux density remaining after magnetization to saturation and removal of the external field.
\hat{B}	T	peak flux density.
C_1	mm ⁻¹	core constant: $C_1 = \Sigma(l/A)$.
D	—	disaccommodation: the fractional change of permeability of a magnetic material measured at a constant temperature over a period of time after cessation of a disturbance $D = \frac{\mu_1 - \mu_2}{\mu_1}$
D_F	—	disaccommodation factor: obtained by dividing D by the first measured relative permeability (at t_1) and the logarithm of the ratio of the measuring times $D_F = \frac{\mu_1 - \mu_2}{\mu_1^2 \log(t_2/t_1)}$ Times t_1 and t_2 are given in the core data.
E_1	V	voltage at fundamental frequency.
E_3	V	voltage at third harmonic.
f_{Cu}	—	space (copper) factor: proportion of the winding cross section occupied by conductor.
f	Hz	frequency.
H	A/m	magnetic field strength.
H_c	A/m	coercivity: the value of the external field strength for which the flux density is zero after the material has been magnetized to saturation.

MnZn and NiZn ferrites

\hat{H}	A/m	peak magnetic field strength.
I_0	A	direct current.
l_e	mm	effective magnetic path length.
L	H	inductance.
N	—	number of turns.
P	kW/m ³	specific power loss in core material.
Q	—	inductance quality factor.
R_h	Ω	effective series resistance of an inductor due to hysteresis losses in the core.
T_c	$^{\circ}\text{C}$	Curie temperature: the temperature at which a ferromagnetic material becomes paramagnetic.
V_e	mm ³	effective volume of a core: the volume of an ideal toroid of the same material and having the same magnetic properties:
		$V_e = \frac{\sum (l/A)^3}{\sum (l/A^2)^2}$
α	—	turns factor: number of turns for an inductance of 1 mH.
α_F	K^{-1}	temperature factor of a core without air gap. The original definition in IEC 133

$$\alpha_F = \frac{\mu\theta - \mu_{\text{ref}}}{\mu^2_{\text{ref}}(\theta - \theta_{\text{ref}})}$$

$$= \frac{0,4\pi(A_{L\theta} - A_{L\text{ref}})}{A^2_{L\text{ref}} C_1 (\theta - \theta_{\text{ref}})}$$

where θ is the applied temperature, was superseded in 1976 by the definition in IEC 367-1:

$$\alpha_F = \frac{\mu\theta - \mu_{\text{ref}}}{\mu\theta\mu_{\text{ref}}(\theta - \theta_{\text{ref}})}$$

$$= \frac{0,4\pi(A_{L\theta} - A_{L\text{ref}})}{A_{L\theta}A_{L\text{ref}} C_1 (\theta - \theta_{\text{ref}})}$$

The second definition is required for new, close-tolerance products, and for products whose properties are guaranteed over a wide temperature range.

α_μ	K^{-1}	temperature coefficient of a core with an (ground) air gap. Where μ_e is the effective permeability of the core,
--------------	-----------------	--

$$\alpha_\mu \approx \alpha_F \mu_e$$

Alternatively,

$$\alpha_\mu \approx \alpha_F C_1 A_L / \mu_0$$

These approximations hold for fairly small changes in μ_e or A_L over the temperature range considered.

β_F	—	d.c. sensitivity constant for a core: $\beta_F = \frac{\mu_e - \mu_e \Delta}{\mu_e \mu_e \Delta}$ where $\mu_e \Delta$ is the relative incremental permeability of the core.
$\frac{\tan \delta}{\mu_i}$		eddy-current and residual loss constant at a given frequency, measured at $\widehat{B} \leq 0,1$ mT. The corresponding R/L value is given by $R/L = 2\pi f \mu \frac{\tan \delta}{\mu_i}$
Δ	mm	air-gap length.
η_B	T ⁻¹	hysteresis constant: $\eta_B = \frac{\Delta R_h}{\Delta \mu_e 2\pi f L}$ where $\Delta \widehat{B} = \widehat{B}_2 - \widehat{B}_1$ and $\Delta R_h = R_{\widehat{B}_2} - R_{\widehat{B}_1}$. (That is, series resistance $R_{\widehat{B}_1}$ is measured at \widehat{B}_1 and then $R_{\widehat{B}_2}$ at \widehat{B}_2 .)
θ	°C	temperature.
μ_a	—	relative amplitude permeability for a signal of amplitude greater than that for μ_Δ so that the value is dependent on flux density B: $\mu_a = \frac{1}{\mu_0} \cdot \frac{B}{H}$
μ_e	—	relative effective permeability: the permeability of a core with an air gap $\mu_e = \frac{C_1}{\Sigma l/A} \text{ or } \frac{l}{\mu_e} \cdot \frac{L}{N^2} C_1$
μ_i	—	relative initial permeability: measured on a core without air gap for a small field change $\Delta H \rightarrow 0$. $\mu_i = \lim_{(H \rightarrow 0)} \mu_a$
μ_{rem}	—	relative incremental permeability about remanence.
μ_Δ	—	relative incremental permeability of a polarized core: at a given d.c. applied field, the permeability observed when a small alternating field is superimposed. $\mu_\Delta = \frac{\Delta B}{\mu_0 \Delta H}$ Here, $\Delta B \leq 0,2$ mT and $f = 4$ kHz.
μ_θ	—	relative permeability at a given temperature.
ρ	Ωm	specific resistance for direct current.

MnZn and NiZn ferrites

FORMULAE

$$L = \frac{\mu_0 \mu_e N^2 \times 10^{-3}}{C_1}$$

$$A_L = 10^6 \mu_e \mu_0 / C_1$$

$$B = E / (4,44 f N A_e) \times 10^{-6}$$

$$E_3 / E_1 = 0,6 \tan \delta_h$$

$$N = \sqrt{(10^9 L / A_L)} = \alpha \sqrt{(10^3 L)}$$

$$Q = 1 / \tan \delta_{tot}$$

$$\tan \delta_h = \mu B \eta_B$$

$$1 \text{ mT} = 10 \text{ Gauss}$$

$$1 \text{ Oe} = 79,6 \text{ A/m}$$

H	inductance.
(nH)	initial induction factor.
(T)	peak flux density.
	3rd harmonic distortion.
(turns)	number of turns.
	quality factor.
	hysteresis loss factor

TECHNICAL DATA

Ferroxcube data are given in the tables on the following pages in accordance with the recommendations of IEC 401, and using symbols defined in the previous section.

GENERAL PROPERTIES

Specific heat at 25 °C

MnZn ferrites (FXC 3--)

1100 J/(kgK)

NiZn ferrites (FXC 4--)

750 J/(kgK)

Thermal conductivity from 25 °C to 85 °C

3,5 to 4,3 W/(mK)

Coefficient of linear expansion

10 to 12 x 10⁻⁶/K

Modulus of elasticity

15 x 10⁴ N/mm²

Ultimate tensile strength


18 N/mm²

Crushing strength

73 N/mm²

NOTES TO THE DATA TABLES

- The data given apply to medium-sized toroids and should be taken as a guide. Cores that are small or have other shapes will have slightly different properties that cannot readily be predicted on the basis of toroid properties. For this reason, product characteristics are guaranteed for the products themselves and are given on the appropriate data sheets.
- The temperature coefficient α_F is measured on circuits without a (ground) air gap, with the exception of 3B7 products, for which α_F is measured on toroidally-wound core halves. For FXC 3-- products, the measuring sequence is that shown in the figure. The measurement circuits for FXC 3H3 and FXC 4-- products are thermally demagnetized by being heated to 25 °C above their Curie temperature, after which they are cooled slowly to room temperature and left for 24 h.



MnZn and NiZn ferrites

		materials for deflection units	
	unit	●2A2	●3C2
Initial permeability μ_i at $\hat{B} \leq 0,1$ mT, $\theta = 25^\circ\text{C}$		$350 \pm 20\%$	$900 \pm 25\%$
Induction B, ballistically measured at H = 500 A/m $\theta = 100^\circ\text{C}$ H = 800 A/m $\theta = 20^\circ\text{C}$ H = 800 A/m $\theta = 25^\circ\text{C}$ H = 800 A/m $\theta = 70^\circ\text{C}$ H = 800 A/m $\theta = 100^\circ\text{C}$ H = 1600 A/m $\theta = 25^\circ\text{C}$ H = 1600 A/m $\theta = 100^\circ\text{C}$ H = 3200 A/m $\theta = 25^\circ\text{C}$ H = 3200 A/m $\theta = 100^\circ\text{C}$ H = 4800 A/m $\theta = 25^\circ\text{C}$ H = 4800 A/m $\theta = 100^\circ\text{C}$	mT	≈ 200 ≈ 140	≈ 350 ≈ 245
Coercivity Hc $\theta = 20^\circ\text{C}$	A/m	60	
Eddy current and residual loss constant $\frac{\tan \delta}{\mu_i}$ at $\hat{B} \leq 0,1$ mT, $\theta = 25^\circ\text{C}$ f = 100 kHz f = 450 kHz f = 500 kHz f = 700 kHz f = 1 MHz f = 1,5 MHz f = 2 MHz f = 3 MHz f = 5 MHz f = 10 MHz f = 20 MHz f = 25 MHz f = 40 MHz	$\times 10^{-6}$	≈ 50	
Hysteresis constant η_B at $\hat{B} = 0,3 - 1,2$ mT f = 100 kHz	$\times 10^{-3} \text{ T}^{-1}$		
Power loss at f = 16 kHz and B = 50 mT $\theta = 20^\circ\text{C}$ B = 400 mT $\theta = 25^\circ\text{C}$ B = 400 mT $\theta = 50^\circ\text{C}$ B = 400 mT $\theta = 100^\circ\text{C}$	kW/m ³	≈ 70	
Resistivity ρ measured with d.c.	Ωm	$\geq 10^6$	$\geq 0,1$
Dielectric constant at f = 1 MHz, $\theta = 25^\circ\text{C}$			
Temperature factor α_F $\theta = +25$ to $+55^\circ\text{C}$ $\theta = +25$ to $+70^\circ\text{C}$	$\times 10^{-6}/\text{K}$	≈ 35	0 to +4,5
Disaccommodation factor D _F between 10 and 100 min after demagnetization, $\hat{B} \leq 0,1$ mT, $\theta = 25 \pm 1^\circ\text{C}$	$\times 10^{-6}$		≤ 10
→ Curie temperature	$^\circ\text{C}$	≥ 135	≥ 150
Mass density	kg/m ³	≈ 4300	4700-4900
Core shapes		yoke rings	

● preferred material

materials for small parts							
•3B	3C6	4A4	•4B1	4D1	4D2	4E1	
900 ± 20%	1700 ± 25%	500 ± 20%	250 ± 20%	50 ± 20%	60 ± 10%	15 ± 20%	
≈ 345 ≈ 230	≥ 290	≈ 270 ≈ 210	≈ 325 ≈ 260	≈ 240 ≈ 220		≈ 175 ≈ 165	
≤ 50		≤ 30 ≤ 40 ≤ 70	≤ 70 ≤ 90 ≤ 140	≤ 180 ≤ 210 ≤ 300	≤ 100 ≤ 200 ≤ 600	≤ 300 ≤ 300 ≤ 360	
		≤ 1,8					
	≤ 170 ≤ 160 ≤ 140						
≥ 0,2		≥ 10 ⁵ 15-20	≥ 10 ⁵	≥ 10 ³	≥ 10 ³	≥ 10 ³	
0 to +3		+5 to +15	0 to +8	0 to +15	0 to +15	0 to +15	
≥ 150	≥ 190	≥ 135	≥ 250	≥ 400	≥ 350	≥ 500	
4700-4900	4750-4850	4700-5100	4400-4800	4000-4400		3500-4000	
tubes and rods		frames for i.f. transformers, tubes and rods		frames for i.f. transformers, screw cores, tubes and rods		tubes and rods	

MnZn and NiZn ferrites

	unit	
Initial permeability μ_i at \hat{B} (mT), $f = 4 \text{ kHz}$ θ (°C) $\leq 0,1$ 25		
Optimum frequency range	kHz	
Induction \hat{B} at f (kHz) \hat{H} (A/m) θ (°C) 0 800 25 0 800 100 0 3000 25 25 250 25 25 250 100	mT	
Power loss at f (kHz) \hat{B} (mT) θ (°C) 25 200 25 25 200 100 25 200 100 100 100 25 100 100 100 400 50 25 400 50 100	kW/m ³	
Temperature factor α_F at θ (°C) +5 to +25 +25 to +55 +25 to +70	$\times 10^{-6}/K$	
Curie temperature	°C	
Mass density	kg/m ³	
D.C. sensitivity constant $\beta_F = \frac{\mu_i - \mu_i \Delta}{\mu_i \mu_i \Delta} \text{ at } \mu_e \times \frac{N \times I_0}{l_e}$ = $1,20 \times 10^5 \text{ A/m}$ = $1,80 \times 10^5 \text{ A/m}$ = $2,60 \times 10^5 \text{ A/m}$	$\times 10^{-6}$	
Core shapes		

high level transformer materials (power materials)				
● 3B8	● 3C8	● 3C85	● 3F3	
2300 ± 20%	2000 ± 25%	2000 ± 20%	2000 ± 20%	
up to 150	up to 100	up to 200	up to 500	
≈ 500	≈ 500	≈ 500	≈ 500	
≥ 330	≥ 330	≥ 330	≥ 330	
≤ 140 ≤ 155	≤ 110* ≤ 100*	≤ 190 ≤ 140 ≤ 230 ≤ 165	≤ 120 ≤ 90 ≤ 110 ≤ 80 ≤ 150 ≤ 150	
5 ± 2 5 ± 2 5 ± 2				
≥ 200	≥ 200	≥ 200	≥ 200	
4700-4900	4750-4850	4700-4900	4650-4850	
≤ 120 ≤ 300 ≤ 1000				
potcores square cores	E, EC, ETD, U and I	E, ETD, square cores	square cores, ETD	

* at 16 kHz.

● Preferred material.

MnZn and NiZn ferrites

	unit	
Initial permeability μ_i , $f = 4$ kHz at $\hat{B} \leq 0,1$ mT $\theta = 25$ °C at $\hat{B} \leq 1$ mT $\theta = 5$ to 70 °C at $\hat{B} 0,7 - 1$ mT $\theta = 25$ to 70 °C		
Induction \hat{B} ballistically measured $H = 800$ A/m $\theta = 25$ °C $\theta = 70$ °C	mT	
Eddy current and residual loss constant $\frac{\tan \delta}{\mu_i}$ at $\hat{B} \leq 0,1$ mT, $\theta = 25$ °C $f = 4$ kHz $f = 10$ kHz $f = 30$ kHz $f = 100$ kHz $f = 500$ kHz	$\times 10^{-6}$	
Hysteresis constant η_B at $\hat{B} = 1,5 - 3,0$ mT $f = 4$ kHz	$\times 10^{-3} T^{-1}$	
Resistivity ρ measured with d.c.	Ωm	
Temperature factor α_F $\theta = +5$ to $+25$ °C $\theta = +25$ to $+55$ °C $\theta = +25$ to $+70$ °C	$\times 10^{-6}/K$	
Disaccommodation factor D_F between 10 and 100 min after demagnetization, $\hat{B} \leq 0,1$ mT $\theta = 25 \pm 1$ °C	$\times 10^{-6}$	
Curie temperature	°C	
Mass density	Kg/m ³	
Core shapes		

* $\pm 20\%$.

● preferred material.

low level transformer materials (broadband materials)						
3E1	●3E2	●3E4	●3E45	3E5	3H2	
3800 ± 20%	≥ 5000	4700 ± 20%	6000 ± 20% ≥ 4200	10000 ± 20%	2300 ± 20%	
≈ 350 ≈ 270	≈ 355 ≈ 260	≈ 350 ≈ 270	≈ 350 ≈ 270	≈ 380 ≈ 280	≈ 400	
≤ 2,5	≤ 2,5	≤ 2,5	≤ 5	≤ 3	≤ 1	
≤ 20 ≤ 200	≤ 15 ≤ 90	≤ 20 ≤ 200	≤ 40	≤ 25 ≤ 75	≤ 6	
≤ 1,1	≤ 1,1	≤ 0,85	≤ 1,0	≤ 0,85	≤ 0,85	
≥ 0,3	≥ 0,1	≥ 0,3	≥ 0,05	≥ 0,01	≥ 1	
1 ± 1 1 ± 1 1 ± 1						
≤ 4,3	≤ 1,9	≤ 4,3	≤ 3	≤ 2	≤ 4,3	
≥ 125	≥ 130	≥ 125	≥ 130	≥ 120	≥ 160	
4700-4900	4700-4900	4700-4900	4700-4900	4800-5000	4700-4900	
E and I cores, toroids potcores square cores	toroids	potcores, square cores	potcores, square cores	square cores, toroids	toroids tubes and rods	


MnZn and NiZn ferrites

	unit	
Initial permeability μ_i at $\dot{B} \leq 0,1 \text{ mT}$ $\theta = 25^\circ\text{C}$		
Induction B ballistically measured at H = 800 A/m $\theta = 25^\circ\text{C}$ $\theta = 70^\circ\text{C}$ H = 2400 A/m $\theta = 25^\circ\text{C}$ $\theta = 70^\circ\text{C}$	mT	
Eddy current and residual loss constant $\frac{\tan \delta}{\eta_i}$ at $\dot{B} \leq 0,1 \text{ mT}$, $\theta = 25^\circ\text{C}$ f = 4 kHz f = 30 kHz f = 100 kHz f = 500 kHz f = 1 MHz f = 2 MHz f = 10 MHz	$\times 10^{-6}$	
Hysteresis constant η_B at $\dot{B} = 0,3 - 1,2 \text{ mT}$ f = 100 kHz at $\dot{B} = 1,5 - 3 \text{ mT}$ f = 4 kHz at $\dot{B} = 1,5 - 3 \text{ mT}$ f = 100 kHz	$\times 10^{-3} \text{ T}^{-1}$	
Resistivity ρ measured with d.c.	Ωm	
Temperature factor α_F $\theta = +5 \text{ to } +25^\circ\text{C}$ $\theta = +25 \text{ to } +55^\circ\text{C}$ $\theta = +25 \text{ to } +70^\circ\text{C}$	$\times 10^{-6}/\text{K}$	
Disaccommodation factor DF between 10-100 min after demagnetization, $\dot{B} \leq 0,1 \text{ mT}$ $\theta = 25 \pm 1^\circ\text{C}$ between 24 and 48 h after thermal demagnetization, $\dot{B} \leq 0,1 \text{ mT}$ $\theta \leq 35^\circ\text{C}$	$\times 10^{-6}$	
Curie temperature	$^\circ\text{C}$	
Mass density	kg/m^3	
Core shapes		

materials for tuned circuits						
3B7	●3D3	●3D35	●3H1	●3H3	●4C6	
2300 ± 20%	750 ± 20%	1000 ± 20%	2300 ± 20%	2000 ± 20%	120 ± 20%	
≈ 430 ≈ 345	≈ 350	≈ 350	≈ 360 ≈ 280	≈ 400	≈ 380 ≈ 350	
≤ 1,0 ≤ 5,0	≤ 8 ≤ 12 ≤ 24	≤ 3 ≤ 8 ≤ 30	≤ 1,0 ≤ 5,0	1,2 ± 0,4 2 ± 0,5	≤ 40 ≤ 100	
≤ 1,1	≤ 0,8	≤ 0,5	≤ 0,85	≤ 0,6	≤ 6,2	
≥ 1	≥ 1,5	≥ 7	≥ 1		≥ 10 ⁵	
0 ± 0,6	1 ± 1	1 ± 0,5 1 ± 0,5 1 ± 0,5	1 ± 0,5 1 ± 0,5 1 ± 0,5	0,7 ± 0,3 0,7 ± 0,3 0,7 ± 0,3	1 ± 3 3 ± 3	
≤ 4,3	≤ 12	≤ 8	≤ 4,3	≤ 3	≤ 10	
≥ 170	≥ 200	≥ 180	≥ 130	≥ 160	≥ 350	
4700-4900	4500-4900	4300-4500	4700-4900		4000-5000	
potcores, square cores	potcores, square cores, screw cores	potcores, square cores, screw cores	potcores, square cores, cross cores	potcores, square cores	potcores square cores, toroids, frames for i.f. transformers, rods and tubes	

CHARACTERISTIC CURVES


The curves are valid for toroids of not too small dimensions and should be considered as a guide. For guarantees on products, refer to the pages on the relevant products.





Eddy current losses and residual losses as a function of the frequency at low induction level.



MnZn and NiZn ferrites



Amplitude permeability as a function of the induction.









MnZn and NiZn ferrites





MnZn and NiZn ferrites







MnZn and NiZn ferrites

TYPICAL BH-CURVES (measured ballistically)


ballistic curves




ballistic curves




ballistic curves




dynamic curves, $f = 10$ kHz




ballistic curves




ballistic curves



ballistic curves




ballistic curves




MnZn and NiZn ferrites


dynamic curves, $f = 10$ kHz




dynamic curves, $f = 10$ kHz




ballistic curves




dynamic curves, $f = 10$ kHz




ballistic curves



dynamic curves, $f = 10$ kHz




ballistic curves




MnZn and NiZn ferrites


dynamic curves, $f = 10$ kHz




ballistic curves





ballistic curves





ballistic curves





Relative initial permeability as a function of the temperature





MnZn and NiZn ferrites




Permeability factor as a function of the temperature







MnZn and NiZn ferrites











Power loss as a function of the induction





















MnZn and NiZn ferrites





Incremental permeability as a function of the field strength






MnZn and NiZn ferrites






MnZn and NiZn ferrites






MnZn and NiZn ferrites



D.C. sensitivity

material grade: 3B8



$$\beta_F = \frac{\mu_e - \mu_{e\Delta}}{\mu_e \times \mu_{e\Delta}}$$

Inductance variation as a function of d.c. polarization. The measured values are situated in the area to the right of the curve.


SECTION B
YOKE RINGS

YOKE RINGS FOR USE IN DEFLECTION COILS FOR PICTURE TUBES

SURVEY OF TYPES

application	grade	mass g	A mm	B mm	C mm	H mm	catalogue number	page
B/W								
90° (tiny vision)	2A2	62	47	37	29	26	3122 134 91680	59
110°	2A2	135	56,3	58	39,5	27,5	3122 134 91940	61
110°	3C2	135	56,3	58	39,5	26	3122 104 93840	54
110°	3C2	215	79	54	—	37	3122 134 90750	56
110° (tiny vision)	3C2	90	57	—	30,6	26,5	4313 020 35380	71
	3C2	196	74	54	38	37	4322 020 35070	70
90°	3C2	112	63	50	38	32	3122 134 90600	55
Data graphic display	3C2	364	94	58	46	54	3122 134 92030	62
COLOUR								
90°	2A2	235	92	60	48	46,5	3122 134 91610	58
90°	2A2	153	74	52	40	37	3122 134 92510	64
90° (39SW)	2A2	228	92	60	48	42	3122 134 92600	66
90° (51FS)	2A2	235	89	60	46,5	42	3122 134 92780	68
90° (36FS)	2A2	157	76	52	40	33	3122 134 93050	69
90°	2A2	268	84	60	48	42	3122 134 91440	57
90° (39SW)	2A2	225	92	66	51	36	3122 134 99370	70
110° (30AX)	3C2	505	138	73,5	60	57,6	3122 134 92500	63
110° (45AX)	3C2	367	113	65,5	49,5	44,8	3122 134 92750	67
data graphic display	3C2	285	92	64,2	52	48	3122 134 92590	65
data graphic display	3C2	760	132	—	51	87	3122 134 91850	60

The data on these yoke rings are arranged on the following pages in order of catalogue number.




YOKE RING FOR 110° B/W TUBES

- Material grade FXC 3C2
- Mass 135 g
- Catalogue number 3122 104 93840

Spring clips for assembling can be supplied, catalogue number 3122 101 06340.



Dimensions in mm



YOKE RING FOR 90° B/W TUBES

- Material grade FXC 3C2
- Mass 112 g
- Catalogue number 3122 134 90600

Dimensions in mm




3122 134 90750

YOKE RING FOR 110° B/W TUBES

- Material grade FXC 3C2
- Mass 215 g
- Catalogue number 3122 134 90750


Dimensions in mm



YOKE RING FOR 90° HYBRID COLOUR TUBES


- Material grade 2A2
- Mass 268 g
- Catalogue number 3122 134 91440

Dimensions in mm



YOKE RING FOR 90° COLOUR TUBES


- Material FXC 2A2
 - Mass 235 g
 - Catalogue number 3122 134 91610
- Dimensions in mm



YOKE RING FOR 90° B/W TINY VISION TUBES



- Material grade FXC 2A2
- Mass 62 g
- Catalogue number 3122 134 91680

Dimensions in mm



YOKE RING FOR COLOUR DATA GRAPHIC DISPLAY TUBES


- Material FXC 3C2
 - Mass 760 g
 - Catalogue number 3122 134 91850
- Dimensions in mm



YOKE RING FOR 110° B/W TUBES



- Material grade FXC 2A2
- Mass 135 g
- Catalogue number 3122 134 91940

Dimensions in mm



YOKE RING FOR B/W DATA GRAPHIC DISPLAY TUBES


- Material grade FXC 3C2
 - Mass 364 g
 - Catalogue number 3122 134 92030 silanated
- Dimensions in mm



YOKE RING FOR 110° COLOUR TUBES 30AX SYSTEM

- Material grade FXC 3C2
- Mass 505 g
- Catalogue number 3122 134 92500 silanated



Dimensions in mm




3122 134 92510

YOKE RING FOR 90° COLOUR TUBES – MN

- Material grade FXC 2A2
- Mass 153 g
- Catalogue number 3122 134 92510



7Z90594




A

YOKE RING FOR COLOUR DATA GRAPHIC DISPLAY TUBES

- Material FXC 3C2
- Mass 285 g
- Catalogue number 3122 134 92590 silanated

Dimensions in mm







YOKE RING FOR 90° COLOUR TUBES – 39SW

- Material grade
- Mass
- Catalogue number

FXC 2A2
 228 g
 3122 134 92600 (4313 020 35400 export packed)



Dimensions in mm



YOKE RING FOR 110° COLOUR TUBES 45AX


- Material grade FXC 3C2
- Mass 367 g
- Catalogue number 3122 134 92750 silanated

Dimensions in mm



YOKE RING FOR 90° COLOUR TUBES — 51FS


- Material grade FXC 2A2
 - Mass 235 g
 - Catalogue number 3122 134 92780 (4313 020 35500 export packed)
- Dimensions in mm



YOKE RING FOR 90° COLOUR TUBES — 36FS



- Material grade FXC 2A2
- Mass 157 g
- Catalogue number 3122 134 93050

Dimensions in mm



YOKE RING FOR 90° COLOUR TUBES – 39SW



- Material grade FXC 2A2
 - Mass 225 g
 - Catalogue number 3122 134 99370 (4313 020 35910 export packed)
- Dimensions in mm



YOKE RING FOR 110° B/W TINY VISION TUBES



- Material grade FXC 3C2
- Mass 90 g
- Catalogue number 4313 020 35380

Dimensions in mm



YOKE RING FOR 90° B/W TUBES

- Material grade FXC 3C2
- Mass 196 g
- Catalogue number 4322 020 35070



SECTION C
E/EC/ETD/U/I CORES

INTRODUCTION

CORE TYPE AND MATERIAL GRADE SELECTION GUIDE

The range of applications of ferrite transformer and choke cores is very wide. This applications survey concentrates on the more popular, and more typical, applications so that these can be used as a guide to other, similar requirements. However, even where a clear indication in the Selection Guide is given for a given core and material, cost/performance trade-offs might be possible, especially where large quantities are involved. Intending users of ferrite cores are always recommended to consult us during equipment development, before a final core selection is made.

Using the selection guide

Starting with the paragraph Applications, below, find the application description that most closely resembles the intended application. Note the number or numbers of the application category. Proceed to the paragraph Application Categories and refer to the Category number obtained previously.

If the description of the application conditions fits the intended application, consult the tables or charts of core types indicated to select the most suitable core and material grade.

Applications

application	application category
Chokes, power	1
suppression	3
Driver transformers	2
Line-output transformers	1
Matching transformers	2
Power-supply transformers, inverters	1
Converters	1
Switched-mode	1

Application categories

1. High power, high flux density, minimum size

Preferred material: Ferroxcube 3C8.

The design of transformers where maximum throughput power is required in the minimum of volume requires careful balancing of core and winding dissipation. For details, refer to the section Cores for switched-mode power supplies. Selection charts for power transformer cores for switch-mode power supplies are also given in this section.

Ferroxcube 3C8 has been developed for optimum performance in power applications, and is the ideal material where transformer or choke volume is a principal consideration. All EC, E and U cores are available in Ferroxcube 3C8, but coil formers for U cores and some E cores are not listed here. Power-choke core selection and design is considered in detail in the section Power Choke Design.

E/EC/ETD/U/I CORES

Round-section U core type U64 in Ferroxcube 3C8 material was developed primarily for line-output transformers in colour TV receivers. A number of other round-section U cores suitable for line-output transformers is available .

Small, square-section U cores in Ferroxcube 3C8 material are especially suitable for small-power-supply applications, such as inverters. The effective magnetic dimensions of pairs of the cores are listed in the following table.

core type	l_e (mm)	effective dimensions A_e (mm ²)	V_e (mm ³)
U10/8/3	38,4	8,63	331
U15/11/6	48	30	1 440
U20/16/7	68	56	3 800
U25/20/13	86	100	8 600
U30/25/16	111	157	17 400

Very large cores for transformers in the kilowatt power range can be assembled from larger, square-section U cores of types U93/52/30 and U100/57/25: either in combination with matching I cores, or by stacking. Please consult us on the properties of large stacks.

2. Minimum loss, low operating flux density

Preferred material: Ferroxcube 3E1.

A wide range of E cores, including DIN E cores, is available in Ferroxcube 3E1. These cores are also available with a ground air gap. The table below gives winding window area and induction factor A_L for the E cores with coil formers used in pairs. The induction factor A_L has a tolerance of 25% for cores selected at random and pressed together.

Small U cores in Ferroxcube 3C8 material often prove more attractive for driver transformers. These are listed under category 1.

core type	winding window area (mm ²)	A_L (nH)
EE20/20/5	27	2 405
EE30/30/7	80	3 330
EE42/42/15	178	7 555
EE55/55/21	250	11 937
EE65/65/13	394	15 450

3. Suppressor chokes

The small, square-section U cores listed under category 1 are ideal for use as cores for suppressor chokes in higher-current applications. Where there is a d.c. component of the line current, a spacer should be used. The data given in the section Power Chokes, together with curves in the data sheets should be used for selecting cores and designing suppressor chokes.

CORES FOR SWITCHED-MODE POWER SUPPLIES

Ferroxcube grade 3C8/3C85 was developed specifically to meet the stringent demands placed on power supply chokes and transformers, especially those in switched-mode power supplies, operating at 10 kHz or higher. At these high frequencies the eddy current losses are very low due to the high bulk resistivity of Ferroxcube 3C8/3C85, whose permeability remains the same as at low frequencies. In general, therefore, this means a much smaller transformer can be designed than with laminated iron cores.

Ferroxcube 3C8/3C85 is a manganese-zinc ferrite which meets the main magnetic requirements for power transformer cores:

- high maximum flux density (B) and high relative amplitude permeability (μ_a).
- high resistivity (ρ) to ensure low eddy current losses.
- high Curie point, so that magnetic properties are retained at high temperature (up to 200 °C).
- in the operating temperature range (up to 100 °C), losses fall as temperature increases.

Switched-mode power supply circuits

The basic arrangement of a switched-mode power supply (SMPS) is shown in Fig. 1. In this system, the power input is rectified and filtered and the resulting d.c. voltage is chopped at a high frequency by a switch. The chopped waveform is applied to the primary of a transformer and the secondary output is rectified and filtered to give the required d.c. output. The output voltage is sensed by a control circuit which supplies a correction signal to the drive circuit to vary the ON-OFF time of the switched waveform and compensate for any change at the output. This same system can operate from a battery or any other d.c. input.

There are numerous circuit designs that can be used to convert d.c. input voltage to the required d.c. output voltage. But some preliminary design selection will have to be made as to the type of converter circuit to use. Since the emphasis here is on the design of the magnetic components used in switched-mode power supplies, the many different designs are considered from a magnetics point of view. Analysing available circuits this way, three broad basic converter designs can be distinguished, based upon the magnetic converting device: flyback, forward and push-pull converters.




Fig. 1 Block diagram of switched-mode power supply.

Flyback converter

Figure 2 shows the basic circuit of a flyback converter and the associated waveforms. When the switch is closed (transistor conducts), the supply voltage is connected across the inductor and the output diode is non-conducting: current rises linearly, storing energy, until the switch is opened. When this happens the voltage across the inductor reverses and the stored energy is transferred into the output capacitor and load. By varying the conduction time of the transistor at a given frequency, the amount of energy stored in the inductor during each ON cycle can be controlled. This is a way of controlling and changing the output of a switched-mode power supply.





Fig. 2 Basic circuit of a flyback d.c. to d.c. converter with associated waveforms.

In Fig. 3, the basic circuit of Fig. 2 is developed into a practical circuit using an inductor with two windings. The progression from Fig. 3a via 3b to 3c can easily be understood. In a flyback converter all the energy to be transferred to the output capacitor and load is first stored in the inductor. It is therefore possible to obtain line isolation by adding a secondary winding to the inductor. (Although an inductor with more than one winding appears in schematic diagrams as a transformer, it is referred to as an inductor in accordance with its function.) Another advantage of the flyback converter is the fact that no smoothing choke is required in the output circuit. This is important in high-voltage supplies and in power supplies with a number of output circuits (see Fig. 4). A disadvantage of this type of converter is that the output capacitor is charged only during the transistor OFF cycle. Hence the output capacitor ripple current is high when compared with the other types of converters. Another disadvantage of the flyback converter relates to the energy storage in the inductor. The inductor is driven in one direction only, which requires a larger core in a flyback design than for an equivalent design using a forward or push-pull converter.




Fig. 3 Development of practical flyback converter circuit.




Fig. 4 Multiple output flyback converter circuit.

Forward converter

Figure 5 gives the basic circuit of the forward converter, along with the associated voltage and current waveforms. When the switch is closed (transistor conducts), the current rises linearly and flows through the inductor into the capacitor and the load. During this ON cycle, energy is both transferred to the output and stored in the inductor L . When the switch is opened the energy stored in the inductor causes the current to continue to flow to the output via the diode.

As in the flyback converter, the amount of energy stored in the inductor can be varied by varying the ON-OFF cycles. This gives a method of controlling the output of the forward converter.

Figure 6 shows a more practical forward converter circuit with a line-isolation transformer. The need for a separate transformer for line isolation is an obvious disadvantage of this converter circuit when compared with the flyback converter. A major advantage of the forward converter in comparison with the flyback converter is the lower ripple voltage at the output. This is due to the fact that the high-frequency ripple current feeding into the smoothing capacitor is limited by the inductor. This advantage is of particular interest for low-voltage supplies.





Fig. 5 Basic circuit of a forward d.c. to d.c. converter with associated waveforms.

Multiple outputs in a forward converter can be obtained by using more secondary windings on the transformer. Each of these windings, however, will have to have the two diodes, an inductor and a capacitor. This method can cause regulation difficulties and is expensive.

Under certain conditions, a better approach is to use a combination of forward and flyback converters. (A dual output converter where this principle is demonstrated is shown in Fig. 7). Here the energy is stored in the inductor, to power another output. At the end of the transistor conduction cycle the voltage across the inductor is equal to the output voltage V_{O1} . Therefore, if V_{O1} is stabilized, V_{O2} will also be stabilized. The amount of energy that can be stored in the inductor is clearly limited. However, this circuit is a practical alternative in cases where a constant-load second output is required that is 30 per cent or less of the main output.




Fig. 6 Forward converter with line isolation transformer.

In Fig. 7 the transformer is shown with a tertiary winding and a diode in series. The purpose of the additional winding and diode is as follows: during the conduction cycle of the transistor, the magnetizing current increases linearly to some final value. As soon as the transistor is turned off, this magnetizing current is transferred, via the additional winding and diode, back to the d.c. supply. This demagnetizing winding should be tightly coupled with the primary winding to avoid voltage spikes during the switching of the transistors. The demagnetizing winding and diode ensure a return of the transformer's magnetic energy back to the d.c. supply and also limits the transistor collector voltage to twice the d.c. input voltage.







Fig. 7 Dual-output forward converter.




(a)



(b)



(c)



(d)

Fig. 8 Basic circuit of a push-pull d.c. to d.c. converter with associated waveforms.

Push-pull converter

Figure 8 gives the basic circuit of the push-pull converter, with voltage and current waveforms. The push-pull converter is, in fact, an arrangement of two forward converters operating in antiphase (push-pull action). With switch S_1 closed (Fig. 8a) diode D_2 conducts and energy is simultaneously stored in the inductor and supplied to the load. With S_1 and S_2 open (Fig. 8b), the energy stored in the inductor will continue to support the load current by the parallel diodes D_1 and D_2 , which are now acting as flywheel diodes. When switch S_2 closes (Fig. 8c), diode D_1 will continue to conduct, diode D_2 will stop conducting and the process will repeat itself.

In Fig. 9 a practical push-pull converter circuit is shown. A push-pull converter circuit doubles the frequency of the ripple current in the output filter and, therefore, reduces the output ripple voltage. A further advantage of the push-pull operation is that the transformer core is excited alternately in both directions in contrast to both the forward and flyback converters. Therefore, for the same operating conditions and power throughput, a push-pull converter design can use a smaller transformer core.

Multiple outputs can be constructed by using several secondary windings, each with its own output diodes, inductor and smoothing capacitor. The method that relies on the energy stored in the output choke can also be used here (see Fig. 7, under Forward Converters).




Fig. 9 Conventional push-pull converter circuit.

Converter selection

In each of the three basic converter designs there are several different circuit possibilities. In the flyback and forward converters, single and two-transistor designs can be used. If two transistors are used, they will switch simultaneously. This type of circuit preference is determined by the allowable collector emitter voltage and collector current of the transistor. In push-pull converter designs, the primary of the transformer can be connected in several ways (see Fig. 10). Depending upon how the transformer primary is driven, it is possible to differentiate between single-ended (Fig. 10a), push-pull (Fig. 10b) and full-bridge circuits (Fig. 10c). Again, decisions on circuit details are determined by the transistor capabilities.




Fig. 10 Several push-pull converter circuits.

For a particular converter design, the first selection that should be considered is obviously the type of converter circuit. To aid in this initial converter circuit selection, Fig. 11 offers a rough guide to the type of converter, its output voltage and power capability. This selection has to be considered along with other requirements such as line isolation, ripple content, overall efficiency, multiple outputs, etc. Table 1 summarizes the most significant properties of a converter design. It shows the relative strengths and weaknesses of the three types of converters with regard to these characteristics.

For a high performance, high power, single output supply, where ripple requirement is well below 1%, the push-pull design is the obvious choice. For smaller power versions of this type of supply, the forward or double forward converter provides a useful alternative to the push-pull converter.

In high-voltage supplies, the flyback converter is the most suitable circuit and should be considered first.

In multiple-output supplies, again, the flyback converter is normally the first choice because it avoids the necessity of providing a number of output windings on the inductor, together with a single diode and capacitor for each.




Fig. 11 Converter circuit selection as a function of output voltage and throughput power.

Table 1

	type of converter circuit		
	flyback	forward	push-pull
Circuit simplicity	+	0	-
Number of components	+	0	-
Drive circuitry	+	0	-
Output ripple	-	0	+
Choke volume	-	0	+
Transformer volume	not required	0	+
Mains isolation	+	-	+
High power	-	0	+
High voltage	+	0	0
Multiple outputs	+	0	0

+ Favourable

0 Average

-- Unfavourable

Core selection curves

When designing a transformer, use the following charts to select a core whose indicated throughput power under the desired operating conditions is equal to, or greater than, the power required.

The power-handling capability of a given core is determined by its geometry and available winding area, which are fixed, and by the following factors which depend on the specific application.

Winding configuration

In the derivation of the curves for three-winding transformers it has been assumed that each winding occupies one third of the winding area. This would apply when the third winding is bifilar wound with the primary and uses the same gauge of wire. However, because the third winding carries only magnetizing current in forward converters, or current spikes caused by leakage inductance in flyback converters, the current in the winding is normally low. Therefore, the third winding may be wound with thinner wire and may occupy less than one third of the winding area. In this case, the throughput power can be increased by up to about 20% when it would equal that for a two-winding curve.

When multiple secondaries are used to supply a number of different output-rectifier circuits, the total number of secondary windings should be regarded as a single secondary. The area of this single secondary should then be divided between the individual secondaries in proportion to the power to be delivered by each winding.

Operating frequency

The preferred operating frequency of a switched-mode power supply is greater than 20 kHz to avoid audible noise from the transformer.

Ambient temperature

Ambient temperature, together with the maximum core temperature (see next paragraph), determines the maximum temperature rise, which in turn fixes the permissible total power dissipation in the transformer. Curves of temperature rise versus power dissipation are included in the published data for each core. In the construction of the core selection curves, a maximum ambient temperature of 60 °C has been assumed. This allows a 40 °C temperature rise from the ambient to the centre of the transformer for a maximum core temperature of 100 °C.

Core temperature

Core temperature determines the maximum flux density, or flux for a given core, to avoid saturation. Curves of maximum recommended flux against temperature are given in the published data for each core. In the construction of the core selection curves, a maximum core (hot spot) temperature of 100 °C has been assumed because this is acceptable for a wide range of applications and does not exceed the maximum temperature rating of generally-available enamelled wire.

Flux density (see relevant graphs on following pages)

To avoid saturation in the cores the flux density in the minimum cross-section must not exceed the saturation flux density of the material at 100 °C. The allowable total flux is the product of this flux density and the bottom-limit minimum core area and must not be exceeded even under transient conditions: when a load is suddenly applied at the power supply output, and maximum duty factor occurs together with maximum supply voltage. Under steady-state conditions, where maximum duty factor occurs with minimum supply voltage, the flux is reduced from its absolute maximum permissible value by the ratio of the minimum-to-maximum supply voltage. (At all higher supply voltages the voltage control loop reduces the duty factor and keeps the steady-state flux constant.)

In the construction of the core selection curves, the minimum-to-maximum supply voltage ratio has been taken as 1 : 1,72, this being typical for most applications. The minimum supply voltage assumed in the curves is defined as that voltage which would correspond to a duty factor δ of 0,5. If in practice the maximum duty factor is limited to less than 0,5, then the practical minimum supply voltage would be increased proportionately; for example, by 10% if $\delta_{\max} = 0,45$.

Winding-window utilization

In the construction of the core selection curves, the gaps of 4 mm on each side of the windings (see Figs 12 and 13) are to comply with IEC 435 mains isolation requirements. If these gaps are omitted, the maximum throughput power is increased to P' where:

$$P' = P\sqrt{\left(\frac{\text{full winding width}}{\text{full winding width} - 8 \text{ mm}}\right)}$$

that is, by about 25% for small cores and about 10% for large cores.

The maximum percentage of copper in the available winding area is generally about 50%, corresponding to windings of circular cross-section and insulation equal to 25% of the wire diameter.




Fig. 12 To allow for creepage distance for 230 V mains isolation, a gap of 4 mm is left at each side of the winding.




Fig. 13 Detailed section of winding showing how creepage distance is used.

Ratio F_W/F_R

The term F_W is the winding copper factor and is defined as:

$$F_W = \frac{A_{Cu}}{A_W} \frac{\text{total cross-sectional area of copper in windings}}{\text{available winding area}}$$

and F_R is defined as:

$$F_R = \frac{\text{a.c. resistance of winding}}{\text{d.c. resistance of winding}}$$

Both F_W and F_R depend on the conductor sizes and winding configuration employed in any particular transformer design, and these will depend on the required input and output voltages, etc. Achievable F_W/F_R ratios for normal solid wire and strip conductors depend on the particular transformer specification and can only be assessed for particular cases. However, the experience of a number of transformer designers, employing various cores and operating frequencies, has produced information on the values of F_W/F_R that can usually be achieved. This information has been used in the construction of the core-selection charts.

Ratio γ (flyback converters)

This is the ratio of minimum-to-maximum load current over which good output-voltage regulation is required, and over which duty factor remains roughly constant for a fixed input voltage.

Push-pull converter balance



Two sets of selection charts are given for push-pull converters. One applies to converters in which precautions have been taken to ensure balanced operation so that there is no d.c. component of core flux. Here the value of α is taken as at least 1,72. The other applies to converter designs where there is a possibility of d.c. core polarization. The value of α used, 3,44, allows for operation on one half of the hysteresis loop only and is thus a worst-case value.



Using the selection charts

These charts are intended as a guide only: the choke selection procedure, based on stored energy, should be used to make the choice of core. These charts can be used to check that choice. See 'Power choke design'.



On the charts, each core type is represented by a shaded area. The upper limit of this area is a curve of throughput power against frequency obtainable under the best possible conditions: no creepage distance, thus maximum winding window; flux density reduced below that for $\alpha = 1,72$ at higher frequencies; and a ratio of $F_W/F_R = 0,5$, which is just attainable at the lower frequencies with bunched (Litz) wire windings. The lower limit of the core area is a curve of throughput power against frequency for a basic transformer design: simple, but optimized, solid-wire windings, 8 mm creepage distance for IEC mains isolation, and optimum flux density sweep is assumed.



To select the best core for the application, draw a line on the chart for the desired converter type at the required throughput power. Possible cores for the transformer are those for which this power line is within or below the operating area at the desired operating frequency. The proximity of the core operating point to the upper boundary of its area will depend on the degree to which the design is to be elaborated.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.









* Without creepage allowance.





* Without creepage allowance.






* Without creepage allowance.


Optimum flux density

Optimum flux density excursion (half the peak-to-peak value) giving maximum throughput power for a variety of cores for SMPS applications.




The two lower broken horizontal lines in the graphs indicate the maximum flux values for converters without feed forward, to allow for transient conditions. The intersections of these horizontal lines with the optimum-sweep curves gives the transition frequencies* for the respective cores.

* Transition frequency is the frequency at which the design changes from 'saturation limited' to 'core loss limited'.



1. UU15/22/6
EE20/20/5
2. UU20/32/7
EE25/25/7
EE30/30/7
3. UU25/40/13
4. UU30/50/16



1. EC35
2. EC41, EC52
3. EE42/42/15
4. EC70
5. EE42/42/20
EE42/54/20
EE42/66/20
6. EE55/55/21
7. EE55/55/25
UU64/79/20
8. EE65/66/27

POWER CHOKE DESIGN

Ferroxcube grade 3C8 is the natural choice for cores for power chokes operating at ultrasonic frequencies, such as those in switched-mode power supplies (SMPS). The data for the cores in this section include design charts that greatly simplify the design of these power chokes. Starting with the peak current I_M (Fig. 14) that the choke shall pass without saturating the core, and the minimum inductance required L_{min} the designer obtains all the information required for the construction of the choke directly. Core size, spacer thickness, number of turns, and winding geometry are derived in straightforward procedures. Note that the magnetic properties of the core do not enter into the design process. The ratio of the a.c. and d.c. current components may be small (smoothing chokes) to large (push-pull converter chokes). Parameter spreads due to manufacturing and temperature variations are taken into account in the construction of the design charts. The design procedures allow for spacer tolerances.




Fig. 14 Choke waveform showing symbols for currents are full load.

Operating conditions

The charts are constructed for cores of Ferroxcube 3C8 operating at a hot-spot temperature of 100 °C. Operation at lower temperatures leads neither to core saturation nor to inductances lower than L_{min} . The design peak flux density is 0,32 T. However, the charts can be used for a lower value B_M by designing for a peak current $0,32 I_M/B_M$.

Applications

For the purposes of this design process, applications are divided into three classes:

- I $I_{ac}/I_0 < 0,3$
Examples: smoothing chokes, and converter chokes in flyback-type SMPS without complete demagnetization.
- II $I_{ac}/I_0 \approx 1$
Example: flyback-converter chokes with complete demagnetization (ringing-choke converters).
- III $I_{ac}/I_0 > 2$
Example: converter chokes in push-pull-type SMPS (symmetrical excitation) as used for fluorescent-lighting.

Core loss rather than saturation is usually the limiting factor in this class of application. Thus, the peak flux density must be lower than 0,32 T by an amount that depends on operating frequency. The special treatment of class III designs given in the following procedures generally yield satisfactory results.

Core selection

The cores are grouped according to shape: EC, EE, ETD, UI, UU.


Selection procedure

- Knowing the values of peak choke current I_M and minimum required inductance L_{\min} , calculate the value of $I_M^2 L_{\min}$.
- Choose — at least provisionally — the shape of core (EE, EC, ETD, UU or UI) and draw a horizontal line $I_M^2 L_{\min}$ across the selection chart for that core shape. For class II designs at frequencies beyond 40 kHz use a value of $I_M^2 L_{\min}$ equal to $f/40$ times the actual value of $I_M^2 L_{\min}$, for class III designs at frequencies beyond 10 kHz use a value of $I_M^2 L_{\min}$ equal to $0,1 f$ times the actual value of $I_M^2 L_{\min}$, where f is the operating frequency in kHz.
- A core whose curve intersects this horizontal line can be used for the application. The spacer thickness or centre pole gap size corresponding to the intersection is only an indication of the final value.


Effect of core size

Where, as is usual, more than one core could be used, the final choice may be governed by the consideration that operation near the right-hand end of the curves carries the risk of overheating.


Selection of a larger core will generally result in a more conservative, efficient design than one based on a core that is marginally large enough.




Choke core selection chart for EE cores.




Choke core selection chart for EE cores.




Choke core selection chart for EC cores.




Choke core selection chart for EC cores.



Choke core selection chart for ETD cores.



Choke core selection chart for UU/UI cores.



Choke core selection chart for UU/UI cores.

Gap size (spacer thickness or centre leg gap width) and number of turns

For ETD cores consult the tables given on the relevant pages. For the other cores turn to the data for the core type selected and refer to the chart giving $(I_M^2 L)_{max}$ and A_L as functions of gap sizes. (Note: A_L for these power cores is the inductance factor in henry.)

The charts comprise a pair of curves of $(I_M^2 L)_{max}$ and A_L for each of the three application classes. Use the pair of curves for the appropriate class of application in the following design procedure.

1. On the chart, draw the horizontal line $I_M^2 L_{min}$, as used for core selection, see under 'Core selection'. The working point of the core must lie above this line and below the $(I_M^2 L)_{max}$ curve for the core. That is, between lines SQ and SP in Fig. 15.
2. Select a suitable gap size, nominal width s . Draw vertical lines s_{min} and s_{max} on the chart, where $s_{max} - s_{min}$ is the tolerance field on the centre pole gap size or thickness of the spacer and the associated adhesive films. (Epoxy adhesive films vary in thickness from about 10 μm to about 20 μm .) Ensure that the horizontal distance between the intersection and s_{min} (a in Fig. 15) is greater than the distance from s_{min} to s_{max} (b in Fig. 15).
3. For s_{min} , read values of $(I_M^2 L)_{max 1}$ and $A_L 1$ from the chart. The maximum number of turns allowed to avoid saturation is

$$N_{max} = \sqrt{\frac{(I_M^2 L)_{max 1}}{I_M^2 A_L 1}}$$

for class II beyond 40 kHz,

$$N_{max} = \sqrt{\frac{(I_M^2 L)_{max 1}}{f/40 \times I_M^2 A_L 1}},$$

for class III beyond 10 kHz,

$$N_{max} = \sqrt{\frac{(I_M^2 L)_{max 1}}{0,1 f \times I_M^2 A_L 1}},$$

where f is expressed in kHz.

Note: The upper left-hand corner of the shaded area of the figure is the most critical point regarding number of turns and core saturation.

4. For s_{max} , read the value of $A_L 2$. The minimum number of turns, for inductance L_{min} , is

$$N_{min} = \sqrt{\frac{L_{min}}{A_L 2}}$$

Note: The lower right-hand corner of the shaded area is the most critical for number of turns and L_{min} .

5. Select an integral number of turns N between N_{min} and N_{max} .

Note: If a was taken to be only marginally greater than b (see Fig. 15), the design attempt might fail since such an integer would not exist. Taking a $< b$ makes $N_{max} < N_{min}$.

6. Establish the winding geometry using the winding-design procedure, given later.




Fig. 15 Graphical design process using core design charts.

Winding design

Because the eddy-current losses in a winding carrying a.c. increase rapidly with conductor size (for wire, with d^4 , whereas d.c. loss increases with d^{-2}), there is a certain "ideal" conductor size for minimum loss. This may set an upper limit to conductor size at the ultrasonic frequencies at which SMPS chokes operate. The procedures that follow allow the ideal number of layers and wire size, or the thickness of strip, to be determined for chokes with an operating-current waveform of the form shown (Fig. 14). They also indicate the course of action when the available winding window will not accommodate the ideal winding.

Copper conductors are assumed; operating temperature is 100 °C, so that conductor resistivity is 1/45 $\Omega\text{mm}^2/\text{m}$ (30% higher than that at 20 °C). Symbols used in the formulae are as follows. (Note: subscript id indicates an ideal (lowest loss) value).

b_w	mm	winding (layer) breadth
d	mm	nominal wire diameter
d_o	mm	overall wire diameter
f	kHz	frequency
f_e	kHz	effective frequency (see text)
F_R	—	resistance factor R_{ac}/R_{dc}
h	mm	thickness of foil conductor
H	mm	winding height
H_a	mm	available winding height
i	mm	thickness of interleaving
I_e	A	r.m.s. current at full load
I_0	A	d.c. component of current at full load (see Fig. 14)
I_{ac}	A	a.c. component of current at full load (see Fig. 14)
I_M	A	peak value of current at full load (see Fig. 14)
N	—	number of turns in a winding
p	—	number of layers
P_w	W	winding loss
R_{ac}	Ω	a.c. resistance
R_{dc}	Ω	d.c. resistance

Effective frequency f_e and effective current I_e

For sinusoidal currents, effective frequency f_e is equal to actual frequency f . This remains the case for small amounts of waveform distortion and small d.c. components.

For the waveform shown in Fig. 14, and provided that the rise and fall times are between 15% and 85% of the repetition period,

$$f_e = \frac{1,3f}{\sqrt{\{1 + 3(I_0/I_{ac})^2\}}}$$

In designs for applications in class I, f_e may be only a few kilohertz. Eddy-current effects are then negligible and windings can be designed as if they carry d.c. Use the correct value of d.c. resistivity (given below).

For the waveform shown,

$$I_e^2 = I_0^2 + I_{ac}^2/3.$$

but for sinusoidal currents with a significant d.c. component

$$I_e^2 = I_0^2 + I_{ac}^2/2.$$

Multi-layer wire windings (solid round wire)

It is assumed that all layers have equal breadth; a difference in number of turns per layer of one is permitted where N/p is not an integer.

- $d_{id} = 2,6 \{ b_w / (N f_e) \}^{1/6}$.
- Select the nearest standard wire size (for d and d_o) from a table such as that for IEC grade-1 winding wires.
- $p_{id} = N / \{ (b_w / d_o) - 1 \}$. Note: this expression is valid only for d_o from step 2.
 - If $p_{id} \geq 1,5$, and current density in wire d_{id} is too high, make a new design using a larger core.
 - If $p_{id} \leq 1,5$, consider a foil or strip winding.
 - If $p_{id} \leq 1$, the expression for d_{id} in step 1 is not valid: go to the single-layer winding procedure.
 Find p by rounding p_{id} to the next highest integer. Due to this rounding, there will be some space between turns.
- $H = p(d_o + i)$.
- If H exceeds H_a , or if current density is low:
 - reduce p by one layer,
 - select thickest wire for which $d_o \leq p b_w / (N + p)$,
 - repeat from step 4, even if $p = 1$.
- $F_R = 1 + 1/2(d/d_{id})^6$. Note: $F_R = 1,5$ for $d = d_{id}$; $F_R \approx 1$ if $d/d_{id} < 0,7$.
- $P_w = I_e^2 R_{ac} = I_e^2 F_R R_{dc}$. Note: d.c. wire resistance $0,0283/d^2 \Omega/m$. For I_e , see previous page.

Single-layer wire windings (solid round wire)

- Select thickest wire for which $d_o \leq b_w / (N + 1)$.
- $F_R = 0,33 d f_e^{1/2} N / (N + 1)$. Note: valid only if $p_{id} \leq 1$ (see above).
- $P_w = I_e^2 R_{ac} = I_e^2 F_R R_{dc}$. Note: wire resistance $0,0283/d^2 \Omega/m$. For I_e see previous page.

Bunched (Litz) wire windings

Eddy-current effects negligible: no special design procedure required. Copper density and thermal conductivity of winding low. Might be attractive if the ideal solid-conductor winding fills less than half the available height. Remember the 30% higher resistance at 100 °C.

Foil or strip windings

Here b_w is the width of the strip.

- $h_{id} = 3,1 (N f_e)^{-1/2}$.
- $h_{min} = 0,8 h_{id} \sqrt{N}$.
- $h_{max} = (H_a / N) - i$ (choose a value for i that is appropriate to a strip of thickness about H_a / N). If $h_{max} < h_{min}$, try a wire winding.
- Select from available materials a conductor of thickness h such that $h_{min} < h < h_{max}$. Aim for $h = h_{id}$.
- $F_R = 1 + (h/h_{id})^4 / 3$. For $h = h_{id}$, $F_R = 1,33$. For $h < 0,6 h_{id}$, $F_R \approx 1$.
- $P_w = I_e^2 R_{ac} = I_e^2 F_R R_{dc}$. Resistance of foil is $1/(45 b_w h) \Omega/m$. For I_e see previous page.

Reference

Jongsma, J. 1978. Minimum-loss transformer windings for ultrasonic frequencies. *E.A.B.* 35: 146 – 163 (no. 3) and 211 – 226 (no. 4).

E CORES (without air gap)*

type number	material grade FXC 3C8	material grade FXC 3E1
	catalogue number of one core	catalogue number of one core
→ E13/7/4 (EF 12,6)	4312 020 34470	
E20/10/5	● 4312 020 34070	● 4322 020 34830
E25/13/7	4312 020 34020	
E125/25/7	3122 134 90960	
E30/15/7	4312 020 34550	4322 020 34840
E42/21/15	● 4312 020 34110	● 4322 020 34850
I42/7/15		4322 020 37320
E42/21/20	● 4312 020 34120	
E42/33/20	4312 020 34190	
E55/28/21	● 4312 020 34100	● 4322 020 34900
E55/28/25	3122 134 90210	
E65/32/13		● 4322 020 34910
E65/32/27	● 4312 020 34380	

EC CORES (without air gap)*

type number	material grade FXC 3C8
	catalogue number of one core
EC35/17/10	● 4322 020 52500
EC41/19/12	● 4322 020 52510
EC52/24/14	● 4322 020 52520
EC70/34/17	● 4322 020 52530

ETD CORES

type number	catalogue number		
	gap width mm	nominal A_L nH	grade 3C8 grade 3C85
ETD34/17/11	$\cong 0$	$2500 \pm 25\%$	● 4312 020 37000 ● 4312 020 37200
	$0,1 \pm 0,02$	800	4312 020 37010 4312 020 37210
	$0,2 \pm 0,03$	480	4312 020 37020 4312 020 37220
	$0,5 \pm 0,05$	230	4312 020 37030 4312 020 37230
	$1,0 \pm 0,1$	140	4312 020 37040 4312 020 37240
ETD39/20/13	$\cong 0$	$2800 \pm 25\%$	● 4312 020 37050 ● 4312 020 37250
	$0,1 \pm 0,02$	1000	4312 020 37060 4312 020 37260
	$0,2 \pm 0,03$	600	4312 020 37070 4312 020 37270
	$0,5 \pm 0,05$	295	4312 020 37080 4312 020 37280
	$1,0 \pm 0,1$	170	4312 020 37090 4312 020 37290

● Preferred types.

* Cores with air gap are available on request.

ETD CORES (continued)

type number	gap width mm	nominal A_L nH	catalogue number	
			grade 3C8	grade 3C85
ETD44/22/15	$\cong 0$	$3500 \pm 25\%$	● 4312 020 37100	● 4312 020 37300
	$0,2 \pm 0,03$	800	4312 020 37110	4312 020 37310
	$0,5 \pm 0,05$	400	4312 020 37120	4312 020 37320
	$1,0 \pm 0,1$	230	4312 020 37130	4312 020 37330
	$1,5 \pm 0,15$	170	4312 020 37140	4312 020 37340
ETD49/25/16	$\cong 0$	$4000 \pm 25\%$	● 4312 020 37150	● 4312 020 37350
	$0,2 \pm 0,03$	1000	4312 020 37160	4312 020 37360
	$0,5 \pm 0,05$	480	4312 020 37170	4312 020 37370
	$1,0 \pm 0,1$	270	4312 020 37180	4312 020 37380
	$2,0 \pm 0,2$	150	4312 020 37190	4312 020 37390


U AND I CORES

type number	material grade FXC 3C8	
	catalogue number of one core	
U10/8/3	115/3/3	● 3122 134 91160
U15/11/6		● 3122 134 90690
U20/16/7	120/6/5	3122 134 90730
		● 3122 134 90200
U25/20/13	125/7/7	3122 134 90720
		● 3122 134 90460
U30/25/16		3122 134 90620
U30/25/16		● 3122 134 90760
U37/25/18	146/10/11	4312 020 34740
U37/29/18		4312 020 33710
U46/33/11		3122 104 90480
		3122 104 90470
U52/27/11		● 3122 134 90480
U57/28/16	158/13/16	4312 020 33190
U58/45/16		3122 104 94760
		3122 104 94770
U64/40/20		3122 134 91390
U70/33/17		3122 104 93950
U93/52/30	193/28/30	4312 020 33580
U93/76/30		4312 020 33570
		4312 020 33590
U93/76/16	193/28/16	4312 020 33550
		4312 020 33560
U100/57/25	1100/25/25	4312 020 33600
		4312 020 33610

The data on these cores are arranged on the following pages in order of type number.

- Preferred types.

E-CORE



Dimensions according to DIN 41985

Mass approx. 0,9 g

MAGNETIC DATA

Guaranteed values measured at 16 kHz for a core pair EE13/13/4, pressed together with a force of 30 N.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	catalogue number of one E core
3C8	25	≥ 140	50	4312 020 34470
	105	≥ 330	250	

Magnetic dimensions

$l_e = 29,6$ mm

$A_e = 13$ mm²


$V_e = 384$ mm³

Inductance factor A_L

at $f < 10$ kHz, $\theta = 25$ °C, $\hat{B} < 0,1$ mT : 800 $\begin{smallmatrix} +30\% \\ -20\% \end{smallmatrix}$

The core is available with air gap on request.

E-CORES



Dimensions according to DIN 41295

Mass approx. 4 g

MAGNETIC DATA

Guaranteed values for a core pair EE20/20/5, pressed together with a force of 55 N, air gap $\Delta = 0$.

	freq. kHz	temperature °C	\hat{B} mT	grade 3E1	grade 3C8
A_L	100	25 ± 10	$\leq 0,1$	1920 to 2890	$1300 \pm 25\%$ ←
μ_e	100	25 ± 10	$\leq 0,1$	2100 to 3155	
μ_e	100	23 to 70	$\leq 0,1$	≥ 2100	
$\frac{\tan \delta}{\mu_i} \times 10^6$	4	25 ± 10	$\leq 0,1$	$\leq 2,5$	
	100	25 ± 10	$\leq 0,1$	≤ 20	
	500	25 ± 10	$\leq 0,1$	≤ 200	
$\eta_B \times 10^3$	4	25 ± 10	1,5 to 3	$\leq 1,8$	
P(W)	16	25	200		$\leq 0,3$
	16	100	200		$\leq 0,25$
\hat{H} (A/m)	16	100	≥ 275		250

Catalogue number of one E core without air gap*, grade 3E1 ● 4322 020 34830
3C8 ● 4312 020 34070

Magnetic dimensions, according to IEC 205:

$$l_e = 42,8 \text{ mm} \quad C_1 = \sum \frac{l}{A} = 1,37 \text{ mm}^{-1}$$

$$A_e = 31,2 \text{ mm}^2 \quad V_e = 1340 \text{ mm}^3$$



* The cores are available with air gap on request.

● Preferred type.

COIL FORMERS

for shell type transformer EE20/20/5 (M20)

Without pins.




catalogue number

4312 021 28430

→ material
 minimum window area
 mean length of turn
 approximate mass
 maximum working temperature

polyamide 6,6, glass fibre reinforced
 27 mm²
 38 mm
 0,5 g
 130 °C


With 8 soldering pins.





catalogue number	4322 021 20240
material	phenolformaldehyde reinforced with glass fibre; brass dip-solder pins
minimum window area	27 mm ²
mean length of turn	38 mm
approximate mass	3 g
maximum temperature for dip-soldering during 5-6 s	280 °C
maximum working temperature	130 °C

E20/10/5

The coil former fits a shell type transformer EE20/20/5 (M20). The soldering pins will fit printed-wiring boards with a grid of 0,1 inch as well as 2,5 mm. The pin length is sufficient for a board thickness of up to 3 mm. The board should be provided with holes of $1,3 \pm 0,1$ mm diameter.



With 6 soldering pins.






7 Z85926

catalogue number	4322 021 20290
material	polyamide 6,6, glass fibre reinforced; copper nickel soldering pins
minimum window area	27 mm ²
mean length of turn	38 mm
approximate mass	3 g
maximum working temperature	130 °C

The coil former fits a shell type transformer EE20/20/5 (M20). The soldering pins will fit printed-wiring boards with a grid of 0,1 inch as well as 2,5 mm. The pin length is sufficient for a board thickness of up to 3 mm. The board should be provided with holes of $1,3 \pm 0,1$ mm diameter.

MOUNTING PARTS




(1). Clasp 4322 021 20160.
Material: brass, tin-plated.

(2). Spring 4322 021 20220.
Material: phosphor-bronze, tin-plated.


The construction is mounted by pushing the spring over the clasp in such a way that the lips A of the spring catch in the square holes B of the clasp. The mechanical pressure, required to keep the two E-cores together is exercised by means of two lips on top of the spring. No special tool is required for mounting the construction.

The construction can be used in the horizontal and vertical positions. If the construction is used in the vertical position, the lips C of the clasp must be bent. The dimensions and mutual distance of these lips are chosen in such a way that they fit printed-wiring boards with a grid of 0,1 " as well as those with a grid of 2,50 mm. If used in a horizontal position the clasp can be earthed by means of a copper wire soldered in hole D.

CHARACTERISTIC CURVES




For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

E-CORES



Dimensions according to DIN 41985

Mass 8,1 g

MAGNETIC DATA

Guaranteed values measured at 16 kHz for a core pair EE25/25/7, pressed together with a force of 60 N.

grade	temperature °C	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one E-core
3C8	25	200	250	$\leq 0,4$	● 4312 020 34020
	100	≥ 330		$\leq 0,35$	
	100	200			

Magnetic dimensions, according to IEC 205:

$$l_e = 57,5 \text{ mm}$$


$$A_e = 52,5 \text{ mm}^2$$

$$C_1 = \Sigma \frac{l_e}{A_e} = 1,095 \text{ mm}^{-1}$$

$$V_e = 3020 \text{ mm}^3$$

$$A_L = 1750 \pm 25\% \text{ at } f = 10 \text{ kHz; } \theta = 25 \text{ }^\circ\text{C; } \hat{B} \leq 0,1 \text{ mT}$$

- Preferred type.



MAGNETIC DATA

Guaranteed values measured at 16 kHz, for an E-and an I core pressed together with a force of 60 N.

grade	temperature °C	\hat{B} mT	H A/m	losses W	catalogue number
3C8	25	200		≤ 0,65	3122 134 90960
	25	≥ 380	250		
	100	≥ 100	50		


Magnetic dimensions

- $l_e = 57,5 \text{ mm}$
- $A_e = 52,5 \text{ mm}^2$
- $V_e = 3020 \text{ mm}^3$

COIL FORMERS

for shell type transformers EE25/25/7
and EI25/25/7

With 6 soldering pins.




7Z95128

catalogue number	4312 021 28540
material	polyamide 6,6 glass fibre reinforced
minimum window area	61 mm ²
mean length of turn	49 mm
approximate mass	4 g
maximum working temperature	130 °C




E25/13/7
E125/25/7

With 8 soldering pins.




catalogue number	4312 021 28750
material	polyamide 6,6 glass fibre reinforced
soldering pins	phosphor bronze dip-soldered
minimum window area	61 mm ²
mean length of turn	49 mm
approximate mass	4 g
maximum working temperature	130 °C

MOUNTING PARTS





7295130

Clasp.
material: nickel plated steel
catalogue number: 4312 021 26120



7295127


Maximum dimensions of the set.



7295129

Spring.
material: stainless steel
catalogue number: 4312 021 26190

E-CORES



Dimensions according to DIN 41295

Mass approx. 11 g

MAGNETIC DATA

Guaranteed values for a core pair EE30/30/7, pressed together with a force of 110 N, air gap $\Delta = 0$

	freq. kHz	temperature °C	\hat{B} mT	grade	
				3E1	3C8
A_L	100	25 ± 10	≤ 0,1	2660 to 4000	1900 ± 25%
μ_e	100	25 ± 10	≤ 0,1	2375 to 3565	
μ_e	100	23 to 70	≤ 0,1	≥ 2375	
$\frac{\tan \delta}{\mu_i} \times 10^6$	4	25 ± 10	≤ 0,1	≤ 2,5	
	100	25 ± 10	≤ 0,1	≤ 20	
	500	25 ± 10	≤ 0,1	≤ 200	
$\eta_B \times 10^3$	4	25 ± 10	1,5 to 3	≤ 1,8	
P (W)	16	25	200		≤ 0,48
	16	100	200		≤ 0,44
\hat{H} (A/m)	16	100	≥ 330		250

Catalogue numbers of one E-core without air gap:*

Ferroxcube grade 3E1 ● 4322 020 34840

3C8 ● 4312 020 34550

Magnetic dimensions according to IEC 205:

$l_e = 66,9 \text{ mm}$

$A_e = 59,7 \text{ mm}$

$C1 = \sum \frac{l}{A} = 1,12 \text{ mm}^{-1}$


$V_e = 4000 \text{ mm}^3$

* Cores with air gap are available on request.

● Preferred type.

COIL FORMERS

for shell type transformer EE30/30/7 (M30)



catalogue number

4312 021 28550

material

polyamide 6,6 glass fibre reinforced

minimum window area

80 mm²

mean length of turn

56 mm


approximate mass

1,3 g

maximum working temperature


130 °C

With soldering pins.




catalogue number	4322 021 20250
material	phenolformaldehyde reinforced with glass fibre; brass dip-solder pins
minimum window area	80 mm ²
mean length of turn	56 mm
approximate mass	3 g
maximum temperature for dip-soldering during 5-6 s	280 °C
maximum working temperature	130 °C

The coil former fits a shell type transformer EE30/30/7 (M30). The soldering pins will fit printed-wiring boards with a grid of 0,1 inch as well as 2,5 mm. The pin length is sufficient for a board thickness up to 3 mm. The board should be provided with holes of $1,3 \pm 0,1$ mm diameter.



72498351

MOUNTING PARTS




(1). Clasp 4322 021 20170
Material: brass, tin-plated.

(2). Spring 4322 021 20230
Material: phosphor-bronze, tin-plated.


The construction is mounted by pushing the spring over the clasp in such a way that the lips A of the spring catch in the square holes B of the clasp. The mechanical pressure, required to keep the two E-cores together is exercised by means of two lips on top of the spring. No special tool is required for mounting the construction.

The construction can be used in the horizontal and vertical positions. If the construction is used in the vertical position, the lips C of the clasp must be bent. The dimensions and mutual distance of these lips are chosen in such a way that they fit printed-wiring boards with a grid of 0,1" as well as those with a grid of 2,50 mm. If used in a horizontal position the clasp can be earthed by means of a copper wire soldered in hole D.

CHARACTERISTIC CURVES



For application classes I, II and III see 'Power choke design' in the Introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

E- AND I-CORES

Dimensions according to DIN 41295.



Mass approx. 42 g

Catalogue numbers

Ferroxcube grade

Catalogue number of E-core, without air gap*

Catalogue number of I-core

3E1

● 4322 020 34850
4322 020 37320

3C8

● 4312 020 34110

* Cores with air gap are available on request.

● Preferred type.

A transformer core can be built up by combining an even number of E-cores. A shape that is often chosen is the shell type transformer EE42/42/15 composed of two cores type E42/21/15 or the E-I combination EI42/29/15.

Magnetic dimensions according to IEC 205:

	EE42/42/15	EI42/29/15
Effective magnetic path length	$l_e = 97,0 \text{ mm}$	67,2 mm
Effective cross-sectional area	$A_e = 182 \text{ mm}^2$	183 mm ²
Core constant	$C_1 = \Sigma \frac{l_e}{A_e} = 0,534 \text{ mm}^{-1}$	0,367 mm ⁻¹
Effective core volume	$V_e = 17600 \text{ mm}^3$	12300 mm ³

MAGNETIC DATA

Guaranteed values for a core pair EE42/42/15 or EI42/29/15, pressed together with a force of 280 N, air gap $\Delta = 0$.

Magnetic properties at 25 ± 10 °C for grade 3E1

	EE42/42/15	EI42/29/15
μ_e	= 2570-3855*	2400-3600
A_L	= 6040-9070	8210-12320

At 4 kHz and \hat{B} between 1,5 and 3 mT

$$\eta_B \times 10^3 \leq 1,8 \text{ T}^{-1}$$

at 4 kHz and $\hat{B} \leq 0,1 \text{ mT}$

$$\frac{\tan \delta}{\mu_i} \times 10^6 \leq 2,5$$

At 100 kHz and $\hat{B} \leq 0,1 \text{ mT}$

$$\frac{\tan \delta}{\mu_i} \times 10^6 \leq 20$$

Magnetic properties for grade 3C8

At 16 kHz, $B = 200 \text{ mT}$ and $\theta = 100 \text{ }^\circ\text{C}$

$$P \leq 2 \text{ W}$$

▶ At 16 kHz, $B \geq 330 \text{ mT}$ and $\theta = 100 \text{ }^\circ\text{C}$

$$\hat{H} = 250 \text{ A/m}$$

At 16 kHz, $B \geq 90 \text{ mT}$ and $\theta = 100 \text{ }^\circ\text{C}$

$$\hat{H} = 50 \text{ A/m}$$


▶ $A_L = 3900 \pm 25\%$ at $f = 10 \text{ kHz}$, $\theta = 25 \text{ }^\circ\text{C}$, $\hat{B} \leq 0,1 \text{ mT}$

* In the temperature range +23 to +70 °C $\mu_e \geq 2575$.

COIL FORMERS

for shell type transformer EE42/42/15 (M42)


Without soldering pins.



catalogue number	4312 021 28620
material	polyamide 6,6 glass fibre reinforced
minimum window area	178 mm ²
mean length of turn	93 mm
approximate mass	4 g
maximum working temperature	130 °C

The dimensions are practically according to German specification DIN 41305.

With 10 soldering pins.



catalogue number

4322 021 31830

material

reinforced polyamide with
brass dip-soldered pins

minimum window area

178 mm²

mean length of turn

93 mm


approximate mass

4 g

maximum working temperature


130 °C

The coil former fits a shell type transformer EE42/42/15 (M42). The soldering pins will fit printed-wiring boards with a grid of 0,1 inch as well as 2,5 mm. The pin length is sufficient for a board thickness of up to 3 mm. The board should be provided with holes of $1,3 \pm 0,1$ mm diameter.



7299300.1

MOUNTING PARTS




Clasp 4322 021 31910
Material: chromium nickel steel.

Spring 4322 021 31920
Material: chromium nickel steel.

The construction is mounted by pushing the spring over the clasp in such a way that the lips A of the spring catch in the square holes B of the clasp. The mechanical pressure, required to keep the two E-cores together is exercised by means of two lips on top of the spring. No special tool is required for mounting the construction.


The construction can be used in the horizontal and vertical positions. If the construction is used in the vertical position, two fixing bushes 4322 021 30720 with nuts 4322 021 30710 must be applied in the holes of the clasp. If used in a horizontal position the clasp can be earthed by means of a copper wire soldered in hole C.

CHARACTERISTIC CURVES



Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.

E-CORES



E42/21/20

Mass 56 g



E42/33/20

Mass 82 g

Catalogue numbers

Ferroxcube grade 3C8

Catalogue number of core E42/21/20 without air gap*

Catalogue number of core E42/33/20 without air gap*

Catalogue number of combination of cores E42/21/20 + E42/33/20

● 4312 020 34120

4312 020 34190

4312 020 34170

SHELL TYPE TRANSFORMERS EE42/42/20 AND EE42/54/20

A transformer core can be built up by combining an even number of E-cores. Shapes that are often chosen are the shell type transformer EE42/42/20 composed of two cores E42/21/20, and shell type transformer EE42/54/20 composed of one core E42/21/20 and one core E42/33/20.

● Preferred type.

* Cores with air gap are available on request.

Magnetic dimensions according IEC 205:


	EE42/42/20	EE42/54/20
l_e	= 98 mm	122 mm
A_e	= 236 mm ²	236 mm ²
$C_1 = \Sigma \frac{l_e}{A_e}$	= 0,415 mm ⁻¹	0,517 mm ⁻¹
V_e	= 23100 mm ³	28800 mm ³

MAGNETIC DATA


At $f = 16$ kHz, $\hat{B} = 200$ mT, $\theta = 25$ °C
 $\theta = 100$ °C
 At $f = 16$ kHz, $\hat{B} \geq 90$ mT, $\theta = 100$ °C
 $\hat{B} \geq 315$ mT, $\theta = 100$ °C
 At $f = 10$ kHz, $\hat{B} \leq 0,1$ mT, $\theta = 25$ °C

	EE42/42/20	EE42/54/20
P		$\leq 3,5$ W
P	$\leq 2,6$ W	$\leq 3,2$ W
\hat{H}	= 50 A/m	
\hat{H}	= 250 A/m	250 A/m
A_L	= 5000 \pm 25%	3600 \pm 25%


CHARACTERISTIC CURVES




A_L based on a typical initial permeability of 2000 as a function of spacer thickness.




Typical magnetization curves for a pair of cores, in 3C8, with ambient temperature as parameter.




Total flux as a function of core temperature.



Typical transformer temperature rise as a function of total transformer loss in free air conditions.




Core loss as a function of total flux at 100°C with frequency as parameter.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

E-CORES



The dimensions are according to DIN 41295.

Mass approx. 115 g

Catalogue numbers

Ferroxcube grade 3E1, no air gap*

● 4322 020 34900

Ferroxcube grade 3C8, no air gap*

● 4312 020 34100

SHELL TYPE TRANSFORMER EE55/55/21

A transformer core can be built up by combining an even number of E-cores. A shape that is often chosen is the shell type transformer EE55/55/21 composed of two cores type EE55/28/21.

* Cores with air gap are available on request.

● Preferred type.

Magnetic dimensions according to IEC 205:

$$l_e = 123 \text{ mm}$$

$$A_e = 354 \text{ mm}^2$$

$$C_1 = \Sigma \frac{l_e}{A_e} = 0,348 \text{ mm}^{-1}$$


$$V_e = 43700 \text{ mm}^3$$

MAGNETIC DATA


Guaranteed values for a core pair EE55/55/21, pressed together with a force of 550 N, air gap $\Delta = 0$.

	freq. kHz	temp. °C	\hat{B} mT	grade	
				3E1	3C8
→ A_L	100	25 ± 10		9545 to 14330	6300 ± 25%
μ_e	100	25 ± 10		2645 to 3970	
$\eta_B \times 10^3$	4	25 ± 10	1,5 to 3	≤ 2,5	
P (W)	16	25	200		≤ 5,5
	16	100	200		≤ 5,0
\hat{H} (A/m)	16	100	315		250


CHARACTERISTIC CURVES




A_L based on a typical initial permeability of 2000 as a function of spacer thickness.




Typical magnetization curves for a pair of cores with ambient temperature as parameter, FXC 3C8.




Total flux as a function of core temperature.



Typical transformer temperature rise as a function of total transformer loss in free air conditions.




Core loss as a function of total flux at 100°C with frequency as parameter, FXC 3C8.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

COIL FORMER




for shell type transformer EE55/55/21




catalogue number	4312 021 28710
material	polyamide 6,6 glass fibre reinforced
minimum window area	250 mm ²
mean length of turn	116 mm
approximate mass	9 g
maximum working temperature	130 °C

The dimensions are according to German specification DIN 41305.

MOUNTING PARTS







Clasp.
Material: zinc plated steel, bichromated.
Catalogue number: 4312 021 26090



Spring.
Material: zinc plated stainless steel, bichromated.
Catalogue number: 4312 021 26130

E-CORES



7270933

Mass approx. 130 g

Catalogue numbers

Ferroxcube grade 3C8

Catalogue number of E-core without air gap*

3122 134 90210

SHELL TYPE TRANSFORMER EE55/55/25

A transformer core can be built up by combining an even number of E-cores. A shape that is often chosen is the shell type transformer EE55/55/25 composed of two cores type EE55/28/25.

Magnetic dimensions according to IEC 205:

$$l_e = 123 \text{ mm}$$

$$A_e = 420 \text{ mm}^2$$

$$C_1 = \Sigma \frac{l_e}{A_e} = 0,293 \text{ mm}^{-1}$$

$$V_e = 52000 \text{ mm}^3$$

Magnetic properties; $\Delta = 0$

$$\text{At } f = 16 \text{ kHz, } \hat{B} = 200 \text{ mT, } \theta = 25 \text{ }^\circ\text{C}$$

$$\theta = 100 \text{ }^\circ\text{C}$$

$$\text{At } f = 16 \text{ kHz, } \hat{B} \geq 315 \text{ mT, } \theta = 100 \text{ }^\circ\text{C}$$


$$P \leq 6,2 \text{ W}$$

$$P \leq 5,7 \text{ W}$$


$$\hat{H} = 250 \text{ A/m}$$

* Cores with air gap are available on request.


CHARACTERISTIC CURVES




Typical magnetization curves for a pair of cores with ambient temperature as parameter.




Total flux as a function of core temperature.




Typical transformer temperature rise as a function of total transformer loss in free air conditions.



Core loss as a function of total flux at 100°C with frequency as parameter.




A_L based on a typical permeability of 2000 as a function of spacer thickness.



Choke design chart.



For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

E-CORES



7242082

The dimensions are according to DIN 41295
 Mass approx. 103 g

Catalogue number

Ferroxcube grade 3E1
 Catalogue number of E-core ● 4322 020 34910

SHELL TYPE TRANSFORMER 65/65/27

A transformer core can be built up by combining an even number of E-cores. A shape that is often chosen is the shell type transformer 65/65/27 composed of four cores type E65/32/13.

Magnetic dimensions according to IEC 205:

$$l_e = 147 \text{ mm}; A_e = 532 \text{ mm}^2; C_1 = \Sigma \frac{l_e}{A_e} = 0,275 \text{ mm}^{-1}; V_e = 78200 \text{ mm}^3$$





MAGNETIC DATA

Guaranteed values for a combination of four E-cores, pressed together with a force of 400 N, air gap $\Delta = 0$.

	freq. kHz	temp. °C	\hat{B} mT	
A_L	100	25 ± 5		12355 to 18545
μ_e	100	25 ± 5		2705 to 4060
$\eta_B \times 10^3$	4	25 ± 5	1,5 to 3	≤ 4,3

* Cores with air gap are available on request.
 ● Preferred type.

E-CORES



7273956.1

Mass

Ferroxcube grade

Catalogue number of E-core, without air gap*

approx. 203 g

3C8

● 4312 020 34380

SHELL TYPE TRANSFORMER EE65/66/27

A transformer core can be built up by combining an even number of E-cores. A shape that is often chosen is the shell type transformer EE65/65/27 composed of two cores type E65/32/27.

Magnetic dimensions according to IEC 205:

$$l_e = 147 \text{ mm}$$

$$A_e = 532 \text{ mm}^2$$

$$C_1 = \Sigma \frac{l_e}{A_e} = 0,275 \text{ mm}^{-1}$$

$$V_e = 78200 \text{ mm}^3$$

Magnetic properties; $\Delta = 0$

$$\text{At } f = 16 \text{ kHz, } \hat{B} = 200 \text{ mT, } \theta = 25 \text{ }^\circ\text{C}$$

$$\theta = 100 \text{ }^\circ\text{C}$$

$$\text{At } f = 16 \text{ kHz, } \hat{B} \geq 315 \text{ mT, } \theta = 100 \text{ }^\circ\text{C}$$

$$\text{At } f = 10 \text{ kHz, } \hat{B} \leq 0,1 \text{ mT, } \theta = 25 \text{ }^\circ\text{C}$$

$$P \leq 9,5 \text{ W}$$

$$P \leq 8,7 \text{ W}$$

$$\hat{H} = 250 \text{ A/m}$$


$$A_L = 8000 \begin{matrix} +30\% \\ -20\% \end{matrix}$$

* Cores with air gap are available on request.


● Preferred type.

CHARACTERISTIC CURVES


Note: The curves shown on the following pages represent typical characteristics for a pair of E65 cores in 3C8.




Typical magnetization curves for a pair of cores with ambient temperature as a parameter.




Total flux as a function of core temperature.




Typical transformer rise as a function of total transformer loss in free air conditions.



Core loss as a function of total flux at 100 °C with frequency as parameter.




A_L based on a typical initial permeability of 2000 as a function of spacer thickness.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.




Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

COIL FORMER



for shell type transformer 65/65/27 (M65)



catalogue number	4312 021 28720
material	polyamide 6,6 glass fibre reinforced
minimum window area	394 mm ²
mean length of turn	150 mm
approximate mass	13 g
maximum working temperature	130 °C


The dimensions are according to German specification DIN 41305.

MOUNTING PARTS




VM 727124

Clasp.
Material: zinc plated steel, bichromated.
Catalogue number: 4312 021 26110



Spring.
Material: zinc plated stainless steel,
bichromated.
Catalogue number: 4312 021 26140

EC-CORE



Mass	approx. 18 g
Ferroxcube grade	3C8
Catalogue number of EC-core without air gap*	● 4322 020 52500

DIMENSIONAL PARAMETERS FOR A PAIR OF CORES

(Assuming nominal dimensions, unless otherwise stated).

Core constant**	$C_1 = 0,918 \text{ mm}^{-1}$
Minimum cross-sectional centre pole area	$A_{CPmin} = 66,5 \text{ mm}^2$
Cross-sectional centre pole area	$A_{min} = 71,0 \text{ mm}^2$
Back and leg cross-sectional area	$A_b = 96,0 \text{ mm}^2$
Centre pole volume	$V_{CP} = 1740 \text{ mm}^3$
Back and leg volume	$V_b = 6040 \text{ mm}^3$
Total core volume	$V_f = 7780 \text{ mm}^3$
Effective magnetic path length**	$l_e = 77,4 \text{ mm}$
Effective cross-sectional area**	$A_e = 84,3 \text{ mm}^2$
Effective core volume**	$V_e = 6530 \text{ mm}^3$

* Cores with air gap are available on request.

** According to IEC 205.




● Preferred type.

MAGNETIC PROPERTIES FOR A PAIR OF CORES WITHOUT AIR GAP

Relative amplitude permeability (μ_a) at $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 320\text{ mT}$ in A_{CPmin}	> 1000
Permissible induction in centre pole (\hat{B}) with min. cross-sectional area, at $\theta = 100\text{ }^\circ\text{C}$	$\leq 320\text{ mT}$
Resistivity (ρ), measured with d.c. current	$\geq 1\text{ }\Omega\text{m}$
Curie point	$\geq 200\text{ }^\circ\text{C}$
Effective total core loss (P) referred to A_e at $f = 25\text{ kHz}$, $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 160\text{ mT}$	$\leq 1,1\text{ W}$
Inductance factor A_L at → $f < 10\text{ kHz}$, $\theta = 25\text{ }^\circ\text{C}$, $\hat{B} < 0,1\text{ mT}$	$2100 \pm 25\%$

COIL FORMERS

Style 1



7269128.2

Material

phenolformaldehyde reinforced with glass fibre; brass dip-solder pins

Mounting

horizontal

Minimum window area

97,5 mm²

Mean length of turn

50 mm

Mass

approx. 6 g


Maximum temperature

140 °C


Catalogue number (coil former with pins)

4322 021 33410

Style 2



Tag arrangement



Material

polyteraphthalate, glass fibre reinforced, 13 solder-plated brass tags are inserted.

Mounting

horizontal

Minimum window area

97 mm²

Mean length of turn

53 mm

Mass

7 g

Flammability



according to UL 94 V-0

Catalogue number *

4322 021 33310

* Catalogue number of coil former, style 2, without tags: 4322 021 33000.

MOUNTING PARTS




1/ X 727116

Clasp.

Material: zinc plated steel, bichromated.

Catalogue number: 4312 021 26010




Spring.

Material: zinc plated steel, bichromated.

Catalogue number: 4312 021 26150


CHARACTERISTIC CURVES




(1) Recommended maximum working flux.
 Total flux as a function of ampere-turns.




Recommended maximum working flux as a function of core temperature.




Transformer temperature rise as a function of total core losses, in free air conditions, without heatsink.






Total core losses as a function of total flux at hot-spot core temperature.




Choke design chart.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

EC-CORE



Mass

approx. 26 g

Ferroxcube grade

3C8

Catalogue number of EC-core without air gap*

● 4322 020 52510

DIMENSIONAL PARAMETERS FOR A PAIR OF CORES

(Assuming nominal dimensions, unless otherwise stated.)

Core constant **

$C_1 = 0,735 \text{ mm}^{-1}$

Minimum cross-sectional centre pole area

$A_{CPmin} = 100,3 \text{ mm}^2$

Cross-sectional centre pole area

$A_{min} = 106 \text{ mm}^2$

Back and leg cross-sectional area

$A_b = 130 \text{ mm}^2$

Centre pole volume

$V_{CP} = 2950 \text{ mm}^3$

Back and leg volume

$V_b = 9650 \text{ mm}^3$

Total core volume

$V_f = 12600 \text{ mm}^3$

Effective magnetic path length **

$l_e = 89,3 \text{ mm}$

Effective cross-sectional area **

$A_e = 121 \text{ mm}^2$

Effective core volume **

$V_e = 10800 \text{ mm}^3$

* Cores with air gap are available on request.

** According to IEC 205.

● Preferred type.

MAGNETIC PROPERTIES FOR A PAIR OF CORES WITHOUT AIR GAP

Relative amplitude permeability (μ_a) at $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 320\text{ mT}$ in A_{CPmin}	> 1000
Permissible induction in centre pole (\hat{B}) with min. cross-sectional area, at $\theta = 100\text{ }^\circ\text{C}$	$\leq 320\text{ mT}$
Resistivity (ρ), measured with d.c. current	$\geq 1\text{ }\Omega\text{m}$
Curie point	$\geq 200\text{ }^\circ\text{C}$
Effective total core loss (P) referred to A_e at $f = 25\text{ kHz}$, $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 160\text{ mT}$	$\leq 2,2\text{ W}$
Inductance factor A_L at $f < 10\text{ kHz}$, $\theta = 25\text{ }^\circ\text{C}$, $\hat{B} < 0,1\text{ mT}$	$2700 \pm 25\%$



COIL FORMERS

Material

glass-fibre-filled polyteraphthalate;
solder-plated brass tags

Minimum window area

138 mm²

Mean length of turn

62 mm

Mass, 9 tags inserted

10 g

Flammability

according to UL 94 V-0

Mounting



horizontal and vertical

Catalogue number

see next page

Tag arrangement

see next page



72756/4.1

Tag arrangement

Horizontal mounting

Vertical mounting

9 tags inserted










12 tags inserted

9 tags inserted

catalogue number
4322 021 33320



catalogue number
4322 021 33480

catalogue number
4322 021 33350




Catalogue number of coil former with 21 tags: 4322 021 33490
 Catalogue number of coil former without tags: 4322 021 33010
 Catalogue number of tag: 4322 021 33060



MOUNTING PARTS



VM 727125




Clasp.
 Material: zinc plated steel, bichromated.
 Catalogue numbers:
 without mounting stud 4312 021 26020
 with mounting stud 4312 021 26030.




Spring.
 Material: zinc plated steel, bichromated.
 Catalogue number: 4312 021 26160.


CHARACTERISTIC CURVES




(1) Recommended maximum working flux.
 Total flux as a function of ampere-turns.




Recommended maximum working flux as a function of core temperature.




Transformer temperature rise as a function of total core losses, in free air conditions, without heatsink.






Total core losses as a function of total flux at hot-spot core temperature.



Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

EC-CORE



Mass

approx. 55,5 g

Ferroxcube grade

3C8

Catalogue number of EC-core without air gap*

● 4322 020 52520

DIMENSIONAL PARAMETERS FOR A PAIR OF CORES

(Assuming nominal dimensions, unless otherwise stated.)

Core constant **

$C_l = 0,581 \text{ mm}^{-1}$

Minimum cross-sectional centre pole area

$A_{CPmin} = 133,8 \text{ mm}^2$

Cross-sectional centre pole area

$A_{min} = 141,0 \text{ mm}^2$

Back and leg cross-sectional area

$A_b = 222,0 \text{ mm}^2$

Centre pole volume

$V_{CP} = 4480 \text{ mm}^3$

Back and leg volume

$V_b = 19820 \text{ mm}^3$

Total core volume

$V_f = 24300 \text{ mm}^3$

Effective magnetic path length **

$l_e = 105 \text{ mm}$

Effective cross-sectional area **

$A_e = 180 \text{ mm}^2$

Effective core volume **

$V_e = 18800 \text{ mm}^3$

* Cores with air gap are available on request.

** According to IEC 205.

● Preferred type.

MAGNETIC PROPERTIES FOR A PAIR OF CORES WITHOUT AIR GAP

Relative amplitude permeability (μ_a) at $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 320\text{ mT}$ in ACPmin	> 1000
Permissible induction in centre pole (\hat{B}) with min. cross-sectional area, at $\theta = 100\text{ }^\circ\text{C}$	$\leq 320\text{ mT}$
Resistivity (ρ), measured with d.c. current	$\geq 1\text{ }\Omega\text{m}$
Curie point	$\geq 200\text{ }^\circ\text{C}$
Effective total core loss (P) referred to A_e at $f = 25\text{ kHz}$, $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 160\text{ mT}$	$\leq 2,7\text{ W}$
Inductive factor A_L at $f < 10\text{ kHz}$, $\theta = 25\text{ }^\circ\text{C}$, $\hat{B} < 0,1\text{ mT}$	$3600 \pm 25\%$

COIL FORMER

Material

glass-fibre-filled polyteraphthalate;
solder-plated brass tags

Minimum window area

210 mm²

Mean length of turn

70 mm

Mass, 11 tags inserted

18 g

Flammability

according to UL 94 V-0

Mounting



horizontal and vertical

Catalogue number

see next page

Tag arrangement

see next page



7275658.1

Tag arrangement

Horizontal mounting

Vertical mounting

11 tags inserted







14 tags inserted

11 tags inserted

catalogue number
4322 021 33330




catalogue number
4322 021 33500

catalogue number
4322 021 33360



- Catalogue number of coil former without tags: 4322 021 33020
- Catalogue number of tag: 4322 021 33070

MOUNTING PARTS




Clasp.

Material: zinc plated steel, bichromated.

Catalogue number:

without mounting stud 4312 021 26040

with mounting stud 4312 021 26050.




Spring.

Material: zinc plated steel, bichromated.

Catalogue number: 4312 021 26170.


CHARACTERISTIC CURVES




(1) Recommended maximum working flux.
Total flux as a function of ampere-turns.





Recommended maximum working flux as a function of core temperature.



Transformer temperature rise as a function of total core losses, in free air conditions, without heatsink.








Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

EC-CORE



Mass
 Ferroxcube grade
 Catalogue number of EC-core without air gap*

approx. 126,5 g
 3C8
 ● 4322 020 52530

DIMENSIONAL PARAMETERS FOR A PAIR OF CORES

(Assuming nominal dimensions, unless otherwise stated.)

Core constant **	$C_l = 0,514 \text{ mm}^{-1}$
Minimum cross-sectional centre pole area	$A_{CPmin} = 201,1 \text{ mm}^2$
Cross-sectional centre pole area	$A_{min} = 211,0 \text{ mm}^2$
Back and leg cross-sectional area	$A_b = 386,0 \text{ mm}^2$
Centre pole volume	$V_{CP} = 9600 \text{ mm}^3$
Back and leg volume	$V_b = 46000 \text{ mm}^3$
Total core volume	$V_f = 55600 \text{ mm}^3$
Effective magnetic path length **	$l_e = 144 \text{ mm}$
Effective cross-sectional area **	$A_e = 279 \text{ mm}^2$
Effective core volume **	$V_e = 40100 \text{ mm}^3$

* Cores with air gap are available on request.

** According to IEC 205.

● Preferred type.

MAGNETIC PROPERTIES FOR A PAIR OF CORES WITHOUT AIR GAP

Relative amplitude permeability (μ_a) at $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 320\text{ mT}$ in A_{CPmin}	> 1000
Permissible induction in centre pole (\hat{B}) with min. cross-sectional area, at $\theta = 100\text{ }^\circ\text{C}$	$\leq 320\text{ mT}$
Resistivity (ρ), measured with d.c. current	$\geq 1\text{ }\Omega\text{m}$
Curie point	$\geq 200\text{ }^\circ\text{C}$
Effective total core loss (P) referred to A_e at $f = 25\text{ kHz}$, $\theta = 100\text{ }^\circ\text{C}$, $\hat{B} = 160\text{ mT}$	$\leq 5\text{ W}$
Inductance factor A_L at $f < 10\text{ kHz}$, $\theta = 25\text{ }^\circ\text{C}$, $\hat{B} < 0,1\text{ mT}$	$3900 \pm 25\%$



COIL FORMERS

Material

glass-fibre-filled polyteraphthalate;
solder-plated brass tags

Minimum window area

464 mm²

Mean length of turn

96 mm

Mass, 15 tags inserted

approx. 36 g

Flammability

according to UL 94 V-0

Mounting



horizontal and vertical

Catalogue numbers

see next page

Tag arrangement

see next page




Tag arrangement

Horizontal mounting

15 tags inserted


catalogue number
4322 021 33340





Vertical mounting

15 tags inserted



catalogue number
4322 021 33370



MOUNTING PARTS




Clasp.
 Material: zinc plated steel, bichromated.
 Catalogue number:
 without mounting stud 4312 021 26060
 with mounting stud 4312 021 26070.




Spring.
 Material: zinc plated steel, bichromated.
 Catalogue number: 4312 021 26180.


CHARACTERISTIC CURVES




(1) Recommended maximum working flux.
 Total flux as a function of ampere-turns.




Recommended maximum working flux as a function of core temperature.




Transformer temperature rise as a function of total core losses, in free air conditions, without heatsink.






Total core losses as a function of total flux at hot-spot core temperature.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.


INTRODUCTION

The Economic Transformer Design (ETD) series consists of a number of high frequency power cores in Ferroxcube 3C8 and 3C85, which have been optimized to meet the current requirements of switched-mode power supplies. The cores are available for assembly as ungapped or gapped versions, with a range of four nominal A_L values for the gapped cores.

Features

- Round centre pole for minimum conductor length.
- Maximum throughput power in the frequency range 20 to 150 kHz.
- Minimum core weight due to constant cross-sectional area and proper choice of transition frequency*.
- Winding breadth sufficient for full IEC mains isolation in specified configurations.
- Sufficient winding height for minimum loss windings.

Assembly and mounting



Coil former assembly operation.

The polyteraphthalate coil former is suitable for single spindle or automatic machine winding. It is terminated, after winding, to integral pins. The two cores are assembled to the coil former in one operation, as shown in the figure.


Two stainless steel clips retain the cores in the coil former assembly, maintaining adequate pressure at the mating pole faces.

The complete assembly is suitable for mounting on a printed-wiring board.

* Transition frequency is the frequency, at which the design changes from 'saturation limited' to 'core loss limited'.

ETD34 SYSTEM

FERROXCUBE CORE



Material: Ferroxcube grade 3C8 and 3C85

Mass per core: 20 g

gap width mm	nominal A_L nH	catalogue number	
		grade 3C8	grade 3C85
$\cong 0$	$2500 \pm 25\%$	● 4312 020 37000	● 4312 020 37200
$0,1 \pm 0,02$	800	4312 020 37010	4312 020 37210
$0,2 \pm 0,03$	480	4312 020 37020	4312 020 37220
$0,5 \pm 0,05$	230	4312 020 37030	4312 020 37230
$1,0 \pm 0,1$	140	4312 020 37040	4312 020 37240

The A_L values shown above apply to the gapped core indicated, assembled with an ungapped core.

- Preferred type.

EFFECTIVE PARAMETERS

For calculating the magnetic properties of a pair of cores, the following parameters should be used.

parameter	symbol	value	unit
effective magnetic path length	l_e	78.6	mm
effective area of magnetic path	A_e	97.1	mm ²
effective magnetic volume	V_e	7640	mm ³
core factor $\sum \frac{l}{A}$	C_1	0,8096	mm ⁻¹

NOMINAL DESIGN DATA FOR A PAIR OF CORES

parameter	symbol	value	unit
centre pole area	A_{min}	91,6	mm ²
length of the mean turn	l_w	60	mm

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C8

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60–100	25	$\hat{B} = 200 \text{ mT}^*$	<1,6	W
saturation induction (\hat{B}_{max})	100	25	H = 250 A/m	≥320	mT

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C85

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60–100	25	$\hat{B} = 200 \text{ mT}^*$	<1,1	W
		100	$\hat{B} = 100 \text{ mT}^*$	<1,3	W
saturation induction (\hat{B}_{max})	100	25	H = 250 A/m	≥320	mT

$$* \hat{B} = \frac{\sqrt{2}U}{\omega A_{min} N}$$

CHOKE DESIGN CHART

For application classes I, II and III see 'Power choke design' in the Introduction.

class I			class II*			class III**			centre leg gap width mm	core halves ▲ catalogue number 4312 020 followed by
$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH		
1,09	55,6	354	0,71	36,2	541	0,47	24,1	803	0,1	37000 & 37010
1,43	72,8	270	1,04	53,2	368	0,79	41,0	472	0,2	37010 & 37010
1,86	90,9	225	1,46	71,1	289	1,21	58,8	350	0,3	37010 & 37020
2,26	108	194	1,86	88,0	240	1,61	75,7	281	0,4	37020 & 37020
2,85	127	176	2,45	108	212	2,20	95,1	244	0,5	37000 & 37030
3,11	141	157	2,71	121	185	2,46	109	208	0,6	37010 & 37030
3,47	156	143	3,06	136	166	2,81	123	185	0,7	37020 & 37030
4,55	199	115	4,15	179	130	3,90	166	141	1,0	37030 & 37030
4,77	210	108	4,37	190	121	4,11	178	130	1,1	37010 & 37040
5,08	223	102	4,67	203	114	4,42	190	122	1,2	37020 & 37040
6,04	260	89	5,63	240	98	5,38	228	104	1,5	37030 & 37040
7,38	316	74	6,97	296	80	6,72	284	84	2,0	37040 & 37040


Calculate N_{min} with $N_{min} = \sqrt{L_{min}/A L_2} \times 10^{-9}$

▲ Preferred combinations.




* For frequencies beyond 40 kHz enter the table at $f/40 \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{f/40}$ (f in kHz).

** For frequencies beyond 10 kHz enter the table at $0,1 f \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{0,1 f}$ (f in kHz).

COIL FORMER



Pin arrangement



M0923.B

Material

glass-fibre-filled polyteraphthalate;
14 copper-nickel alloy pins are inserted

Minimum window area

123 mm²

Mean length of turn

60 mm

Flammability

according to UL94 V-0



Solderability

400 °C for 4 s

Catalogue number

4322 021 33850

MOUNTING PARTS




Assembly clip.
Material
Catalogue number

stainless steel
4322 021 33890

Earth clip.
Material
Terminations
Catalogue number


nickel silver
hot tinned
4322 021 33940



Both core halves can be connected to earth by means of this clip.

ETD39 SYSTEM

FERROXCUBE CORE



Material: Ferroxcube grade 3C8 and 3C85

Mass per core: 30 g

gap width mm	nominal A_L nH	catalogue number	
		grade 3C8	grade 3C85
$\cong 0$	$2800 \pm 25\%$	● 4312 020 37050	● 4312 020 37250
$0,1 \pm 0,02$	1000	4312 020 37060	4312 020 37260
$0,2 \pm 0,03$	600	4312 020 37070	4312 020 37270
$0,5 \pm 0,05$	295	4312 020 37080	4312 020 37280
$1,0 \pm 0,1$	170	4312 020 37090	4312 020 37290

The A_L values shown above apply to the gapped core indicated, assembled with an ungapped core.

- Preferred type.

EFFECTIVE PARAMETERS

For calculating the magnetic properties of a pair of cores, the following parameters should be used.

parameter	symbol	value	unit
effective magnetic path length	ℓ_e	92.2	mm
effective area of magnetic path	A_e	125	mm ²
effective magnetic volume	V_e	11 500	mm ³
core factor $\sum \frac{\ell}{A}$	C_1	0,7373	mm ⁻¹

NOMINAL DESIGN DATA FOR A PAIR OF CORES

parameter	symbol	value	unit
centre pole area	A_{min}	123	mm ²
length of the mean turn	ℓ_w	69	mm

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C8

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25	$\hat{B} = 200 \text{ mT}^*$	< 2,2	W
saturation induction (\hat{B}_{max})	100	25	$H = 250 \text{ A/m}$	≥ 320	mT

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C85

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25	$\hat{B} = 200 \text{ mT}^*$	< 1,6	W
		100	$\hat{B} = 100 \text{ mT}^*$	< 1,9	W
saturation induction (\hat{B}_{max})	100	25	$H = 250 \text{ A/m}$	≥ 320	mT

$$* \hat{B} = \frac{\sqrt{2} U}{\omega A_{min} N}$$

CHOKE DESIGN CHART

For application classes I, II and III see 'Power choke design' in the Introduction.

class I			class II*			class III**			centre leg gap width mm	core halves ▲ catalogue number 4312 020 followed by
$I_M^2 L$	$N_{max} \times I_M$	A_{L2}	$I_M^2 L$	$N_{max} \times I_M$	A_{L2}	$I_M^2 L$	$N_{max} \times I_M$	A_{L2}		
mJ	A	nH	mJ	A	nH	mJ	A	nH		
1,70	64,2	413	1,07	40,4	655	0,67	25,6	1022	0,1	37050 & 37060
2,17	81,8	324	1,53	57,8	457	1,12	42,8	610	0,2	37060 & 37060
2,76	100	274	2,11	76,2	363	1,69	61,1	453	0,3	37060 & 37070
3,32	118	239	2,66	93,6	304	2,24	78,5	365	0,4	37070 & 37070
4,15	138	217	3,49	114	270	3,07	98,6	316	0,5	37050 & 37080
4,51	152	195	3,85	128	236	3,43	113	270	0,6	37060 & 37080
5,01	168	178	4,34	143	212	3,92	128	240	0,7	37070 & 37080
6,53	212	145	5,86	188	167	5,44	172	183	1,0	37080 & 37080
6,84	224	136	6,17	200	155	5,75	184	169	1,1	37060 & 37090
7,27	237	129	6,60	213	146	6,18	197	158	1,2	37070 & 37090
8,62	277	113	7,94	252	125	7,53	237	135	1,5	37080 & 37090
10,51	335	94	9,84	310	102	9,42	295	108	2,0	37090 & 37090


Calculate N_{min} with $N_{min} = \sqrt{L_{min}/A_{L2}} \times 10^9$

▲ Preferred combinations.



* For frequencies beyond 40 kHz enter the table at $f/40 \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{f/40}$ (f in kHz).

** For frequencies beyond 10 kHz enter the table at $0,1 f \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{0,1 f}$ (f in kHz).

COIL FORMER



Pin arrangement



Material

glass-fibre-filled polyteraphthalate;
16 copper-nickel alloy pins are inserted

Minimum window area

177 mm²

Mean length of turn

69 mm

Flammability

according to UL94 V-0



Solderability

400 °C for 4 s

Catalogue number

4322 021 33860

MOUNTING PARTS




Assembly clip.
Material
Catalogue number

stainless steel
4322 021 33900

Earth clip.
Material
Terminations
Catalogue number


nickel silver
hot tinned
4322 021 33950



Both core halves can be connected to earth by means of this clip.

ETD44 SYSTEM

FERROXCUBE CORE



Material: Ferroxcube grade 3C8 and 3C85

Mass per core: 47 g

gap width mm	nominal A_L nH	catalogue number	
		grade 3C8	grade 3C85
$\cong 0$	$3500 \pm 25\%$	● 4312 020 37100	● 4312 020 37300
$0,2 \pm 0,03$	800	4312 020 37110	4312 020 37310
$0,5 \pm 0,05$	400	4312 020 37120	4312 020 37320
$1,0 \pm 0,1$	230	4312 020 37130	4312 020 37330
$1,5 \pm 0,15$	170	4312 020 37140	4312 020 37340

The A_L values shown above apply to the gapped core indicated, assembled with an ungapped core.

- Preferred type.

EFFECTIVE PARAMETERS

For calculating the magnetic properties of a pair of cores, the following parameters should be used.

parameter	symbol	value	unit
effective magnetic path length	ℓ_e	103	mm
effective area of magnetic path	A_e	173	mm ²
effective magnetic volume	V_e	17 800	mm ³
core factor $\sum \frac{\ell}{A}$	C_1	0,5886	mm ⁻¹

NOMINAL DESIGN DATA FOR A PAIR OF CORES

parameter	symbol	value	unit
centre pole area	A_{\min}	174	mm ²
length of the mean turn	ℓ_w	77	mm

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C8

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25	$\hat{B} = 200 \text{ mT}^*$	< 3,6	W
saturation induction (\hat{B}_{\max})	100	25	$H = 250 \text{ A/m}$	≥ 320	mT

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C85

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25 100	$\hat{B} = 200 \text{ mT}^*$ $\hat{B} = 100 \text{ mT}^*$	< 2,5 < 3	W
saturation induction (\hat{B}_{\max})	100	25	$H = 250 \text{ A/m}$	≥ 320	mT

$$* \hat{B} = \frac{\sqrt{2} U}{\omega A_{\min} N}$$

CHOKE DESIGN CHART

For application classes I, II and III see 'Power choke design' in the Introduction.

class I			class II*			class III**			centre leg gap width mm	core halves ▲ catalogue number 4312 020 followed by
$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	$A L_2$ nH		
3,63	91,7	431	2,56	63,9	626	1,89	46,7	866	0,2	37100 & 37110
5,10	127	317	4,01	98,8	410	3,32	81,4	501	0,4	37110 & 37110
6,33	148	289	5,24	120	364	4,56	102	435	0,5	37100 & 37120
7,62	179	238	6,52	151	287	5,82	133	329	0,7	37110 & 37120
9,91	226	194	8,81	198	225	8,12	180	250	1,0	37120 & 37120
11,0	253	172	9,93	225	197	9,23	207	216	1,2	37110 & 37130
13,1	295	151	12,0	266	169	11,3	249	183	1,5	37120 & 37130
14,1	319	139	13,0	291	154	12,3	273	165	1,7	37110 & 37140
16,0	357	125	14,9	329	138	14,2	311	147	2,0	37130 & 37130
18,7	416	108	17,6	387	117	16,9	369	124	2,5	37130 & 37140
21,2	470	96	20,1	442	103	19,4	424	108	3,0	37140 & 37140


Calculate N_{min} with $N_{min} = \sqrt{L_{min}/A L_2} \times 10^{-9}$

▲ Preferred combinations.




* For frequencies beyond 40 kHz enter the table at $f/40 \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{f/40}$ (f in kHz).

** For frequencies beyond 10 kHz enter the table at $0,1 f \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{0,1 f}$ (f in kHz).

COIL FORMER



Pin arrangement



M0929.B

Material

Minimum window area

Mean length of turn



Flammability

Solderability

Catalogue number

glass-fibre-filled polyteraphthalate;
 18 copper-nickel alloy pins are inserted
 214 mm²
 77 mm
 according to UL94 V-0
 400 °C for 4 s
 4322 021 33870


MOUNTING PARTS



Assembly clip.
Material
Catalogue number

stainless steel
4322 021 33910

M0930



Earth clip.
Material
Terminations
Catalogue number


nickel silver
hot tinned
4322 021 33960

7295126

Both core halves can be connected to earth by means of this clip.

ETD49 SYSTEM

FERROXCUBE CORE



Material: Ferroxcube grade 3C8 and 3C85

Mass per core: 62 g

gap width mm	nominal A_L nH	catalogue number	
		grade 3C8	grade 3C85
$\cong 0$	$4000 \pm 25\%$	● 4312 020 37150	● 4312 020 37350
$0,2 \pm 0,03$	1000	4312 020 37160	4312 020 37360
$0,5 \pm 0,05$	480	4312 020 37170	4312 020 37370
$1,0 \pm 0,1$	270	4312 020 37180	4312 020 37380
$2,0 \pm 0,2$	150	4312 020 37190	4312 020 37390

The A_L values shown above apply to the gapped core indicated, assembled with an ungapped core.

● Preferred type.

EFFECTIVE PARAMETERS

For calculating the magnetic properties of a pair of cores, the following parameters should be used.

parameter	symbol	value	unit
effective magnetic path length	ℓ_e	114	mm
effective area of magnetic path	A_e	211	mm ²
effective magnetic volume	V_e	24 000	mm ³
core factor $\sum \frac{\ell}{A}$	C_1	0,5335	mm ⁻¹

NOMINAL DESIGN DATA FOR A PAIR OF CORES

parameter	symbol	value	unit
centre pole area	A_{min}	211	mm ²
length of mean turn	ℓ_w	85	mm

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C8

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25	$\hat{B} = 200 \text{ mT}^*$	< 4,6	W
saturation induction (\hat{B}_{max})	100	25	$H = 250 \text{ A/m}$	≥ 320	mT

ELECTRICAL AND MAGNETIC PROPERTIES OF A PAIR OF CORES IN FXC 3C85

property	temperature (°C)	frequency (kHz)	parameter	value	unit
total power loss (P)	60 – 100	25 100	$\hat{B} = 200 \text{ mT}^*$ $\hat{B} = 100 \text{ mT}^*$	< 3,4 < 4	W
saturation induction (\hat{B}_{max})	100	25	$H = 250 \text{ A/m}$	≥ 330	mT

$$* \hat{B} = \frac{\sqrt{2} U}{\omega A_{min} N}$$

CHOKE DESIGN CHART

For application classes I, II and III see 'Power choke design' in the Introduction.



class I			class II*			class III**			centre leg gap width mm	core halves ▲ catalogue number 4312 020 followed by
$I_M^2 L$ mJ	$N_{max} \times I_M$ A	A_{L2} nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	A_{L2} nH	$I_M^2 L$ mJ	$N_{max} \times I_M$ A	A_{L2} nH		
4,68	97,5	492	3,25	66,9	727	2,35	47,8	1026	0,2	37150 & 37160
6,50	133	366	5,04	102	481	4,12	83,1	596	0,4	37160 & 37160
8,02	155	334	6,57	124	428	5,65	105	516	0,5	37150 & 37170
9,63	187	276	8,15	155	337	7,33	136	390	0,7	37160 & 37170
12,5	235	226	11,0	204	265	10,1	184	297	1,0	37170 & 37170
13,9	263	201	12,4	231	232	11,5	212	256	1,2	37160 & 37180
16,5	306	176	15,0	274	199	14,1	255	216	1,5	37170 & 37180
20,1	370	147	18,6	339	162	17,7	319	173	2,0	37180 & 37180
21,3	394	137	19,8	362	151	18,9	342	161	2,2	37160 & 37190
23,5	430	127	22,0	399	138	21,1	379	146	2,5	37170 & 37190
26,7	487	113	25,2	455	122	24,3	436	128	3,0	37180 & 37190
32,7	593	93	31,2	561	99	30,2	542	103	4,0	37190 & 37190

Calculate N_{min} with $N_{min} = \sqrt{L_{min}/A_{L2} \times 10^{-9}}$

▲ Preferred combinations.


* For frequencies beyond 40 kHz enter the table at $f/40 \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{f/40}$ (f in kHz).** For frequencies beyond 10 kHz enter the table at $0,1 f \times I_M^2 L$ and calculate $N_{max} = (N_{max} \times I_M)/I_M \times \sqrt{0,1 f}$ (f in kHz).

MOUNTING PARTS



Assembly clip.
Material
Catalogue number

stainless steel
4322 021 33920




Earth clip.
Material
Terminations
Catalogue number

nickel silver
hot tinned
4322 021 33970

Both core halves can be connected to earth by means of this clip.

I-15/3/3

I-CORE




7Z95133

Ferroxcube grade
Catalogue number

3C8
3122 134 90730

COIL FORMER


suited for one core I-15/3/3



Catalogue number

3122 134 02590

I-CORE




Ferroxcube grade
Catalogue number

3C8
3122 134 90720

COIL FORMER

suited for one core I-20/6/5




Catalogue number

3122 134 02540

I-25/7/7

I-CORE






7Z95132

Ferroxcube grade
Catalogue number

3C8
3122 134 90620

COIL FORMER


suited for one core I-25/7/7



Catalogue number

3122 137 64140

U-CORE



Mass 0,85 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-10/16/3.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	catalogue number of one U-core
3C8	25 100	≥ 140 ≥ 315	50 250	● 3122 134 91160


Magnetic dimensions

$l_e = 38,4$ mm
 $A_e = 8,6$ mm²
 $V_e = 330$ mm³

● Preferred type.


COIL FORMER

suited for two cores U-10/8/3



Catalogue number 3122 134 02590

U-CORE



Mass 4,35 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-15/22/6.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	≤ 0,18	● 3122 134 90690
	100	200	—	≤ 0,16	
	100	≥ 315	250	—	


Magnetic dimensions

$l_e = 48$ mm
 $A_e = 30$ mm²
 $V_e = 1440$ mm³

● Preferred type.


COIL FORMER

suited for two cores U-15/11/6



Catalogue number 3122 134 02540


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

U-CORE



Mass 9 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-20/32/7.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	$\leq 0,46$	● 3122 134 90200
	100	200	—	$\leq 0,42$	
	100	≥ 315	250	—	

Magnetic dimensions

$l_e = 68$ mm


$A_e = 56$ mm²

$V_e = 3800$ mm³

● Preferred type.


COIL FORMER

suited for two cores U-20/16/7



Catalogue number 3122 137 64140


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

U-CORE



Mass 21 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-25/40/13.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	$\leq 1,1$	● 3122 134 90460
	100	200	—	$\leq 1,0$	
	100	≥ 315	250	—	




Magnetic dimensions

$l_e = 86 \text{ mm}$
 $A_e = 100 \text{ mm}^2$
 $V_e = 8600 \text{ mm}^3$

● Preferred type.

COIL FORMER


suited for two cores U-25/20/13



7285871

Catalogue number 3122 137 61910


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

U-CORE



Mass 48 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-30/50/16.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	≤ 2,4	● 3122 134 90760
	100	200	—	≤ 2,0	
	100	≥ 335	400	—	




Magnetic dimensions

$l_e = 111 \text{ mm}$
 $A_e = 157 \text{ mm}^2$
 $V_e = 17400 \text{ mm}^3$

● Preferred type.

COIL FORMER


suited for two cores U-30/25/16



7285870

Catalogue number 3122 137 55360


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

U-CORE



Mass 48 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for a core pair UU 37/50/18

grade	temperature °C ± 5%	induction B (mT)	field strength H (A/m)	losses W	catalogue number
3C8	25	200	—	≤ 2,3	4312 020 34740
	100	200	—	≤ 2,1	
	100	≥ 330	250	—	

Magnetic dimensions

$l_e = 125 \text{ mm}$
 $A_e = 150 \text{ mm}^2$
 $V_e = 18800 \text{ mm}^3$

U-CORE



Mass 55.9

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core pair UU 37/58/18

grade	temperature °C ± 5%	induction B (mT)	field strength H (A/m)	losses W	catalogue number
3C8	25	200	—	≤ 2,6	● 4312 020 33710
	100	200	—	≤ 2,4	
	100	≥ 330	250	—	

Magnetic dimensions


$l_e = 145 \text{ mm}$

$A_e = 150 \text{ mm}^2$

$V_e = 21500 \text{ mm}^3$

- Preferred type.

UI-CORES



Mass U-core 38 g
I-core 20 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for a core-pair UI-46/43/11.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	shape	catalogue number of one core
3C8	25	200	—	≤ 1,97	U	3122 104 90480
	100	200	—	≤ 1,62	I	3122 104 90470
	100	≥ 290	250	—		

Magnetic dimensions

l_e = 129 mm
 A_e = 88 mm²
 V_e = 11600 mm³

U-CORE



Mass 40 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-52/56/11.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number one U-core
3C8	25	200	—	≤ 1,9	● 3122 134 90480
	100	200	—	≤ 1,75	
	100	≥ 330	250	—	

Magnetic dimensions


$l_e = 165$ mm

$A_e = 95$ mm²

$V_e = 15700$ mm³

● Preferred type.

U-CORE



Mass 70 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-57/57/16.




grade	temperature °C ± 5	induction \vec{B} (mT)	field strength \vec{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	≤ 3,3	4312 020 33190
	100	200	—	≤ 3,05	
	100	≥ 330	250	—	

Magnetic dimensions

$l_e = 163$ mm
 $A_e = 171$ mm²
 $V_e = 27500$ mm³

* The difference in splay between two U-cores, taken at random from one packing, will never exceed 0,8 mm.

UI-CORES



Mass U-core 98 g
I-core 50 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for a core-pair UI-58/58/16.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	shape	catalogue number of one core
3C8	25	200	—	$\leq 3,5$	U	3122 104 94760
	100	200	—	$\leq 3,2$	I	3122 104 94770
	100	≥ 330	250	—		

Magnetic dimensions

$l_e = 164$ mm; $A_e = 175$ mm²; $V_e = 28\,800$ mm³.

U-CORE



Mass 155 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for a core-pair UU-64/79/20

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength H (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	$\leq 8,5$	3122 134 91390
	100	200	—	$\leq 7,0$	
	100	≥ 330	250	—	

Magnetic dimensions

$l_e = 210$ mm
 $A_e = 290$ mm²
 $V_e = 61000$ mm³


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

U-CORE



Mass 108 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for a core-pair UU-70/67/17.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	catalogue number of one U-core
3C8	25	200	—	≤ 5,3	3122 104 93950
	100	200	—	≤ 5,0	
	100	≥ 330	250	—	

Magnetic dimensions


l_e = 197 mm

A_e = 214 mm²

V_e = 43800 mm³

* The difference in splay between two U-cores taken at random from one packing will never exceed 1 mm.

UI-CORES



Mass U-core 403 g
I-core 194 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for core-pairs UI-93/104/16 and UU-93/152/16.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	shape	catalogue number of one core
3C8	25	200	—	≤ 12,8	UI	4312 020 33550 4312 020 33560
	100	200	—	≤ 11,8		
	100	≥ 330	250	—		
3C8	25	200	—	≤ 17,6	UU	4312 020 33550
	100	200	—	≤ 16,2		
	100	≥ 290	250	—		

Magnetic dimensions

	UI-93/104/16	UU-93/152/16	
l_e	254	350	mm
A_e	420	450	mm ²
V_e	107 000	147 000	mm ³


CHARACTERISTIC CURVES



Choke design chart.


For application classes I, II and III see 'Power choke design' in the Introduction.

CHARACTERISTIC CURVES



Choke design chart.
For application classes I, II and III see 'Power choke design' in the Introduction.

UI-CORES



Mass U-core 756 g
 I-core 365 g

MAGNETIC DATA


Guaranteed values, measured at 16 kHz, for core-pairs UI-93/104/30 and UU-93/152/30.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	shape	catalogue number of one core
3C8	25	200	—	≤ 24,0	UI	4312 020 33570 4312 020 33590
	100	200	—	≤ 22,0		
	100	≥ 330	250	—		
3C8	25	200	—	≤ 32,8	UU	4312 020 33570
	100	200	—	≤ 30,0		
	100	≥ 290	250	—		

Magnetic dimensions

	UI-93/104/30	UU-93/152/30	
l_e	254	350	mm
A_e	780	780	mm ²
V_e	200 000	273 000	mm ³


CHARACTERISTIC CURVES



Choke design chart.

For application classes I, II and III see 'Power choke design' in the Introduction.

UI-CORES



Mass U-core 506 g
I-core 310 g

MAGNETIC DATA

Guaranteed values, measured at 16 kHz, for core-pairs UI-100/82/25 and UU-100/114/25.

grade	temperature °C ± 5	induction \hat{B} (mT)	field strength \hat{H} (A/m)	losses W	shape	catalogue number of one core
3C8	25	200	—	≤ 17,9	UI	4312 020 33600 4312 020 33610
	100	200	—	≤ 16,4		
	100	≥ 330	250	—		
3C8	25	200	—	≤ 24,5	UU	4312 020 33600
	100	200	—	≤ 20,5		
	100	≥ 290	250	—		

Magnetic dimensions

	UI-100/82/25	UU-100/114/25	
l_e	240	300	mm
A_e	620	620	mm ²
V_e	149 000	186 000	mm ³

SECTION D
MATERIALS AND CORES FOR MAGNETIC RECORDING

MATERIALS AND CORES FOR MAGNETIC RECORDING

These grades of Ferroxcube were developed primarily for the production of magnetic recording heads in audio, video and industrial and professional applications. Their high density give these materials excellent performance in these applications. The main features are the high resistance to wear and good magnetic performance resulting from the well-controlled micro-structure. This structure enables machining, lapping and high-gloss polishing. Glass or epoxy bonding may be used. The materials are available void-free in the form of bars, tiles, core configurations and cores with glass-bonded gaps. Our experience in the processing and machining of ferrite allows ferrite materials to be ground to virtually any shape with very tight tolerances.

MATERIAL DATA

FXC 8C1

This NiZn material is used for the manufacturing of recording heads for industrial and professional applications, including data processing, professional audio recorders and instrumentation recorders.

Material properties

Unless otherwise stated, all properties of the material have been measured at an atmospheric pressure of 86 to 106 kPa and at a relative humidity of 45 to 75%. Measured on a machined toroid, dimensions approx. ϕ 23 x ϕ 14 x 6 mm. The coefficient of expansion, α_m , is measured on a rod of approx. 2 x 2 x 10 mm and determined by : $\alpha_m = \Delta L/L_{20} (T-20)$.

	freq. kHz	B mT	temp. °C	typical values
initial permeability	4	< 0,1	25 ± 5	1600
Curie point	4	< 0,1		150 °C
resistivity	d.c.		25 ± 5	1 x 10 ⁴ Ωm
density			25 ± 5	5330 kg/m ³
hardness (Vickers)*			25 ± 5	750 Hv 0,05/30
coefficient of linear expansion, α_m				see Fig. 4

FXC 8C1 is available in the form of bars:

140 ± 2 mm x 45 ± 2 mm x 35 + 2 mm, catalogue number 4322 020 43020 or custom-made shapes on request.

* Measured with 0,05 kg for 30 s.

8C1




Fig. 1.

8C1






Fig. 2.



8C1

Fig. 3.



8C1

Fig. 4 Coefficient of linear expansion as a function of the temperature.

NON-MAGNETIC STRUCTURAL MATERIALS

Two grades of non-magnetic structural materials, 8A5 and 8A41 for use in combination with NiZn and MnZn ferrites respectively are available as the non-magnetic component of glass-bonded structures. The matched coefficient of thermal expansion, the absence of pores and the excellent resistance to wear give a stable and tight-toleranced tape contact surface to the recorder head.

Material properties

The properties of the materials have been measured at an atmospheric pressure of 86 to 106 kPa and at a relative humidity of 45 to 75%. The density has been measured on a plate, dimensions approx. 22 x 35 x 4 mm; the coefficient of expansion on a rod of approx. 2 x 2 x 10 mm. The α_m value is determined by $\alpha_m = \Delta L/L_{20} (T-20)$.

material	8A5	8A41	
density	typ. 4700	4090	kg/m ³
coefficient of linear expansion α_m	See Fig. 5.	See Fig. 5	
hardness (Vickers), measured with 0,05 kg for 30 s	1300	1100	Hv 0,05/30




Fig. 5.

Available shapes

grade	dimensions (mm)	catalogue number
8A5	145 ± 5 x 35 ± 3 x 22 ± 2	4322 020 97630
8A5	210 ± 6 x 37 ± 3 x 34 ± 3	4322 020 97640
8A41	145 ± 5 x 35 ± 3 x 22 ± 2	4322 020 97720

Other shapes on request.

FXC 8E1, 8E2 and 8E21

These manganese-zinc materials are intended for the production of erasing heads for audio and video applications. Effective erasing of magnetic tape for a low-noise level requires a high level of induction at a frequency in the range 50 to 100 kHz. Thus, for the use in erasing heads, a low eddy-current-loss core material is recommended. Low eddy current losses imply low heat dissipation and consequently less erasing power. Material FXC 8E1 is intended for erasing heads for iron-oxide or chromium dioxide tapes. Materials FXC 8E2 and 8E21 are for erasing heads for metal tapes.


Material properties

Unless otherwise stated, all properties of the material have been measured at an atmospheric pressure of 86 to 106 kPa and at a relative humidity of 45 to 75%. The coefficient of expansion, α_m , is measured on a rod of approx. 2 x 2 x 10 mm and determined by : $\alpha_m = \Delta L/L_{20} (T-20)$.

	freq. kHz	B mT	H A/m	temp. °C	8E1	grade 8E2 typical values	8E21	
μ_i	4	< 0,1		25 ± 5	3200	2800	3600	
B_s	ballistic		250	25 ± 5	400	490	490	mT
$\frac{\tan \delta}{\mu_i}$	100	< 0,1		25 ± 5	$3 \cdot 10^{-6}$	$3 \cdot 10^{-6}$	$2,5 \cdot 10^{-6}$	
η_B	100	1,5 to 3		25 ± 5	$0,5 \cdot 10^{-3}$	$0,5 \cdot 10^{-3}$	$0,5 \cdot 10^{-3}$	T ⁻¹
power losses	45	100	25	25 ± 5 85 ± 5	$40 \cdot 10^3$ $60 \cdot 10^3$	$40 \cdot 10^3$ $60 \cdot 10^3$	$20 \cdot 10^3$ $50 \cdot 10^3$	W/m ³ W/m ³
Curie temp.	4	< 0,1			180	180	210	°C
resistivity	d.c.			25 ± 5	5*	5*	3*	Ωm
density				25 ± 5	4700	4700	4750	kg/m ³
hardness (Vickers)**					560	730	730	Hv 0,05/30
linear expansion coefficient α_m					Fig. 9	Fig. 13	Fig. 17	

Unless otherwise stated, measured on a machined toroid, dimensions approximately $\phi 23 \times \phi 14,5 \times 6$ mm. Note: The properties of the products made from this material are dependent on dimensions and technology of the product. Deviations may occur.

The materials are available in the form of bars:
 100 x 35 x 7,8 mm 8E2 catalogue number 4322 020 97500
 100 x 28 x 12,5 mm 8E1 catalogue number 4322 020 37400
 100 x 35 x 12,5 mm 8E1 catalogue number 4322 020 37480
 100 x 35 x 14 mm 8E1 catalogue number 4322 020 37470
 100 x 49 x 14 mm 8E1 catalogue number 4322 020 37460
 215 x 37 x 26 mm 8E21 catalogue number 4322 020 97680
 and in custom made shapes on request, see photograph.



780118-21-02

* Measured on a machined bar, dimensions approximately 3 x 2 x 15 mm.

** Measured with 0,05 kg for 30 s.

8E1




Fig. 6.

8E1






Fig. 7.



8E1

Fig. 8.



8E1

Fig. 9 Coefficient of linear expansion as a function of the temperature.

8E2




Fig. 10.

8E2






Fig. 11.



8E2

Fig. 12.



8E2

Fig. 13 Coefficient of linear expansion as a function of the temperature.

8E21




Fig. 14.

8E21






Fig. 15.

Measured on a toroid $\phi 9 \times \phi 5 \times 0,5$ mm.



8E21

Fig. 16.



8E21

Fig. 17 Coefficient of linear expansion as a function of temperature.

MAGNETIC RECORDING

FXC 8X1

This MnZn single-crystal ferrite is mainly used as the basic material for the manufacture of video cassette recorder heads. The unique magnetic properties, homogeneity, outstanding wear resistance and the ability to machine this material to extremely tight tolerances, makes FXC 8X1 ideal for video use and other applications where a specified signal level with high information density on a very small track width is required.

Magnetic and mechanical characteristics of MnZn single-crystal ferrites depend on the direction of orientation of the crystal.

For details please consult us.

- The coefficient of expansion, α_m , is measured on a rod of approx. $2 \times 2 \times 10$ mm and determined by: $\alpha_m = \Delta L/L_{20}$ (T-20).

Material properties


	freq. kHz	B mT	H A/m	typical value	
μ_i	500	≤ 1		1800*	
	5000	≤ 1		600**	
$\frac{\tan \delta}{\mu_i}$	5000	≤ 1		2×10^{-3} **	
B_{sat}	ballistic		800	490*	mT
B_r	ballistic			140*	mT
H_c	ballistic		800	3*	A/m
resistivity	d.c.			$3 \cdot 10^{-3}$	Ωm
linear expansion coefficient α_m				see Fig. 21	
Curie point	< 10			180	$^{\circ}C$
hardness (Vickers), measured with 0,05 kg during 30 s				730	Hv 0,05/30

The material is available in oriented tiles; one side polished to a flatness of $0,5 \mu m$:

- $16 \times 8 \times 1,52$ mm, catalogue number 4322 020 97690.


Other dimensions and orientations can be supplied on request.

Diagram showing the orientations of the tile 4322 020 97690.




* Measured on toroid $\phi 9 \times \phi 5 \times 0,5$ mm.

** Measured on toroid $\phi 9 \times \phi 5 \times 0,2$ mm.



8X1

Fig. 18.



8X1

Fig. 19.

8X1




Fig. 20.

8X1




Fig. 21 Coefficient of linear expansion as a function of the temperature.


SECTION E
SMALL CORES AND CHOKES

IRON POWDER MATERIALS

Small cores, e.g. pins, rods, tubes, toroids and U cores can be supplied in iron powder materials. Six different grades can be made as mentioned below.

Details on dimensions and catalogue numbers on request.

grade	1P04	1P11	1P30	2P45	2P70	2P90	unit
initial permeability	4	11	30	45	70	90	± 10%
frequency	3 - 63	1,5 - 45	0,3 - 5	0,01 - 0,1	0,01 - 0,1	0,01 - 0,1	MHz
loss factor	800 - 3000	350 - 2000	300 - 2500	2500	2000	2000	$\times 10^{-6}$
temp. factor	10	15	3	19	12	15	$\times 10^{-9}/K$
max. operating temp.	130	130	140	140	140	140	°C
radial breaking strength	10	37	25	12	19	24	kN/mm ²



Frequency ranges for the various iron powder materials.

TOROIDS

Toroids, having no air gap, generate only a small magnetic stray field and thus have a high permeability. In spite of the closed magnetic circuit the losses are low due to the favourable properties of Ferroxcube. They are used in small broadband transformers and pulse transformers. Toroids are also effective for interference suppression filters when they function as differential transformers offering no impedance to symmetrical line-current flow, since no flux change takes place in the core due to these currents. However, unsymmetrical current drawn unequally from either the line or the power supply will cause flux changes and the windings will act as an impedance to this current flow. Toroids are not recommended for tuned circuits.

Toroids are available in various sizes and Ferroxcube grades. They are barrel-finished and can be obtained in nylon insulated or non-coated versions.




Table 1 Dimensional quantities, tolerances and mass of non-coated toroids.

D mm	d mm	h mm	l_e mm	$\Sigma \frac{1}{A}$ mm^{-1}	V_e mm^3	mass g
4 ± 0,1	2,2 ± 0,1	1,1 ± 0,1	9,46	9,56	9,37	0,045
6 ± 0,15	4 ± 0,15	2 ± 0,1	15,5	7,75	31,0	0,15
9 ± 0,2	6 ± 0,2	3 ± 0,1	23,3	5,17	105	0,50
14 ± 0,3	9 ± 0,25	5 ± 0,15	35,5	2,85	445	2,14
19 ± 0,4	10,6 ± 0,3	15 ± 0,3	44,0	0,718	2690	14
23 ± 0,5	14 ± 0,35	7 ± 0,2	57,0	1,81	1790	8,6
26 ± 0,55	14,5 ± 0,45	10 ± 0,3	60,3	1,08	3360	17
26 ± 0,55	14,5 ± 0,45	20 ± 0,45	60	0,538	6660	35
29 ± 0,5	19 ± 0,4	7,5 ± 0,2	75,0	2,01	2580	13
36 ± 0,7	23 ± 0,5	10 ± 0,2	92,0	1,42	5600	29
36 ± 0,7	23 ± 0,5	15 ± 0,3	92,0	0,942	8500	44

Notes

1. All μ -values in the following pages are determined with the $\Sigma \frac{1}{A}$ values of Table 1 at 25 °C.

The relevant A_L values can be calculated from: $A_L = \frac{0,4 \pi \mu}{\Sigma \frac{1}{A}}$. (A_L in nH, $\Sigma \frac{1}{A}$ in mm^{-1}).

2. L can be calculated from the formula: $L = A_L \cdot N^2$ (L in nH).

3. The smaller a toroid, the more its properties deviate from the material properties. Therefore a straightforward translation of the material figures is not always possible.

TOROIDS

Table 2. Dimensions and tolerances of coated toroids

D mm	d mm	h mm	Insulation breakdown kV	Derived from non-coated toroids with dimensions
≤ 4,5	≥ 1,7	≤ 1,6	≥ 1,5	4 x 2,2 x 1,1
≤ 6,55	≥ 3,45	≤ 2,5	≥ 1,5	6 x 4 x 2
≤ 9,7	≥ 5,3	≤ 3,6	≥ 1,5	9 x 6 x 3
≤ 14,9	≥ 8,15	≤ 5,75	≥ 1,5	14 x 9 x 5
≤ 24,3	≥ 12,85	≤ 8,0	≥ 2	23 x 14 x 7
≤ 30,3	≥ 17,7	≤ 8,5	≥ 2	29 x 19 x 7,5
≤ 37,5	≥ 21,7	≤ 11,0	≥ 2	36 x 23 x 10
≤ 37,5	≥ 21,7	≤ 16,0	≥ 2	36 x 23 x 15

Table 3. Grades, sizes and catalogue numbers.


grade	μ_i	colour coating	dimensions * mm	nylon coated non-coated	
				catalogue number 4322 020	
3E1	2700 ± 20% at 25 °C	green	29 x 19 x 7,5	97000	31310
			36 x 23 x 10	97010	31320
			36 x 23 x 15	97020	31330
3E2	> 5000 at +25 to +70 °C	blue	4 x 2,2 x 1,1	97030	31420
			6 x 4 x 2	97040	31430
			9 x 6 x 3	97050	31440
			14 x 9 x 5	97060	31450
			23 x 14 x 7	97070	31460
3E5	10 000 ± 25% at 25 °C	—	14 x 9 x 5	—	95190
			29 x 19 x 7,5	—	95160
			36 x 23 x 10	—	95520
			36 x 23 x 15	—	95180
3H2	2300 to 3100 at +25 °C $D_F \leq 5 \times 10^{-6}$ at 23 ± 1 °C	grey	4 x 2,2 x 1,1	97110	31350
			6 x 4 x 2	97120	31370
			9 x 6 x 3	97130	31380
			14 x 9 x 5	97140	31390
			23 x 14 x 7	97150	31400
4C6	> 100 at +5 to +55 °C	violet	6 x 4 x 2	97160	90750
			9 x 6 x 3	97170	90760
			14 x 9 x 5	97180	90770
			23 x 14 x 7	97190	90860
			36 x 23 x 15	97200	90870
				catalogue number 4312 020	
3C11	4000 ± 25%	white	19 x 10,6 x 15	—	36300
			26 x 14,5 x 10	—	36280
			26 x 14,5 x 20	—	36250
			36 x 23 x 15	—	36310

* These dimensions refer to non-coated toroids. More exact details are given in Tables 1 and 2.

RODS AND TUBES

Ferroxcube rods and tubes can be used in r.f. and h.f. coils with an open magnetic circuit such as in i.f. transformers, fixed or adjustable inductances, and filters. Not only tubes, used as beads, are suitable for interference suppression but also small rods (pins) can effectively be used because of their relatively high insensitivity for premagnetization.

The table below lists standard diameters and matching lengths of rods and tubes. On the next page details are given on length tolerances and curvature limits, followed by a type list of currently available types.



RODS

grade	dia. group	length group	dia. tol. group	matching length
	mm	mm	mm	mm
	1,6	5-30	-0,2	5-30
			-0,05	5-8
			-0,03	5-8
	2,0	5-30	-0,2	5-30
			-0,05	5-10
			-0,03	5-10
3B	2,5	5-30	-0,25	5-30
3C6			-0,1	5-20
3C8			-0,05	5-10
3D3	3,1	5-30	-0,25	5-30
3E1			-0,1	5-25
3H2			-0,05	5-15
4A4	4,0	8-30	-0,3	8-30
4B1			-0,1	8-30
4C6			-0,05	8-20
4D1	5,0	10-50	-0,3	10-50
4D2			-0,1	10-40
4E1			-0,05	10-30
	6,3	10-60	-0,3	10-60
			-0,1	10-45
			-0,5	10-100
	10,0	10,100		

TUBES

outer dia. group	inner dia. max.	inner dia. tol.	length group	outer dia. tol. group	matching length
mm	mm	mm	mm	mm	mm
	2,5	1,0	+0,15	3-30	-0,3
					-0,1
					-0,05
	3,1	1,5	+0,15	3-30	-0,3
					-0,1
					-0,05
	4,0	2,0	+0,2	4-40	-0,3
					-0,1
					-0,05
	5,0	3,0	+0,2	5-50	-0,3
					-0,1
					-0,05
	6,3	4,0	+0,3	10-60	-0,3
					-0,1
					-0,05
	10,0	6,0	+0,3	10,60	-0,4

CORES FOR SMALL FIXED CHOKES

Tolerances on length (in mm) of standard-size rods and tubes.

length	tolerance class	
	coarse	fine
< 6	0	0
	-0,4	-0,2
6-8	0	0
	-0,5	-0,3
8-10	0	0
	-0,6	-0,6
10-13	0	0
	-0,7	-0,4
13-16	0	0
	-0,8	-0,4
16-20	0	0
	-0,9	-0,4
> 20	0	0
	4%	-0,4


Curvature

The curvature of rods and tubes is the maximum deviation from the straight line through the end face centres. This curvature may be checked by means of a tubular gauge with dimensions as given below:

$$\text{gauge inner diameter } d = d_1 + \frac{\ell_1}{100}$$

$$\text{gauge length } \ell = \geq \ell_1$$

where d_1 = maximum outer dia. of the rod or tube
 ℓ_1 = maximum length of the rod or tube



Rod permeability as a function of the ratio l/d with the relative initial permeability of a toroidal core as parameter.

Type list of rods

D		L		FXC grade		catalogue number
max.	tol.	max.	tol.	3	4	
1,40	-0,02	6,85	- 0,2		4C5	3122 104 92040
1,40	-0,02	6,85	- 0,20	3D3		3122 104 91920
1,60	-0,10	3,95	- 0,20		4D2	3122 134 91190
1,65	-0,05	9,2	- 0,4	3D3		4312 020 30160
1,65	-0,05	9,2	- 0,4		4B1	3122 104 91060
1,65	-0,05	12,2	- 0,4	3B		3122 104 91100
1,65	-0,05	12,2	- 0,4		4B1	3122 104 91110
1,65	-0,05	14	- 0,4		4B1	4330 020 31770
1,65	-0,05	25,2	- 0,4	3B		3122 104 91170
1,65	-0,05	28,2	- 0,4		4B1	4330 020 32090
1,70	-0,15	14,2	- 0,4		4E1	4322 020 32060
1,70	-0,15	17,8	- 1,0	3B		3122 104 92020
1,70	-0,15	18,5	- 1		4B1	3122 104 91150
1,75	-0,2	6,2	- 0,4	3B		4312 020 30020
1,75	-0,2	10,2	- 0,4	3B		3122 104 91130
1,75	-0,20	12,2	- 0,4		4B1	3122 104 92070
1,75	-0,20	14,2	- 0,4		4B1	4312 020 30560
1,75	-0,2	14,2	- 0,4		4A4	8230 302 05540
1,78	-0,03	8,95	- 0,45	3D3		4322 020 39480
2,0	-0,2	12,0	- 0,7		4C6	4330 030 30320
2,0	-0,2	16,5	- 1,0		4B1	4330 030 30360
2,0	-0,05	16,5	- 1		4B1	4330 030 30590
2,0	-0,2	16,5	- 1		4B1	8230 302 05790
2,1	-0,2	12,5	- 1,0		4B1	4330 030 30130
2,2	-0,2	16,5	- 1,0		4B1	4312 020 30460
2,30	-0,05	10,2	- 0,4	3D3		4312 020 30030
2,50	-0,25	16,3	- 0,8		4B1	4330 030 30450
2,50	-0,25	20	- 1		4B1	4312 020 30510
2,5	-0,25	24	- 0,9		4B1	8230 302 03530
3,0	-0,1	14	- 0,5		4B1	4330 030 30060
3,0	-0,1	14	- 0,5		4C6	4330 030 30270
3,0	-0,05	17,3	- 0,6	3B		8230 302 05400
3,0	-0,25	20	- 0,6		4B1	4330 030 30220
3,0	-0,05	22,5	- 1		4B1	4330 030 30490
3,05	-0,1	16,5	- 1		4C6	4330 030 30390
3,15	-0,3	16,5	- 1,0		4C6	4330 030 30070
3,15	-0,3	24,35	- 0,7		4B1	4312 020 30520
3,2	-0,2	11,5	- 1		4B1	4330 020 30560
3,4	-0,2	35	- 1	3C6		4330 030 30370
3,43	-0,50	11,35	- 0,5	3C6		4330 030 30620
3,5	-0,3	17	- 0,5	3B		4330 030 30400
4,0	-0,2	9	- 0,3	3B		8230 302 05750
4,0	-0,05	10	- 0,4		4E1	4330 030 30410
4,0	-0,05	13,3	- 0,8		4B1	4330 030 30210
4,0	-0,3	16	- 0,8		4B1	4330 030 30560
4,0	-0,3	20	- 0,6	3C6		4312 020 30320
4,0	-0,05	21	- 1		4C6	4330 030 30040
4,0	-0,3	25	- 1		4B1	4330 030 30250
4,00	-0,05	25	- 1	3C6		4312 020 30290
4,1	-0,2	21	- 1		4B1	4330 030 30120
4,1	-0,2	25,5	- 1	3B		4330 030 30310

CORES FOR SMALL FIXED CHOKES

Type list of rods (continued)

D		L		FXC grade		catalogue number
max.	tol.	max.	tol.	3	4	
4,1	-0,2	40	- 1	3B		4330 020 30380
4,5	-0,05	15,5	- 0,8		4B1	8230 302 03500
4,75	-0,05	30	- 1,2		4B1	4330 030 30580
4,95	-0,1	36	- 0,5	3C6		3122 104 90490
4,95	-0,1	50	- 0,5	3C6		3122 134 90110
5,0	-0,3	14	- 0,8		4B1	4330 030 30110
5,0	-0,05	18,3	- 0,6		4B1	4330 030 30240
5,0	-0,3	18,3	- 0,6	3D3		4330 030 30530
5,0	-0,3	18,3	- 0,6		4B1	4312 020 30490
5,0	-0,3	20,5	- 1		4B1	4312 020 30570
5,0	-0,05	21	- 1	3C6		4330 030 30280
5,0	-0,3	24,5	- 1	3D3		4312 020 30190
5,0	-0,3	25	- 1		4B1	4330 030 30080
5,0	-0,2	25,5	- 1	3B		4322 020 39450
5,0	-0,1	25,5	- 1	3C6		4330 030 30630
5,0	-0,05	29,8	- 0,4	3C6		4330 030 30600
5,0	-0,3	30	- 1,2		4B1	4330 030 30030
5,0	-0,05	30,2	- 0,4	3C6		3122 134 91120
5,0	-0,2	41	- 2	3B		4322 020 39470
5,3	-0,6	35,6	- 1,2		4B1	4330 030 30470
5,4	-0,05	25,2	- 0,4	3B		3122 104 91850
5,65	-0,05	15	- 0,5	3C6		4330 030 30540
6,55	-0,4	25,5	- 1		4A4	8230 302 05600
6,8	-0,6	25,6	- 1,2		4B1	4330 030 30520
7,5	-0,05	35	- 0,6	3C6		8230 302 05710
7,5	-0,05	50	- 0,6	3C6		8230 302 05720
8,25	-0,5	164	- 8	3B		8230 302 05020
10,0	-0,5	20,5	- 1	3C6		4330 030 30380
10,0	-0,5	30,5	- 1	3C6		4330 030 30510
10,0	-0,5	32,5	- 0,5		4B1	4330 030 30570
10,0	-0,5	50,5	- 1		4B1	4330 030 30350
10,0	-0,5	51	- 2	3C6		4330 030 30010
10,0	-0,5	55	- 1		4E1	8230 302 04850
10,0	-0,6	125	- 10		4B1	4330 020 30030
10,0	-0,5	164	- 8	3B		8230 302 05030
10,0	-0,6	185	- 10		4B1	4330 020 30690
10,0	-0,5	204	- 8		4B1	8230 302 03350
10,1	-0,8	167,3	- 0,6		4B1	4330 020 30580
12	-0,7	164	- 8	3B		8230 302 05040

Rods and tubes

Type list of tubes

D		d		L		FXC grade		catalogue number
max.	tol.	min.	tol.	max.	tol.	3	4	
1,6	-0,03	0,7	+0,1	7,55	-0,3		4A4	4322 020 38440
1,6	-0,03	0,7	+0,1	7,55	-0,3		4E1	4322 090 22740
2,2	-0,4	0,6	+0,2	3,25	-0,5		4E1	4330 030 32670
2,5	-0,1	1,0	+0,2	1,2	-0,4		4B1	4330 030 37010
2,6	-0,3	1,05	+0,3	1,75	-0,3		4E1	4330 030 32850
2,7	-0,4	1,2	+0,2	3,5	-0,5		4E1	3122 104 91690
2,75	-0,2	1,85	+0,2	8,15	-0,3		4A4	4322 020 38450
2,75	-0,2	1,85	+0,2	8,15	-0,3		4E1	4322 090 22730
2,8	-0,05	1,2	+0,2	8,4	-0,4	3B		4322 020 34340
3,0	-0,2	0,9	+0,1	6,5	-0,4		4A4	4330 030 32000
3,0	-0,05	1,0	+0,15	17,2	-0,6	3D3		8230 302 01880
3,10	-0,02	1,3	+0,2	18,8	-0,5	3B		3122 134 90770
3,2	-0,4	0,8	+0,4	5,2	-0,4		4E1	4330 030 32640
3,35	-0,03	0,9	+0,1	7,55	-0,3		4A4	4322 020 36940
3,5	-0,1	1,6	+0,2	13,5	-0,5	3D3		8230 302 05080
3,5	-0,05	1,7	+0,2	14,2	-0,4	3B		3122 104 92800
3,6	-0,3	1,3	+0,2	3,5	-0,5	3B		4312 020 31050
3,6	-0,1	1,3	+0,2	4,2	-0,4		4C6	4322 020 38350
3,7	-0,4	1,0	+0,4	5,5	-1,0		4E1	4330 030 32660
3,7	-0,4	1,0	+0,4	5,5	-1,0		4D1	4330 030 32630
3,7	-0,4	1,2	+0,2	3,5	-0,5	3B		4322 020 34400
3,7	-0,4	1,2	+0,2	3,5	-0,5		4A1	4322 020 34410
3,7	-0,4	1,2	+0,2	3,5	-0,5		4B1	4322 020 34420
3,7	-0,4	1,2	+0,3	15,8	-0,1		4A4	4330 030 32720
3,7	-0,4	1,3	+0,2	5,5	-0,5	3B		4312 020 31060
3,7	-0,4	1,3	+0,2	5,5	-0,5		4B1	4330 030 32520
3,7	-0,4	1,3	+0,2	8,0	-0,5	3E		4312 020 31330
3,7	-0,4	1,3	+0,2	15,2	-0,4	3B		4312 020 31320
3,7	-0,4	1,5	+0,2	3,5	-0,5	3B		4322 020 34430
3,7	-0,4	1,5	+0,2	8,0	-0,5	3B		4330 030 32650
4,0	-0,2	0,75	+0,1	14,0	-0,7		4B1	4330 030 32830
4,05	-0,25	1,35	+0,3	5,7	-0,4		4B1	4312 020 15460
4,15	-0,05	2,0	+0,2	7,2	-0,4		4A1	4322 020 34440
4,15	-0,05	2,0	+0,2	12,2	-0,4		4B1	4322 020 34450
4,15	-0,05	2,0	+0,2	12,2	-0,4		4C6	4322 020 34460
4,15	-0,05	2,0	+0,2	12,2	-0,4		4D1	4322 020 34470
4,15	-0,05	2,0	+0,2	15,2	-0,4		4B1	4322 020 34380
4,15	-0,05	2,0	+0,2	21,2	-0,4		4A1	4322 020 34390
4,15	-0,3	2,0	+0,2	36,6	-1,2	3C6		4312 020 31450
4,2	-0,4	1,8	+0,4	5,5	-1,0	3B5		4313 020 15170
4,2	-0,1	2,0	+0,2	7,2	-0,4	3D3		4312 020 31220
4,2	-0,1	2,0	+0,2	11,2	-0,4	3D3		4312 020 31250
4,2	-0,1	2,0	+0,2	20,2	-0,4	3B		4312 020 31030
4,2	-0,1	2,0	+0,2	25,4	-1,0	3B1		4330 030 32800
4,3	-0,4	1,8	+0,4	45,3	-0,6	3B1		4330 030 32750
4,3	-0,2	2,0	+0,2	3,2	-0,4	3B1		4330 020 30230
4,3	-0,2	2,0	+0,2	3,5	-0,5	3B1		4330 030 32910
4,3	-0,2	2,0	+0,2	3,5	-0,5		4A1	4330 030 32950
4,3	-0,2	2,0	+0,2	4,7	-0,4	3B1		8230 301 03710
4,3	-0,2	2,0	+0,2	7,2	-0,4	3B		3122 104 92900
4,3	-0,2	2,0	+0,2	7,2	-0,4		4A1	4311 020 53460

CORES FOR SMALL FIXED CHOKES


Type list of tubes (continued)

D		d		L		FXC grade		catalogue number
max.	tol.	min.	tol.	max.	tol.	3	4	
4,3	-0,2	2,0	+0,2	7,2	- 0,4		4B1	4311 020 50710
4,3	-0,2	2,0	+0,2	7,2	- 0,4		4D1	3122 104 93890
4,3	-0,2	2,0	+0,2	12,8	- 0,6	3B1		4322 020 34490
4,3	-0,2	2,0	+0,2	15,4	- 0,8	3B		4322 020 36750
4,3	-0,2	2,0	+0,2	16,4	- 0,8	3B1		8230 302 02390
4,3	-0,2	2,0	+0,2	18,5	- 0,5	3B1		4322 020 36770
4,3	-0,2	2,0	+0,2	25,5	- 1,0	3B		4322 020 36780
4,3	-0,2	2,0	+0,2	25,5	- 1,0		4B1	3122 104 90810
4,3	-0,2	2,0	+0,2	30,5	- 1,0		4B1	4311 020 54310
4,3	-0,2	2,0	+0,2	35,7	- 1,4	3B1		4311 020 50430
4,4	-0,3	2,0	+0,2	29,8	- 0,8	3B1		4312 020 31080
4,45	-0,3	2,0	+0,3	21,2	- 0,4		4B1	4322 020 34480
4,95	-0,1	1,3	+0,2	15,2	- 0,4	3C6		3122 104 90370
4,95	-0,1	1,3	+0,2	23,2	- 0,4	3C6		3122 104 90390
4,95	-0,1	1,3	+0,2	26,2	- 0,5	3C6		3122 104 94030
4,95	-0,1	1,3	+0,2	40,5	- 1,0	3C6		3122 104 93110
4,95	-0,1	2,9	+0,2	36,0	- 0,5	3C6		3122 104 93760
5,0	-0,3	1,3	+0,2	40,5	- 1,0	3C6		4330 030 32610
5,0	-0,2	1,8	+0,4	6,0	- 0,2	3D3		8230 301 02980
5,0	-0,3	2,5	+0,2	12,0	- 0,5	3C6		8230 302 04630
5,0	-0,3	2,5	+0,2	23,0	- 1,0	3D3		8230 302 04640
5,0	-0,3	2,5	+0,2	29,5	- 1,0	3C6		8230 302 04100
5,1	-0,3	1,5	+0,15	10,3	- 0,6		4D2	4330 030 32900
5,1	-0,4	3,9	+0,3	8,0	- 0,15		4A4	4322 020 36970
5,3	-0,2	3,0	+0,2	22,4	- 0,8	3B		4322 020 36810
5,4	-0,4	3,3	+0,3	21,2	- 0,4		4A1	3104 101 80630
6,0	-0,3	3,0	+0,2	18,0	- 0,9	3C6		4330 030 32940
6,15	-0,3	2,9	+0,2	18,0	- 1,0	3C6		4330 030 32770
6,3	-0,3	3,8	+0,3	10,2	- 0,5	3C6		4330 030 32880
7,0	-0,4	2,6	+0,2	10,4	- 0,7	3D3		4330 030 32890
7,0	-0,3	2,8	+0,2	17,15	- 0,65	3B1		4330 030 32050
8,0	-0,4	3,0	+0,2	8,0	- 0,4	3B1		4330 030 32710
8,0	-0,4	4,2	+0,6	51,4	- 2,8	3B		4322 020 34310
8,0	-0,4	4,2	+0,6	51,4	- 2,8		4B1	4322 020 34320
8,2	-0,4	4,3	+0,4	8,4	- 0,4		4A1	3922 074 01120
8,5	-0,5	3,5	+0,3	15,3	- 0,6		4B1	4312 020 31200
9,5	-0,5	4,5	+0,3	16,0	- 0,8		4B1	4330 030 32020
9,8	-0,6	6,3	+0,4	17,5	- 0,5	3B		4313 020 15180
10,0	-0,5	4,0	+0,3	143,0	- 6,0		4B1	4330 030 32620
10,0	-0,6	4,0	+0,1	183,6	- 7,2		4B1	4330 030 32870
10,15	-0,3	7,8	+0,25	20,2	- 0,5	3B1		4330 030 32820
10,3	-0,6	3,8	+0,4	205,0	-10,0	3B1		4330 030 32860
10,3	-0,6	4,8	+0,4	155,0	-10,0	3B1		4330 030 32930
10,8	-0,5	6,7	+0,4	19,5	- 0,4		4A4	3122 134 90780
12,0	-0,8	6,0	+2,0	183,6	- 7,2		4B1	8230 302 00910
12,3	-0,6	4,8	+0,4	124,0	- 8,0		4A4	4330 030 32810
12,4	0,8	5,8	+0,4	155,0	-10,0	3B1		4330 030 32920
14,5	-1,0	4,8	+1,0	51,0	- 2,0	3B1		8230 302 02510
14,5	-1,0	7,3	+1,0	28,0	- 6,0		4A1	4311 020 51880
16,0	-1,0	8,0	+3,0	183,6	- 7,2		4B1	8230 302 00900
17,2	-1,2	10,4	+1,2	60,0	- 2,5	3B1		4330 030 32030

FERRITE COIL FORMERS for axial coils

These cylindrical ferrites with two axial wires glued into the ferrite are very suitable to be provided with a number of turns to form a required axial coil.

Available types:



dimensions in mm				FXC grade	catalogue number
D	d	L	l		
2,7	0,7	8	34	4A4	8230 302 02080
4	0,7	14	34	4B1	4330 030 38070
6	0,6	20	28	4A4	8230 302 02170

The coil formers can also be made available with lead diameters from 0,5 mm to 0,7 mm.

BEADS

for interference suppression

Three grades of Ferroxcube have been developed primarily for interference suppression in such applications as power supplies, radio and television receivers, and automotive and domestic equipment. These grades are FXC3S1, FXC3S2 and FXC4S3. The table on the next page lists the ferrite beads available in these three material grades, together with their dimensions and guaranteed minimum impedances. Impedances are measured with the beads threaded on a straight copper wire.

Choice of material grade

In practice, choosing the correct material grade for a given application is very simple. First, determine the frequency range of the interfering signals that are to be suppressed, then, from the graph of Fig. 1, find the most suitable material grade and, finally, using the table of impedances, determine the bead dimensions for the required attenuation.




Fig. 1 Impedance of Ferroxcube grades as a function of frequency. The curves are typical for a bead size of $5 \times 2 \times 10$ mm.

The high surface resistivity of FXC4S3 beads makes them suitable for mounting on bare wires. Increasing the surface resistivity of all grades by means of lacquer or any other insulation does not interfere with the magnetic properties of the Ferroxcube material.

The values of initial permeability μ_i and saturation flux density B_s of FXC3S1, FXC3S2 and FXC4S3 have been optimized for the following ranges of application:

- FXC3S1: a very high μ_i combined with a high B_s . Beads of this grade have a high $|Z_S|$ at frequencies from 1 MHz to 50 MHz* (maximum $|Z_S|$ occurs between 6 MHz and 10 MHz), but are easily saturated by d.c. owing to the high μ_i .
- FXC3S2: a medium μ_i and a high B_s . At frequencies greater than about 20 MHz, these beads have a higher $|Z_S|$ than those of grade 3S1. They can be used up to about 200 MHz.* Maximum $|Z_S|$ occurs between 40 MHz and 60 MHz.
- FXC4S3: a low μ_i and a high B_s . At frequencies greater than about 80 MHz, these beads have a higher $|Z_S|$ than those of grade 3S2. They can be used up to about 1 GHz.* Maximum $|Z_S|$ occurs between 100 MHz and 200 MHz.

* See "Notes".

CORES FOR SMALL FIXED CHOKES

Guaranteed minimum bead impedances $|Z_S|$ (Ω) at various frequencies.




Fig. 2.

	frequency in MHz						catalogue number	dimensions (mm)			
	1	3	10	30	100	300		D	d	L	$L \cdot I_n (D/d)$
	$ Z_S (\Omega)$										
grade 3S1	10	18	24	20	17	15	4330 030 32180	5	2,0	4	3,7
	14	29	30	24	20	18	32120	3	1,0	4	4,4
	10	20	32	26	22	20	32160	5	1,5	4	4,8
	19	38	39	31	26	23	32100	3	0,7	4	5,8
	27	52	53	42	36	32	32140	5	0,7	4	7,9
	29	51	61	49	42	37	32190	5	2,0	10	9,2
	33	72	73	58	50	44	32130	3	1,0	10	11,0
	40	72	80	64	55	48	32170	5	1,5	10	12,0
	58	95	97	77	66	58	32110	3	0,7	10	14,5
	70	125	128	90	70	50	32150	5	0,7	10	19,7
grade 3S2 (blue)	2	8	16	20	26	17	4330 030 32280	5	2,0	4	3,7
	2	8	17	22	28	18	32340	8	3,0	4	3,9
	3	9	19	25	32	20	32220	3	1,0	4	4,4
	3	10	21	27	35	22	32260	5	1,5	4	4,8
	4	11	24	31	33	26	32320	8	2,0	4	5,6
	2	8	25	32	42	27	32200	3	0,7	4	5,8
	5	16	34	44	57	37	32240	5	0,7	4	7,9
	6	19	40	51	66	43	32290	5	2,0	10	9,2
	6	20	42	55	62	45	32350	8	3,0	10	9,8
	7	23	48	61	79	51	32230	3	1,0	10	11,0
	7	25	52	68	87	55	32270	5	1,5	10	12,0
	9	28	60	77	100	64	32330	8	2,0	10	13,9
9	30	63	81	104	67	32210	3	0,7	10	14,5	
10	34	72	93	90	77	32310	8	1,5	10	16,7	
12	40	75	110	142	91	32250	5	0,7	10	19,7	
grade 4S3 (red)	1	2	7	17	32	36	4330 030 32440	5	2,0	4	3,7
	1	3	8	18	34	38	32500	8	3,0	4	3,9
	1	3	9	20	38	43	32380	3	1,0	4	4,4
	1	3	9	22	41	47	32420	5	1,5	4	4,8
	1	3	11	26	49	55	32480	8	2,0	4	5,6
	1	3	11	27	50	57	32360	3	0,7	4	5,8
	1	4	13	31	57	65	32460	8	1,5	4	6,7
	2	5	16	36	68	77	32400	5	0,7	4	9,7
	2	6	18	42	80	89	32450	5	2,0	10	9,2
	2	6	19	45	85	95	32510	8	3,0	10	9,8
	2	8	21	50	95	107	32390	3	1,0	10	11,0
	2	7	23	55	104	116	32430	5	1,5	10	12,0
	2	9	27	64	121	134	32490	8	2,0	10	13,9
	2	9	28	67	126	140	32370	3	0,7	10	14,5
	3	10	32	77	145	161	32470	8	1,5	10	16,7
	4	12	38	90	170	190	32410	5	0,7	10	19,7

In many applications, leads through suppressor beads also carry a d.c. or a 50 Hz a.c. current. In such cases the impedance of grades 3S1 and 3S2 will decrease.

Figure 3 shows the effect of d.c. on the impedance of 3S1 and 3S2 beads. This is caused by partial saturation of the beads, which will, of course, be more pronounced with smaller beads, and those of lower B_S and higher μ_i material. Therefore, the effect of d.c. on grade 4S3 is negligible. Consequently, where high d.c. (or 50 Hz a.c.) currents flow, grades 4S3 or 3S2 should be used.




Fig. 3a Impedance $|Z_S|$ of a $5 \times 2 \times 10$ mm bead of grade 3S2 as a function of frequency with the premagnetizing current as a parameter.




Fig. 3b Impedance $|Z_S|$ of a $5 \times 2 \times 10$ mm bead of grade 3S1 as a function of frequency with the premagnetizing current as a parameter.


Notes

The attenuation of a given type of bead used beyond the frequency limit for its material grade may vary significantly from batch to batch. Although the attenuation will never be less than that given in the table of guaranteed minimum values, it may be much higher. However, the guaranteed minimum attenuation of a bead of the correct material grade for the frequency will always be higher than that of one beyond its frequency limit.

Beads used beyond the frequency limit for their grade should not be too large. This is because the possible deterioration of attenuation may become excessive for greater $L \cdot \ln(D/d)$ values. Rather than increase $L \cdot \ln(D/d)$ it is usually better to use several well-separated beads with smaller $L \cdot \ln(D/d)$ values.

BEADS ON WIRE
on tape

A number of beads on wire, for suppression of incoming or outgoing interferences in various applications, can be supplied on tape for automatic processing. The bandolier fits most commonly used automatic mounting machines. See Fig. 1 and Table 1.



7Z90595.2

Table 1

grade	frequency in MHz						catalogue number	dimensions				tape standard
	1	3	10	30	100	300		D	L	l	d	
	$ Z_S (\Omega)$											
3D3	11	36	100	130	80	60	8230 301 04180	4,1	11,0	75,0	0,6	IEC 286 part 1
3S2	5	18	48	70	80	65	8230 301 03330	3,5	6,0	75,0	0,6	IEC 286 part 1
4E1				2	7,5	25	8230 301 04760	2,0	3,0	75,0	0,6	IEC 286 part 1
3S2					34		8230 301 04100	3,5	3,5	64,4	0,64	EIA-RS-296-D
4A1					35		8230 301 04110	3,5	3,5	64,4	0,64	EIA-RS-296-D
4S3						54	8230 301 04120	3,5	3,5	64,4	0,64	EIA-RS-296-D
4S2					46		8230 301 04130	3,5	3,5	64,4	0,64	EIA-RS-296-D
3E2		30					8230 301 04140	3,5	3,5	64,4	0,64	EIA-RS-296-D
4S2					60		8230 301 04050	3,5	4,7	64,4	0,64	EIA-RS-296-D
4S2					80		8230 301 04060	3,5	6,0	64,4	0,64	EIA-RS-296-D
4S2					88		8230 301 04070	3,5	6,7	64,4	0,64	EIA-RS-296-D
4S2					105		8230 301 04080	3,5	7,6	64,4	0,64	EIA-RS-296-D
4S2					117		8230 301 04090	3,5	8,9	64,4	0,64	EIA-RS-296-D

MULTI-HOLE TUBES

Multi-hole tubes are used for small h.f. transformers for voltage or impedance matching in television, communications, data transmission, instrumentation and similar applications.

A. With two holes, "twin beads"




Fig. 1.




Fig. 2.

Fig.	D mm	d mm	L mm	H mm	grade	catalogue number
1	5,6 ± 0,25	0,95 + 0,15	4,5 - 0,5	—	4D1	3122 134 90800
	5,6 ± 0,15	1,5 ± 0,15	12 ± 0,2	—	4B1	4330 030 32740
	5,9 - 0,6	0,75 + 0,3	12,4 - 0,8	—	4B1	3122 104 90960
	6,6 - 0,6	1,05 + 0,3	5 ± 0,2	—	4B1	3122 104 94840
2	8,5 - 0,5	3,5 + 0,5	8 ± 0,3	14 + 0,5	4B1	4312 020 31570
	8,5 - 0,5	3,5 + 0,5	14 ± 0,4	14 + 0,5	4B1	4312 020 31520

With twin beads advantages can be taken of mutual inductance to increase inductance L and loss resistance R caused by ΔL and ΔR respectively. This is shown in Fig. 3 for a twin bead 4312 020 31520 on two straight wires. Grade 4B1 provides ample insulation between bare wires.




Fig. 3.

CORES FOR SMALL FIXED CHOKES

B. With six holes





Fig. 4.

D mm	d mm	L mm	grade	catalogue number
$6 \pm 0,3$	$0,7 + 0,2$	$10 \pm 0,5$	3B	4312 020 31500
$6 \pm 0,3$	$0,7 + 0,2$	$10 \pm 0,5$	4B1	4312 020 31550

SCREW CORES

Ferroxcube screw cores are used in adjustable inductances in r.f. and h.f. coils with an open magnetic circuit.

Stud trimming



nom. diameter x pitch	l mm	d mm	grade	catalogue number
3,5 x 0,7	10 ± 0,2	3,5 ± 0,05	3B	3122 104 90550

WOUND SIX-HOLE BEADS

Wide-band h.f. chokes are used for interference suppression, e.g. in electric motors. Double chokes are used for twin leads, in which case the advantage of mutual inductance can be utilized.

The chokes can be supplied with six axial holes through which 1,5, 2,5 or 2 x 1,5 (double chokes) turns of tinned copper wire are threaded.




Fig. 1.

number of turns	Z_{\max} k Ω	f at Z_{\max} MHz	decrease of impedance		grade	catalogue number
			In the freq. range MHz	dB		
1,5	$\geq 0,3$	120	10-300	≤ 7	3B	4312 020 36630
1,5	$\geq 0,35$	250	80-300	≤ 3	4B1	4312 020 36690
2,5	$\geq 0,6$	50	10-200, 30-100	$\leq 7, \leq 3$	3B	4312 020 36640
2,5	$\geq 0,7$	180	50-300, 80-220	$\leq 6, \leq 3$	4B1	4312 020 36700
2 x 1,5	$\geq 0,7$	50	10-220, 30-100	$\leq 7, \leq 3$	3B	4312 020 36650
2 x 1,5	$\geq 0,8$	110	50-300, 80-220	$\leq 7, \leq 3$	4B1	4312 020 36710




Fig. 2 Performance of three single chokes.

Type a = 4312 020 36700

b = 4312 020 36640

c = 4312 020 36690

Figure 2 shows some performance details of three single chokes. It will be noted that above approx. 80 MHz the impedance is substantially resistive and tends to be constant. Double chokes are used for twin leads, in which case the advantages of mutual inductance can be utilized. Figure 3 compares the typical obtainable performance.




Fig. 3 Damping in an LC circuit consisting of a Ferroxcube choke and a ceramic disc capacitor.

- a. L = 4312 020 36690, C = 1500 pF
- b. L = 4312 020 36700, C = 1500 pF

- c. L = 4312 020 36700, C = 550 pF
- d. L = 4312 020 36690, C = 550 pF.




Fig. 4.




Fig. 5.

number	Fig.	L μH	grade	catalogue number
2,5	4	≥ 9	3B	4330 030 38080
3	5		3B	4312 020 36760

SECTION F
MATERIALS FOR PARTICLE ACCELERATORS

MATERIALS FOR PARTICLE ACCELERATORS

Several grades of Ferroxcube have been developed especially for use in particle accelerators. Applications include kicker magnets for beam extraction, and accelerating stations. For kicker magnets, materials of low coercivity and low degassing rate are required. Materials for accelerating stations must have a high μQ_f product at the working flux density. The dynamic behaviour of the materials under pulse conditions is important for both applications.

The data given in the following table allows a preliminary selection of material grade to be made. However, consultation with the manufacturer is always advisable to establish finally the material properties and component geometries for each application.

NOTE ON DATA

Losses given in terms of μQ factors may be converted into losses in kW/m^3 (mW/cm^3) using the following expression.

$$\text{Losses in } \text{kW/m}^3 = \frac{2,5 \times f \times B^2}{\mu Q}$$

where f is in kHz and B in mT. For example, the losses in FXC 3F1 material at 200 kHz and 10 mT induction are

$$\frac{2,5 \times 200 \times 10^2}{200 \times 10^3} = 0,25 \text{ kW/m}^3.$$

material	3H22	8C11	3F1	8C12	4L2	4M2	4E2
μ_i	≥ 2500	≥ 1000	1800 ± 360	900 ± 150	250 ± 50	140 ± 30	25 ± 5
μ_{rem} approx.	2300	850	1500	600	200	130	20
B_{sat} 25° (mT, 800 A/m)	≥ 400	≥ 300	≥ 400	280	240	250	250
B_{sat} 40° (mT, 800 A/m)	≥ 350	≥ 280	≥ 350	250	220	220	220
H_c (A/m, after 800 A/m)	≤ 15	≤ 20	≤ 20	30	90	100	500
ρ d.c. (Ω M)	> 1	$> 10^3$	> 10	$> 10^3$	$> 10^3$	$> 10^3$	$> 10^3$
T_c (°C)	≥ 125	≥ 125	≥ 200	≥ 125	≥ 150	≥ 150	≥ 400
μQ in remanence							
200 kHz	10 mT		$200 \cdot 10^3$	$15 \cdot 10^3$			
	20 mT		$160 \cdot 10^3$	$9 \cdot 10^3$			
	50 mT		$75 \cdot 10^3$	$4 \cdot 10^3$			
	100 mT		$30 \cdot 10^3$				
500 kHz	10 mT		$110 \cdot 10^3$	$10 \cdot 10^3$			
	20 mT		$90 \cdot 10^3$	$6 \cdot 10^3$			
	50 mT		$40 \cdot 10^3$	$2,5 \cdot 10^3$			
	100 mT		$20 \cdot 10^3$				
1 MHz	5 mT		$25 \cdot 10^3$	$10 \cdot 10^3$	$35 \cdot 10^3$	$20 \cdot 10^3$	
	10 mT		$23 \cdot 10^3$	$7,5 \cdot 10^3$	$26 \cdot 10^3$	$20 \cdot 10^3$	
	20 mT		$17 \cdot 10^3$	$5 \cdot 10^3$	$13 \cdot 10^3$	$15 \cdot 10^3$	
	30 mT		$15 \cdot 10^3$		$7 \cdot 10^3$	$8 \cdot 10^3$	
	50 mT		$14 \cdot 10^3$				
2,5 MHz	5 mT				$25 \cdot 10^3$	$20 \cdot 10^3$	
	10 mT				$20 \cdot 10^3$	$20 \cdot 10^3$	
	20 mT				$9 \cdot 10^3$	$15 \cdot 10^3$	
	30 mT				$5 \cdot 10^3$	$7 \cdot 10^3$	
5 MHz	5 mT				$15 \cdot 10^3$	$15 \cdot 10^3$	
	10 mT				$11 \cdot 10^3$	$15 \cdot 10^3$	
	20 mT				$5 \cdot 10^3$	$10 \cdot 10^3$	
	30 mT				$2 \cdot 10^3$	$7 \cdot 10^3$	

10 MHz	5 mT 10 mT					12.10 ³ 10.10 ³	
80 MHz	1 mT						2,5.10 ³
100 MHz							2.10 ³
Decrease in $\mu\Omega$, measured 10 ms after application of d.c. bias in % (approx.)			10	10	30	15	30
$\mu\Delta$ with d.c. bias field (approx.)							
0 A/m			1500	600	200	130	
250 A/m			270	120	120	80	
500 A/m			33	50	55	40	
1000 A/m			13	22	25	22	
2000 A/m			6	8	12	12	
3000 A/m			4	5,5	8	8	
Freq. range (with or without d.c. bias) in MHz			0,1–1	0,5–10	1–5	2–10	20–100
Application area and special features	Kickers	Kickers High resistance	Low freq. For large dimensions, eddy current losses have to be considered	High freq. ratio possible with d.c. bias	Rel. high $\mu\Omega$	Fast recovery after magnetic bias	High freq. material

SECTION G
FERROXCUBE FOR MICROWAVE APPLICATIONS

FERROXCUBE FOR MICROWAVE APPLICATIONS

Ferroxcube 5 is a material grade which is especially suited for microwave applications such as circulators and isolators.

The main application areas for these ferrites are radio, television, microwave communication, radar, security systems and industrial control.

They are available as blocks, bars, discs and substrates with dimensions as requested by the customer.

Substrates for microwave integrated circuit (MIC) technology are manufactured in advanced hot isostatic sintering kilns, so that low porosity and high-quality polished surfaces can be guaranteed.

SURVEY OF FERROXCUBE 5 MATERIALS


Table

	symbol	conditions			unit
		frequency MHz	field strength A/m	temp. °C	
saturation polarization	J_s		8×10^5	25 ± 5	mT
line width	ΔH	9600			A/m
spin wave line width	ΔH_K	9600			A/m
coercive field strength	H_c		800		A/m
dielectric loss factor	$\tan \delta(\epsilon)$	9600			
dielectric constant	ϵ'				
temp. coefficient of J_s			8×10^5	0 - 25 25 - 60	mT/K
Landé factor	g			25 ± 5	-
remanence	B_r		800		mT
saturation flux density	B_s		800		mT
Curie temp.	T_c				°C
specific resistance for d.c.	ρ			25 ± 5	Ωm
density					kg/m ³

materials for microwave applications


	5G1	5G3	5G4	5G5	5G6	5G7	5G8	5D3
	178 ± 9	55 ± 2,5	125 ± 6	87,5 ± 4,5	52,5 ± 2,5	37,5 ± 2,5	182,5 ± 9	300 ± 15
	2200 ± 600	2640 ± 400	≤ 6000	6800 ± 2000	≤ 6000	5200 ± 800	< 800	< 20 000
	> 24	> 80	> 400	> 600		> 560	> 24	> 800
	35						15,9	
	< 2 × 10 ⁻⁴	< 2 × 10 ⁻⁴	< 2 × 10 ⁻⁴	< 2 × 10 ⁻⁴	< 2 × 10 ⁻⁴	< 2 × 10 ⁻⁴	< 3 × 10 ⁻⁴	< 20 × 10 ⁻⁴
	15,5 ± 0,5	14,4 ± 0,25	15,5 ± 0,5	15,25 ± 0,25	14,7 ± 0,5	14,5 ± 0,5	15,3 ± 0,75	13,9 ± 0,5
	-0,36	-0,20		-0,14		-0,11	-0,61	-0,32
	2,00	2,00	2,00	2,02	2,02	2,02	2,00	2,24
	120						102	
	145							
	240	155	280	280	175	145	230	≥ 500
	> 10 ⁴						> 10 ⁸	10 ⁵
	5140	5000	5500	5360	5240	5100	5210	5300

BLOCKS




grade	catalogue number
5G1	4322 020 94160
5G4	4322 020 94460
5G5	4322 020 94560
5G6	4322 020 94660
5G7	4322 020 94760

DISCS



grade	d mm	h mm	catalogue number
5G1	27	1,5	3312 060 74440
	37	1,5	3312 059 01600
	67	2	8222 037 54970
	51	1,5	4322 020 30210
	56	2,9	4322 020 30090
5G8	25	1	3312 060 60430

SUBSTRATES



7Z96108

grade	a mm	b mm	c mm	catalogue number
5G1	25,4	25,4	0,51	4322 020 65100
	25,4	38,1	0,51	4322 020 65110
5G4	25,4	25,4	0,51	8222 293 32470
	25,4	25,4	1,02	8222 293 32480
	25,4	38,1	1,02	8222 293 32490
5G5	25,4	38,1	1,02	8222 293 32500
5G6	25,4	25,4	1,02	8222 293 32510
5G7	38,1	38,1	1,02	8222 293 32520 **
				8222 293 32680
5D3	25,4	25,4	0,51	8222 293 32530

** Not polished; R_a not applicable.

INDEX OF CATALOGUE NUMBERS

The purpose of this index is to provide identification of the component type when only the catalogue number is known. Details of the particular component are given in the relevant section of this book. See also book C4.

catalogue number	page	description	catalogue number	page	description
3104 101 80630	324	Tube core	3122 134 90720	264	I-core
3122 104 90370	324	Tube core	90730	262	I-core
90380	324	Tube core	90750	56	Yoke ring
90470	284	I-core	90760	279	U-core
90480	284	U-core	90770	323	Tube core
90490	322	Rod core	90780	324	Tube core
90550	333	Screw core	90800	331	Multi-hole tube
90810	324	Tube core	90960	138	E-core
90960	331	Multi-hole tube	91120	322	Rod core
91020	321	Rod core	91160	268	U-core
91060	321	Rod core	91390	288	U-core
91100	321	Rod core	91440	57	Yoke ring
91110	321	Rod core	91610	58	Yoke ring
91130	321	Rod core	91680	59	Yoke ring
91150	321	Rod core	91850	60	Yoke ring
91170	321	Rod core	91940	61	Yoke ring
91190	321	Rod core	92030	62	Yoke ring
91690	323	Tube core	92500	63	Yoke ring
91850	322	Rod core	92510	64	Yoke ring
91920	321	Rod core	92590	65	Yoke ring
92040	321	Rod core	92600	66	Yoke ring
92070	321	Rod core	92750	67	Yoke ring
92800	323	Tube core	92780	68	Yoke ring
92900	323	Tube core	93050	69	Yoke ring
93110	324	Tube core	99370	70	Yoke ring
93760	324	Tube core	3122 137 55360	280	Coil former
93840	54	Yoke ring	61910	277	Coil former
93890	324	Tube core	64140	267	Coil former
93950	290	U-core	3922 074 01120	324	Tube core
94030	324	Tube core	4311 020 50430	324	Tube core
94760	287	U-core	50710	324	Tube core
94770	287	I-core	51880	324	Tube core
94840	331	Multi-hole core	53460	323	Tube core
3122 134 02540	265	Coil former	54310	324	Tube core
02590	263	Coil former	4312 020 15460	323	Tube core
90110	322	Rod core	30020	321	Rod core
90200	273	U-core	30030	321	Rod core
90210	179	E-core	30160	321	Rod core
90460	276	U-core	30190	322	Rod core
90480	285	U-core	30290	321	Rod core
90600	55	Yoke ring	30320	321	Rod core
90620	266	I-core	30460	321	Rod core
90690	270	U-core	30490	322	Rod core

INDEX

catalogue number	page	description	catalogue number	page	description
4312 020 30510	321	Rod core	4312 020 37050	247	ETD core
30520	321	Rod core	37060	247	ETD core
30560	321	Rod core	37070	247	ETD core
30570	322	Rod core	37080	247	ETD core
31030	323	Tube core	37090	247	ETD core
31050	323	Tube core	37100	252	ETD core
31060	323	Tube core	37110	252	ETD core
31080	324	Tube core	37120	252	ETD core
31200	324	Tube core	37130	252	ETD core
31220	323	Tube core	37140	252	ETD core
31250	323	Tube core	37150	257	ETD core
31320	323	Tube core	37160	257	ETD core
31330	323	Tube core	37170	257	ETD core
31450	323	Tube core	37180	257	ETD core
31500	332	Multi-hole tube	37190	257	ETD core
31520	331	Multi-hole tube	37200	242	ETD core
31550	332	Multi-hole tube	37210	242	ETD core
31570	331	Multi-hole tube	37220	242	ETD core
33190	286	U-core	37230	242	ETD core
33550	291	U-core	37240	242	ETD core
33560	291	I-core	37250	247	ETD core
33570	295	U-core	37260	247	ETD core
33580	293	U-core	37270	247	ETD core
33590	293	I-core	37280	247	ETD core
33600	297	U-core	37290	247	ETD core
33610	297	I-core	37300	252	ETD core
33710	285	U-core	37310	252	ETD core
34020	137	E-core	37320	252	ETD core
34070	129	E-core	37330	252	ETD core
34100	169	E-core	37340	252	ETD core
34110	149	E-core	37350	257	ETD core
34120	157	E-core	37360	257	ETD core
34170	157	E-core	37370	257	ETD core
34190	157	E-core	37380	257	ETD core
34380	187	E-core	37390	257	ETD core
34470	128	E-core	4312 021 26010	201	Clasp
34550	142	E-core	26020	212	Clasp
34740	282	U-core	26030	212	Clasp
36250	318	Toroid	26040	223	Clasp
36280	318	Toroid	26050	223	Clasp
36300	318	Toroid	26060	234	Clasp
36310	318	Toroid	26070	234	Clasp
36630	334	Wound bead	26090	178	Clasp
36640	334	Wound bead	26110	196	Clasp
36650	334	Wound bead	26120	141	Clasp
36690	334	Wound bead	26130	178	Spring
36700	334	Wound bead	26140	196	Spring
36710	334	Wound bead	26150	201	Spring
36760	335	Wound bead	26160	212	Spring
37000	242	ETD core	26170	223	Spring
37010	242	ETD core	26180	234	Spring
37020	242	ETD core	26190	141	Spring
37030	242	ETD core	28430	130	Coil former
37040	242	ETD core	28540	139	Coil former

catalogue number	page	description	catalogue number	page	description		
4312 021	28550	143	Coil former	4322 020	38450	323	Tube core
	28620	151	Coil former		39450	322	Rod core
	28710	177	Coil former		39470	322	Rod core
	28720	195	Coil former		39480	322	Rod core
	28750	140	Coil former		43020	301	Bar
4313 020	15170	323	Tube core		52500	197	EC-core
	15180	324	Tube core		52510	208	EC-core
	35380	71	Yoke ring		52520	219	EC-core
4322 020	31310	318	Toroid		52530	230	EC-core
	31320	318	Toroid		90750	318	Toroid
	31330	318	Toroid		90760	318	Toroid
	31350	318	Toroid		90770	318	Toroid
	31370	318	Toroid		90860	318	Toroid
	31380	318	Toroid		91870	318	Toroid
	31390	318	Toroid		95160	318	Toroid
	31400	318	Toroid		95180	318	Toroid
	31420	318	Toroid		95190	318	Toroid
	31430	318	Toroid		95520	318	Toroid
	31440	318	Toroid		97000	318	Toroid
	31450	318	Toroid		97010	318	Toroid
	31460	318	Toroid		97020	318	Toroid
	34310	324	Tube core		97030	318	Toroid
	34320	324	Tube core		97040	318	Toroid
	34340	323	Tube core		97050	318	Toroid
	34380	323	Tube core		97060	318	Toroid
	34390	323	Tube core		97070	318	Toroid
	34400	323	Tube core		97110	318	Toroid
	34410	323	Tube core		97120	318	Toroid
	34420	323	Tube core		97130	318	Toroid
	34430	323	Tube core		97140	318	Toroid
	34440	323	Tube core		97150	318	Toroid
	34450	323	Tube core		97160	318	Toroid
	34460	323	Tube core		97170	318	Toroid
	34470	323	Tube core		97180	318	Toroid
	34490	324	Tube core		97190	318	Toroid
	34830	129	E-core		97200	318	Toroid
	34840	142	E-core		97500	305	Bar
	34850	149	E-core		97630	304	Bar
	34900	169	E-core		97640	304	Bar
	34910	186	E-core		97680	305	Bar
	35070	72	Yoke ring		97690	312	Tile
	36750	324	Tube core	4322 021	20160	134	Clasp
	36770	324	Tube core		20170	146	Clasp
	36780	324	Tube core		20220	134	Spring
	36810	324	Tube core		20230	146	Spring
	36940	323	Tube core		20240	131	Coil former
	36970	324	Tube core		20250	144	Coil former
	37320	149	I-core		20290	133	Coil former
	37400	305	Bar		31830	152	Coil former
	37460	305	Bar		31910	154	Clasp
	37470	305	Bar		31920	154	Spring
	37480	305	Bar		33010	211	Coil former
	38350	323	Tube core		33020	222	Coil former
	38440	323	Tube core		33060	211	Tag

INDEX

catalogue number	page	description	catalogue number	page	description
4322 021	33070	222 Tag	4330 030	30370	321 Rod core
	33310	200 Coil former		30380	322 Rod core
	33320	211 Coil former		30390	321 Rod core
	33330	222 Coil former		30400	321 Rod core
	33340	233 Coil former		30410	321 Rod core
	33350	211 Coil former		30450	321 Rod core
	33360	222 Coil former		30470	322 Rod core
	33370	233 Coil former		30490	321 Rod core
	33410	199 Coil former		30510	322 Rod core
	33480	211 Coil former		30520	322 Rod core
	33490	211 Coil former		30530	322 Rod core
	33500	222 Coil former		30540	322 Rod core
	33850	245 Coil former		30560	321 Rod core
	33860	250 Coil former		30570	322 Rod core
	33870	255 Coil former		30580	321 Rod core
	33880	260 Coil former		30600	322 Rod core
	33890	246 Assembly clip		30630	322 Rod core
	33900	251 Assembly clip		30530	322 Rod core
	33910	256 Assembly clip		32000	323 Tube core
	33920	261 Assembly clip		32020	324 Tube core
	33940	246 Earth clip		32030	324 Tube core
	33950	251 Earth clip		32050	324 Tube core
	33960	256 Earth clip		32100	328 Bead
	33970	261 Earth clip		32110	328 Bead
4322 090	22730	323 Tube core		32120	328 Bead
	22740	323 Tube core		32130	328 Bead
4330 020	30030	322 Rod core		32140	328 Bead
	30380	322 Rod core		32150	328 Bead
	30560	321 Rod core		32160	328 Bead
	30580	322 Rod core		32170	328 Bead
	30690	322 Rod core		32180	328 Bead
	31770	321 Rod core		32190	328 Bead
	32060	321 Rod core		32200	328 Bead
	32090	321 Rod core		32210	328 Bead
4330 030	30010	322 Rod core		32220	328 Bead
	30030	322 Rod core		32230	328 Bead
	30040	321 Rod core		32240	328 Bead
	30060	321 Rod core		32250	328 Bead
	30070	321 Rod core		32260	328 Bead
	30080	322 Rod core		32270	324 Bead
	30110	322 Rod core		32280	328 Bead
	30120	321 Rod core		32290	328 Bead
	30130	321 Rod core		32310	328 Bead
	30210	321 Rod core		32320	328 Bead
	30220	321 Rod core		32330	328 Bead
	30230	323 Tube core		32340	328 Bead
	30240	322 Rod core		32350	328 Bead
	30250	321 Rod core		32360	328 Bead
	30270	321 Rod core		32370	328 Bead
	30280	322 Rod core		32380	328 Bead
	30310	322 Rod core		32390	328 Bead
	30320	321 Rod core		32400	328 Bead
	30350	322 Rod core		32410	328 Bead
	30360	321 Rod core		32420	328 Bead

catalogue number	page	description	catalogue number	page	description
4330 030 32430	328	Bead	8230 302 00900	324	Tube core
32440	328	Bead	00910	324	Tube core
32450	328	Bead	01880	323	Tube core
32460	328	Bead	02080	326	Coil former
32470	328	Bead	02170	326	Coil former
32480	328	Bead	02390	324	Tube core
32490	328	Bead	02510	324	Tube core
32400	328	Bead	03350	322	Rod core
32410	328	Bead	03500	322	Rod core
32420	323	Tube core	03530	321	Rod core
32610	324	Tube core	04100	324	Tube core
32620	324	Tube core	04630	324	Tube core
32630	323	Tube core	04640	324	Tube core
32640	323	Tube core	04850	322	Rod core
32650	323	Tube core	05020	322	Rod core
32660	323	Tube core	05030	322	Rod core
32670	323	Tube core	05040	322	Rod core
32710	324	Tube core	05080	323	Tube core
32720	323	Tube core	05400	321	Rod core
32750	323	Tube core	05540	321	Rod core
32770	324	Tube core	05600	322	Rod core
32800	323	Tube core	05710	322	Rod core
32810	324	Tube core	05720	322	Rod core
32820	324	Tube core	05750	321	Rod core
32830	323	Tube core	05790	321	Rod core
32850	323	Tube core			
32860	324	Tube core			
32870	324	Tube core			
32880	324	Tube core			
32890	324	Tube core			
32900	324	Tube core			
32910	323	Tube core			
32920	324	Tube core			
32930	324	Tube core			
32940	324	Tube core			
32950	323	Tube core			
32740	331	Multi-hole tube			
37010	323	Tube core			
38070	326	Coil former			
38080	335	Wound bead			
8230 301 02980	324	Tube core			
03330	330	Bead on wire			
03710	323	Tube core			
04100	330	Bead on wire			
04110	330	Bead on wire			
04120	330	Bead on wire			
04130	330	Bead on wire			
04140	330	Bead on wire			
04150	330	Bead on wire			
04160	330	Bead on wire			
04170	330	Bead on wire			
04180	330	Bead on wire			
04190	330	Bead on wire			
04760	330	Bead on wire			

NOTES

NOTES

NOTES

NOTES

Electronic components and materials for professional, industrial and consumer uses from the world-wide Philips Group of Companies

- Argentina:** PHILIPS ARGENTINA S.A., Div. Elcoma, Vedia 3892, 1430 BUENOS AIRES, Tel. 541-7141/7242/7343/7444/7545.
- Australia:** PHILIPS INDUSTRIES HOLDINGS LTD., Elcoma Division, 11 Waltham Street, ARTARMON, N.S.W. 2064, Tel. (02) 439 3322.
- Austria:** ÖSTERREICHISCHE PHILIPS BAUELEMENTE INDUSTRIE G.m.b.H., Triester Str. 64, A-1101 WIEN, Tel. 62 91 11-0.
- Belgium:** N.V. PHILIPS & MBLÉ ASSOCIATED, 9 rue du Pavillon, B-1030 BRUXELLES, Tel. (02) 242 74 00.
- Brazil:** IBRAPE, Caixa Postal 7383, Av. Brigadeiro Faria Lima, 1735 SAO PAULO, SP, Tel. (011) 211-2600.
- Canada:** PHILIPS ELECTRONICS LTD., Elcoma Division, 601 Milner Ave., SCARBOROUGH, Ontario, M1B 1M8, Tel. 292-5161.
- Chile:** PHILIPS CHILENA S.A., Av. Santa Maria 0760, SANTIAGO, Tel. 39-4001.
- Colombia:** IND. PHILIPS DE COLOMBIA S.A., c/o IPRELENSO LTD., Cra. 21, No. 56-17, BOGOTÁ, D.E., Tel. 249 76 24.
- Denmark:** MINIWATT A/S, Strandlombsvej 2, P.O. Box 1919, DK 2300 COPENHAGEN S, Tel. (01) 54 11 33.
- Finland:** OY PHILIPS AB, Elcoma Division, Kaivokatu 8, SF-00100 HELSINKI 10, Tel. 172 71.
- France:** RTC-COMPELEC, 130 Avenue Ledru Rollin, F-75540 PARIS 11, Tel. 43388000.
- Germany (Fed. Republic):** VALVO, UB Bauelemente der Philips G.m.b.H., Valvo Haus, Burchardstrasse 19, D-2 HAMBURG 1, Tel. (040) 3296-0.
- Greece:** PHILIPS HELLENIQUE S.A., Elcoma Division, 54, Syngrou Av., ATHENS 11742, Tel. 9215311/319.
- Hong Kong:** PHILIPS HONG KONG LTD., Elcoma Div., 15/F Philips Ind. Bldg., 24-28 Kung Yip St., KWAI CHUNG, Tel. (0)-2451 21.
- India:** PEICO ELECTRONICS & ELECTRICALS LTD., Elcoma Dept., Band Box Building, 254-D Dr. Annie Besant Rd., BOMBAY - 400 025, Tel. 4930311/4930590.
- Indonesia:** P.T. PHILIPS-RALIN ELECTRONICS, Elcoma Div., Setiabudi II Building, 6th Fl., Jalan H.R. Rasuna Said (P.O. Box 223/KBY) Kuningan, JAKARTA - Selatan, Tel. 512572.
- Ireland:** PHILIPS ELECTRICAL (IRELAND) LTD., Newstead, Clonskeagh, DUBLIN 14, Tel. 693355.
- Italy:** PHILIPS S.p.A., Sezione Elcoma, Piazza IV Novembre 3, I-20124 MILANO, Tel. 2-6752.1.
- Japan:** NIHON PHILIPS CORP., Shuwa Shinagawa Bldg., 26-33 Takanawa 3-chome, Minato-ku, TOKYO (108), Tel. 448-5611.
(IC Products) SIGNETICS JAPAN LTD., 8-7 Sanbancho Chiyoda-ku, TOKYO 102, Tel. (03) 230-1521.
- Korea (Republic of):** PHILIPS ELECTRONICS (KOREA) LTD., Elcoma Div., Philips House, 260-199 Itaewon-dong, Yongsan-ku, SEOUL, Tel. 794-5011.
- Malaysia:** PHILIPS MALAYSIA SDN. BERHAD, No. 4 Persiaran Barat, Petaling Jaya, P.O.B. 2163, KUALA LUMPUR, Selangor, Tel. 77 44 11.
- Mexico:** ELECTRONICA, S.A. de C.V., Carr. México-Toluca km. 62.5, TOLUCA, Edo. de México 50140, Tel. Toluca 91 (721) 613-00.
- Netherlands:** PHILIPS NEDERLAND, Marktgroep Elcon, Postbus 90050, 5600 PB EINDHOVEN, Tel. (040) 793333.
- New Zealand:** PHILIPS NEW ZEALAND LTD., Elcoma Division, 110 Mt. Eden Road, C.P.O. Box 1041, AUCKLAND, Tel. 605-914.
- Norway:** NORSK A/S PHILIPS, Electronica Dept., Sandstuveien 70, OSLO 6, Tel. 68 02 00.
- Peru:** CADESA, Av. Alfonso Ugarte 1268, LIMA 5, Tel. 326070.
- Philippines:** PHILIPS INDUSTRIAL DEV. INC., 2246 Pasong Tamo, P.O. Box 911, Makati Comm. Centre, MAKATI-RIZAL 3116, Tel. 86-89-51 to 59.
- Portugal:** PHILIPS PORTUGUESA S.A.R.L., Av. Eng. Duarte Pacheco 6, 1009 LISBOA Codex, Tel. 68 31 21.
- Singapore:** PHILIPS PROJECT DEV. (Singapore) PTE LTD., Elcoma Div., Lorong 1, Toa Payoh, SINGAPORE 1231, Tel. 35 02 000.
- South Africa:** EDAC (PTY.) LTD., 3rd Floor Rainer House, Upper Railway Rd. & Ove St., New Doornfontein, JOHANNESBURG 2001, Tel. 614-2362/9.
- Spain:** MINIWATT S.A., Balmes 22, BARCELONA 7, Tel. 301 63 12.
- Sweden:** PHILIPS KOMPLEMENTER A.B., Lidingövägen 50, S-11584 STOCKHOLM 27, Tel. 08/7821000.
- Switzerland:** PHILIPS A.G., Elcoma Dept., Allmendstrasse 140-142, CH-8027 ZÜRICH, Tel. 01-488 22 11.
- Taiwan:** PHILIPS TAIWAN LTD., 150 Tun Hua North Road, P.O. Box 22978, TAIPEI, Taiwan, Tel. 7120500.
- Thailand:** PHILIPS ELECTRICAL CO. OF THAILAND LTD., 283 Silom Road, P.O. Box 961, BANGKOK, Tel. 233-6330-9.
- Turkey:** TÜRK PHILIPS TICARET A.S., Elcoma Department, İnönü Cad, No. 78-80, P.K.504, 80074 ISTANBUL, Tel. 4359 10.
- United Kingdom:** MULLARD LTD., Mullard House, Torrington Place, LONDON WC1E 7HD, Tel. 01-580 6633.
- United States:** (Active Devices & Materials) AMPEREX SALES CORP., Providence Pike, SLATERSVILLE, R.I. 02876, Tel. (401) 762-9000.
(Passive Devices) MEPCO/ELECTRA INC., Columbia Rd., MORRISTOWN, N.J. 07960, Tel. (201) 539-2000.
(Passive Devices & Electromechanical Devices) CENTRALAB INC., 5855 N. Glen Park Rd., MILWAUKEE, WI 53201, Tel. (414)228-7380.
(IC Products) SIGNETICS CORPORATION, 811 East Arques Avenue, SUNNYVALE, California 94086, Tel. (408) 991-2000.
- Uruguay:** LUZILECTRON S.A., Avda Uruguay 1287, P.O. Box 907, MONTEVIDEO, Tel. 91 43 21.
- Venezuela:** IND. VENEZOLANAS PHILIPS S.A., c/o MAGNETICA S.A., Calle 6, Ed. Las Tres Jotas, App. Post. 78117, CARACAS, Tel. (02) 2393931.

For all other countries apply to: Philips Electronic Components and Materials Division, International Business Relations, P.O. Box 218, 5600 MD EINDHOVEN, The Netherlands, Telex 35000 phctnl