
Digital

National Computer Conference 1983



Industry Spotlight: Laura Conigliaro on Robotics

Gate Arrays ● Modems ● Supercomputers

VOL. 13 NO. 5

Loaded with Features — Loaded with Benefits.

Kennedy products have always provided innovative new features. And these features have always provided added benefits and convenience for the user. For instance, our Model 6455 offers these features and benefits:

Feature: Start/Stop Operation

Benefit: Drive can emulate a 1/2" tape drive by providing

the ability to perform selective file back-ups, file-restructuring, journaling and software

updates.

The drive is effectively a 1/2" Tape Drive in a

smaller package.

Feature: Hard Read Error Spec. of 1 in 1011 bits.

Benefit: Best data reliability of any tape cartridge drive.

Gives the user confidence in the integrity of the

back-up medium.

Feature: On-board Diagnostics

Benefit: Drive can be tested off-line with no test

equipment required. Use of S.A. also lowers the

MTTR.

Feature: Cartridge Jam Protection

Benefit: Protects the cartridge from damage if cartridge

jams. This is accomplished by sensing a current

surge and then disabling the motor. Thus insuring that the cartridge will not be damaged.

Feature: High Density Recording

Benefit: Storage capacity of 23 MB on a single cartridge.

By now you can see what we're driving at. Model 6455 is full of unique features and benefits for you. For the complete story, write or call us today.

KENNEDY

An Allegheny International Company 1600 Shamrock Ave., Monrovia, CA. 91016 (213) 357-8831 TELEX 472-0116 KENNEDY TWX 910-585-3249

KENNEDY INTERNATIONAL INC.

U.K. and Scandinavia McGraw-Hill House Shoppenhangers Road Maidenhead Berkshire SL6 2QL England Tel: (0628) 73939

(851) 847871 KEN UKS G

KENNEDY INTERNATIONAL Koningin Elisabethplein, 8

B-2700 Sint-Niklaas Belgium Tel: (03) 777.1962 Telex: 71870 KEN CO





MULTIBUS* PLUS PERFORMANCE DEPENDABILITY FLEXIBILITY

Monolithic Systems Corporation has always been synonymous with Multibus technology. In fact, MSC has the distinction of having designed the first patented single board computer. Other firsts include: the first use of 64K RAM elements, on-board EPROMS, floppy disk controllers, APU's, user selectable addressing and multimaster CPU configurations. These board level accomplishments have benefited OEM's for over 12 years and have culminated into a powerful line of systems, the MSC 8800 series.

As the leading innovator in Multibus products, Monolithic Systems offers a family of systems intended to do things never done before. Systems to assist and create test programs for the scientific and industrial markets, to be multi-user and multi-tasking, to be expandable, rugged and reliable beyond anyone's expectations. Available with operating systems by Digital Research, the MSC 8800 series and board level products will be prominent factors in Multibus applications now and in the future.

For more information about Monolithic Systems Corporation and its Multibus product line call Toll Free 1-800-525-7661.



N corp. ... means technically advanced solutions.

USA


84 INVERNESS CIRCLE EAST ENGLEWOOD COLORADO 80112 303-770-7400 TELEX: 45-4498

EUROPE

JUSTINIANSTRASSE 22 6000 FRANKFURT aM MAIN 1 WEST GERMANY 611590061 TELEX: 41-4561

CANADA

6503 NORTHAM DRIVE MISSISSAUGA ONTARIO, CANADA L4V IJ2 416-678-1500 TELEX: 96-8769




- MULTIUSER SYSTEM
 MP/M* 7 USERS
 - CP/NOS* 16 USERS
- PERFORMANCE TRACK BUFFERED CP/M
- FLOPPIES / 10 MB CARTRIDGES / WINCHESTERS

- - MODULAR-EXPANDABLE DESIGN
 - 8 AND 16 BIT MICROPROCESSORS
 - HIGH SPEED RAM DISK
 - CUSTOM CONFIGURATIONS

*MP/M and CP/NOS are registered trademarks of Digital Research.

*Multibus is a registered trademark of Intel Corporation.

The rumor is true.



Only one company under the sun makes every type of peripheral controller for DEC* Computers.

See them all together for the first time at the N.C.C.

Booth #'s W6017, W6019, W6021, W6023

*TM Digital Equipment Corp.



THE WORLD'S LARGEST
INDEPENDENT MANUFACTURER
OF COMPUTER INTERFACES.

1995 N. Batavia Street, Orange, California 92665 714-998-6900 TWX: 910-593-1339

Write 3 for LSI-11; Write 5 for PDP-11


Digital Design



p. 32 (photo courtesy Cincinnati Milicron)



p. 59 (courtesy National Semiconductor)



p. 94 (photo courtesy Digital Productions)

Cover

The IC lay-out design on this month's cover is courtesy of Digital Equipment Corp., Engineering Systems Group, 200 Forest St., Marlboro, MA 01752.

Published monthly thirteen times a year with two issues in November. Copyright © 1983 by Morgan-Grampian Publishing Company, 1050 Commonwealth Ave., Boston, MA 02215. Second class postage paid at Boston, MA and at additional mailing offices. POSTMASTER: Send address changes to Morgan-Grampian Publishing Company, 1050 Commonwealth Ave., Boston, MA 02215. ISSN 0147-9245

COMPUTERS/SYSTEMS
Industry Spotlight: Trends in the Robotics Industry
IBM Compatibility—The IBM PC Comes Of Age
Supercomputers for the Eighties
Market Trends
Graphics System Design
PERIPHERALS
Floppy Emulation, Data Recording For Harsh Environments86 These new bubble memory based data recorders insure high data integrity under extreme conditions.
LSI Circuit Design Gives Modems More Capabilities
Technology Trends
COMPONENTS
Designers' Guide To Gate Arrays
Off-the-Shelf ICs Simplify Modem Design
Industry Firsts at ISSCC
Applications Notebook. 29 Fujitsu MBM27C64 Free Offer
Market Trends

Digital Design ■ May 1983

Calendar......12


News Update......16

Reader Service......115

CONVERT RGB to COMPOSITE VIDEO with LENCO's CCE-850 ENCODER.



Now you can display computer colorgraphics on a standard NTSC color television monitor, or videotape the information for distribution.



Lenco's CCE-850 Color Encoder is specifically designed to encode most RGB colorgraphics displays to NTSC type video.

This small, self-contained unit may be used in either tabletop or 19" rack mounted configuration, and includes a built-in color reference bar test pattern to ensure proper NTSC color monitor alignment.

Check these outstanding features:

- RGB To Composite Video
- Auto Sync Detector
- Detailed Enhancement
- High Resolution
- Color Test Patterns
- Self-Contained

Call or write today for detailed specifications, application notes, and price.

LENCO, INC., ELECTRONICS DIVISION

300 N. Maryland St., Jackson MO 63755, (314) 243-3147

Write 6 on Reader Inquiry Card

Digital Design

Publisher Jeffrey C. Hoopes Editor Jerry Borrell

Managing Editor Bob Hirshon Senior Technical Editor Dave Wilson

West Coast Doug Eidsmore Technical Editor

Associate Editor/

Directory Editor Julie Pingry **Assistant Editor** Mary Rose Hanrahan

Editorial Assistant

Andrea Coville

Ron Neale

International **Electronics Editor**

International Computers Editor Eric Wignall

Contributing Editor

Data Communications Walter Bolter, Ph.D.

Contributing Editor

Thomas DeFanti, Ph.D. **Graphics Systems**

Contributing Editor

Software William Ten Eick

Contributing Editor Software Andrew Rubel

Publication Services Manager Charlotte King **Production Manager** Jon Buchbinder

Art Director Richard D. Sarno **Associate Art Director** Tilly Berenson

Assistant Art Director Maureen Bernardini Production/Graphics Judy Osburn.

> Joan Scheffler. Vete Saulenas, Don Schaff

Promotion Manager Elaine Bull **Promotion Assistant** Sarah Pennington

Research Helen Obermayer, Peter Micheli Circulation Manager **Hugh Dowling**

Circulation Sarah Binder, Gary Byrne,

Deborah Goldstein, Lynda Neue **General Administration** Karen Melanson

Nancy Deveau Cassandra Ewing Dianna Lynn Reed Mal Rankin, Paul Christo Gloria D'Alessandro

Group Publishing Director Albert J. Forman

Advertising Sales

Northeast: John C. Moon (617) 232-5470, 1050 Commonwealth Avenue, Boston, MA 02215

Middle Atlantic: Barbara L. Smith (212) 340-9700, Morgan-Grampian Publishing, 2 Park Avenue, New York, NY 10016

Southeast: Rich Santos (404) 393-2505, 1224 Mt. Vernon Road, Dunwoody, GA 30338

Midwest: Hank Bean (312) 346-4611, Morgan-Grampian Publishing, 2 North Riverside Plaza, Chicago, IL 60606

South Central: Jerry Ambroze (713) 780-3326, Ambroze and Associates, 2186 Augusta, Houston, TX 77057

Northwest: Jim Teller, Ralph Peterson (408) 371-9620, 1901 S. Bascom, Suite 1005, Campbell, CA

Southwest: Pam Rock (213) 981-3300, 15910 Ventura Boulevard, Suite 1215, Encino, CA 91436

Telemarketing/Northwest: Cassandra Ewing (408) 371-9620, 1901 S. Bascom, Suite 1005, Campbell, CA 95008

Telemarketing/Southwest: (213) 981-3300, 15910 Ventura Boulevard, Suite 1215, Encino, CA


WE'RE PLOTTING A REVOLUTION IN

COlor

Now you can plot color faster, more easily, and more reliably than ever before. With a greater selection of brighter colors. In wider and longer formats. Create complex drawings and maps impossible to produce with any other machine. All with the revolutionary new Versatec electrostatic color plotter.

Produce an E-sized (34" by 44") full color drawing in eight minutes. And do it over and over again with all-electronic writing. This is a plotter that requires no operator intervention. It's perfect for remote and second-shift plotting. No pens. No jets. And no mess.

XEROX* is a trademark of XEROX CORPORATION




Draw plots of any complexity on 42-inch-wide paper in any length. Draw in full color or black & white. Use the full color spectrum with bright translucent toners. Gain the finest registration and plotting quality of any electrostatic plotter.

Versatec is plotting a revolution in color. So brighten up your world. Circle our readers'

service number for a free brochure.



2710 Walsh Avenue, Santa Clara, California 95051, (408) 988-2800 27/35 London Road, Newbury, Berkshire, England (0635) 31221 See Us at Canadian CAD/CAM, Systems '83 and NCGA





Less cost. Immediate delivery. Just two reasons system houses have looked to us for DEC compatible cabinets during the past seven years.

Want more? Ask about our superior quality. And our complete physical and functional interchangeability including DEC compatible power sources.

Choose from our complete line of the most popular DEC enclosures. But choose us. We look like DEC, you'll look like a hero.

Everest
Electronic
Equipment, Inc.



2100 E. Orangewood Ave. Anaheim, California 92806 (714) 634-2200

*DEC is a trademark of Digital Equipment Corporation

Write 8 on Reader Inquiry Card

HAS YOUR ADDRESS CHANGED— ARE YOU PLANNING TO MOVE IN THE NEAR FUTURE??

Please use the enclosed qualification form to notify us of your address change. A change of address requires that you fill out the entire form.

Please allow 6-8 weeks for your change to take effect.

Digital Design

EDITORIAL, SALES, AND CIRCULATION OFFICES

Digital Design 1050 Commonwealth Avenue Boston, MA 02215 Telephone: (617) 232-5470



MORGAN-GRAMPIAN

CORPORATE HEADQUARTERS

Morgan-Grampian Publishing Company, 2 Park Avenue, New York, NY 10016, (212) 340-9700. Domenic A. Mucchetti, President.

EXPOSITIONS GROUP

Morgan-Grampian Expositions Group, 2 Park Avenue, New York, NY 10016 (212) 340-9700. Robert Poggi, Director.

Morgan-Grampian publishes the following in the United States: American City & County
• Circuits Manufacturing • Contractor • Electronic Imaging • Electronics Test • Industrial Distribution • Industrial Product Bulletin • Mart • Municipal Index

New Publication Development

H.G. Buchbinder, Director

Morgan-Grampian also publishes the following in the United Kingdom: Electronic Engineering • Control & Instrumentation • Electronic Times • What's New in Electronics • What's New in Computers.





SUBSCRIPTION POLICY

DIGITAL DESIGN is circulated only to qualified research, development and design engineers and engineering managers primarily responsible for computer products and systems in OEM plants. To obtain a complimentary subscription, request (on company letterhead) a qualification card from Circulation Director. For change of address, attach old address label from recent issue to new company letterhead or note. Send this plus request for new qualification card to:

Circulation Department
DIGITAL DESIGN
1050 Commonwealth Avenue
Boston, MA 02215

Subscription rates: non-qualified subscribers (US and Canada) — \$35/yr; foreign — surface mail — \$45; air mail — \$70. Single copies — \$4.

DIGITAL DESIGN solicits editorial material and articles from engineers and scientists. Contributors should submit duplicate manuscripts typed with two spaces between lines. All illustrations should be clear; components on all schematics and line drawings should be labeled. The editors assume no responsibility for the safety or return of any unsolicted manuscripts.

Lundy computer graphics maintenance always generates a very reassuring picture for you and your company.

The Lundy service network offers you 4 types of service, over 40 service locations, 6 maintenance depots, over 130 service personnel, plus a special backup service team consisting of over 30 trouble shooters.

Lundy computer graphics terminals, workstations and rack-mounted generators have earned a well-deserved reputation for reliability. But if a problem does arise, you want service—and you want it now. Lundy delivers.

Service tailored to your requirements.

Lundy offers you a choice of four types of service:

- 1. Network Service. We assign highly trained personnel from over 40 service locations nationwide. Available service options include: on-call, on-site or time and material.
- **2. Backup Service.** To guarantee that even the most difficult problem finds its solution, we maintain a special trouble shooting team. Sixteen engineers and 15 technical specialists are available to help our customers anywhere.
- **3. Customized Service.** If your particular operation calls for special service requirements, we sit down with your



Lundy offers over 130 servicemen.

people to discuss and analyze your precise needs. Then we plan a program that meets those needs.

4. Depot Service. This service covers instances when it is impractical to repair equipment on site. Equipment is shipped to one of the nearest 6 maintenance depots for immediate attention.

Whichever type of service is best for you, you can count on our trained and experienced servicemen. And their training is constantly updated by a series of Training Refresh Seminars held at regular intervals at our service centers.


We'll help you see more in graphics.

When you take a close look at our graphics terminals, service, support, software, systems capability, enhancements—and our company—you'll understand why Lundy can help you see more in graphics now and in the long term.

For more information, write Lundy Electronics & Systems, Inc., Glen Head, New York 11545, or call: (516) 671-9000.



The Lundy service map was generated on a Lundy T5688 raster terminal. Both Lundy products and Lundy service set industry standards.




Write 9 on Reader Inquiry Card

SIGNA'S ITAGAIN LOW DLV 11J.



FEATURES:

- + Four-channel asynchronous serial line interface
- Each channel has individually switch selectable baud rates from 150 to 38.4K, along with switch selectable address and vectors
- Improved receivers and transmitters provide outstanding reliability, plus support of RS-232C, RS-422 and RS-423 protocols
- Fully compatible with DEC* operating systems and diagnostics designed for the DLV11J
- Proven product, we have delivered thousands



Sigma Information Systems

SIGMA offers a complete line of DEC* compatible disk controllers, interface devices and system enclosures for the LSI-11.


CALL your nearest sales office for information on <u>all</u> products. ASK about our New 1/4" tape controller.

USERS: DONE ANDAGAIN! LOW DLV 11J/8.



FEATURES:

- + Eight-channel asynchronous serial line interface
- Supports standard EIA RS232C (data leads only)
- Fully compatible with DEC* operating systems and diagnostics written for the DLV11J
- Switch selectable baud rates for each channel ranging from 50 to 19.2 K baud
- Switch selectable device addressing vector assignments and data word format
- Operates as a polled or interrupting device dictated by software
- * OEM Quantities
- * DEC Compatibility
- * Registered trademark of Digital Equipment Corporation





6505C Serrano Avenue, Anaheim CA 92807 Telex 298607 SGMA (714) 974-0166

Orange CA (714) 633-0652 / 771-7320 • San Jose CA (408) 243-9112
Valencia CA (805) 259-6559 • Winter Park FL (305) 628-8896
Boston MA (617) 938-1310 • Minneapolis MN (612) 881-5015
Edison NJ (201) 572-3722 • Gresham OR (503) 241-2216
Houston TX (713) 451-0466 X71 • Salt Lake City UT (801) 355-3045
Vienna VA (703) 448-6800 • Toronto ONT (416) 499-6201

Dear Editor:

Your March 1983 "News Update" use of the term "Japscam" is totally inappropriate. "Jap" (and your derivation, "Japscam") is a racial slur. This type of racist reporting falls below minimal professional journalistic standards, and it denigrates the engineering profession as well. Sir, you owe all of us an apology.

Larry Widigen 2918 Paseo del Refugio Santa Barbara, CA 93105

Ed. Reply: We apologize to those who were offended by the term "Japscam" in our March News Update. It should be noted, however, that the term was enclosed in quotation marks to indicate that it was a colloquial term not coined by our staff, who were merely reporting the facts—one of which was that the controversy was commonly referred to as "Japscam." Also, it is our opinion that whoev-

er coined the term "Japscam" was probably following the trend to describe any national controversy by the first syllable of the country followed by "scam." As such, "Japscam" is probably as devoid of racist intent as would be "Amscam," "Mexiscam" or "Canscam".

Dear Editor:

Since we believe that Raster Technologies currently enjoys the distinction of being the fastest-growing supplier of intelligent color graphics controllers, we were quite surprised that we were omitted from your article on color graphics terminals and workstations in the February issue of Digital Design. Raster Technologies offers the fully compatible Model One family of color graphics controllers using 64K RAM memories for superior price/performance. (In fact, Raster was the first to use 64K RAM chips; its architecture was specifically developed for 64K RAM.) Raster's graphics controllers are used by original equipment manufacturers and by end-users for widely varied applications, incuding computer-aided design, business graphics, and land resource analysis.

Readers of *Digital Design* who wish further information should contact me directly.

Roger P. Nielson VP, Sales and Marketing 9 Executive Park Dr. North Billerica, MA 01862

Errata

The diagram used to lead our February feature on ergonomics (p. 24) ran without a credit line. The diagram was derived from a photograph supplied courtesy of Wright Line, Inc. *Digital Design* regrets the oversight.



Memory Mapped Process Interfaces... The Missing VME Link.



Monitek has found the missing link between today's microcomputers and industrial processes: M² π Memory Mapped Process

Interface Subsystems. $M^2\pi$ places the system/process interface where it's always belonged: between processes and programs.

So for the very first time, programs "see" industrial processes as automatically mapped blocks of memory. And communications between programs and processes are handled by simple read and write operations.

With $M^2\pi$, you'll free the CPU from database update chores. Simplify programming. End hassles with hardware. And have a stand-alone process interface subsystem that offers you single-point modularity, Eurocard design, and VME synergy. For full details, call or write us today. Monitek, Inc., Digital Systems Division, 1495 Zephyr Avenue, Hayward, CA 94544.Phone: (415)471-8300.

MOUNTER

Write 13 on Reader Inquiry Card

SCHERERS

MODEM SALE

* * * Brand New * * *

DEC DF03-AA or VADIC 212-LC

YOUR CHOICE

300/1200 Baud — Bell 103/212A Compatible Originate and Auto Answer

*\$495.00 Each

*During MAY & JUNE 1983 with the purchase of ANY of our NEW or USED

DEC Terminals & TI Printers you have the fantastic option to purchase a 300/1200 Baud Modem for \$495.00

SCHERERS

FOR MORE DETAILS

CALL:

HERERS*SCHERE


6145 Scherers Place Dublin, OH 43017 (614) 889-0810

SPECIALISTS IN: DEC EQUIPMENT TI PRINTERS

*SCHERERS*SCHERERS*

Write 15 on Reader Inquiry Card

MPA-2000 Intelligent I/O Controller Your Key to Multibus Modularity



As Versatile As Your Imagination

Imagine, a single MULTIBUS board that can measure up to your most demanding requirements, now and in the future! The MPA-2000 packs more plug-in versatility in a SINGLE CARDSLOT, for applications as diverse as data communications, disk, inter-bus link or single board computers. In fact, the possibilities offered by the unique modularity of the MPA-2000 are limited only by your imagination. And since it is from METACOMP, the MPA-2000 means high performance . . .

- ON-BOARD 8 MHz. iAPX-186 CPU WITH:
 - Full 16M address, Multimaster capability
 - 64K EPROM
 - 128K RAM with parity (64K can be dual-ported)
 - i80130 OSF (iRMX-86* kernel)
 - Flexible interrupt structure
 - Serial I/O Monitor/Debug Port
- EIGHT PROGRAMMABLE DMA CHANNELS
- LOW PROFILE PLUG-IN MODULES
 - Field interchangeable
 - Modules for Serial I/O, Disk, Parallel I/O
 - Custom modules easily designed
 - Serviced by DMA channels
 - Can be configured as iSBX* module sites
- STANDARD MULTIBUS INTERFACE
 - Single unit load
 - Single cardslot height (even with plug-in modules)
- UNIQUE MetaPaket[™] ARCHITECTURE
 - High speed hardware/firmware technique allows message transfer between intelligent devices
 - Shared memory not required



METACOMP, INC.

7290 Engineer Rd., Suite F · San Diego, CA 92111 (619) 571-1168 · TWX: 910-335-1736 METACOMP SDG

*MULTIBUS, iRMX-86. iSBX are trademarks INTEL CORP. MetaPaket is trademark METACOMP, INC., patent pending

May 31-June 2

CAD/CAM & Robotics. Toronto International Center of Commerce, Toronto, Canada. Contact: Macgregor & Assoc., 662 Queen St., Toronto, Ont., M6JIE5. (416) 363-2201.

June 1-3

ICA Conference & Expo. Anaheim Convention Center, Anaheim, CA. Contact: ICA (301)656-5794.

June 2

Personal Computer Workshop. Charlotte, NC; June 16–18, Reston, VA. Contact: CEC, Virginia Tech., Blacksburg, VA 24061. (703) 961-4848.

June 2-5

Seattle Computer Showcase Exposition. Seattle Center. Contact: The Interface Group (617)879-4502.

June 5-8

International Summer Consumer Electronics Show. McCormick Place, Chicago, IL. Contact: William Glassgow (312)861-1040.

June 6-7

IC Processing Techniques & Ion Implantation. Hyatt Palo Alto, Palo Alto, CA. Contact: Dept. 564 N, U of C Ext., 2223 Fulton St., Berkeley, CA 94720. (415) 642-4151.

June 6-10

Optical Storage Conference. Arlington, VA. Contact: SPIE, P.O. Box 10, Bellingham, WA 98227. (206) 676-3290.

June 6-8

Intermexpo. Monterrey, Nuevo Leon, Mexico. Contact: SME, One SME Drive, Dearborn, MI 48121. (313) 271-0023.

June 6-10

Cell Designer Course. Melbourne, FL. Contact: Harris Corp., P.O. Box 883, Semiconductor Group, Melbourne, FL 32901. (305) 724-7800.

June 6-12

Microprocessor Application Course. MIT, Cambridge, MA. Contact: MIT, 105 Mass. Ave., Cambridge, MA 02139. (617) 253-7406

June 7-9

The Office Automation Show. Barbican Centre, London, England. Contact: Phone (301)657-3090.

June 7-9

Industrial Exposition. Milwaukee Exposition Ctr., Milwaukee, WI. Contact: SME, One SME Dr., Dearborn, MI 48128. (313) 271-0023.

June 7-10

Hong Kong Computer '83. Wanchai, Hong Kong. Contact: Terry Hill, Industrial and Trade Fairs International, Ltd. Radcliffe House, Blenhelm Court, Solihull, West Midlands B91 2BG UK. (021)705-6707.

June 7-10

Network Design Course. Washington, D.C. Contact: ICS, 3304 Pico Blvd., Santa Monica, CA 90405. (213) 450-2060.

June 8-9

Robotics Overview. Indianapolis, IN. Contact: John McEachran (313)271-1500.

June 8-10

Computer Showcase Exposition. H. Roe Bartle Hall, Kansas City, MO. Contact: David Sudkin (617)879-4502.

June 8-10

X.25 Seminar. Hyatt Regency Crystal City, Arlington, VA. Contact: TTI, 741 10th St., Santa Monica, CA 90402. (213) 394-8305.

June 9-11

Microcomputer Education Workshop. Watertown, CT. Contact: TERC, 8 Eliot St., Cambridge, MA 02138. (617) 547-3890.

June 13-15

Production Project. Rochester, NY. Contact: The University of Rochester, Rochester, NY 14627. (716) 275-3106.

June 13-16

ATE East Conference. Hynes Auditorium, Boston, MA. Contact: Katherine Bochonko, Morgan-Grampian Expositions Group, 1050 Commonwealth Ave., Boston, MA 02215. (212)340-9780.

June 13-16

Syntopican XI. San Francisco, CA. Contact: James L. Donlo, International Information/Word Processing Association, 1015 N. York Rd., Willow Gr., PA 19090. (215)657-6300.

June 13-16

Data Aquisition Seminar. Sunnyvale, CA. Contact: Continuing Education Institute, Oliver's Carriage House, 4510 Leaf Treader Way, Columbia, MD 21044. (301)596-0111.

June 13-17

Power Electronic Course. Los Angeles, CA. Contact: TESLAco, 490 S. Rosemead Blvd., Pasadena, CA 91107. (213)795-1699.

June 14-16

AFCEA 37th Annual Convention. Sheraton Washington, Washington, DC. Contact: John Spargo (703)820-5028.

June 14-16

Ohmcon '83. Contact: Jerry Fossler, Electronic Conventions, 8110 Airport Blvd., Los Angeles, CA 90045. (213)772-2965.

June 14-16

International Information/Word Processing Syntopican. Moscone Center, San Francisco, CA. Contact: H.G. Asmus (201)444-0505.

June 14-16

International Robot Conference. Long Beach Convention Center, Long Beach, CA. Contact: Bill Harrington (312)668-8100.

June 14-18

Technology Exhibition. Earls Court Exhibition Ctr., London. Contact: Radeliffe House, Blenheim Ct., Solihull, West Midlands, B912B6. (021) 705-6707.

June 14-18

Techtronica '83. Earls Court Exhibition Center, London, England. Contact: Industrial and Trade Fairs Ltd. (021)705-6707.

June 15-18

EMC Workshop. Washington, DC. Contact: Don White Consultants Inc., (703) 347-0030.

June 17-19

PC '83. San Francisco, CA. Contact: The National Computer Shows, Boylston St., Chestnut Hill, MA 02167. (800)841-7000.

June 20-22

Symposium on Computer Arithmetic. Aarhus, Denmark. Contact: Prof. T.R.N. Rao, USL, Box 44330, Lafayette, LA.

June 20-July 15

CE '83. Princeton, NJ. Contact: Institute for Professional Development, 245 Nassua St., Princeton, NJ 08540. (609)924-8333.

June 20-24

Seminar on Computer System Implementation. Jamestown, NY. Contact: Camconco, P.O. Box 53, Berne, NY 12023. (518)872-2426.

June 22-24

Computerama '83. Automotive Exhibition Place, Toronto, Ontario, Canada. Contact: James Mahon (416)967-6200.

June 23

ACM Symposium. Red Lion Motor Inn, Sacramento, CA. Contact: A. Hankinson, B266 Technology Bldg., National Bureau of Standards, Washington, DC 20234. (301)921-2208.

June 21-22

Digital Filters and Spectral Analysis Course. San Diego, CA. Contact: Ruth

HUGHES


SOLID STATE PRODUCTS

Read Only Memories

SELECT HUGHES CMOS ROMS AND BENEFIT:

- High Density CMOS
- Lower Power
- Fast Turnaround
- Industry Standard Pin Outs also 1802 Compatibility
- Military & Commercial Specifications
- Select your package from five options

HUGHES has your CMOS ROM problems solved!



HUGHES... A leader in CMOS Technology

Hughes Solid State Products 500 Superior Avenue Newport Beach, CA. 92663 Telephone: (714) 759-2942 TWX: 910-596-1374 (800) 854-7438 In Europe: Hughes Aircraft Intl. Service Co. Schmaedel Str. 22, 8000 Münich, Germany Telephone: 49-89-8347088 Telex: 5213856 HSPD

REPRESENTATIVES: R.H. Sturdy Co. (617) 235-2330; Tri-Tech Electronics, Inc. (315) 446-2881; Robert Diamond, Inc. (212) 423-7330; B.G.R. Associates (609) 428-2440; Arbotek (301) 461-1323; L. & D. Inc. (919) 292-3201; Delmac Sales (305) 898-4688; Luebbe Sales (513) 871-4211; Bill Deming & Associates, Inc. (612) 888-5000; Carlson Electronic Sales Co. (312) 956-8240; J & W Sales (317) 842-3740; Technical Sales Associates (913) 888-3330; Sundance Sales (214) 699-0451; Compass Marketing & Sales (602) 266-5400; N.R. Schultz Co. (206) 454-0300; 12 Inc. (408) 988-3400; Select Electronics (714) 739-8891; Wesa Engineering (714) 278-8021; Vitel Electronics (514) 331-7393

Calendar

Dordick, Integrated Computer Systems, 3304 Pico Blvd., Santa Monica, CA 90405. (213)450-2060.

June 26-30

National Computer Graphics Association. Chicago, IL. Contact: Nancy Lefebvre, NCGA, 8401 Arlington Blvd., Fairfax, VA 22031. (703)698-9600.

June 26-29

ACM/IEEE Design Automation Conference. Fountainbleu Hotel, Miami Beach, Fl. Contact: American Federation of Image Processing Societies (301)589-8142.

June 27-29

Design Automation Conference. Fontainbleau Hotel, Miami Beach, FL. Contact: Hillel Ofek, IBM Corp., Columbia St., Poughkeepsie, NY 12602. (914)485-7763.

June 27-29

Localnet '83. The New York Hilton, New York, NY. Contact: On-Line Conference (212)563-1000.

June 27-29

Videotex '83. The New York Hilton, New York, NY. Contact: London On-Line Inc., 1133 Avenue of the Americas, New York, NY 10036. (212)692-9003.

June 27-July 1

Laser '83 Opto-Electronik. Trade Fair Center, Munich, Germany. Contact: Lallman Associates (201)652-7070.

June 28-30

Symposium on Fault-Tolerant Computing. Jolly Hotel, Milano, Italy. Contact: Luca Simoncini, I.E.I. C.N.R., Via Santa Maria 46, 1-16100 Pisa PI, Italy +39 50 500159.

July 4-5

Optical Imaging Systems Meeting. International Conference Center, Kobe, Japan. Contact: Dr. Ichiro Kitano, Nippon Sheet Glass Co. Ltd. 1, Kaido Shita Konoiki, Itami, Hyogo 664 Japan.

July 8

System Documentation Seminar. Seattle, WA. Contact: TCA, 1250 Oakmead Pkwy., #210, Los Angeles, CA (800)792-0990.

July 9-12

NCC Board Conference. Las Vegas, NV. Contact: Ann-Marie Bartels, 1815 N. Lynn St., Arlington, VA 22209. (703)558-3641.

July 11-13

Summer Computer Simulation Conference. Hyatt Regency, Vancouver, B.C.,

Canada. Contact: The Society for Computer Simulation, P.O. Box 2228, La Jolla, CA 92038. (714)459-3888.

July 11-15

Digital Signal and Image Processing Course. Washington, DC. Contact: Integrated Computer Systems, 3304 Pico Blvd., Santa Monica, CA 90405. (213)450-2060.

July 12-13

Fiber Optics Course. Hyatt Regency Montreal, Canada. Contact: Information Gate-keepers Inc. (617)739-2022.

July 17-22

Power Engineering Society Summer Meeting. Los Angeles Hilton, Los Angeles, CA. Contact: Robert L. McMillen, Los Angeles Dept. of Water and Power, 11 N. Hope St., Los Angeles, CA 90051.

July 24-29

Siggraph '83. Detroit, MI. Contact: Siggraph '83 Conference Office, 111 E. Wacker Dr., Chicago, IL 60601. (312)644-6610.

July 27-28

Softfair, Hyatt Regency, Crystal City, Arlington, VA. Contact: IEEE, Harry Hayman (301)589-8142.



for STD BUS Products

In the poker game of today's STD Bus Board market, dy-4 systems now provides you with the winning hand — using only two cards. The DSTD-711 64K RAM/Floppy Disk Controller/DMA card, and the DSTD-102 CPU/Serial I/O (2-RS232C)/Bytewide processor card is a two card call on a full house from the other major STD players.


The result is a big pot in savings to you the customer. Lower board cost, reduced slots, reduced power requirements, — cost savings all around the table.

If you're going to play the game, play it with the best hand — contact dy-4 systems

and make a deal.

dy-4 SYSTEMS INC.

888 Lady Ellen Place Ottawa, Ontario, Canada K1Z 5M1 (613) 728-3711



...HIGHEST DENSITY, VERSATILITY.

Designed for economy, short lead time and changeability, Methode Logic Boards offer the maximum number of pins per column based on 16 pin devices. They accommodate .300", .400", .600" and .900" spaced devices and provide a continuous ground plane, to reduce noise and cross-talk, and include a single or dual voltage plane option. A full range of accessories are available.

ADVANTAGES OF (WRAPPABLE) LOGIC BOARDS VS. PRINTED **WIRING BOARDS:**

- Wire-wrap socket panels have a shorter R & D and manufacturing lead time and are more economical in low quantities.
- Logic boards have a system density of 2 - 21/2 times greater
- Wire-wrap systems are easier to adapt or modify to engineering changes.
- Ideal for prototyping, Logic Boards are frequently employed for production use, too.

STANDARD DESIGNS: Intel Multibus **DEC Quad & Dual** Eurocard Single & Dual Motorola Exorciser® & Hybrid (above) S-100 BUS & Voltage Regulated Ziloa Z-80 Prolog STD BUS

DEVICE MANUFACTURERS OF NEW SURFACE MOUNTED CONFIGURATIONS ARE INVITED TO CONSULT ON NEW LOGIC BOARD APPLICATIONS.



Write 18 on Reader Inquiry Card

News Update

Device Driver Development Program

Graphic Software Systems Inc. and Digital Research Inc. have announced that eleven major graphics peripherals manufacturers have agreed to participate in their joint device driver development program. Through the program, announced last month, graphic software and operating system specialists develop device drivers. These device drivers are then offered to customers through the Graphics System Extension (GSX) for the CP/M operating system.

Microcomputer Market

Intelligent Technologies International, Palo Alto, CA will introduce its first products; a series of board-level micro-to-micro and micro-to-mainframe communications packages for the IBM PC, within the next two months.

CTC/Allen-Bradley Agreement

Computer Technology Corp., Milford, OH has announced the signing of a marketing and investment agreement with the Allen-Bradley Co., Milwaukee, WI. The marketing agreement gives Allen-Bradley exclusive marketing rights of the IPS in computer applications. CTC maintains the manufacturing rights and will be the sole supplier of the IPS system components to Allen-Bradley. The investment agreement covers the purchase by Allen-Bradley of a minority equity position.

PolyComputers To Develop Desk-Top

PolyComputers, Inc. has announced that it has received \$800,000 in funding from a Research and Development Limited Partnership to develop a desk-top version of the PolyComputer which will be capable of processing at a sustained rate of 7 million instructions per second ("MIPS") in concurrent time-sharing, real-time, and multiple batch stream modes, with virtual memory support.

James Tolley, President of PolyComputers, indicated that, "this new development funding will enable us to offer a complete line of multiprocessing virtual memory systems from well under \$20,000 to a 17-CPU, 16 MIPS version at under \$100,000.

Plated Media Joint Venture

Onyx + IMI, Inc has announced the formation of a joint venture between Onyx + IMI,

Inc. and Knudsen Systems, Inc. of Chino, CA to manufacture thin-film plated media for use in Winchester disk drives. The company will be called KSI Disk Products and will also engage in R&D for vertical recording technology.

TI, SEEQ Technology To Cross License

Texas Instruments, Inc., and Seeq Technology, Inc., have announced an agreement for the application of Seeq's nonvolatile E²ROM (electrically erasable, read-only memory) technology to TI's TMS7000 eight-bit, single-chip microcomputer family. Under the terms of the agreement, Seeq will develop versions of the TMS7000 family using Seeq's 2K×8 five-volt-only E²ROM program memory in place of TI's standard ROM memory. Seeq, in turn, will make the resulting E²ROM TMS7000 and several future versions available to TI beginning in 1984.

Esprit Purchases Hazeltine Line

Esprit Systems, Inc. has announced it has completed the purchase of the Computer Terminal Equipment Product Line from Hazeltine Corp. Esprit Systems is a new company formed by the management group of this product line together with Rosenkranz & Co., a New York City based Investment Banking Firm, and Oxford Partners, a Stamford, Connecticut based Venture Capital Firm specializing in high technology investments.

Magnex Signs Benchmark Contract

Magnex Corp. has signed a "benchmark multi-million dollar contract" to provide its MIS-180 thin-film magnetic disk read-out heads to Storage Technology Corporation (STC). The Magnex MIS-180 heads will be used by STC in its 8380 disk drive subsystem, a data storage system with a capacity of 2.5 Gbytes that is plug-compatible with the IBM 3380 disk drive.

Archive Corp. Signs \$2.5M Contract

Archive Corp. has been awarded a \$2.5M contract to provide streaming cartridge tape drives to Sun Microsystems, Mountain View, CA. Under the terms of the agreement, Sun Microsystems will purchase both Archive's 20 and 45 Mbyte Intelligent Sidewinder and Super Sidewinder.



It's a rare graphics system that can produce business graphics and also operate as an engineering work station for under \$20,000. The Beacon™ System from Florida Computer Graphics puts it all right at your fingertips.

Using Multi-Processor Architecture (MPA) and 48-bit microcoded firmware, the Beacon System produces virtually instan-

taneous generation of vectors, arcs, circles, rectangles,

and polygon fills. And BeaconBRIGHT™ makes those images far more visible even in brightly lit areas.

With the addition of 640KB of optional graphics memory, Beacon's 640 X 480 resolution can create a 1280 X 960 addressable image, typical of many CAD/CAM applications. This higher resolution, combined with the standard BeaconROAMTM and Zoom features, makes Beacon ideal for many engineering and scientific applications.

Check these unique Beacon features, standard on all models.

A wide range of true graphics and

addressability, 1X zoom increments (up to 16X), horizontal and vertical scrolling in variable speed, and more.

A palette of 256 colors; 32 usable at one time (16 in the graphics planes, 16 in the alphanumeric plane).

 Superior ergonomic design. From a display that's twice as steady as those advertised as "flicker free" to the monitor that tilts, swivels, and adjusts in height. Beacon leads the way in human-factors engineering.


Beacon works with joysticks, light pens, digitizer tablets, printers or plotters. It also interfaces with slide cameras, color copiers and even large screen video projectors.

For generating either business or engineering graphics, the Beacon System (stand alone or host dependent), offers a spectrum of capabilities unmatched in its price category. To find out more write for our full color literature:

Marketing Communications Manager Florida Computer Graphics, Inc. 1000 Sand Pond Road, Lake Mary, FL 32746. Or call (305) 321-3000. In the Continental



WE SOLVE PROBLEMS!



Integrated PCB

Kit form

Chassis version

Meet some of our new problem solvers.

AUDIOTRONICS

High performance, innovative design data displays in 9", 12" and 15" screen sizes, for system designers like you. And they're all available in integrated, chassis or kit versions.

Using these basic displays, our engineers become your engineers! They custom design a display for your specific application, meeting your particular system design requirements. Scanning frequencies to 32 KHz and more. Up to 1200 line resolution. TTL or composite

video. 120 or 240V AC, or 12 or 24V DC. Give us your specifications and we'll solve all your display problems. And we'll deliver on time, when you want them.

Audiotronics has been solving problems for over 25 years, designing hundreds of custom data displays for important customers, large and small. Call today. Turn our engineers loose with your display system problems.

See Us at NCC Booth D1100, Disneyland Hotel

North Hollywood California 91605 (213) 765-2645

Write 34 on Reader Inquiry Card

MiniScribe V

MiniScribe will announce 3 and 4 platter 51/4" Winchesters at NCC. Designated MiniScribe V, the hard disk systems are expected to have a maximum capacity of 40 Mbytes with oxide media and 52 Mbytes if plated media is used. The V features an access time of 65 ms, almost double the performance of the MiniScribe IV. OEM pricing is about \$700 or \$200 less than closed loop drives of similar capacities. Production is slated for the 3Q of 1983.

Winchester Disk Controller Board

Adaptec Inc., Milpitas, CA recently announced a new fully SASI/SCSI compatible Winchester disk controller board. The ACB-4000 is priced at \$150 in high volume OEM qty. The ACB-4000 is currently available as a board along with ACS-4000, a licensed chipset version of the product.

Raster, Auto-trol Sign \$1.5M Deal

Raster Technologies, Inc. signed a 2-year OEM agreement worth approximately \$1.5M to supply Auto-trol Technology with color raster-scan controllers for their CAD work-stations. Raster Technologies' Model One controller is capable of 1024×1024 resolution with four bit planes of image memory allowing simultaneous display of up to 16 colors.

DEC, Molecular Design Agreement

DEC and Molecular Design Ltd. (MDL) announced a cooperative marketing agreement to promote use of MDL application software packages on DEC's VAX superminicomputer systems. Under the agreement, MDL is adapting its line of chemistry-oriented application software packages to DEC's family of VAX 32-bit superminicomputers.





SUBSCRIBE TO SUCCESS REFERENCE The Business Journal For IBM Personal Computing

Are you in business?
Read **REFERENCE** to find out how you can utilize the IBM Personal Computer in your business.

Yes, I want to subscribe to REFERENCE magazine for 1 year (6 issues) for only \$18.00.
Add \$3.00 for Canada and Mexico. Other foreign countries add \$6.00 (surface mail).

PLEASE PRINT

NAME

COMPANY

ADDRESS

CITY

STATE

ZIP

- □ Personal Check Enclosed□ Money Order Enclosed
- ☐ MasterCard
- □ Visa

Card #

Exp.

Interbank #

Signature

(4)/KESKKKES

P.O. Box 100, Dept. **M-5** Milford, NH 03055 603-673-9544

Write 21 on Reader Inquiry Card

Technology Trends

3M Preparing For New Media

The 3M company of St. Paul, Minnesota has one of the more optimistic outlooks on the market for magnetic media and storage products. The firm's St. Paulbased research laboratories reportedly have several technologies prepared for use in media products. In the area of micro floppy media, 3M is working on all sizes announced to date: 3.0, 3.25, 3.5 as well as the recent IBM announcement, 4.1. Representatives indicate, however, that they consider the media or sub-

strate their crucial consideration, rather than size. Vertical recording, particulate versus thin film, thin media applications processes, coercive recording processes and stable recording substrates are among the key issues being studied. The company is likely to bring a great deal of hidden strength to the field, being the largest producer of magnetic media in the world, or second after TDK if flexible media only are considered.

—Borrell

Write 232

IBM Introduces 4" Diskette Drive

IBM recently introduced their new 4" diskette drive at the January 26, 1983 ANSI meeting in San Diego. ANSI is currently considering three proposals: the 3", 3.25" and 3.5" media format. IBM's introduction could produce even longer delays in setting standards should they decide to push for support.

The IBM 0341 diskette drive records on one side of the 4" IBM

DemiDiskette using FM encoding. Capacity is 358 Kbytes unformatted. Other specs include: 46 tracks, 6865 bpi, and 68 tpi. The drive has both read and write capabilities and contains the required power drivers for controlling the drive.

The drive is available now and is priced at \$600 in single quantity and at \$165 each for OEM quantity 10,000. Write 231





Figure 1: IBM 0341 4" diskette drive.



Renco understands motion control. And the need for high reliability encoders in industrial automation systems. And since we've been engaged in the control of incremental motion and its conversion to digital logic since 1968, we also understand and deliver interface electronics for robotics and other industrial applications requiring precise mo-

tion control.

cludes incrementals, modulars, absolutes, analogs and linears. All of these, whether supplied as part of our off-the-shelf programs or in custom configurations, are compatible with CNC and programmable controllers.

To learn more about how Renco turns to industrial automation, send for our comprehensive Reference Guide to Optical Encoders. Then at your next opportunity to incorporate encoders in an industrial automation system design, turn to us.

> Division of Electro-Craft Corporation 26 Coromar Drive, Goleta, CA 93117 805/968-1525



Write 22 on Reader Inquiry Card

Flat Electronic Displays In Computer Products & EDP Applications

The current and anticipated growth in the computer terminal display market is a reflection of the ever expanding market for computers and related equipment.

The traditional CRT display will continue to dominate as the major display technology used in computer terminals, at least through the end of this decade. The CRT's ability to display several thousand characters and its tremendous cost effectiveness (4 to 6 cents/character) are the main reasons for this projected domination. By comparison, the emerging flat, dot matrix display technologies will be limited to smaller numbers of characters. and will be more expensive on a per character basis.

Competing Technologies

During the next seven years, we see a number of competing flat panel display technology types emerging: flat CRTs, LCDs (Liquid Crystal Displays), VFDs (Vacuum Fluorescent Displays), PDPs (Plasma Display Panels), EL (Electroluminescent), GEP (Gas-Electron-Phosphor), and Electrophoretic Information Displays (EPID). At present, LCDs, VFDs, PDPs and EL panels are being used in computer/EDP applications but only on a limited basis.

The projected U.S. and worldwide markets for flat panel displays used in computer applications are shown graphically in Figure 1. The U.S. market will grow from \$24 million this year to nearly \$40 million by 1985 and to over \$90 million by 1990. This year's worldwide market will be just over \$65 million. As the economy improves this year and next, the worldwide market for these displays will grow by 30% in 1984. An average annual growth rate of 25-30% is expected between 1985 and 1990; the wordwide market should exceed \$270 million by the end of the decade.

Dedicated CRT

All desk-top and nearly all µCs now incorporate dedicated CRT displays, with diagonal screen sizes ranging from 10 to 15 inches. The CRTs used in these systems have a resolution of 300 to 500 lines and can routinely display about 2000 characters. The flat CRTs currently under development by Sony, Philips and others will most likely be introduced on the market for computer application during 1984. Sony has already introduced a hand-held TV using their flat CRT concept while Philips has demonstrated a prototype of their channel electron multiplier faceplate device. The U.S. market for flat CRTs will be about \$0.5 million initially but should grow to over \$10 million by the end of the decade. On a worldwide basis, the flat CRT data display market is expected to reach \$45 million by 1990, 16.6% of the total market (Figure 2). Because of the relatively higher cost of the flat device, this represents only about 6% of the projected \$676 million worldwide market for all CRTs (value of bulb, yoke, and E-gun) used in non-consumer applications.

Currently, the most commonly manufactured VFDs are the bluegreen segmented displays for use in digital clocks, radio/TV tuner indicators, stereo equipment, VCRs, vending and gaming machines. The dot matrix type VFDs are designed for use in computer terminals, word processors, and graphical display applications.

All In Japan

There are only three manufacturers of VFDs, all based in Japan and each controlling about one third of the world market. One of the three, ISE Electronics, Ltd., is concentrating its efforts on the development of large area, dot matrix panels for eventual application to PCs and data processing equipment. ISE now offers 45 models of their "ITRON" series VFDs which can display from a minimum of 8 characters (14 segment arrays) to as many as 480 characters. They also offer continuous dot matrix arrays in various sizes and in 1982 announced the development of a 256 \times 256 element VFD matrix display.

The other VFD manufacturers





Figure 1: Projected U.S. and worldwide markets for flat panel displays used in computer related equipment.



IF WORDS ALONE AREN'T GRAPHIC ENOUGH, USE DECO'S NEW HIGH RESOLUTION

GRAPHIC DISPLAY MODULES!

DECO offers the latest in display technology. Close dot spacing and Vacuum Fluorescent technology make the display bright, sharp and highly readable even in daylight with proper filtering. Each dot is independently addressable allowing formation of almost any character or shape the mind can imagine! Graphs, charts, ideograms, waveforms and more can all be displayed. Even reverse video is possible. Complete drive, interface, control logic, refresh and buffer electronics are on board. Only +5 VDC is required to power the unit.

BUT, IF WORDS ARE WHAT YOU WANT, DECO'S



M128² Thin profile and low voltage made the M128² an ideal alternative to CRT in many applications.

Watch this space for the latest GRAPHICS DISPLAYS!



Alphanumeric Displays are specified by engineers all over the world. The bright vacuum fluorescent characters are highly readable and filter from natural blue-green to blue, green, aqua, amber and red. VF tube technology offers high reliability and tube MTTF up to 100,000 hours. Low Power requirements (as low as 65 milliwatts/character) are well below the dissipation of LED or gas discharge displays. DECO's displays are self-contained ready to use subsystems. They are microprocessor controlled with all drive, refresh, interface, control logic and buffer circuitry on board. Some units have user programmable character generators. All models have on board power conversion circuitry. Just input +5 VDC and a 7-bit ASCII signal and you're in business!

M26 x 256 is ideal in many foreign language or mixed character size applications. Intermix graphics and alphanumerics at user option.

DECO'S SINGLE LINERS come in a wide range of sizes from 10 to 40 character positions and 5mm to 9mm character height. 14 segment, 5x7 and even 5x12 matrices available.

WORLDWIDE DISTRIBUTION

United States Digital Electronics Corp. (415) 786-0520

United Kingdom/Ireland Auriema Ltd. 6286-4353

> France Alfatronic S.A.

791-44-44 ext 5735 W. Germany/Austria Bitronic GmbH 089-470-2098

Switzerland/Liechtenstein Memotec AG

063-281122 Sweden/Denmark Auriema AB

08-730-5160 Netherlands Auriema Nederland BV (040) 816-565

Norway Schive Electronics 02-785-160

Italy Auriema Italia SRL. 02-430602 Spain Unitronics S.A. 242 52 04

Israel Vectronics Ltd. 052-56070

Australia/New Zealand Soanar Electronics Pty. Ltd. 03-840-1222

Brazil/Argentina/Greece Turkey/So. Africa/Taiwan Ad. Auriema Int. (212) 938-0930 (New York, N.Y., U.S.A.)

Belgium/Luxembourg Betea, SA/NV (02) 7368050

Eastern Canada Gidden-Morton Assoc. Inc. 416-671-8111

Western Canada T.W. Racey Sales 604-987-1730

Local representation throughout the U.S.







These 5x7 dot matrix displays offer the fastest data transfer rate available and are completely flicker free.


M6400A 6 lines x 40 characters M2400 2 lines x 40 characters



THE DISPLAY INNOVATORS

DIGITAL ELECTRONICS CORPORATION

26142 EDEN LANDING RD., HAYWARD, CA 94545 • (415) 786-0520 • TELEX: 172073 DIGELEC HYWD



CONTROL DATA: AFTER 25 YEARS, STILL THE LEADER IN THE PERFORMING ARTS.

Designing peripherals with exceptional performance is as much an art as a science. We know. We've been doing it since 1962. From the beginning, we've been dedicated to giving you solutions to on-line and back-up storage needs. Example: the Storage Module Drive (SMD) we introduced became the industry standard for removable media disk drives. The SMD is just one of the high-performance products that helped make us the world's leading independent supplier of storage peripherals.

We're still adding star performers to our product family.

The LARK with a combined 50 Mbytes of fixed and removable media. The WREN high-performance 5-1/4" winchester drive. The Sentinel 1/4" cartridge streaming tape drive and the RSD that provides 80 Mbytes of removable media in a unit one-half the size of the original SMD.

Today there are more than 35 different products designed to help you meet any storage or back-up requirement, with maximum reliability and low cost of ownership built right in.

There's more—the direct support that Control Data offers.

We can deliver maintenance on everything we make. So wherever your customers are, Control Data peripherals can

be counted on for less downtime and more productivity than unsupported products. Our spare parts programs help ensure that your reputation for excellent service with your customers is backed to the hilt, 24 hours a day,

365 days a year. In the United States and around the globe.

Add to this the commitment to research, to development and to manufacturing quality that a corporation the size of Control Data contributes, and you're looking at precisely the kind of performance that makes our OEM peripherals top-rated in independent preference studies year after year.

Every performance needs a program. We'll send you one free: our new 48-page OEM products catalog. Write OEM Product Sales, Control Data Corporation, P.O. Box 0, HQN08H, Minneapolis, MN 55440.



Write 10 on Reader Inquiry Card




Figure 2: Projected worldwide market shares by technology type.

are Nippon Electric Company (NEC) of Tokyo and Futaba Corp., based in Akihabara, Japan. Most of both companies' products are sold to consumer electronic manufacturers but they are also concentrating their efforts on the emerging office equipment and automotive markets. Futaba now offers a variety of dot matrix VFDs with up to 15 lines of 80 characters per line for use in electronic memory typewriters and computer terminals.

The U.S. market for dot matrix VFDs for computer related equipment is expected to grow from less than \$4 million this year to about \$12 million by 1990. The worldwide market should exceed \$49 million or 18% of the flat dis-

play market by the end of the decade (Figure 2).

Of all the flat panel display technologies used in computer related products, PDPs have thus far captured the largest market share. Burroughs is conceded to be the world's largest producer of all types of PDPs. Industrial Electronic Engineers (IEE) is believed to be second only to Burroughs in U.S. sales, although the company buys all of its PDP units from Oki and Okaya of Japan. Cherry Electrical, Beckman, NEC and Fujitsu are also major suppliers. Burroughs is now building a 25 line × 80 character PDP for use in computer systems. The company expects to build at least 2000 units in 1983. Although initially it will be offered at a higher price, company spokesmen believe that the product's price will be reduced to \$500 or less within the next several years as volume increases.

Companies such as Electro-Plasma, Interstate, Photonics and Science Applications, Inc. (SAI) produce displays for military applications under government contract; the PDPs are usually part of some larger system which includes peripheral components and software. Electro-Plasma has recently introduced a PDP for computer terminal application with up to 51 lines of 80 characters per line for the commercial market.

The worldwide PDP market will grow from \$30 million in 1983 to \$73 million by 1990, making it second only to LCDs in market share (**Figure 2**). The potential cost effectiveness of PDPs on a per character basis for a large number of characters, will create markets for PDPs in graphics terminals, other EDP applications and perhaps even the "portable" or "transportable" personal computer market.

The only other light emitting technology which will show a significant increase in market share during the next few years is the dot matrix Electroluminescent (EL) panel. Sharp Corporation is presently the only manufacturer of these devices, which emit yellow-orange light. Most of the units sold in 1982 were consumed by Grid Systems and several other μ C makers for evaluation purposes. If Sharp solves the techni-

	PROJECTED U.S. MARKET FOR FLAT DOT MATRIX DISPLAYS FOR COMPUTERS/EDP APPLICATIONS										
		(Millio	ons of Consta	nt 1982 Dolla	rs)						
Display Technology Type	1983	1984	1985	1986	1987	1988	1989	1990			
CRT (Flat)		0.50	1.00	2.00	3.00	4.50	6.75	10.13			
LCD	2.70	4.05	5.67	7.65	9.95	12.44	15.55	18.66			
VFD	3.80	4.56	5.47	6.57	7.88	9.30	10.79	12.40			
Plasma (Gas-Discharge)	17.00	20.40	23.66	26.50	29.15	31.49	34.01	36.05			
Other Light Emitting	0.80	1.60	2.56	3.84	5.38	6.45	7.42	8.16			
Other Flat Passive		0.00	0.50	1.00	2.00	3.00	4.20	5.46			
Total	24.30	31.11	38.87	47.56	57.36	67.17	78.71	90.85			

Table 1: Projected U.S. market for Flat Dot Matrix Displays for computers/EDP applications.

PROJECTED WORLDWIDE MARKET FOR FLAT DOT MATRIX DISPLAYS FOR COMPUTERS/EDP APPLICATIONS

(Millions of Constant 1982 Dollars)

Display Technology Type	1983	1984	1985	1986	1987	1988	1989	1990
CRT (Flat)		1.00	2.00	4.00	10.00	20.00	30.00	45.00
LCD	24.10	30.13	37.66	47.07	56.48	64.96	74.70	85.91
VFD	10.00	14.00	18.90	24.57	30.71	36.86	42.75	49.16
Plasma (Gas-Discharge)	30.00	37.50	45.00	51.75	57.96	63.76	68.86	72.99
Other Light Emitting	1.50	2.40	3.36	4.37	5.46	6.55	7.53	8.29
Other Flat Passive		0.00	0.90	1.80	3.60	5.40	7.56	9.83
Total	65.60	85.03	107.82	133.56	164.22	197.52	231.40	271.17

Table 2: Projected worldwide market for Flat Dot Matrix Displays for computers/EDP applications.

cal (reliability) problems associated with the manufacture of these devices, the price of the thin-film EL could become competitive with those of the other flat panel technologies. However, lack of a second source and the uncertainty regarding reliability makes it unlikely that EL will make as great an impact on the market as the other discussed here. Gas-electron-phosphor (GEP) displays, which are presently under development by Siemens, will not make an impact on the market until late in the decade. If Siemens is successful with its development of a cost-effective, full-color, computer terminal display, this GEP technology could begin to displace some of the CRTs pre-eminent position in color graphics terminals. For these reasons, the worldwide market for other light emitting displays is only projected to be \$8.3 million by 1990 (**Figure 2**).

Non-LCD Market

The markets for non-LCD passive displays are essentially the same ones that are now served by LCDs. Unfortunately, many of the technologies are under development and it would appear that products using these technologies

will not appear on the market until 1985 or later. The worldwide market for these displays is projected to approach \$10 million by 1990. The leading candidate for application to computer products is the electrophoretic (EPID) display using the control electrode concept. The EPID display has received the most attention in recent years and companies such as Exxon Information Systems, North American Philips, Tektronix and Xerox have active development programs.

Joseph A. Castellano, Ph.D., Stanford Resources, Inc., San Jose, CA

Sleeping Giant To Enter CAD/CAM 32 Bit Market

Gerber Systems Technology, subsidiary of Gerber Scientific Inc. (\$115 million sales in 1983), is quietly gearing up for major announcements in CAD workstation systems for the summer conference season. The company's main strength lies in CAD for mechanical products, but its electrical/electronic products are growing rapidly. Gerber Systems has had a

great deal of success over the past year with its 16 bit Autograph product line, particularly in Southern California where it claims to be displacing Computer vision in small installations. The Autograph is a monochrome, standalone workstation with a price range of \$80k to over \$100k. Success for the product is due to the fact that at \$100k the cost of a

system makes it roughly equivalent to a commodity, that is approximately equal to the cost of capital equipment for the engineer in a design lab. Over 50 of the systems have been sold at an average cost of \$110k.


Based upon this success for standalone products, GST is planning to enter the market with an even more powerful, but less costly, system over the course of the summer. Early indications are that the company will take a twofold approach in evaluating or producing such systems: one to be based upon the newly released Hewlett-Packard 9000 Desktop Main-

PICK COMPUTING MACHINERY ANNOUNCES

THE ALL NEW DEC COMPATIBLE MICRO-MAINFRAME

MEMORY - 1 MB equivalent to DEC MSV11-LK. All parameters switch selectable. Optionally up to 4 MB.

CENTRAL PROCESSOR - DEC LSI-11/23 with hardware speed-up for up to 50% greater throughput. 22 bit addressing; hardware bootstrap; line time clock. **SERIAL I/O** - 16 Plug compatible I/O ports equivalent to DLV11-J. All parameters switch selectable DMA multiplexor soon available



TWO 8" FLOPPY DISKS -Emulates DEC RX02/RX03 (total storage 2MB). 8" cartridge tape drive also available.

LSI-11 and DEC are trademarks of Digital Equipment Corp. Three quad (six dual) expansion slots for additional memory, peripheral controllers, or PCM's new and unique Z80V11 CP/M processor. System runs all DEC operating systems including RT11, TSX-PLUS, RSX11/M, RSTS/E, and UNIX

5½" WINCHESTER DISK - Emulates four DEC RL02 drives (total storage 42MB). Optionally up to 84MB.

PRICED UNDER \$10,000 IN QUANTITY!!! CALL TOLL FREE 1-800-558-7832



AVAILABLE NOW in system or component form. Other configurations also offered with 51/4" and free standing disk drives.

57 NORTH MAIN ST. ● HARTFORD, WI 53027 ● (414) 673-6800 Telex. 269686

Nationwide maintenance from KALBRO

Write 25 on Reader Inquiry Card

ell us your thoughts

Digital Design is your forum — your inputs help keep the magazine interesting and vital to

the design community. So let us know how we're doing and how we can serve you better in the future. We want to know what you like or dislike about *Digital Design*, the subjects you'd like to see us address, how you feel about the problems you face every day as design professionals.

If you have thoughts your peers should know about, put them in a letter in *Digital Design*. Have your say in *your* magazine! Send letters and comments to: Editor, *Digital Design*, 1050 Commonwealth Ave., Boston, MA 02215.

Market Trends

frame, and another around a National Semiconductor 32 bit μP . The company feels that 32 bit systems are the key because they will allow engineers to perform analysis rather than merely draft. The primary market for such systems is felt to be in companies with annual revenues under \$100k annually.

Under the HP 9000 based approach, the system would be approximately \$80k to \$90k, but would have 80% again the capability of its existing IDS system. Such a system would also be designed with the implementation of solids modelling software in mind. The Romulus Software now provided by Evans and Sutherland is already under consideration for

such an application.

With a Motorola chip, a lower cost but also color system could be configured in the price range of \$40 to \$60k; such a system might have a 50 Mbyte Winchester tape backup. While both hardware approaches are spoken of, a single set of Unix, Fortran and Pascal/C programs would be developed for both. However, while the Motorola based system would be oriented for the lower cost single workstation approach, the HP model would form part of a networking system, based around HP's Ungermann/Bass networking or around some type of Ethernet controller. The former approach would be provided with additional market appeal through the strength of HP's international marketing capabilities.

The real importance of these scenarios, however, is found in the other operating subsidiaries of Gerber Scientific—in its Scientific Instruments and Garment Technology Groups where CAM applications provide a hidden base of technology available to no other major CAD vendor. These are the company's original areas of expertise, and if coupled with 32 bit CAD capabilities, the firm will have a chance to become significantly larger in the entire field of process technology. Write 233

-Borrell

Fujitsu's MBM27C64 — A Step Ahead

Introduction

The Fujitsu MBM27C64 is a high speed 64K UV Eraseable Programmable Read Only Memory (EPROM), organized into a µP compatible 8K words by 8 bits.

The MBM27C64 is available in speeds of 300, 250 and 200 ns. Operating with a single 5V (+/-10%) supply (for read operation) it features fully static switching circuitry to eliminate the need for external clock circuitry. All devices are available in the commercial temperature range of 0 to 70°C. Selected devices are available in extended $(-40^{\circ} \text{ to } +85^{\circ}\text{C})$ and high reliability (-55°) to +125°C) temperature ranges. All devices are available with the MIL-STD-883B test flow processing.

Two Dimensional Output Buffer Control

The G control input and the P/G control input provide the user with a two dimensional high-speed output-enable accessing feature with accessing times of less than 150 ns. Each output-enable input allows the user to OR-TIE the respective outputs without invoking bus contention. This feature also simplifies future system memory expansion.

Single Input Power Down Control

The MBM27C64 will enter one of two standby modes dependent on the level of the E input. Applying a TTL compatible input will invoke a power down operation, vielding a current consumption equal to 1 mA (ISB1). Applying a CMOS compatible input (from $V_{CC} - 0.3V$ to $V_{CC} + 0.3V$) to this E input yields a typical device current consumption of 1 µA (ISB2) compared to ISB1 for the TTL input. An internal pull-up resistor to V_{CC} on the E pin eliminates the need for an external pull-up. The three control signals E, G and P (P/G) provide the




Figure 1: Read operation timing diagram.

user with an easy read operation timing sequence (Figure 1).

Power Consumption Savings

As is the case in all CMOS devices, the power consumption of the MBM27C64 depends on the frequency in which the device is operating. Operating at 5 MHz, the MBM27C64 draws a maximum of 100 mW over the entire temperature range, approximately $\frac{1}{5}$ that of industry available 64K NMOS EPROMs. Typically (TA = 25°C and $\frac{1}{5}$ C and $\frac{1}{5}$ C, this device draws approximately 33 mW for 4 MHz operation.

The standby current (ISB1 and ISB2) consumption of the MBM27C64 is 3 or 4 orders of magnitude less than its NMOS counterpart. Typically, the MBM27C64 draws 5.5 μ W for a CMOS (V_{CC} +0.3V to V_{CC} -0.3V) input level on the E input. Expressed as a power-per-bit ratio, the MBM27C64 consumes approximately 0.27% (8.0nw to 2900 mW) that of its NMOS competition.

Programming

The standard 50 ms programming pulse width can be utilized with

the MBM27C64. This algorithm is available on many commercially available PROM Programmers. However, the device will achieve extremely high data retention characteristics even when pulse width is reduced to 25 ms.

In addition to the standard 25–50 ms pulse width programming procedure, the MBM27C64 can be programmed with a fast programming algorithm designed by Fujitsu called QuickPro. The algorithm (**Figure 2**) uses a sequence of 1 ms pulses to program each location and will typically yield a savings of 86% in programming time per device. In custom programmer designs that require less overhead the savings can be even greater.

The programming mode is entered when +6V is applied to the V_{CC} pin followed by applying +21V to the V_{pp} pin. A TTL low input must be applied to the E input, and a TTL high input must be applied to the G input. After the programming voltages and TTL levels have stabilized, a sequence of 1 ms pulses must be applied to the P pin for programming. After each pulse, a counter must be stepped and the location

Digital Design ■ May 1983




Figure 2: Quick programming flow chart for MBM27C64 EPROM.

should be checked for accuracy. Upon verification, an additional sequence of 1 ms pulses equal to the present value of the pulse counter must be applied to the location to ensure proper levels of stored charge.

An alternate approach to the additional pulses would be to apply a single TTL low pulse with a width equivalent to the value of the pulse counter multiplied by 1 ms. When the pulse counter reaches a maximum of 20, the verification procedure is skipped and a flag is set to indicate a program failure. Upon completion of programming of the entire device, a final array verification (all locations) is required. All Fujitsu MBM27C64 devices will typically require only two 1 ms pulses (one initial and one additional) to reach proper stored charge levels.

Typical Applications

Due to the non-volatile characteristics of EPROMs, the majority of applications for EPROMs are in a μP-based system's development cycles. Since micro-code frequently involves many iterations before the released revision of the code is produced, non-volatile, quickly and easily alterable devices are necessary. The popular µPs of today can be seen in Table 1 with their corresponding access time requirements. As can be seen by the table, the speed versions of the MBM27C64 accommodate many µP systems.

Packaging

The MBM27C64 is available in a Jedec Standard 28 pin dual-in-line

PROCESSOR	OCESSOR MBL8086		86	Z8000		68000	8085A			6809		Z80		NSC800	
DEVICE/MHz	5	8	10	4	5	8	3	5	1	1.5	2	2.5	4	2.5	5
MBM27C64-30	X			M			X		X	X		X		· X	
MBM27C64-25	X			X	X		X	X	X	X	X	X		X	
MBM27C64-20	X	M		X	X	М	X	X	X	X	X	X	X	X	٨

Note: M = Marginal compatibility

Table 1: The MBM27C64 series devices are compatible with many popular μPs , limited by the required access time of each μP .

Applications Notebook


package (DIP). The package is manufactured in ceramic with a transparent crystal window for ultra violet memory array erasing. This device is also available in a 32 pin leadless chip carrier. With dimensions of $450 \times 550 \text{ mm}^2$ (typical), this LCC is also manufactured in ceramic with a transparent crystal window and a metal seal. Additional hybrid packaging techniques are also available upon request.

Conclusion


The CMOS 64K MBM27C64 EPROM provides a high density, low power consumptive and easily alterable EPROM primarily for use in µP based systems. The 5.5 μW typical standby current drain and 150ns typical access times combine to offer the designer a program storage device with no trade-offs. The NMOS MBM2764 is also available in similar speeds and packaging options for users who don't require the advantages that the CMOS device offers. Rob Stransky, Applications Engineer, Fujitsu Microelectronics Inc., 2985 Kifer Rd., Santa Clara, CA. 95051. (408) 727-1700. Write 234

Attention 8K × 8 EPROM Users! Free Samples. . . .

If you are interested in obtaining samples of the Fujitsu CMOS MBM27C64 or its NMOS counterpart the MBM2764, please write on company letterhead to Bob Sykes, Product Marketing Engineer, Byte-Wide Memories, Fujitsu Microelectronics, Inc., 2985 Kifer Rd., Santa Clara, CA 95051. To receive the free part you must include description of your 8K × 8 EPROM application, including total memory size, speed and power consumption requirements, and packaging needs. One free MBM27C64 or one free MBM2764 will be delivered to the first 500 qualified inquiries.



Write 27 on Reader Inquiry Card



Robots are performing as contributing assets, not as inevitable costs.

Laura Conigliaro is Vice President in the Research Department at Prudential-Bache Securities Inc. As an analyst, she covers the field of factory automation, including robotics, computer-based vision systems, advanced technology machine tools, and CAD/CAM, both from an industry and company perspective. Ms. Conigliaro's previous employment includes several years spent as an intelligence analyst at the National Security Agency. She was contributing author to a book on investment and, more recently, has contributed numerous articles to various publications and studies done about robotics, including her own "Robotics Newsletter.

by Laura Conigliaro

When did the robot industry begin? Clearly, the use of the first industrial robot commercially, in 1961, occurred many years before the more recent frenetic focus on the industry. But robotics was not even an industry during the 1960s. It was an occasional order, sometimes a multiple order and, in terms of dollar value, it was primarily whatever business Unimation and Versatran, and later Prab, managed to get.

Historic though they may be, I believe it is important to view these so-called "phases" in order to put what is now occurring in

perspective (Figure 1). Not until the mid- to late-1970s did robotics actually become the beginnings of an industry. Between 1975 and 1977, it is estimated that unit sales for Unimation—the company that virtually was the entire robotics industry in terms of dollar volume—jumped by over 2.5 times. Prab had its first \$1M year by calendar 1977. Cincinnati Milacron had decided to become a serious participant in robotics. Copperweld Robotics (then Autoplace), DeVilbiss and Asea pretty much rounded out the industry and added a few million dollars more to dollar volume. And the auto industry, having "discovered" robots years earlier and used them on a modest scale, began a major retooling program in which robots figured prominently.

As a result of all these events, robot sales jumped from about \$15M in 1976 to about \$45M in 1979, and the rest of the country slowly began to discover robots.

Robotics during Phase I was a

series of uses, a few users and a few vendors, but not really an industry. During Phase II, the few more companies selling robots experienced rapid growth; the few users wanted more as they began to learn what the early robots could do. By the third phase, robotics had evolved from a novelty to an industry, with far more companies in it and far more users aware of it.

A year ago, a euphoric atmosphere pervaded the robotics industry. The thoughts were that this would be an ever onwards-and-upwards industry and that fast growth was virtually inevitable. But thanks to the recession, what was inevitable was that this industry—still so tied to the automotive industry and very much dependent on capital spending—would slow.

Over the past year, corporate balance sheets got worse and worse: Braniff, Penn Square Bank of Oklahoma, Wickes Cos., and others filed under the Bankruptcy Act; huge operating losses were recorded by hosts of companies; Caterpillar, Deere, GM, Ford and multitudes of others were forced to slash capital spending budgets. I, for one, cut my own forecasts for estimated sales in 1982 by USbased robot vendors from \$250M to \$190M. For 1983, forecasts shrank from \$300M to about \$225M, with even these numbers predicated only on the assumption that an economic recovery will have slowly begun building some strength by mid-1983.

Does this mean that robotics will go back to being more a fad than a strongly growing industry? Does it lessen the importance of robotics? Not at all—it means quite the opposite. Companies have, in fact, cut back their capital spending plans and have also cut back on certain product lines or pared away certain assets. They have also recognized that in a slower growing environment there must be a far sharper focus on the process of manufacturing in order to get as much profit out of what little growth there is.

Concurrently, we have been bombarded with publicity about Japan. It may not all be accurate, but the challenge is there nonetheless. The robotics industry may have slowed in its growth temporarily but it is inevitable that companies will upgrade their manufacturing technology. Since robots are an important part of this scheme, the industry is just marking time.

Japan's Impact

Whenever the issue of Japanese manufacturing prowess arises in a conversation with well-informed American manufacturers, someone will always note that the Japanese are not really ahead of us technologically, but that it is merely a *perception*.

ed that, if taken apart part-bypart, some of their newest models would compare quite favorably with Japanese models? And yet imports have commanded a rising share of automotive consumption. Apparently, perception is often more important than reality.

In terms of the manufacturing process, many Japanese companies have implemented available technologies in efficient and useful ways. Are they ahead technologically in this area? Probably not—but it probably does not matter much. They have emphasized the factory floor, cut costs by doing so, improved quality and automated facilities where possible. In short, they have turned manufacturing into an asset.

Most Japanese companies,



Cincinnati Milicron's electric-driven T³-726 Robot performs a plasma arc cutting operation on a steel pipe.

This may be true, but the quick dismissal of that point as merely "perceived" (and presumably, then, not real) is to overlook the importance of perception. How many consumer products are bought on the basis of the *perceived* value of one versus another? How many times have US automotive manufacturers assert-

however, haven't yet done this. In fact, Japan's manufacturing process spans a broader spectrum than our own. There are companies even in Japan that will argue forcefully that automated facilities built, for example, by Fanuc and Yamazaki are merely showplaces that are not cost effective. The truth of this is hard to determine,




Figure 1: The three phases of the Robot Industry.




Figure 2: Changes in market share composition 1980-1983.

although it is important to bear in mind that Japan has a lower cost of capital than the US; that labor often works only one shift there; and that Japan is really a production-oriented and not a market-oriented society. In short, what may be cost effective in Japan may not be so in the US.

Nevertheless, it is difficult to believe that, over time, the automation seen at the best of these companies will not be more cost effective than conventional manufacturing seen at many other companies. Manufacturing is probably not an area where one company will "leapfrog" over another. Solutions will more likely come about through slow and steady incremental types of improvements. This means that companies cannot continue to wait indefinitely before improving their manufacturing.

US companies know that competition is now just as likely to come from anywhere in the world as it is from their own country. As a result, even in a period of slower growth and more modest capital spending over the next several years, priorities will change from adding more production capacity and product lines to modernizing and improving current manufacturing facilities. This should favor robots and related technologies.

Who Will Be Successful?

The fact that there are so many robot companies—nearly 100 in the US, over 250 in Japan and several dozen in Europe—and yet still so small an industry, clearly presents an imbalance. Also, several of the newest members of the robotics community are so large that they could absorb the entire 1981 US robot industry with negligible effect on their corporate sales (Table 1). And yet all of the companies, as well as the new start-ups, the medium-sized companies that have newly-formed robot divisions, and the original six or so companies are having important effects on the industry (Figure 2).

What is it that will make one company stand out against another? For one thing, just as companies recognize their competitors' weaknesses and use these for their own benefit, they must also recognize and use their competitors' strengths. Some of the licensing agreements US companies have signed with Japanese vendors are prime evidence of such recognition. Why duplicate what already exists if you can use it to your own advantage? Japanese companies are offering lowpriced, high-quality manipulators. Some smart US vendors will take these manipulators, add value to them in the form of better computer controls, software, pre- and post-installation support and other ancillary equipment, and create a value-added premium-priced robot system.

Some companies have adopted the philosophy of recognizing competitors' overwhelming




Figure 3: The core of the robot industry is divisible into three groups.

strengths and not even attempting to go head-to-head against them. For example, Control Automation, a venture-financed start-up, is emphasizing its universal communications capability—thereby admitting that the probability of its imposing its own networking standards on the entire robot industry is slim to none.

Furthermore, it seems likely that companies that attempt to compete with Japanese robot vendors on a product-to-product

Robotics And Vision

A robot is basically a controlled arm ceaselessly moving from one position to another. The movement might be complex, as in programmed arc welding of a triple-dimensioned joint, but the cycle is invariant unless some sensor is involved to feedback new information or orders.

The robot arm is extremely well articulated, using up to eight axial movements in a given motion (torso, shoulder rotate, shoulder bend, elbow bend, elbow rotate, wrist bend & rotate, hand closure). However, in order to function, the workpiece and the components used must be oriented and positioned correctly. There are a host of tasks that such a non-sensory robot can do well. These include: spot welding, cast forging, spray painting, palletizing and depalletizing, machining, assembly, and arc welding.

The market volumes for the various types of robots is essentially in the order listed above. In most cases, one really can't call pick and place automatons "robots." More sophisticated quasi-prehensile robot arms, without sensory feedback, must not get out of sequence, lest they produce remarkably reproducible junk. More intelligent robot generations require sensory feedback to monitor progress.

There are two main types of sensors: tactile and vision. *Tactile sensors* respond to the degree of fit, to the correct location of a part or to its orientation by a sense of touch. Discounting the single point sensors on the effectors or graspers themselves, there are no real multi-

point tactile sensors. Many methods have been proposed and one of them may be useful. But it has been demonstrated time and again that to move an idea into production takes some fifteen years. Quite aptly, this was the case for electronic vision (CCD, CID, and Photodiode arrays).

Vision Sensors, developed in 1970, were the first real imagers (although at the time they were promoted as anything but imagers). These were the Charge Coupled Devices (CCDs). By 1980, imagers were commercially available at near reasonable cost (reasonable, that is, for R&D experiments). At that point, thanks to American innovation, they were more than adequate for any robotic application. At this point, thanks to Japanese pricing strategy, they have become practical, cost-effective tools.

Electronic Vision

Excluding Vidicons, which present some problems for accurate positional location due to eddy currents, etc., most electronic cameras employ silicon to sense the light reflected from a target. The silicon chip provides an electronic image capable of being analyzed by other electronics. Resolution is achieved by arraying large numbers of light sensitive capacitors or diodes on the chip. Each element records a small section of the target and stores its intensity level as a proportionate number of electrons.

The arrays come in endless formats from 32×32

(1024) to 1000 \times 1000 (10 6) (the latter is not commercially available). They also come in three varieties: Self Scan Photodiodes (SSPD), whose photoelements are photodiodes; Charge Coupled Devices (CCD), whose photoelements are capacitors; and Charge Injection Devices (CID), whose photoelements are also capacitors. In the first case, the charge has to be read out serially and in the last it can be read out randomly, when so desired.

All three are equally useful, although there are trade-offs in size, blooming control, speed and specmanship. The long term winner will be the one that lowers its price the most quickly. For robotic vision, an array significantly larger than 256 \times 256 is especially desirable.

Once the target has been imaged on the array (by using some suitable lensing system and often using special illumination such as lasers, strobes and sheets of light), the next step is to read it out and to adapt its format so that it can be seen on a monitor (for setup) and processed by the follow-on image processor (called the Vision Module).

Read out is accomplished by other integrated circuits on the imager chip itself. Formatting is performed by printed circuit boards (following NTSC or CCIR standards) that are placed within the camera housing itself. The final step is to feed this formatted signal into the Vision Module so that it can be identified, recognized, inspected, located, gauged or counted.

Just a few years ago, robotic vision was the slowest module in the robot package. The target was to get vision to perform its analysis in two seconds to keep up with the robot. At that time image analysis took 2 minutes; in 1980 this was reduced to 20 sec. It is now \(^1/_{30}\) sec, which equates to 1,000,000 parts/shift.

Vision Modules

A robot needs only one type of information to perform its task. It needs to know where a part is; it asks simply for location and nothing else. It is true that robots can be used for other tasks besides grabbing and sticking, but if they are not primarily being employed to move to some point, then their size and cost shall be neither space nor cost effective. Once a robot locates a part and grasps it, then it can be effectively used for other add-on tasks such as inspection, identification or gauging before it moves the component to its secondary location.

A robot has one of two other recognizable application traits. It either works in an environment hostile or hum-

drum to humans or it is employed in an effort to increase productivity. To a lesser extent, it does enhance quality or, at least, it ensures that any defect in workmanship is uniformly present. In all cases, the added vision system is constrained to the robot's work ethic and environment.

Since location is quintessential, most robot vision modules have location software or location hardware. The most general need is to locate the center of something; often it is a hole into which a pin or a rivet has to be inserted. To accomplish this, only the centroid (first moment divided by area) has to be calculated. This is given by:

$$\overline{X} = (1/A); X_i, \overline{Y} = (1/A), Y_i$$

This algorithm is relatively straightforward and simple to implement. Since the round hole has pure 2D symmetry and a square peg is seldom to be inserted, centroid data alone suffices to service this application class.

If there are various hole sizes on the target, then the correct one has to be recognized first. This is done by measuring either the diameters (maximum widths) or areas; again, straightforward problems. If the hole or other features to be located is of lesser symmetry (ovals, squares) and/or other is randomly oriented, then the image needs to be electronically derotated until it is aligned with robot coordinates. With this angular knowledge and prior knowledge as to how the pin or rivet sits in the robot's grasp, the hand can be rotated until the pin lies precisely over the hole.

Robotics is the simplest field for Vision Modules to service. But it is not an easy field for vision to penetrate. Over the past few years, robot companies have been application-driven—and there are many applications. In addition, they try to discourage their customers from purchasing the top of the line robot to try out, lest it sit unused on the production floor. Even though robot manufacturers believe much of their future growth will come from vision and that half of the robots will be sighted, there is a definite reluctance to either retrofit on-line robots with vision or to add it to new generations.

Robotic vision itself might become application-driven and have to be proven out on an individual basis. As a result, sighted robots sit at the edge of a long lead time to acceptance.

—Lawrence A. Murray, Vuebotics Corp. 6068 Corte Del Cedro, Carlsbad, CA 92008. Write **350**

price-to-price basis are going to have difficulty succeeding. Japanese robots, many of which are of acceptably high quality (many of which are, in fact, being used by US robot vendors through licensing agreements) are almost invariably going to command a lower price. Their per unit production costs are lower. Were end-users simply interested in purchasing a

robot at the lowest possible price and willing to do their own engineering, applications software, support and hardware and software integration, most US robot companies would be unable to compete. However, a majority of US end-users will want more than simply a robot and directly related equipment. They will be far more demanding and, given the

number of vendors presently in the industry, they can afford to be just that.

Successful companies in the US will have to be strong in the areas of management, research and development, marketing and sales, support and field service. Robot vendors which may have previously been able to get away with simply taking orders will have to

Now, A 46 M/Byte Digital Recorder That Cuts Reels of the Down To Size. a ser option.

Spanning undersea, ground/mobile, and airborne applications, this ruggedized MIL-SPEC recorder proves large recorder size is no longer a prerequisite for outstanding recorder storage capacity and performance.

Measuring only 5.4" W (x) 9.8" H (x) 19.5" L, the ECR-40 Digital Cartridge Recorder provides a massive 46 M/Byte storage capacity on a single ½" certified tape cartridge, yet weighs in at a mere 35 lbs.

Reel-To-Reel Performance At A Fraction Of The Size

Designed to emulate reel-to-reel recorder performance and storage capacity at a fraction of the size and power consumption, the ECR-40 receives 9-track parallel phase encoded data at 1600 bpi and records at 6400 bpi. The unit offers tape shuttle speeds up to 150 ips.

Equally impressive is its data transfer rate: 200 K bytes per second or 72 K bytes per second, plus fast 12m/sec. start/stop time which permits greater data compression per inch of tape, thus setting the ECR-40 apart from existing cartridge recorders and providing an accurate, cost effective approach to data recording/reproduction.

To optimize performance, the ECR-40 powers up on only 100 watts at steady state, and idles at a low 35 watts in standby. And, the ECR-40's quick-loading

cartridge and positive locking mechanism saves time, effort and offers little opportunity for tape contamination.

Built To Last

Predecessors to the ECR-40, the ECR-10 Digital Cartridge Recorder and the ECR-20 Bi-Directional Analog Cartridge Recorder provide a rugged MIL-SPEC alternative to their high capacity counterpart.

Weighing less than 15 lbs., fully loaded, the ECR-10 provides a 4.3 M/Byte storage capacity on ½" tape, and measures only 4.0" W (x) 8.7" H (x) 12.7" L. The ECR-10 was also selected for numerous tri-service military programs, including TRI-TAC, the Army's worldwide communications program; SEA NYMPH; TSQ-73; TFCC; and more.

Using a 9-track, 800 bpi NRZI ANSI read while write format, this computer compatible unit is available with a data transfer rate of 12 or 20 K bytes per second, yet consumes only 40 watts of power in run mode and 10 watts in standby.

And where analog data is required, the rugged ECR-20 has earned its bars in numerous military sensor recording programs and test flight applications.

Utilizing 8-tracks on 4 passes of 2-channel record/reproduce electronics, the ECR-20 features a servo capstan motor drive with optional tack and bi-directional tape drive for added reliability and

performance. Offering tape speeds of 1.875 ips and 60 ips, the ECR-20 maintains a frequency response of 100 Kz. to 5 KHz., and 3.2 KHz. to 160 KHz. respectively. Signal-to-noise ratio levels out



Cut Your Reels Down To Size

Send for complete specifications on these high-performance recorders, reproducers and Genisco's complete line of certified digital and analog tape cartridges. Call or write today to: Genisco, Memory Products Division.



MEMORY PRODUCTS DIVISION
A Division of Genisco Technology Corporation

polyFORTH II

The Operating System and **Programming Language** designed especially for

REAL-TIME **APPLICATIONS**

- Robotics
- Instrumentation
- Process Control
- Graphics
- ... and many more.

polyFORTH II has the high-performance features you need to slash development time by months:

POWER

All the programming tools you need - multiprogrammed OS, FORTH compiler and assembler, editor, over 400 primitives and debugging aids - resident and ready to use.

SPEED

3-5 times faster than Pascal, 20 times faster than Basic, with a resident assembler for time-critical functions.

MULTITASKING/MULTI-USER

Supports any number of tasks. Even the smallest systems may have two or more programmers coding and testing interactively.

COMPACT CODE

Entire development system resident in under 12K. ROMable applications can run under 1K. Large applications up to 10 times smaller than with other techniques.


SUPPORT

On-line interactive documentation, over a thousand pages of manuals, FORTH Programming Courses, and the FORTH, Inc. Hot Line plus Contract Programming and Consulting Services.


Available for most popular minis and micros. From FORTH, Inc., the inventors of FORTH, serving professional FORTH programmers for ten years.

FORTH.Inc.

2309 Pacific Coast Hwy Hermosa Beach CA 90254



Robotics



Cincinnati Milicron offers its computer-controlled T³ Robots as the basic tools in turnkey welding packages.

Company	1981 Corporate Sales	Entire 1981 Robot Industry as a Percentage of Company Sales
General Motors	\$62.7B	0.2%
IBM	\$29.1B	0.5%
General Electric	\$27.2B	0.6%
United Technologies	\$13.7B	1.1%
Westinghouse	\$ 9.4B	1.7%
Bendix	\$ 4.4B	3.5%
Textron	\$ 3.3B	4.7%
Allegheny International	\$ 1.9B	8.1%

Table 1: 1981 Robot Industry as a percentage of some of its participants' sales.

learn to sell. Although this may sound fairly basic, it represents a fundamental change in business strategy.

The core of the robot industry-the most successful companies, discounting those companies that will be marginal but will survive anyway-will fall into three groups (Figure 3).

Low cost, high volume producers. This group will primarily consist of about a dozen large Japanese robot vendors selling basically commodity robots for various applications.

Value-added, systems oriented companies. This group will in-



(A quantum gain in plotter throughput.)

Nicolet's idea of an intelligent plotter is one you can tell what to do. Our users maintain total control over plot quality. The result? More plots of better quality without being chained to your plotter.

Our intelligent features let you control plot speed and acceleration, pen up/down time, individual pen pressure, windowing and scaling. Automatic pen sensing allows you to mix pen types for finer lines and better shading. Plus, dozens of other subtle features that any plotter user can appreciate.


Automatic error correction—the great times aver.

We've practically eliminated the classic drudgery of plotting. Because we've put all the pens on one carriage — for both our four pen and eight pen models. The plotter never has to stop to change pens and neither do you. When using continuous feed paper you can create multiple plots on up to 240 foot-long rolls without operator intervention. Free costly manpower for work more promising than plotter watching.

And intelligence guarantees compatibility.

You'll get RS 232C or IEEE 488 interfaces as standard

including serial line printer emulation. We support all major protocols including IBM SNA/SDLC, 2780, 3780, etc. And we support such plotting languages as HPGL™, PLOT 50™ and our own highly compact Graphic Machine Language that is generated by our industry standard software. Plus, we can interpret CalComp 925 tape format and 960 plotter code.



COMPUTER DISC DIMENSIONS, DISC DYNAMICS, STRUCTURAL D PARTS SORTING, SHAFT ALIGNMENT, VIBRATION, AXIAL RUNOUT URBINE BLADE PROFILING, THICKNESS, ID. OI

PARTS SORTING, SHAFT ALIGNMENT, VIBRATION CONCENTRICITY, TURBINE BLADE PROFILING, C COMPUTER DISC DIMENSIONS, DISC DYNAMICS, CONCENTRICTI PARTS SORTING, SHAFT ALIGNMENT, VIBRATION, STRUCTURAL D CONCENTRICITY, TURBINE BLADE PROFILING, COMPUTER DISC I STRUCTURAL DYNAMICS, THICKNESS, ID, OD, TURBINE BLADE PR AXIAL RUNOUT, PARTS SORTING, STRUCTURAL DYNAMICS, VIBRA



Kaman Instrumentation's new KD-4000 Series, the "smarter" displacement measuring systems (with resolution to better than 1 micro inch) do more than give you raw analog

displacement data that you still have to process and analyze.

With the KD-4000 Series you can specify the system functions that fit your application needs: ID, OD, Thickness, Alignment, Comparator Logic (for parts sorting, computer interrupts, etc.). TIR, and more "smarts" on the way.

These systems are available in various packaging options (rack, lab, or NEMA type


enclosures) or work with us to your packaging requirements. Many sensor sizes are available to cover measurement ranges to 2.5 inches. For single and multi-channel applications, you'll find that these systems can help you solve a broad range of position measurement problems. The KD-4000 Series, for more complete solutions to your precision measurement problems. For more information, please write, or call us (303) 599-1825.



KAMAN INSTRUMENTATION CORPORATION P.O. Box 7463 Colorado Springs, CO 80933

Write 30 on Reader Inquiry Card

Multibus boards that really communicate.



Introducing the MZ (Multibus-Zilog) product line.

Designed expressly for communications work.

Beginning with our data communications workhorse - the MZ 80 Processor Board featuring the fast 6MHz Z80B cpu. And our Serial I/O Board can handle 8 independent RS 232 channels. You'll like our combination I/O and Memory Board, too. Four serial I/O channels plus 32kb of static RAM. And our Multi-Purpose Memory Board gives you 32kb of static RAM using 16k "Bytewide" devices. Plus, optional backup battery. Coming soon: SNA/SDLC board based upon the MC68000.

Best of all, we can provide these boards immediately. In any volume. So if you need real data communications power, get the MZ boards designed to do the job. Just ask for Art Coombes.

Let's communicate.

(415) 680-8640

Thomas Engineering Co.

1040 Oak Grove Road Concord, CA 94518

Multibus is a trademark of Intel Corp. ®

Write 31 on Reader Inquiry Card

Robotics

clude many of the successful US robotics companies. Value added can come in the form of turnkey systems, computer controls, or service, but whatever form it takes, it will have to be measurably beneficial to the customer who will therefore be willing to pay a higher price for it. Ironically, nearly all US robot vendors I queried responded that they were value added companies, offering systems, superior software, etc. In the end, customers will tend to cluster around those few where the added value is more real than ephemeral and has the greatest depth. Although it is still far too early to be certain of the names, I believe it possible that some of the most distinguished value added will emanate from smaller companies germinating on the sidelines—companies that have been formed with this in mind.

Factory automation companies. This will consist mainly of the largest corporations in the industry. These companies may not make a great deal of money from robots, their margins may not be nearly as attractive as those of the first two groups, but they will sell robots as parts of a far broader line of single-source systems for automating portions of the factory floor.

Robotics Realism

During the euphoria of a year ago, hardly a week went by that did not see a significant article on robots in a major newspaper or journal. The robot industry may not have been new, but its break into stardom was.

The atmosphere this year is quite different, grounded in cold and hard realism. Robots are not a panacea nor is their installation entirely a painless effort. But they are part of the solution to bringing the manufacturing process out of the dark ages, and to making it perform as a contributing asset and not merely an inevitable cost of doing business.

Reprinted with permission of the author and the publisher, Society of Manufacturing Engineers.

Now you can escape the mouse trap.



Write 24 on Reader Inquiry Card

Summaghaphics

Industry Firsts at ISSCC

by Dave Wilson, Sr. Technical Editor

This year's prestigious International Solid State Circuits Conference featured a number of notable industry firsts.

The phrase "industry first" continues to remain very close to the heart of Seeq Technology's President, Gordon Campbell. His company, innovators of the first 5V only EEROM and the Ethernet controller, has introduced the "industry's first" five volt only EEROM 8-bit microcomputer. Based on TI's 7000 family, the new chip (the Seeq 72720) is self-programmable and uses a 2K × 8 EEROM in place of TI's traditional ROM. (**Figure 1**).


ISSCC highlights included recent developments in memory, µCs and graphics.

Seeq has also announced that it has come to a technology exchange agreement with Texas Instruments. TI will supply Seeq with TMS7000 information in exchange for future production rights to Seeq's 72720 and future TMS7000 products employing non-volatile technology.

At present, TI's 7000 series has not gained a wide market acceptance; Campbell feels his EEROM part will have a volatile effect upon that fact.

And although the part is an "industry first", other companies including Intel and Motorola with expertise in EEROM and a widely installed base of 8-bit µCs are certain to introduce parts later that will offer strong competition to Seeq.

As the role of 8-bit μ Cs has moved towards the use of CMOS,



Typical output on screen using Signetics Devices.

it is inevitable that a Seeq/TI part using this technology is on the designers table. It has been reported that the marriage of an EEROM with CMOS is at present a headache but "not an insolvable one" according to Campbell.

EEROM memory runs about 2 or 3 times the cost of UV EPROM today, a fact which may also influence the buying decisions of 8-bit μC users.

One Motorola spokesman felt that the aspect ratio of the Seeq chip would lead to poor production yields, packaging difficulties and high cost. "It looks more like a memory" he said. Campbell seemed unconcerned, but did comment that the next μ C from Seeq Technology would have different dimensions.

As **Figure 1** illustrates, the next primary targets for EEPROM may well be the RAM and the microcode control store, offering a truly versatile μC product into the marketplace.

John Heightly, President of In-

mos, discussed his company's solution to electrically-erasable memory. 5V operation for all modes is a must these days, and the Inmos IMS3630 8K × 8 bit part is no exception (**Figure 2**). The part uses Inmos' own NITROX process, differing from the Seeq/Intel floating gate approach. At present both technologies only offer 10⁴ cycle endurance, an indication of how many times the part may be read to. In the race to boost this figure past 10⁶ cycles, it will be interesting to observe which technology wins the day.

Graphic Displays

On February 22, Signetics introduced two new ICs to extend the range of its CRT controller family. A demonstration model of a typical system threw up some impressive graphic displays.

In a typical display terminal using the Signetics SCN2670, SCN2671, SCN2674 and SCB2675 CRT terminal devices, the CPU examines inputs from the data com-

FROM THE SIZE OF THIS PAGE TO THE SIZE OF YOUR PALM.




INTRODUCING CERMETEK'S HIGHLY INTELLIGENT 212A-TYPE MODEM COMPONENT.



A complete integral 212A modem component. At Cermetek, modem technology has evolved to reduce the size of an integral 212A-type modem from a very large PCB down to the size of a component. In a space of 8 square inches, the CH1760 implements a fully featured 212A-type modem, including an FCC registered telephone line interface and advanced autodial capability.

No more custom PCBs. Since the CH1760 is a standard modem component and is fully featured, you no longer have to commit to a custom PCB to enjoy 212A-type modem integration. No NRE s or custom contracts to worry about.

If you still need custom, the CH1760's firmware can be reconfigured to meet your special needs. An EPROM version of the component, the CH1760E, enables custom features to be fully evaluated before committed to hard masks.



Features:

- Small size 2.4" × 3.6" × .65"
- 300/1200 BPS operation
- Bell 212A and 103 compatible
- Intelligent serial command interpreter
- Auto/Manual dialing DTMF or PULSE
- Auto/Manual ANSWER
- Auto/Forced selection of DTMF or PULSE dialing
- · Auto speed selection
- Auto parity selection
- Call progress tone detection (dial, busy, ringback, modem answer tone and human voice)
- 32 digit last number dialed storage
- Memory expansion port (stores an additional 52 telephone numbers or log-on messages)
- TTL Host serial interface

Cermetek

Advanced data systems through innovative components

Leave of the state of the state




Figure 1: Seeq's single chip EEROM microcomputer.




Figure 2: The Inmos IMS3630 8K × 8 bit EEPROM.

munications line and the keyboard and places the data to be displayed in the display buffer memory. This buffer is typically a RAM which holds the data for a single or multiple screen lead (page) or for a single character row.

The SCN2674 Advanced Video Display Controller (AVDC) is a programmable device designed for use in CRT terminals and display systems that employ raster scan techniques.

The AVDC generates the vertical

and horizontal timing signals necessary for the display of interlaced or non-interlaced data on a CRT monitor. The AVDC supports four common system configurations of display buffer memory, designated the independent, transparent, shared and row buffer modes.

The first three modes utilize a single or multiple or multiple page RAM and differ primarily in the means used to transfer display data between the RAM and the CPU. The row buffer mode makes use of

a single row buffer (which can be a shift register or a small RAM) that is updated in real-time to contain the appropriate display data.

The SCB2675 Color/Monochrome Attributes Controller (CMAC) contains a programmable dot clock divider to generate a character clock, a high-speed shift register to serialize input dot data into a video stream, latches and logic to apply visual attributes to the resulting display, and logic to display a cursor on the screen.

Both new ICs are available in two standard speed versions: 25 and 18MHz with higher speeds available on a special order basis.

At the same time, Motorola, and Signetics signed an alternate source agreement involving Motorola's M6804 and M6805 families of 8-bit μCs and Signetics' 267X family of CRT controllers. As a result of this agreement each company has an assured alternative manufacturing source, thus strengthening their respective product lines.

Motorola is licensed to alternate source the following Signetics

parts:

 SCN2670 Display Character and Graphics Generator


- SCN2671 Programmable Keyboard and Communications Controller
- SCN2672 Programmable Video Timing Controller
- SCB2673 Video Attributes Controller
- SCN2674 Advanced Video Display Controller
- SCB2675 Color/Monochrome Attributes Controller

Signetics is licensed to alternate source Motorola's M6804 and M6805 families of 8-bit microprocessor in both HMOS and HCMOS process technologies.

The first seven members of the Motorola M6805 µC family involved in the agreement are: MC6805P2, MC6805P4, MC6805R2 with A/D Converter, MC6805T2 with A/D Converter, MC6805T2 with Phased Locked Loop, MC6805U2, and MC6805U3.

The alternate source agreement provides for the exchange of technical information, test procedures, documentation and training.

Like DEC's.





Write 28 on Reader Inquiry Card

How to dress up your IBM.

Low cost data acquisition and control for the IBM Personal Computer.™

Data Translation is fashioning a new look in the personal computer market.

Our new single board plug-ins bring complete analog and digital I/O capability to your IBM Personal

The complete DT2801 I/O system fits on just one board. It includes A/D with programmable gain, D/A, digital I/O, and a programmable clock and has direct memory access capabilities. The DT2805 features the same functionality, with provision for low level analog input.


With power and performance to match that of the IBM PC, either board provides 12-bits of resolution with over 14kHz throughput rates under BASIC.

And whether your application is in laboratory data acquisition or in industrial process control, you will find both boards highly reliable at a very low cost.

The DT2801 and DT2805 are easy to use. Just plug either one into an IBM Personal Computer expansion slot. No need for separate housing or cables. A screw terminal panel with optional thermocouple cold junction compensation is available for connecting analog and digital input signals.

And they're easy to program. More than 30 I/O functions are accessed with just 3 commands from BASIC. Programming instructions and sample routines are detailed in the comprehensive User Manual.

Plus, as with all Data Translation products, the DT2801 and



board data acquisition systems for the IBM

Personal Computer.



DATA TRANSLATION

World Headquarters: Data Translation, Inc., 100 Locke Dr., Marlboro, MA 01752 (617) 481-3700 Tlx 951-646. European Headquarters: Data Translation, Ltd., 430 Bath Rd., Slough, Berkshire SLI 6BB England (06286) 3412 Tlx 849-862. IBM Personal Computer is a registered trademark of IBM.

IBM Compatibility— The IBM PC Comes Of Age



Figure 1: Hercules Computer card replaces the 10M display/printer adapter (display illustrates Lotus Development Corp's 1-2-3 program).

by Jerry Borrell

After two years of explosive sales growth, the IBM PC (personal computer) has not only become a primary contender for the role of top-selling µC, but is being acquired for a broad range of scientific, technical, and industrial roles as a low-cost alternative computer. In the process, the PC is spawning an enormous cottage industry of suppliers who are applying the system in robotics, signal acquisition, CAD, process control, laboratory functions, and other technical applications. The marketplace for the system is developing so fast that IBM has to change its outlook on

existing markets and refocus its technology announcements in light of new developments for the PC. These industrial/technical developments for the IBM PC indicate shifts likely to occur in the design of related systems.

The PC Marketplace

The announcement of the PC was almost concurrent with changes in the entire marketing structure of IBM, and it is said that both were an indication of the company's ability to change and adapt in response to shifts in the purchasing habits of computer consumers. Industry consultants say that while the PC was not a dramatic advancement in

The ready market that the IBM PC helped develop has led to a migration of the system's application into a quickly broadening industrial/technical market.

small computers, it was effective in establishing the company in the market. It was apparent from its reception shortly after its announcement that the imprimatur of the company had provided the sort of credibility for consumers that guaranteed its success. Other actions by IBM (i.e., providing design diagrams for the product—Figure 2) and initiating a program for third party software development insured that it would follow in the successful path of the Apple. One of Apple's greatest strengths has proven to be the army of independent hardware and software suppliers that have adopted the Apple for hundreds of applications. So too have developers provided peripherals, software, and compatible hardware products for the IBM PC. The announcement on March 8th by IBM of a 10 Mbyte hard disk, expansion unit, enhanced system (the XT-which has eight PC card slots), color monitor, upgraded

TECMAR'S AFFORDABLE INDUSTRIAL/SCIENTIFIC LINE FOR THE IBM PC

CONFIDENCE IS NO EXTRA CHARGE.

COMPATIBLE

All TECMAR products are designed to be fully compatible with each other and the IBM PC for smooth, trouble-free performance in your system.

SUPPORTABLE

Our philosophy of total support adds uncommon value to your TECMAR products. All TECMAR boards feature a one-year warranty, with guaranteed 72-hour maximum repair turnaround on all standard products. Replacement loaner units are available. Thorough and straightforward documentation comes with each unit. Our customer service staff is available to answer questions or solve your problems.

EXPANDABLE

Our products allow easy expandability, so your system capabilities can grow with your needs.

There's more! TECMAR's broad line of compatible IBM PC Industrial/ Scientific products includes:

- · High Resolution Graphics
- · 51/4" and 8" Floppy Disc Controller
- · Video Digitizer
- · Video Cassette Recorder Controller
- · Speech Synthesizer
- · Voice Recognition
- · D/A Converter
- · Stepper Motor Controller
- · EPROM or EEPROM Programmer/ Reader
- · Static RAM/ROM
- · CMOS Memory



IEEE488 INTERFACE DIUS SOFTWARE

\$395 \$95


Board implements IEEE488 industry standard to enable PC to operate as system/controller or as an addressed talker/listener. Has DMA and interrupt capabilities. Available library of machine-language subroutines called from BASIC or FORTRAN for data transactions with GPIB. Order #20030 INTERFACE, #30030 SOFTWARE.



LAB MASTER™

\$99

A sophisticated system that includes 16 channels of 12-bit A/D with a 30KHz conversion rate, two channels of 12-bit D/A, five timer/counters, and three 8-bit parallel ports. Options Include programmable gain up to 1000, 14-and 16-bit accuracy, 40 and 100 KHz conversion, up to 256 channels. Order #20009.



LAB TENDER™

CADE

An economical and versatile system designed for data acquisition and control applications, with 32 channels of 8-bit A/D conversion, 16 channels of 8-bit D/A conversion, five timers, and three 8-bit parallel ports. Order #20028-



BASE BOARD™

534

Digital Input/Digital Output board with four sections of 24 DI/DO lines. Each section can be used as a stand-alone DI/DO interface or with a daughter board for prototyping or specific functions such as opto-isolated input or opto-isolated output. Order #20025.

Write 35 on Reader Inquiry Card

Call or write for

Call or write for the latest catalog of PC-MATE peripherals from TECMAR. Updated continuously as new products come on-line.



We are proud to offer the largest line of options available anywhere for the IBM Personal Computer. All Tecmar products are designed with advanced technology as it becomes available. We add new products monthly, like the PC-MATE removable Cartridge Winchester drive. TECMAR offers complete reliability and backs it up with support.

TECMAR

PERSONAL COMPUTER PRODUCTS DIVISION 23600 Mercantile Road Cleveland, Ohio 44122 Phone (216) 464-7410 Telex 241735




Figure 2: Motherboard diagram for the original IBM PC. XT version retains original cabinet but incorporates a fixed disk drive and 3 additional PC slots.

RAM memory, and additional software indicate that while the company is going to compete for the commodity market of PC related products, it is not going to compete directly with the companies developing specialized products.

International Data Corp. estimates that IBM sold about 195,000 units in 1982, at an average cost of approximately \$5055, for a total market volume of over one billion dollars. Its projections for 1983 are even larger, indicating the sale of 350,000 units in the US and the development of an overseas market of up to 200,000 units. (Brian Jefferey of Strategic Inc. predicts an even larger market for the system of 1 to 1.5 million of the systems to be sold in 1983). To assist in the latter market the firm has announced its intent to invest \$13 million in a plant for Scotland. The company is also said to be negotiating for the rights to distribute the system in Ja-

pan. Newer predictions will be needed in light of the higher price range of the recently announced XT product (prices vary from under \$5,000 to over \$7,000). Early indications are that the company will have greater success in increasing production than was the case after the initial announcement. If successful it will rival Apple and Tandy as the largest producer of a small computer. Analysts also expect further announcements from IBM in this market including a lowend computer suitable for home or personal applications, and a highend machine that would be designed around a 32-bit processor. It has shown unusual foresight in encouraging the growth of software by removing the \$100,000 dollar royalty limit for authors.

Another emerging market window is in the area of emulation and communication with the 3270 series of terminals. There are estimated

to be over one million 3278's alone installed, and if the IBM can emulate and communicate with this installed base its attractiveness will become even greater. Finally the company is implementing further change in its marketing and distribution channels to insure an increased market share. While the Sears Business Store Centers have proven effective, there are only about 25 at present. Two additional programs are the Dealer Associate Value-Added Reseller, and the Authorized IBM Personal Computer Value Added Dealers (VADS). The dealer associates will deal directly with Sears, Computerland, or other retailers of the PC. VADS will become independent dealers with a direct relationship to IBM.

Industrial/Technical Systems

The ready market that IBM recognition helped to develop in business and education for the PC has,

over the past year, been followed with a migration of the systems' application and related technology into a quickly broadening industrial/technical market. While these applications are nascent for the IBM PC, Andrew Davis, Marketing Director for Data Translation expects that they will eventually grow to between 3% to 6% of the total market for the system. The market is the classic chicken and egg syndrome-users would not demand the PC for such industrial application until the boards were available to allow its use; IBM and the suppliers for the system were unwilling to build the boards without existing demand. In retrospect, the industrial/scientific market may prove more important for the system than the home market.

Data Translation. This Marlboro, MA firm builds the DT2801 (Figure 3) and a soon-to-be-released DT 2805 board for the PC; a single board device that performs analog and digital I/O through the use of an on-board μP . While the 2801 offers 16 channels of 12 bit analog input with a software programmable gain of 1, 2, 4, or 8, the 2805 will offer 1, 10, 100 and 500 signal gain functions. These two products are suited for data acquisition in laboratory and process control environments. Initial system applications include industrial cooking systems, where the board allows remote sensors to monitor temperature and fuel consumption. Analysis and maintenance of process records can also be handled by the PC. In laboratory and instrumentation applications, scientists performing analysis of spectrographic and chromatographic functions require a similar sampling of signals. They may also need to do some post-processing of data, such as Fast Fourier Transforms. Chemical processes in particular require a relatively slow rate of sampling (i.e., 2 times per second) although the PC is capable of much higher rates (13,000 per second). The IBM PC is, however, now merely another instrument for the laboratory, because the user also has the capability to perform report generating and analysis functions, graphics for documentation, and a tool on which to write up the research. In these applications, the PC may become an OEM device supplied by a board producer already configured for a particular industrial/scientific use.

Data Acquisition Systems. DAS

Ohio, has the broadest series of products for the IBM including graphics, memory, expansion chassis, and others. It has also been at the forefront of laboratory and industrial applications. Part of the impetus for its PC products have come from its S-100 bus products,




Figure 3: Data Translation's DT 2801 signal acquisition system which is being used in industrial, and scientific system designs.

is a Boston-based firm which offers in its 500 Series three different board-based products for a broad range of measurement and control devices. Capacity may be expanded to 336 channels of 12- or 14-bit analog-to-digital (A/D) single-ended input, and many other combinations of different input, digital-to-analog (D/A) output, pulse counting, and AC and DC power control. Two or more DAS Series 500 systems can be interfaced to the same computer.

The system also includes a software package, called Soft500, that extends BASIC to measurement and control functions, adding more than 40 new data acquisition and control statements. Soft500's foreground/background architecture allows the user to collect and analyze data simultaneously.


Tecmar. Tecmar of Cleveland,

which are parallelled now in PC systems. The DADIO (Digital to Analog, and Digital Input/Output) board has a data conversion rate of 200 kHz, with 12-bit resolution, and is directed towards a variety of control functions. Among current applications is Koch Hydrocarbon of Oklahoma which uses the board for monitoring fire control in pipeline systems. Another of its products allows for simultaneous independent control of two stepper motors. The board implements a CY512 peripheral controller chip to control step rate, acceleration, number and direction of steps. Application areas for this board include robotic devices. The company's Lab Master board system is designed for D/A and A/D conversion with 12, 14, or 16 bit resolution for up to 256 channels with the use of expansion boards, and 1, 10,

New Amdek 3" micro-floppydisk drive system!

AMDISK-III . . . the engineer's choice:

- New 3" hard plastic encased diskette.
- Up to 1 megabyte storage. (unformatted)
- Plug-in compatible with 5¼ " drives.
- Compatible with IBM-PC.



Specifications

	Unit	Double Density
Capacity		
Unformatted Per Surface	Bytes	250K
Media		
Record Surfaces	2	
Tracks	80	
Recording		
Max Recording Density	Bpi	8946
Track Density	Трі	100
Transfer Rate	bits/sec	250K
Access Time		
Average Access Time	msec	55
Track to Track	msec	3
Setting Time	msec	15
Average Latency Time	msec	100
Motor Start Time	sec	
Disk Speed	rpm	300
Reliability		
Error Rates		
Soft Error		10-9
Hard Error		10-12
Seek Error		10-6
Media	3 inch Cartridge	
Drive Interfere Dive C	amontible with E	OF I

External Interface

Connector:	37 nin	"D"	chell	connector

Pin No.	Signal	Pin No.	Signal
1-5	Unused	13	Write data
6	Index	14	Write enable
	Motor enable C	15	Track 00
8	Drive select D	16	Write protect
9	Drive select C	17	Read data
10	Motor enable D	18*	Select head
11	Direction	19	GND
12	Step pulse	20 37	GND





Evaluation samples \$480

Includes two-drive Amdisk unit with built-in power supply, 4 diskettes and application literature . . . Call (312) 364-1180.

The AMDISK-III Micro-floppydisk System is an engineering breakthrough in disk size, storage capacity, media protection and user convenience. Designed for microcomputers for many applications, the Amdek system is ruggedly constructed to provide years of trouble-free operation. Warranty is 90 days (parts & labor).

Put the new AMDISK-III to test . . . its recording format, data transfer rate and disk rotation speed are compatible with $5\frac{1}{4}$ " floppydisk drives. Call, or write for evaluation samples at only \$480.00 . . . or circle the reader service number for full technical details.

2201 Lively Blvd. • Elk Grove Village, IL 60007

AMDEK CORP. (312) 364-1180 TLX: 25-4786

See us at NCC/83 Booth P7638

Amdek . . . your guide to innovative computing!

QUADBOARD

256K Memory Expansion

Expandable in 64K increments, Quadboard[™] is socketed for 256K bytes of memory. Full parity and checking standard.

Qspool™


With Qspool, you can also use part of system memory as a software print buffer. Choose from 8K to 56K of memory and stop waiting for your printer.

QuadRAM Drive[™]

This software program lets you use part of your total system memory as multiple disk drives. Super-fast drives that let you store important information for easy access.

Chronograph

Quadboard features a real time chronograph to always keep your system's clock/calendar up-to-date. Even when your system's been off for months.



THE FIRST AND ONLY BOARD YOUR IBM PC MAY EVER NEED.

Your IBM Personal Computer is very versatile. New functions and applications are being developed for it everyday. And now with Quadram's Quadboard, you can keep your PC options open for tomorrow's technology. In the tradition of Quadram Quality, six of the most needed PC functions have been com-

bined into one package, using only one expansion slot. Your remaining IBM slots are left free for future expansion needs.

All-On-One-Board and Software, too.

Every board you may ever need for your IBM PC is in the Quadboard package.
From serial port to print buffer. Plus, there's Quad-Master software, too. Included on this disk are utilites for ac-

curately setting the Quadboard's chronograph for time and date, and for performing diagnostics on all Quadboard functions. There's



BYOUADRAM

Parallel Port

There's a parallel I/O designed to operate most printers and parallel devices.

Or a second serial port on Quadboard II.

Serial Port

Used for connecting modems, printers, and other serial devices, Quadboard's serial adapter can be configured as COM1 or COM2 and fully supports IBM PC communications software.

\$395(64K) \$595(256K) Quadmaste © 1982 Quadram Corporation

DESCRIPTION OF THE PROPERTY OF

QUADRA,

also Qswap,™ the feature that lets you switch line printers one and two, back and forth, as your printing needs change.

Proven Design

Quadboard is the number one IBM PC option board on the market today. Nothing even comes close, because Quadboard is designed with performance in mind. Engineered for dependability and built with only the finest components available. Each board has been thoroughly tested and "burned-in" for years of reliable service.

INCREDIBLE PRICE, ASK YOUR DEALER.

Our full line of IBM PC accessories: Quadboard II, Quad 512+, Quadcolor, Quadchrome, Quadscreen, Quadmodem, Memory Board,

Serial Board (Single or Dual ports), Parallel Board,Chronograph, and Microfazer.



All products are sold through local personal computer dealers. If yours does not stock Quadram, please ask him to call us at (404) 923-6666.



4357 Park Drive / Norcross, Ga. 30093 / (404) 923-6666 TWX 810-766-4915 (QUADRAM NCRS)

Write 36 on Reader Inquiry Card




Figure 4: AST Research system diagram for 3270 terminal emulation. AST offers comprehensive facilities for terminal emulation or the PC providing access to several mainframe manufacturers.

100, and 500 signal gain options (with other configurations possible). The board uses 2 DAC80 converters, an AMD 9513 timer, and an 8255 parallel port and can support up to 24 digital I/O signals. An IEEE 488 interface board provides talker, listener, and controller functions. As such the board is directed at instrumentation interfaces for process monitoring, offering programmable data transfer rates, and selectable hardware interrupts.

Two more advanced products are designed to allow the PC to be implemented for newer computer applications including machine vision and voice I/O. The Video Van Gogh board is a video digitizer interface which can accept camera signals from either NTSC or industrial composite (EIA) video. The signal can address up to 256×256 pixels, and with 8-bit value for intensity; it is capable of 256 levels of grey scale. While the company promotes the system for applications in microscopics, signature recognition, robotics, and pattern recognition (for assembly line inspection) there is probably little developed software for the IBM system in this area. The company's parallel product for the S-100 board is in use at Ford for a pattern recognition application. Given large companies' penchant for the purchase of wellknown manufacturers' products,

the device will no doubt have a large growth potential.

The PC-Mate (expansion unit) supports the Speech Master voice digitizer, and Speech Mate software. The company claims this is being considered for factory automation applications in which workers may call out the status of a process or project to control an action or supply of materials.

Computer Graphics

In some ways computer graphics appear to have been neglected by IBM. While the resolution support-

ed with the initial announcement was at 640×200 , IBM offered a color graphics card but no color monitor. However, with its XT System announcement the company has introduced an IBM RGB monitor with 16 displayable colors selected from a palette of 256. While the system still lacks any IBM interface to I/O devices such as tablet, mouse, or digitizers, other are actively seeking to fill the marketplace. Riva Terminals Ltd, of England is one of the first companies to have addressed the graphics market. The company's PC 1024 is a 20" monochrome device, with a resolution of 1024×780 (as a window on a total display capability of 1024 \times 1024). In a terminal mode, the system can emulate the Tektronix 4014, as well as DEC VT52 terminals.

Quadram Corp. of Norcross, GA also supplies a large format (17") monochrome, raster display for the PC but has chosen to keep resolution at 480×260 . The terminal is DEC VT 100 compatible, and may be sold with a Plot-10 graphics option. More recently, the company has introduced a 12" RGB monitor, with 690 × 480 resolution. Quadram also produces three 16-color PC boards for use with its monitors with 640×200 or 640×400 resolution. Other RGB monitors for the system are now produced by Amdek, Sony, and Electrohome (as well as IBM itself for the XT ver-




Figure 5: Quadram Corp's Quadboard for up to 512K of additional RAM.

sion of the system).

Hercules Computer Corp. of Berkeley, CA produces a card which replaces the IBM Display/Printer Adapter and allows a monochrome display of 720 × 348 on the IBM monochrome monitor (**Figure 1**). The board also offers a light pen interface. The Hercules board is currently being implemented in 3D CAD applications and for 2D PC board design.

Terminal Emulation

One of the recurring demands for the PC has been to use it as an IBM terminal emulator. In the fall of 1982 the first such emulation hardware/software packages were released by DataSource Systems Corp. of Minneapolis, MN. IBM quickly followed suit to ensure that it would maintain control of the market for terminals compatible with its mainframe products. There are two protocols supported by IBM for the PC, the Synchronous Data Link Control (SDLC) for the SNA environment, and the Binary Synchronous Communications (BSC) Protocol. IBM also provides a 3101 emulation package, and a 2.0 version of Asynchronous Support Communications Support Package, allowing the PC to work as an asynchronous teletype terminal.

Other companies providing emulation packages include Forte Data Systems of Santa Clara, CA who offer a 3278-2 terminal emulator, Aztek, of Ottawa, Canada, also selling a 3278 emulator, and Techland of Mt. Vernon, New York (any 3270 device is emulated under SDLC).

AST Research of Irvine, CA probably offers the widest selection of IBM terminal emulation software/hardware products. AST-SNA (Figure 4) provides the PC with the ability to emulate the 3274, 3278, and 3770 communication terminal, while AST-3780 allows the terminal to emulate IBM 2780/3780 RJE workstations. The latter has particular importance because it will provide the PC with the ability to communicate with IBM 370, 4300, & 3000 series computers as well as




Figure 6: Mbyte cartridge Winchester drive from Tecmar, Cleveland, OH.

UNIVAC, CDC, Data General, DEC, Wang, Honeywell, and others. Microlog of Suffern, NY, which makes Z-80B based Baby Blue products for 3270, 2780/3780 emulation, may be the first company to offer 3279 graphics terminal emulation for the PC. This will allow designers to consider implementing more advanced, high resolution packages of systems as such offered by the Spectragraphics Corp. Dennis Murray, VP sales of Microlog, indicates 3279 development is possible under the XT version of the PC. The Baby Blue products have an additional advantage in that they allow the PC to run CP/M 80 based applications.

The most important implication of the emulation work is that the PC becomes even more attractive for acquisition or for developing applications software—the installed base of IBM terminals is well over one million. The advantages occur through the benefit of acquiring additional terminals for mainframes that have standalone capability, or of adding access to mainframe processing and data for a μ C. There

are further advantages for the industrial and scientific developments mentioned earlier in that the PC's functions become enhanced by mainframe access. In addition the company released simultaneously with its XT product a conversion kit for its 3270 terminals which will allow it to become a PC. The additional push that this is likely to give to applications development is not to be underestimated.

Memory and Peripherals

One of the primary constraints mentioned by applications developers for the PC has been the limitation of PC slots. Only five are available on the original product, and all of them can quickly be filled up by memory expansion, clock, communications adapter, and other basic cards. The XT announcement was based upon a redesigned motherboard with eight slots, but if the XT is configured with communications, and hard and floppy disk drive interfaces, then only five remain. In addition the expansion comes at a cost of width to the cards, which are now only al-

Manufacturers' Listing

To obtain more information about the companies listed below, write in the appropriate Write number on the *Digital Design* reader service card.

Apparat Inc. 4401 S. Tamarac Pkwy. Denver, CO 80237 Write 334

AST Research, Inc. 2372 Morse Ave. Irvine, CA 92714 Write 335

Aztek Computing 969 Bronson Ave., Suite 212 Ottawa, Ontario, Canada K1S 4G8 Write 336

Data Acquisition Systems, Inc. 349 Congress Street Boston, MA 02210 Write 337

Data Translation 100 Locke Dr. Marlboro, MA 01752 Write 338 Forte Data Systems, Inc. 1500 Norman Ave. Santa Clara, CA 95050 Write 339

Hercules Computer Technology 160 Beechnut Dr. Hercules, CA 94547 Write 340

IBM Systems Product Div., Entry Systems PO Box 1328 Boca Raton, FL 33432 Write 341

Microlog Corporation 222 Route 9 Suffern, NY 10901 Write, 342

Quadram Corp. 4357 Park Dr. Norcross, GA 30093 Write 343 Riva Terminals Ltd. 9 Woking Park Albert Dr. Woking, Surrey GU21 5JY England Write 344

Seattle Computer 1114 Industry Dr. Seattle, WA 96188 Write 345

Sony Trinitron Tokyo Electronics 222 Kearney St. San Francisco, CA 94108 Write 346

Techland Systems, Inc. 39 Carwall Ave. Mt. Vernon, NY 10552 Write 347

Tecmar Inc.
Personal Computer
Division
23600 Merchantile Rd.
Cleveland, OH 44122
Write 348

lowed 3/4" per slot—a problem for any of the cards that have piggybacked ICs, analog devices or sub assembly cards. This internal limitation has had two results: designers have developed multiple function boards, and expansion chassis to allow the implementer more freedom.

Quadram. Quadram Corp. of Norcross, GA (recently merged with Intelligent Systems Corp.) is one of the largest producers of IBM PC products in the country. The firm has acquired recognition for its multiple function board for the PC—Quadboard II for example combines six functions: 2 serial ports, chronograph, up to 256K of expanded memory RAM drive, and printer spooler. Other products of the company will provide up to ½ Mbyte of memory and a communi-

cations interface (**Figure 5**). Similar boards are provided by Profit Systems (clock calendar and 512 on board RAM), Seattle Computer and several others. Seattle also sells an 8087 co-processor for the IBM cpu (8086) which considerably enhances speed of operations.

For those designing applications with the PC, Apparat Inc. of Denver makes an EPROM programmer at a very low cost, but which is suitable only for low volume production of PROMs. In terms of additional memory, Tecmar, mentioned above has offered 10 Mbyte drives, and a 5 Mbyte removable Winchester for several months (**Figure 6**). The announcement of a hard disk by IBM may affect the price and profitability of secondary suppliers, but other sub-systems are being designed based on the new XT.

Summary

The rapidly developing marketplace for the system has changed IBM strategy concerning existing markets and has led them to refocus in light of new PC developments. The response to the PC is pushing secondary suppliers into the industrial and scientific market rapidly. One of the greatest problems for designers is in developing the analog interfaces (both software and hardware) to the outside world. However, the results are providing scientists and industrial users of computers with new avenues of access to digital technology. The opportunity with the system today is for the designer who must have an understanding of both the application, and the likely shifts by IBM to retain the largest product markets.

The OEM's Choice for Multibus* Quality and Reliability

NEW 512K Memory Boards



Central Data Corporation

1602 Newton Drive, Champaign, IL 61821-1098, (217) 359-8010 TWX 910-245-0787

128K-512K Dynamic RAM with EDC

Error detection/correction (EDC), high speed and increased noise immunity are standard features that give you a number of user options with this versatile new board. Completely Multibus compatible, this board allows you to add 128K, 256K, 384K or 512K of RAM to any 8- or 16-bit system without making changes. It decodes the full 24-bit address bus for a system-wide memory of 16 megabytes and runs at a fast read access time of 275ns. EDC corrects all single-bit errors without processor intervention. It also flags double-bit errors, generating an interrupt so input ports can be read to determine which RAM chip failed. Or, you can strap the board to interrupt on any error. And noise won't bother this board, either — its five-layer construction incorporates power and ground into the two internal layers. High reliability sockets with integral by-pass capacitors further minimize noise.

128K-512K Parity Only Dynamic RAM Board

This new board delivers all the quality features of the 128K-512K EDC Dynamic RAM Board except that parity detection is used rather than error correction. The parity circuitry will detect any single-bit errors, optionally generating an interrupt so the CPU can determine which row of RAMs had the error. Four easy to read LED's on the top of the board show the check condition, allowing fast replacement in the event of a failure. Writing to the corresponding output port clears the parity error. Completely Multibus compatible, the board runs at a rapid 245ns access time. And here's some refreshing news about wait states — the on-board arbitration circuitry cuts down on wait states caused by refresh cycles. You also get hidden refresh — if the processor accesses another board in the system at any time between refresh cycles, a new refresh cycle is initiated to overlap the memory cycle on the other board.

OEM quantities and pricing are available on these and on Central Data's complete line of Multibus boards. For more information call or write.

^{*}Multibus is a trademark of Intel Corporation. Prices shown are quantity 100, 512K RAM.

Our Gate Arrays Will Save You Money



GATE ARRAYS FROM INTERNATIONAL MICROCIRCUITS USE LESS SILICON.

- 1. Integrated circuit production costs depend on chip size. Small chips are necessary for credible low prices.
- 2. It is easy to design large, inefficient chips. The challenge is to design tight gate arrays that use very little area and are developed very quickly. It is not true that gate arrays are inherently inefficient.
- 3. At International Microcircuits we have been making efficient gate arrays since 1974. Our corporate commitment is to provide small, efficient chips for your logic, smaller than with other approaches. This means that we focus our development resources in four critical areas:
- We develop our own processing and interconnect technologies, optimized for our gate arrays;
- We design our base arrays with small areas per gate and small numbers of wiring channels;
- We provide a large and growing number of base arrays (currently 38) with a fine resolution of gates-per-chip so that one will be just right for your logic problem;
- Our wiring techniques provide at least 95% utilization of the gates on each array, using computer-verified interactive design techniques rather than fully automatic layout.
- **4.** The results: small, competitive chip sizes and viable low production prices. Even if many millions of your circuit will be produced, efficiently-sized gate arrays compete easily with standard cell approaches and with full custom.

Interested? Send us your logic for a quick, confidential quote. Or ask for more information about our products. Our gate arrays will save you money!



The Logical Choice for Gate Arrays

TELEPHONE: 408 727 2280 • TWX: 910 338 2032 3350 SCOTT BLV D • BUILDING 37 • SANTA CLARA • CA 95051

Designers Guide Series.



Gate Arrays.




photo courtesy National Semiconductor

by Douglas Eidsmore, West Coast Technical Editor

Larger, faster gate arrays and more powerful design tools are the trend but upfront decisions can make or break a design

Driven by design automation hardware and software, the demand for new circuitry and a shortage of IC designers, the gate array market should reach \$9 billion in 10 years. There are now over 60 vendors on the gate array bandwagon. Indications are that designers are rapidly shifting from redesigns of existing systems to new designs that take advantage of the performance, privacy and reliability of the semi-custom approach. The technology is now so advanced that it is used by semiconductor companies to produce standard parts.

Gate Array Benefits


The advantages of gate arrays are numerous and well-documented. When compared with discrete ICs, implementing a system on a gate array can save money both in the circuitry used and in supporting hardware, such as power supplies. Because parts count is lowered, inventory and associated inspection and maintenance costs are also reduced.

Fewer parts also means improved reliability. Some failure analyses show that 70% of printed circuit board system failures are due to faulty interconnection—i.e., device to circuit board, bonding wire to package pin, bonding wire to die, and die to package. A 2400 gate array device can replace over 70 SSI/MSI ICs, resulting in a system with 10% of the interconnects of a discrete-based system. Putting interconnects on-chip also means improved performance with higher speeds and increased throughput. Power savings over discrete designs are an added benefit.

Which Technology?

One of the first tasks is to decide if the gate array approach is appropriate. The characteristics of gate ar-

DESIGNERS GUIDE



rays must be compared with competing custom technologies: standard cells, full custom and programmable logic arrays. None of the custom approaches is a panacea but each is appropriate for its own set of applications.

Full custom offers full functional freedom but, even with CAD and silicon compilers to streamline development, is costly in both time and dollars. High volumes and/or high performance must be required to justify the relatively high investment.




Figure 1: Small arrays such as Texas Instruments' TAL-004 with 500 gates and TAL-002 with 320 gates can easily be placed by hand. Grids representing macrocells can be pasted onto layout sheets similar to the one above.

Programmable logic arrays (PLAs) are excellent where low volumes and low gate counts are all that are required. Personalized with a PROM programmer, PLAs are often used to create prototypes of parts to be built using other custom technologies. Semi Processes Inc. recently announced a series of silicon gate CMOS arrays that can be programmed using the logic equations used to create a PLA. This conversion is so simple that the company is quoting 8 weeks turnaround from receipt of PLA equations to CMOS arrays.

At one time PLAs were slower than the discrete ICs they were designed to replace. But programmable logic array performance is continually improving. Monolithic Memories' (Sunnyvale, CA) latest programmable logic arrays are implemented in a self-aligned washed emitter process to attain propagation and frequency time improvements of 36% and 50%, respec-

tively, over previous offerings. PLAs are available from several manufacturers, including Monolithic Memories, AMD and Signetics.

Standard cells compete most directly with gate arrays. They are especially attractive as a gate array alternative when special functions, such as high function comparators or differential amplifiers, need to be implemented. Gate arrays, on the other hand, are a fixed grid of logic cells and are most useful in implementing circuits composed of random or sequential logic.

Since standard cells must be processed from the ground up, development is typically more costly and time consuming than with gate arrays. However, this is not always the case. Some circuits are a poor gate array fit, and a standard cell solution is easier and faster than cramming or gerryrigging the circuit onto a gate array. George Stephan, President of Universal Semiconductor, describes standard cells as "characterized by elegant engineering and inelegant manufacturing." The reverse is true of gate arrays, he claims. Gate array design is restricted by fixed logic geometries, inability to implement complex macros, and fixed I/O buffers. Standard cells can be designed with special cells, easily accomodate hierarchical design and are not limited by I/O restrictions.

On the other hand, standard cells are less flexible in terms of making design changes and in varying production quantities than are gate arrays. Gate arrays, with their reliance on partially processed wafers, require fewer masks for personalization and therefore for redesign. Another less obvious reason for the flexibility



Figure 2: Motorola metalization mask patterns. Company's MOSAIC process is used to fabricate low power Schottky arrays, including MCA2800 ALS as well as ECL arrays. Three masks are required: one for each metal level and one for via holes.

Technologies for the Eighties



The Leader in Semi-Custom ICs









Analog

Digital

Bipolar 14 Monochips 110 to 1200 Components

1.2 to 36V Supply

Analog CMOS 1 Monochip

1700 Components incl. 135 Gates Switch Capacitor Applications

ULA 3 Monochips

225 Cells Output to 40mA

CMOS ISO Si-Gate 5 Monochips

150 to 2000 Gates 4ns Prop Delay

CMOS Metal Gate 7 Monochips

140 to 800 Gates 3V to 15V Supply

CML Bipolar 3 Monochips


450 to 2000 Gates Toggle Rate to 20MHz

For more information please call:

(408) 438-2900

Interdesign Inc., 1500 Green Hills Road, Scotts Valley, CA 95066

Write 40 on Reader Inquiry Card



of gate array manufacturing is that since the gates in an array are never fully utilized, the remaining gates can be used to implement a last minute design change or to add features in a redesign.

Matching the attributes of the various custom approaches with turnaround and production requirements of the circuit, as well as size and operational needs, will allow selection of a custom technique. If gate array technology seems promising, the next step is to start looking at the circuit in question as a gate array.

Circuit Partitioning

Partitioning the circuit into logical modules is a first step in fitting the circuit to an array. The goal is to identify the circuitry that is "arrayable" and that which should be implemented with standard parts. Because each vendor has his own "modus operandi" there is some disagreement about whether vendors should be approached before or after partitioning. Bill White, Director of Gate Array/Standard Cell Products with Harris Corp., feels the vendor can help the designer avoid sending out RFQs for a gate array with 500

gates and 400 pins. In most cases, a rough partitioning will be required before selecting an array vendor.

Fitting an existing PCB-based or new design to an array are somewhat different processes. Partitioning of existing logic involves blocking out and combining as many TTL glue chips as possible with an eye towards minimizing I/O: If a new system is under development, the designer works from his logic diagram and builds abstract blocks such as ALUs, register files or multiplexers.

The next step is counting or estimating the number of gates in the circuit. A crude estimate can be made by using the rule of thumb that a typical MSI circuit will require 60–75 gates. LSI Logic Corp and other vendors publish gate equivalents for popular TTL components; Universal Semiconductor offers a slide rule that makes the conversion almost automatic. Such a gate count conversion should take into account the processing technology. Flip/flops are implemented in fewer gates with CMOS than bipolar, for example.

Selecting a fabrication technology is another early design task. The performance and I/O of the array must meet the requirements of the system. Fortunately,

The Economics of Gate Arrays

by Allan M. Cox, Marketing Manager Digital Products, Interdesign, Scotts Valley, CA

The cost savings of moving electronic products based on MSI standard IC families to LSI semi-custom gate arrays have become too significant for the product designer to ignore. Also, the gate array based product manufacturer can get to market fast, with significant advantages in addition to cost. It is hard to envision designs in the 80's being implemented in anything other than LSI/VLSI standards (such as μP families and codecs), standard memory and semi-custom.

The relative costs for custom, standard cells and gate arrays are generally summarized by the curves in Figure 1. Designers strive to follow the minimum cost curve. To do that, it's necessary to know the cross-over points A, B and C. A, B and C, however, can vary by as much as two orders, due mainly to device complexity. Device complexity and hence silicon area is a major factor in device cost. However, at the lower complexities, die cost tends to become less significant, and product cost is dominated by packaging, testing and labor costs. The vendor with access to a high yielding process and low wafer costs has the ability to push the gate array/standard cell cross-over point (the annual volume between A and B) to a very impressive limit.

It is not uncommon today to find gate arrays meeting volume requirements of 50 thousand to 250 thousand units per year, and occasionally up to 500 thousand per year. Efficiently utilized arrays are even now filling annual production requirements of over 1 million units annually.

With the prospect of continued learning curve and volume production economics coupled with the inherent flexibility, fast response and design cycle of gate arrays, the product and system designer has available the tools he needs to meet his challenges in the 80's.





Figure 1: These curves represent the costs of full-custom, standard cell, gate arrays, and standard product approaches based on annual production volume. Points A, B, and C represent the cross-over points of the various approaches.






Figure 3: Electron microscope photo of double level metal CMOS array from International Microcircuits, Inc. Via holes connecting first and second mask can be seen.

gate arrays are fabricated in a range of processes, each with unique density, speed and power characteristics. The trend is clearly towards CMOS and ECL. CMOS clock rates are 40 MHz and better, with 2ns delays and very low power consumption. ECL boasts 300 MHz clock rates and gate delays of less than 500ps. Low power Schottky TTL is also a solution for many applications and has proved to be very durable in the marketplace.

CMOS is available in metal gate and silicon gate versions. Silicon gate CMOS is faster and denser than

metal gate. Metal gate CMOS arrays are limited to about 500 gates, whereas 3μ silicon gate arrays with 10,000 gates and extremely high speeds have been announced. As line widths drop, even higher gate counts and speeds will be available, especially with oxide-isolated silicon gate technology. CMOS arrays have been used to great advantage as collectors of the glue circuitry surrounding μPs . With 2μ and finer geometries, CMOS arrays will challenge ECL as the technology of choice for semicustom CPU circuitry. Storage Technology (Sunnyvale, CA) is developing their new line of IBM-compatible mainframes from such technology.

Arrays are presently personalized by one or two metal levels. Double level metal results in a denser array than single level. Interconnections, and therefore, delays, are correspondingly shorter, and as a result higher speeds are obtained.

Double level architecture offers much greater layout flexibility than single level configurations with double level metal arrays. Automatic placement and routing can therefore be used effectively. Single level arrays are almost always placed and routed by hand or interactively at a CAD station. However, Signetics now offers automatic routing and placement on its new single level metal CMOS arrays.

When reviewing a vendor's product line, attention should be paid to more than technology and gate count. The positioning of the product line and the gate count iterations are also important. One tactic for achieving high silicon utilization is effectively matching the gate count of the circuit to be implemented with





Figure 4: Plessey Semiconductors' semi-custom array mask production (SCAMP) flow chart.



the number of gates on an array. Placing a 480 gate circuit on a 600 gate array uses silicon more efficiently than if it were placed on a 800 gate array.

Design Cycle

An important consideration in selecting a vendor is the design cycle used, not only in terms of turnaround time but in terms of the type of user participation required or allowed by the vendor. Working with a gate array vendor is much more intimate than purchasing parts off the shelf. Some vendors encourage customer participation through the design cycle, while others do not. Most are flexible and allow customers to enter a design cycle just about anywhere. The customer may do none of the design, or he may submit a final design on a pattern generation tape. In general customers can save money by accepting part of the design responsibility, but they also assume a greater risk if the part is discovered to have designed-in flaws.

If a customer chooses to participate in some phase of the design, the location is another consideration. Usually, customers go to a vendor's facility for training and to do the design. A cozier situation would be to work at one's own facility. In such a situation the customer would either do a hand layout (for a small array), use a company-owned Engineering Work Station (Daisy or Mentor Graphics) or larger CAD system, or

work at a terminal with a line, such as Harris' Dial a Chip, to a vendor's CAD system. The problem with such arrangements is lack of vendor support.

Many companies have established or are establishing regional design centers. Such centers combine the best of both worlds: vendor support and a facility near the customer's home. Motorola and Texas Instruments were among the first to establish design centers. But the idea is catching on. Some companies are adding design centers to their regional sales offices.

Lack of alternate sources has been, in some people's eyes, a major flaw in using gate array technology. In reality, most customers' volumes are small enough that the risk in using a single source is fairly small. If a problem should occur during production most vendors can fall back on their own alternate foundry sources. A greater problem could arise if a disaster were to occur to a customer's design facility at a crucial point in a design. For many users both problems have been solved because several gate array vendors have agreed to share processing technologies and design tools. Some of these agreements include: Texas Instruments and Harris Semiconductor, Motorola and National, LSI Logic with Toshiba and Advanced Micro Devices, Universal Semiconductor with Siliconix and Nitron, California Devices and Telmos, and Interdesign and GTE Microcircuits.

Use the Reader Inquiry Cards on page 115 to obtain more information on the products and services appearing in this issue.






Figure 5: AMI's GA series development flow. The heart of the system is BOLT logic data base. Using common data base allows conversion of gate array to standard cell or full custom circuit with minimal risk.

Design Process

Once the vendor and virgin array have been selected, the design cycle begins. Each vendor has his own unique design process, but there are some universal tasks that must be completed. The functional logic design has to be entered into the vendor's system. This is often called schematic entry. It may occur at a work station as the logic design takes place or it may be entered via a digitizer from a layout drawing. The entered logic description is often said to have been "captured." In some systems, the logic is defined as it is entered in the format of the vendor's macrocells. The macrocells are used to create a network of higher and higher levels of integration. This process is called net list or network entry.

A simulation of the entered logic is then performed. The operation of the entire gate array or blocks of it may be simulated. The purpose of the simulation is to verify that the description entered into the CAD system truly represents the circuit as the designer intended it to. The simulation is usually run using TEGAS software from COMSAT Corp (Austin, TX). Many companies use their own simulation/verification software and some of them have developed translators to convert to TEGAS formats. COMSAT has developed

a new software package called TEXSIM that accesses a library of delay data, rather than relying on the unit delays used in TEGAS. LSI Logic is probably the first vendor to incorporate TEXSIM into a design system. Their LDS system goes a step further. They use nominal delays that are based on estimated wire lengths before layout for a more accurate simulation. After layout the simulation is repeated.

The simulation data is fed into a test verification program. Critical timing paths are scrutinized at this point and race conditions investigated. Some vendors automatically evaluate the nodal activity as part of the test program generation. Such an evaluation is performed in an effort to determine the testability of the array. This evaluation may include a complete fault grading. In fault grading each node is examined to make sure that, if the node were stuck at 0 or 1, the fault would be detected from the array's I/O. This procedure is an option with most vendors because it eats up so much computer time. Even using mini-computers, fault grading can take several hours. Instead, an estimate of the node coverage or nodal activity can be made and a testability percentage determined. The latter procedure is usually adequate and saves hours of expensive computer time.

THE UNIVERSAL FAST CMOS GATE ARRAY SOLUTION. THREE OR FIVE MICRON TECHNOLOGY! 360 to 2400 GATES!

There are many sound reasons to select Universal as your CMOS gate array partner. Here are a few:

Advanced Technology—We don't buy technology from others—we make it! For toggle rates to 25MHz, our 5μ process serves nicely. For frequencies beyond, our 3μ process is

employed. In either case, you're dealing with a company in full command of the technology behind its arrays.

Broad Array Selection—No other company has a more useful selection of arrays. There are 14 different arrays logically sized between 360 and 2400 gates available. Large or small, fast or faster performance, we have an array to serve your needs.

Gates	Size	Speed	Pads
360	118 × 140	50 or 25MHz	44
540	132 × 167	50 or 25 MHz	58
720	159 × 167	50 or 25 MHz	64
960	161 × 208	50 or 25 MHz	70
1200	188 × 208	50 or 25 MHz	74
1500	188 × 244	50 or 25 MHz	80
1800	202 × 230	50 or 25 MHz	92
2400	232 × 252	50 or 25 MHz	110
	360 540 720 960 1200 1500 1800	360 118 × 140 540 132 × 167 720 159 × 167 960 161 × 208 1200 188 × 208 1500 188 × 244 1800 202 × 230	360 118 × 140 50 or 25MHz 540 132 × 167 50 or 25 MHz 720 159 × 167 50 or 25 MHz 960 161 × 208 50 or 25 MHz 1200 188 × 208 50 or 25 MHz 1500 188 × 244 50 or 25 MHz 1800 202 × 230 50 or 25 MHz


Complete CAD Support—No other company has more sophisticated CAD tools. Every Universal array is completely simulated and verified prior to converting it to silicon. And that's not all:



- Macrocells are placed automatically
- Macrocells are routed automatically
- Logic and circuit functions are fully simulated
- The design is completely verified.
- Test program automatically generated

Fast Turnaround—For arrays of 800 gates or less, we guarantee an 8-week turnaround. For larger arrays, add one week per 150 gates. And because of our powerful CAD tools, when you get your prototypes, they'll work and perform to spec!

Start Today—What size array do you need? With our Handy Dandy Gate Counter, you can convert your TTL or LSTTL design to CMOS gate equivalents quickly. In less than an hour, you'll know exactly what size array will do your job. *Write* or *call* today for your *FREE* Handy Dandy. We'll also send you a full color brochure describing our products and services.




Write 43 on Reader Inquiry Card



UNIVERSAL SEMICONDUCTOR INC.

HOW TO CUT THE CAE WORKSTATION UMBILICAL

Introducing GateMark. The only affordable CAE system with a built-in cell library.



Once your design is complete, you can also cut your fabrication time to less than two weeks, with Matra or other sources. That's because you start with a pre-fabricated array wafer, and make only the final metallization layer mask. So you no longer waste time making 8 to 12 unnecessary masks. Or evaluating a lot of mask and fabrication vendors. Which means now you can get your products to market sooner, and still be competitive in lowto-medium volume applications, where full custom designs can't be justified.

Design costs these days are averaging \$25K to \$50K for a single chip. And eating up roughly 12 weeks of lead time, just to get to prototypes. So if you're doing as little as two designs a year, you can't afford not to be doing them the Gate-Mark way: quickly, reliably, cost-effectively.

For full information on GateMark, write: Matra Design Systems, 120 B Albright Way Los Gatos CA 95030. Or call (408) 370-0977.

Most CAE systems these days are just workstations, tied to a design center mainframe by umbilicals. Long, expensive umbilicals that also tie you down to one manufacturing source.

But not GateMark. It's a truly stand-alone CAE work-station, including dual-processor CPU, 30-Megabyte hard disk, high-resolution color display and complete software package. With its built-in CMOS cell library, you not only cut the mainframe umbilical, you cut design time and costs too. Plus

your productivity is enhanced significantly.

When you start a design with GateMark, you go from idea to PG tape in a matter of days.

That's because you start with a library of pre-characterized cells: off-the-shelf circuits right out of a standard data book. So you start with functionality you trust. And save possible weeks of checkout later on.

Part No.	Equivalent	Inverter	No. of
	Number	Delay	Pads
MA 400	400	1.5 nsec	40
MA 800	800	1.5 nsec	54
MA 1200	1,200	1.5 nsec	66



Write 44 on Reader Inquiry Card



Our ANSI X3.64 terminal has all the VT100 features you'll ever need in a conversational terminal. Plus color and vector graphics.

quickly and with greater comprehension than monochrome. ANSI X3.64 system compatibility. The 2405 is the ideal replacement or add-on terminal. Highly compatible with VT100 and numerous other ANSI X3.64 terminals, the 2405 is easily integrated into any ANSI X3.64 environment. It also includes ASCII codes and a VT52 mode.

line screen, without sacrificing the most important capabilities

you want from a VT100 terminal. Plus, the 2405's vibrant color conveys more information, more

With all the features you need. Eight foreground and eight background colors. Terminal based

vector graphics. Data transmission baud rates from 50 to 19,200. English language menu set-up mode. Non-volatile set-up memory. Two full pages of screen RAM. In-line CRT. Auto degaussing. Powerful, 6 MHz 8085 microprocessor with four hardware interrupts. Plus, up to 72 function key definitions, optional.

Introductory price good through May 31, 1983. After that, our regular single-piece price of \$1195 goes into effect. So act now. Take full advantage of the color, vector graphics and flexibility of the Intecolor 2405—at the 100-piece price. Once you


do, we're confident that you'll enthusiastically agree with the growing number of OEMs and users who are making it dramatically clear that, "The future belongs to color!

For the name of the distributor or sales representative in your area, or for complete specs, ask about our \$995 special: Call 404/449-5961.



AN INTELLIGENT SYSTEMS COMPANY

Intecolor Drive, 225 Technology Park Norcross, GA 30092, TWX 810-766-1581






Figure 6: LSI Logic's LDS Design Automation System. The design verifier provides propagation delays through each network for both rising and falling inputs. Delays are used by the TEXSIM simulator. Interactive place and route is compared with design data to avoid layout violations. Following completion of layout, the actual metal (double layer) and metal/poly (single layer) lengths are recorded and the capacitance and resistance are calculated. These are then incorporated for use in recalculating the network delays and verifying the design.

Designing the array layout is the next step. Most vendors feel customers should not be bothered by layout and prefer that they bow out at this point. Layout means that macrocells are placed and routed. This can be done interactively on a CAD system or automatically Automatic place and route is faster than the interactive method, and it guarantees an accurate translation of logic to silicon, but high silicon utilization is rarely attained. Low silicon utilization is costly: 60% utilization will double the size of a chip!

International Microcircuits Inc. uses an interactive placement system. As cells are placed, a net list is automatically generated, to ensure that an accurate translation is made. This placement net list is compared with the schematic net list to validate the layout.

Routing can be done automatically after the cells have been placed. Computers do a poor job at pattern recognition, which is required in cell placement, but they do a good job as routers. Most auto-routed arrays still require some interactive routing. Once the cells are placed and routed, the layout is re-simulated and performance is verified. If the circuit "runs" as designed, a pattern generation tape is created and tooling is produced for a prototype run. The prototypes are tested using the test vectors generated in the early stages of the design. If the prototypes check out, the production run of packaged arrays begins. Gate arrays can be housed in a variety of packages including: flat packages, leadless chip carriers (LCC), leaded chip carriers, and pin grid arrays.

Gate Array Trends

With so much activity on the gate array front, it has become nearly impossible to describe every array currently on the market. But some of the more recent announcements are indicative of technology trends. Some recent CMOS arrays include: LSI Logic's LL7000, with 2μ line widths, up to 10,000 gates, and propagation delays of $1.3 \, \mathrm{ns}$; National Semiconductor's 3μ , 2400 gate SCX6324 with $2 \, \mathrm{ns}$ internal gate delays (a 2μ part with ins delays will be available this summer); Universal Semiconductor's ISO-36 and -56, 3μ and 5μ arrays with 1800 gates and 92 bonding pads, Signetic's 330 to 1700 gate LS/TTL compatible 3 and 4μ arrays, and AMI's 3μ GA series with up to 5000 gates and $2 \, \mathrm{ns}$ delays.

ECL arrays have also progressed. The Electron Division of NEC Electronics USA announced three arrays ranging from 300 to 3000 gates. Internal gate de-





Figure 7: Motorola's MCA2800 ALS array is supplied in this 149 pin grid array. The TTL compatible array has 2800 gate equivalent and 130 cells. Propagation delay is 600ps.



lays are 0.5ns for the 300-gate array, and 0.7ns for the 1,100 and 2,000-gate arrays. By virtue of its agreement with Motorola, National Semiconductor announced 600 and 1200 MCA ECL arrays. Both devices feature a typical gate speed of 1ns. The MCA1200 includes 48 major internal macrocells while the MCA600 includes 24.

Integrated Schottky Logic (ISL) arrays are based on single-input NAND functions. The technology rivals I²L for density and STL for speed. Raytheon's Semiconductor Div. (Mountain View, CA) introduced a family of ISL arrays with gate counts from 800 to 2400. Typical propagation is 2.3 ns/gate.

Fujitsu Microelectronics will introduce a family of STTL arrays with 224 to 1120 gates in the second quarter of '83. Arrays with specialized functions are also available. Telmos and Interdesign both offer silicon CMOS arrays with A/D conversion on chip. Silicon Systems (Tustin, CA) recently announced a CMOS switched capacitor array to use in developing filters.

The array technology that will be offered to systems designers in the near future can be seen today at captive semiconductor manufacturers and at technical conferences. Control Data (St. Paul, MN) has developed 6000 gate silicon CMOS arrays with 2500 addi-

tional non-alterable peripheral gates for self testing. Designed for internal use only, the 2 or 3μ circuits were developed using layout rules and processing parameters from Motorola, National Semiconductor and Fairchild. The self testing circuitry acts as a wafer probe device. Onchip function registers and input and output registers allow operands to be entered through input pins.

Control Data developed a variable macro technology for use with the array. Variable macros are flexible both vertically and horizontally. They can also be stacked. For example, assume an 8-bit register needs to be designed. With conventional macro technology, four 2-bit register macrocells would be used, each with its own duplicate controlling register. The variable macros developed by Control Data do not require the designer to duplicate the control circuitry. Instead the designer calls four 2-bit registers and the controlling circuitry as a separate "hat" that, because of vertical flexibility, is stacked on top of the four registers.

IBM has developed a four-level metal process for increased density in bipolar arrays. The fourth level of metal, combined with metalization advancements, resulted in a 75% density increase over three-level arrays.

Up Front Decisions

by Joe Conway Marketing/Applications Manager Applied Micro Circuits Corporation San Diego, CA

Users can save themselves and vendors time and grief by making the right decisions up front in a gate array design. Some questions should be answered early. Can the circuit be partitioned into uniform slices? How big are those slices? Are both very high speed and lower speed logic required? What kind of I/O is needed? Is military qualification required? When are prototypes required? When are production parts needed? How many parts are needed?

Each gate array technology has advantages, based on performance and temperature range requirements. The smart user matches the array technology to the circuit requirements—not the other way around. The list of technologies includes: Metal Gate CMOS, Silicon Gate CMOS, I²L (Integrated Injection Logic) Bipolar, ISL (Integrated Schottky Logic) Bipolar, STL (Schottky Transistor Logic) Bipolar, ECL (Emitter Coupled Logic) low and high power.

Gate array suppliers are each seeking a niche. AMCC, for example, supports the low power ECL market with the availability of TTL or ECL (or both) I/O in a device family up to 1500 gates with full MIL availability. This product offering supports only the customers who require high performance with TTL I/O, mixed TTL and ECL I/O or complete ECL I/O requirements with up to full MIL temperature range.

Array users should understand the circuit's performance requirements and narrow down the range of options prior to contacting suppliers. If an array user discusses a circuit requiring ECL performance with a CMOS or TTL array vendor or a CMOS or TTL performance circuit with ECL vendors, both the prospective array user and the logic array vendors are wasting time.


Since the array concept is new to most of the electronics industry, many users enter the hunt for an array ill-prepared for the detailed discussions that are required. Simply circling a piece of logic on a schematic of an existing design often is not enough. Usually a leftover collection circled on a logic print will end up being a poorly utilized array. For example, the circuit density versus the amount of I/O required or the mixture of required logic speeds often poorly matches the capability of the chosen

array. Instead the gate array user should have the circuit defined well enough to describe the array to the vendor in terms of these characteristics:

- The technology(s) needed.
- The approximate circuit size.
- The level of screening required (i.e., MIL temp. range, burn in).
- The critical performance paths.
- The type of I/O desired (i.e., MOS, TTL, ECL, Mixed).
- The number of I/Os needed.
- The packaging required.

Some vendors require the customer to do a large part of the work in defining the circuit in the vendor's logic or simulation conventions using expensive, dedicated equipment while others will work from customer drawings and provide the talent for circuit conversion and simulation. Users should know their needs and determine the vendor's capability at an early stage.


Also, consider whether the prospective vendor is a viable and reputable supplier. If the prospective vendor is simply a store front which offers designs implemented in another manufacturer's array, do they have the engineering and manufacturing expertise to solve problems should they arise?



Today's measure of a printer's performance goes beyond line speed and purchase price. The true test is print quality and costper-character operating expense. Porelon ink rolls, designed specifically for impact printer ribbon cartridges, will dramatically improve the number of quality

impressions and greatly increase the life of every ribbon.

Better impressions, increased ribbon life. At less cost. That's what you'll get




PORELON
YOUR LAST IMPRESSION IS WHERE WE BEGIN

every time you design a ribbon cartridge featuring Porelon ink rolls.

Find out how simple it is to add this performance feature to your impact printers. For further information, call 615/432-4134, or write: Porelon, Inc., 1480 Gould Drive, Cookeville, Tennessee 38501.

Write 11 on Reader Inquiry Card



Standard Cell Design: An Alternative to Gate Arrays

by Bill Loesch, Director of Marketing and Sales, ZyMOS Corp, Sunnyvale, CA

Gate arrays are pre-processed with fixed patterns of unit-size transistors, characteristics that inherently limit design flexibility and production economy. Consequently, as design complexity increases, die size, and therefore production cost, increase disproportionately because of the increasing percentage of unused silicon area. Moreover, present gate-array designs are restricted to systems not requiring on-chip complexities such as RAM, ROM and special I/O.

A standard-cell design does not use pre-defined mask layers. Instead, this method generates a customized set of masks defining the interconnects between completely characterized building blocks or cells. Each cell is a full-custom circuit handcrafted by the IC maker to minimize silicon area and optimize performance.

Advanced cell libraries comprise a rich variety of functions from which to choose. For example, ZyMOS Corp maintains several cell libraries in support of its ZyP automated design system: Zy4000 silicon-gate CMOS cell library, Zy2000 metal-gate CMOS cell library, and, available in June, an advanced 3μ silicon gate CMOS cell library. Over 350 digital standard cells, ranging in complexity from simple gates to macro functions such as UARTs, DACs, A/D converters, ROM, RAM and core μPs are available in the Zy40000 series library.

In addition, the Zy40000 Series analog standard cell library offers over 70 analog functions, including operational amplifiers, oscillators, switches and switch drivers, comparators and current references. These cells can be combined with digital cells on the same chip.

Thus, standard-cell design provides a higher degree of design flexibility than is possible with gate arrays, including the ultimate flexibility of allowing a designer to specify a new cell to meet performance requirements precisely. Standard-cell design time is somewhat longer than that for gate arrays, and so the direct cost of development is slightly higher. However, this cost differential is mini-




Figure 1: Custom chip designed with standard cell technology from ZyMOS. Developed by Cain Encoder Co., circuit is used in miniature electric-field sensor.

mized by the use of CAD techniques.

Standard-cell design is supported by CAD logic simulation, which predicts system timing and functionality without the need for breadboarding. Automatic place-and-route software ensures continuity between logic design and photomask tooling. CAD software also automatically generates a test program while prototype parts are being fabricated.

State-of-the-art CAD workstations such as the ZyPAWS (ZyP Automated Workstation) from ZyMOS have color graphics capability for performing all phases of the design cycle, including artwork generation. These workstations are supported by original and mature software packages tied to libraries of well-modeled standard cells. Such CAD tools minimize indi-

rect development cost since the user controls the development schedule, and computerized design virtually ensures working prototypes on the first attempt.

From the standpoint of production cost, standard-cell designs cost less than gate arrays. This is because gate arrays may require from 50% to 100% more silicon area for a given design. For very low complexity chips the cost difference is small since packaging and testing costs dominate production costs.

System designers can look forward to a proliferation of comprehensive standard cell libraries as well as the creation of new cells like the Zy-COMP-4 core µP, to greatly improve system design in this decade.

Write 236

Several new arrays were described at the 1983 International Solid State Circuits Conference. A 1.5µ CMOS gate array with 4,268 gates and a 2,304-bit configurable memory was developed by NEC (Kanagawa, Japan). The memory can be configured with regard to word depth and bit width by changing the metalization pattern. Hitachi (Tokyo, Japan) also presented a CMOS array with variable memory. Called "CMOS Building Block VLSIs," the circuits use 2µ technology and two metal and one poly-silicon layer for interconnections. RAM and ROM is composed of several basic cells. Memory size can be varied simply by changing the number and combination of basic cells. A third CMOS array was described by Toshiba's R & D Center (Kawasaki, Japan). Their device is a 20K-gate CMOS gate array, implemented with 2µ design rules. A threelevel metalization technology is used. A 32b × 32b parallel multiplier designed on the gate array offers a multiplying speed of 150ns with a 300mW power dissipation at a 5MHz clock rate. The typical gate delay is 1.5ns for a fanout of 3 and a 3mm interconnect length.

In addition, a 5,000 gate ECL-compatible bipolar array was presented by Nippon Tel & Tel (Tokyo, Japan). With a power dissipation of less than 6W/chip, it has a .5ns loaded gate delay.




Figure 8: SCC CMOS array. Signetics' single level metal arrays are among first with auto route and place support. 98% utilization was attained with auto connection.





Figure 9: Daisy Systems' Gatemaster work station dedicated to gate array design. Station is used for schematic capture, simulation, layout and verification.

Work Stations Bring Array Design Home

Engineering work stations (EWS) dedicated to gate array design are an inevitable addition to semi-custom design. Two EWS are especially useful during the early stages of a design. The first is Daisy Systems' (Sunnyvale, CA) Gatemaster gate array development system. Gatemaster provides engineers with a set of tools for Logic Design (including the conversion of traditional logic to gate array logic), Interactive Logic Simulation, Timing Verification, Test Vector Generation, Placement and Routing and output to manufacturer's formats. By automating each design step and by tying all of the steps together through a single data base, Gatemaster reduces gate array design to a graphics-aided software process. Gatemaster is based on the company's Logician engineering work station and has a 19", high-resolution color monitor. The Multibus architecture supports 8 different processors, 1.5M of dynamic RAM, a 40M Winchester hard disk for data storage, a 1M floppy disk, and interface electronics for mainframe communications. Options include magnetic tape, bit pad tablet, electrostatic plotter, and high speed networking.

The designer creates logic and schematic drawings at the station. The work station provides programs to aid in conversion from TTL to gate aray logic, syntax checking of the schematic, and local simulation routines to verify the boolean functionality of the design as well as its timing delays. It is especially useful during this upfront state. Once the logic design is created and verified locally, the option exists to translate the data base into any number of different input formats for direct interface to mainframe-based design automation programs.

The physical layout of the array is created interac-






Figure 10: Layout display on Mentor Graphics work station with gate array software from California Automated Design, Inc. CADIPLACE and CADIROUTE automatically place and route. CADIGRAPH is interactive and is used to complete connections and modify routes.

tively. The system will not allow mistakes to be entered once the electrical net list description of the circuit has been defined. This list, generated by the Logician schematic database, contains all component and signal names as well as other parametric information. It is compared in real time with layout entries, and the system will not allow any electrical errors. This feature eliminates the need for external electrical and design rule verification programs.

The Gatemaster can be used to design arrays from several companies. Daisy has acquired the rights to macro cell libraries and processing parameters from National Semiconductor, Motorola, Fairchild, Mitel,

AMCC and Semi Processes.

Mentor Graphics Corp (Portland, OR) announced a package of automatic gate array software for its Idea 1000 Apollo-based engineering work station. The software streamlines gate array logic design and layout. Like Gatemaster it automatically satisfies electrical constraints so that final mask data meets design rules, electrical checks, and logical connectivity.

The software has been made available exclusively for Mentor engineering work stations through a marketing agreement between Mentor Graphics and California Automated Design, Inc. (Santa Clara, CA). Mentor/CADISYS consists of automatic placement



VEW! 68000-based Single Board < Computer Plus REAL TIME Operating System

ANTARES

Our new "Starfield Series" offers you a universe of configuration alternatives for creating advanced processing systems.

Cornerstar of the series is ANTARES—a state-of-the-art system for major development projects. With 1M ECC memory, 40M 8" Winchester, 1/4" streamer tape backup and 16channel intelligent I/O, ANTARES is the optimum solution for getting new applications developed quickly.

Western Regional Office Tom McKee-Western Regional Sales Mgr. 30100 Crown Valley Parkway, Suite 32 Laguna Niguel, CA 92677 (714) 495-2661

ORION

Centerstar is ORION—designed with 474M mass storage, 1/2" streamer tape backup, 1M ECC memory plus floating-point hardware and optional Ethernet. * ORION is your solution for rapidly developing and running scientific applications.

- MC6800 is a trademark of Motorola, Inc.
- Ethernet is a trademark of Xerox
- * UNIX is a trademark of Bell Laboratories, Inc.
 * MULTIBUS is a trademark of Intel Corp.



430 Toyama Drive, Sunnyvale, CA 94086 (408) 744-0721/TELEX: 334417 CABLE: CHIMINGCO

Write 45 on Reader Inquiry Card

Targetstar is LYRA, comprised of 8" 20M Winchester, 8" 1M floppy and 1/2M ECC memory. This sophisticated target-system solution shares aggressive volume pricing with all Cosmos products.

The Starfield Series supports "C," COBOL, FORTRAN, PASCAL and **BASIC** languages

Combine Starfield capabilities with your imagination and our marketoriented policies. We don't promise the moon, but we do promise rightnow options for right-now solutions. Call us today for full details.

Eastern Regional Office

Walt Waldron—Eastern Regional Sales Mgr. 569 River Road

Fair Haven, NJ 07701 (201) 530-7788

SEE WHAT A DIFFERENCE A YEAR MAKES IN ATE TECHNOLOGY

Plan to Attend



Automated Testing for Electronics Manufacturing Conference

John B. Hynes Veteran's Auditorium Boston, MA June 13-16, 1983



The Only Conference Devoted Exclusively to Automated Testing

ATE Change is Rampant – ATE is changing rapidly, and the best place to catch up with it is at the ATE Conference.

Consider robotics. It's gaining ground even more swiftly than most believed possible a year ago. Or take networking between testers and central stations. It's producing more detailed intelligence on yield and fault distribution. And LSI/VLSI testers are becoming more complex — and more costly.

Do you need to know the substance and consequences of these innovations? Then be sure to attend ATE East 83, where the focus of attention is — exclusively — on Automated Testing for Electronics.

A 4-Day Program of Technical Sessions, Courses, and Workshops – You'll attend the most respected Technical Program on automated testing in the field — 6 Technical Sessions where 30 original papers will be presented by their authors . . . 20 Workshops where informal give-and-take learning is the norm . . . A Two-Day Professional Advancement Course and two One-Day Professional Advancement Courses.

New! Commercial Clinics – Sit in on 2-hour evenings lecture demonstrations. They'll be held by manufacturers of ATE equipment to explain their latest application technologies. And they're available *at no extra charge* to everyone enrolled in the Technical Program.

Visit the Exhibit June 14-16 – Circulate through the 3-day Exhibit — showcase of the ATE industry — where 175 vendors will be showing better than 500 pieces of operating equipment, hundreds of them brand-new. It's where you'll see the principles and practices translated into hardware and software reality for your evaluation.

Hear John Young, CEO of Hewlett-Packard – He'll speak on *Retaining* World Leadership in Electronics Manufacturing at the Tuesday, June 14 Keynote Luncheon.



Sponsored by Electronics Test magazine

Two Park Avenue, New York, N.Y. 10016, or phone (212) 340-9780.

A	r E EAST≝//
Autom. Mar	ated Testing for Electronics nufacturing Conference

☐ Please send me the ATE EAST Technical Program Registration application.


☐ I am interested in attending the ATE Exhibit only.

INFORMA	TION REQU	EST FORM
---------	-----------	----------

Name _____Title _____

Address ______City/State/Zip

Return coupon: to Registrar, ATE EAST, Morgan-Grampian Expositions Group,



(CADIPLACE), automatic routing (CADIROUTE), and interactive graphics (CADIGRAPH). Before placement occurs, the input design data is captured and verified. The data design is then supplied from the Mentor data base to the placement and routing programs. Using hierarchical methods, CADIPLACE automatically places function blocks consisting of gates, macros, or clusters.

In contrast to most current CAE/CAD tools, CADI-PLACE does not require fixed block sizes or shapes. The placement software accounts for internal partitioning, critical nets, wire length, pre-assigned elements, and anticipated interconnect paths. CADIROUTE automatically routes the circuit connections, after determining a grid and connection list from technology and design files.

CADIGRAPH can be used to complete residual connections, to modify routes to pre-wire critical nets, or to complete the total wiring interactively. Designed

to handle a wide variety of technologies, CADISYS also operates on IBM, DEC VAX, Data General, and Prime mainframes. Programs are written in Pascal or Fortran to ensure portability. These programs are used by many gate array vendors.

Conclusion

For the gate array boom to continue, gate array technology must continue to improve. To compete with standard cells, gate arrays will have to be designed with expanded capabilities, such as on-chip memory, now seen only in the laboratory. Customers are going to have to assume a greater role in the design process, relieving vendors of much of the hand-holding they now do. For customers to do more design, they will need friendly CAD systems with standardized software. Indications are that these events are starting to take place. If so, the semicustom approach and those involved in it have a rosy future.

COMPANIES IN THE GATE ARRAY INDUSTRY

The following list of suppliers, although not exhaustive, does include most companies selling gate arrays in the U.S. Use the accompanying write numbers and the *Digital Design* inquiry card to obtain further information.

Advanced Micro Devices (AMD) Sunnyvale, CA Write 214

American Microsystems, Inc. (AMI) Santa Clara, CA Write 215

Analog Innovations, Inc. Los Gatos, CA Write 216

Applied Micro Circuits Corporation (AMCC) San Diego, CA Write 217

Array Devices, Inc. San Diego, CA Write 218

Array Technology, Inc. Sunnyvale Road San Jose, CA Write 219 California Devices, Inc. San Jose, CA Write 220

Cherry Semiconductor E. Greenwich, RI Write 221

Custom Integrated Circuits Minneapolis, MN Write 222

Custom MOS Arrays, Inc. Milpitas, CA Write 223

Datel-Intersil Mansfield, MA Write 224

EXAR Integrated Circuits Sunnyvale, CA Write 225

Fairchild Semiconductor Mountain View, CA Write 226

Ferranti Electric Commack, NY Write 227

Fujitsu MicroElectronics Santa Clara, CA Write 228 General Instruments Corporation Hicksville, NY Write 229

GTE Micro Circuits Tempe, AZ Write 230

Harris Semiconductor Melbourne, FL Write 300

Hitachi America, Ltd. San Jose, CA Write 301

Holt, Inc. Irving, CA Write 302

Hughes Aircraft Company Solid State Products Div. Newport Beach, CA Write 303

Integrated Microcircuits, Inc. Hopkins, MN Write 304

Interdesign, Inc. Scotts Valley, CA Write 305

International Microcircuits, Inc. (IMI) Santa Clara, CA Write 306

(continued on following page)

For the decision maker: A new report analyzing gate array technology and markets.

Gate Arrays: Implementing LSI Technology

A REPORT BY

SOURCE III, INC.

HIGHLIGHTS OF THE REPORT

Gate array technology represents a viable approach for "Systems on Silicon" implementation. The 1980's will see the worldwide gate array marketplace pass the \$1 billion mark. There are many issues which the decision maker involved in considering LSI implementation must face.

In a systematic approach, the report provides both a strategic and tactical planning tool for assessing future trends and reaching immediate decisions involving semicustom LSI implementation. The report contains over 100 supporting charts and figures along with fact-filled analysis and data. In addition, more than 50 gate array companies are listed with a comprehensive profile.

To Receive A Report Immediately Send Your Check For \$1250

Contact Us For A Copy Of The Four Page Report Outline.



Electronic Trend Publications

10080 North Wolfe Road, Suite 372 Cupertino, CA 95014 Telephone (408) 996-7401

Gate Arrays

COMPANIES IN THE GATE ARRAY INDUSTRY

(continued from preceding page)

Intersil, Inc. Cupertino, CA Write 307

LSI Logic Corporation Milpitas, CA Write 308

Master Logic Corp. Sunnyvale, CA Write 309

Micro-Circuit Engineering W. Palm Beach, FL Write 310

Mitel Semiconductor Kanata, Ontario, Canada Write 311

Monosil, Inc. Santa Clara, CA Write 312

Motorola Phoenix, AZ Write 313

National Semiconductor Santa Clara, CA Write 314

NEC Electronics USA, Inc. Electron Division Sunnyvale, CA Write 315

Nitron Cupertino, CA Write 316

Plessey Semiconductors Irving, CA Write 317

Precision Monolithics, Inc. Santa Clara, CA Write 318

Raytheon Mountain View, CA Write 319 RCA Somerville, NJ Write 320

Signetics Sunnyvale, CA Write 321

Semi Processes, Inc. San Jose, CA Write 322

Siliconix, Inc. Santa Clara, CA Write 323

Source III San Jose, CA Write 324

STC Microtechnology Louisville, CO Write 325

Supertex, Inc. Sunnyvale, CA Write 326

Synertek, Inc. Santa Clara, CA Write 327

Telmos, Inc. Sunnyvale, CA Write 328

Toshiba America, Inc. Tustin, CA Write 329

Universal Semiconductors, Inc. San Jose, CA Write 330

UTC Microelectronics (Mostek) Carrollton, TX Write 331

Western Digital Newport Beach, CA Write 332

Black and white facts about color graphics.

Fact 1.

Software development is expensive.

Raster Technologies' Model One graphics systems feature software tools that speed application development. Like an integrated local debugger. Command stream translator. Local command execution. A complete HELP facility. And truly easy to use macro programming. These unmatched software tools save you time and money.

Fact 4.

Graphics applications demand flexibility.

The Model One family from Raster Technologies offers maximum flexibility at the lowest cost. Because it lets the user select the combinations of display resolution, color and refresh rates that are right for that particular application. Factors that are different for every application.

Fact 2.

Software redevelopment is even more expensive.

With Raster Technologies' fully compatible Model One family, you can take advantage of the latest hardware without any software rewrites. This means an easy upgrade to a more powerful product while still using the same graphic commands, program development tools and host library. So the application developed for the best hardware today can run on the best hardware tomorrow. Without modification.

Fact 5.

Graphics technology is moving fast.

Raster Technologies is dedicated to one business: graphics. All our development efforts focus on advancing graphics technologies. With the latest microcircuitry. The newest and fastest microprocessors. The most advanced display list architectures. And the most innovative pipelined multiple processor designs. All to advance graphics capabilities compatibly. And keep today's customers with us tomorrow.

Fact 3.


Performance is a lot more than good specs.

Graphics performance goes beyond pixel and vector timing specs. It is the ability to display a complex picture without having to wait. Provide instantaneous interaction between an application program and its user. And efficiently communicate with a host computer. The kind of total graphics performance you should measure before you buy.

Fact 6.

You should benchmark the Model One.

The Model One/25 features vivid full color imaging performance with 512×512 resolution. The Model One/40 features ultra high 1024×1024 resolution. The Model One/60 features 100% flicker-free 60 Hz non-interlaced display with 768 x 576 resolution. All support our Advanced Graphics Application Development Firmware and powerful display list package. Put the Model One family to the test.




Raster

The benchmark of computer graphics.

9 Executive Park Drive North Billerica, Massachusetts 01862 (617) 667-8900 TWX: 710-347-0202

Write 47 on Reader Inquiry Card



Why settle for a plodding plotter when you can double your throughput with an all-new Model 945 or Model 965 beltbed plotter from CalComp for approximately the same price?

Productivity gains can range from 25% to more than 500%. It's like having up to two plotters for the price of one.

What's the difference? The basic philosophy behind each plotter design. Their plotters trade off speed for one-time economies of smaller size, lighter weight, less powerful components. *You* pay the price in plotting time with each pen and paper movement (their 24-ips maximum vs. CalComp's 42-ips) and each excursion of the single-pen carriage to a side-mounted carousel.

CalComp's Model 945 and Model 965 plotters, by comparison, allow you to map up to 16 logical pens to four physical pens continuously poised over the plot surface—ready to be activated

CalComp Model 945 beltbed plotter (left) for sheets up to ANSI size D (or ISO size AI), and Model 965 plotter for drawings up to sheet size E (or size A0).





in a fraction of a second. If more than four pens are needed, the plotter performs an automatic stop and prompts the operator to change pens.

Plus the user-friendly control panel provides local control and plot manipulation with easily understood English language messages.

The same interactive firmware gives the operator complete control over plot parameters. Training time is all but eliminated.

Your CalComp Model 945 or Model 965 plotter starts delivering high-speed plots the day it is installed, without changing a line of industry-standard software. Industry-standard because it was developed by CalComp-world leader in

So write or phone today for your

computer graphics and CAD/CAM. illustrated copy of "The Plotter and the 714-821-2011 TWX: 910-951-1154

Computer Products, Inc., 2411 West La

Palma Avenue, Anaheim, CA 92801.

Plodder." Compare

the performance

specifications. Then

into the fast track of

plotter technologywith CalComp. California

make your own move



Write 48 on Reader Inquiry Card

Floppy Emulation, Data Recording For Harsh Environments

by Gavin McClintock

Today's bubble memory is non-volatile and reliable storage for use in a variety of "difficult" environments. While many portable electronic equipment manufacturers are incorporating this technology into some of their component and board level products, one Canadian company, Targa, has built a family of ruggedized data recording systems employing Intel's 1 Mbit bubble device in a removable cartridge format.

Using Intel's newest bubble devices, these floppy disk emulators and data recorders provide highly reliable mass memory under extreme conditions.

Targa offers three products: a data recorder; floppy disk emulators (fixed or removable); and OEM Cartridge Holder Interfaces. The removable cartridge used for all three systems is about the size of an 8-track stereo cassette, and contains one or two Intel devices (2 Mbits) and interface electronics.

The DR3101 data recorder connects to a host system through either its RS232C or IEEE 488 port.

Gavin McClintock is President of Targa Electronics Systems, Inc., P.O. Box 8485, 3101 B Hawthorne Rd., Ottawa, Canada K1G 3H9.



Figure 1: The Targa removable cartridge uses Intel bubble devices.

In the RS232C mode, the unit acts as a "tape recorder" with fast data access speed (48 msec average) and can receive or transmit data at up to 38,400 bits/sec. In the IEEE 488 operation, the unit emulates a disk drive. The data recorder's software allows communication to it as to an HP82902 or DEC TU-58.

The bubble memory floppy disk emulators are package, protocol and electrically plug-compatible with most 5-1/4" and 8" floppy disk units. By replacing the mechanical drive with this floppy drive, the unit operates transparently to the host system. A fixed media version is also available.

The Cartridge Holder Interface (CH2100), is a hardware component consisting of a metal holder with cartridge release mechanism and associated PCB to support the connector and host system interface. Used in place of a built-in disk drive or tape unit, the CH2100 provides a serial or parallel port to the internal µcontroller board.

Reliable Media

These bubble memory devices evolved in an effort to build a more

rugged and reliable data recording system for use on small boats for the Canadian government. After an investigation of all storage media applicable for harsh environment usage, bubble memories proved to be the most error-free and reliable data storage media available. The 1 Mbit Intel Magnetics 7110 bubble device used at 70°C has the following failure rates per Mbit compared to alternatives:

7110 Bubble Memory
Dynamic
RAM
EPROM
0.8% per 1
kHour
4.0% per 1
kHour

The Intel device has an MTBF of 30 years of continuous operation at maximum temperature ranges. This compares favorably to all rotating media (disks and tapes), which require routine maintenance and usually need servicing about every 6 months. It is also virtually errorfree, with an estimated error rate of 1 to 10^{-16} .

Operating temperatures range from 0°C to 55°C, with non-volatile

	Bubble Memory Systems	Tape Recorders	Floppy Disks	Ruggedized Tape or Disk	CMOS EPROM
Storage Media	Solid State	Magnetic Plastic Tape	Magnetic Plastic Disk	Magnetic Plastic	Solid State
Access	Fast	Slow	Medium	Medium	Very Fast
On-Going Maintenance	Virtually Non- Existent	About every 6 months	About every 6 months	About every 6 months	Little Maintenance Required
Ruggedness	High Level	Low Level	Low Level	Medium- High Level	Medium Level
Mechanical Failure Prone	No	Yes	Yes	Yes	No
Reliability-Failure* rates per megabit at 70°C (per 1khour)	0.8%	>4.0	·4.0	—Unknown	Dynamic RAM 1.1% EPROM 4.0%
Initial System Cost	High	Low	Low	High	High
Integrated Package Cost of Ownership	Med	High	High	High	High
Harsh Environment Suitability	High	Low	Low	Med-High	Med-High
Non-Volatility	Yes	Yes	Yes	Yes	Limited by Battery
Removable Media	Yes	Yes	Yes	Yes	No
Power	Low	Med-High	Med-High	High	Low
Security of Data on Media	System Needed		— Universally Repro	oducible —	Media not Removable
Electrical Susceptibility	Low	Med-High	Med-High	Med	Med-High

Table 1: Characteristics of bubble memory compared with other data storage media.

storage from -40° C to $+100^{\circ}$ C. The media can also withstand operating vibrations of 20G and non-operating shock of 200G.

Thus, compared to alternative solid state memories, bubbles have lower failure rate per Mbit and are infinitely non-volatile. Bubbles have equivalent or better error rates compared to other magnetic media, and are highly durable and reliable in harsh environments while offering few maintenance problems, hence low cost of ownership.

Intel's Bubble

About the size of a matchbook, Intel's 7110 bubble memory device is a magnetic, non-volatile, solid state device capable of operating under a variety of environments. This component consists of a garnet substrate surrounded by two layers of copper coils overlapped at right angles to each other, all sandwiched between two magnets and surrounded by a metal shield. Patterns are deposited on the substrate material similar to those in semicon-

ductor memory chips; the user controls the creation, destruction and location of bubbles within the device. The existence or non-existence of bubbles equate to the "ones and zeros" of the binary form of data encoding.

As data is "recorded" onto the substrate by the "write" lead, it shifts along the chevrons towards preferred regions of magnetism on "strings." The "read" conductor can retrieve the data as the string rotates within the memory devices and "duplicate" that data for trans-

mission to the requesting host equipment for processing or display. Each device contains 1,048,576 bits of usable data storage in a binary organization consisting of 512 bits per page over the 2048 pages. The device operates in serial-parallel-serial mode, with each of its 256 data loops containing up to 4096 bits per loop. Separate read and write tracks are implemented.

Design Considerations

The original data recorder was a heavier, more power-consuming piece of marine equipment with the bubble memory built-in. The prototype worked fine, but the client wanted a new design, to be smaller, lighter in weight and 19" rack mountable, with reduced power consumption and media removability. The reworking also included a standard interchangeable cartridge (2 capacities, 2 operating temperature ranges), more software, a visual LCD for operational data, and choice of virtually any power supply. The new version, DR3101, was successfully field tested in the late summer of 1982 and production commenced in November 1982.

Designing the bubble into a cartridge had definite advantages for harsh/mobile environments. Standard plug-in boards with edge connectors cannot stand up to the same physical abuse as can the cartridge's rugged connector and metal casing. The connector alone is warranted by the manufacturer for 20,000 insertion/removal cycles. Also, fixed PCBs are, by definition, less portable. It's easier to bring a cartridge back for processing than a heavy piece of field gear.

Another design criterion was to provide for future technological changes at the lowest possible cost and inconvenience to the customer. As things change, only what is *inside* the cartridge changes, *not* the interface hardware customers have already purchased. For example, once new 4 Mbit devices are available later this year, a 256 kByte cartridge user can return a cartridge to Targa for upgrade to a 1 Mbyte device. All interfacing and



Figure 2: The data recorder, floppy emulator, and cartridge holder all use the same removable cartridge.

system software remain the same. This also holds true for future advances in solid-state memory technologies.

The designers also realized that not everyone working in these rough applications needs a fully-equipped peripheral device. Thus a family of less expensive systems which could utilize the same cartridges was designed, namely the floppy disk emulators and cartridge holder interfaces.

Harsh Environments

These products are geared to the high reliability demands of users operating in mobile and harsh environments. Applications include airborne, truck and ship recording and program load functions, as well as replacements for less reliable media for use in factories, chemical and laboratory situations.

The original proponents of the DR3101, the Canadian Federal Government's Canada Centre for Inland Waters (CCIW) use the device for hydrographic recording on the Great Lakes. The CCIW uses the system on board small 26 foot launches travelling at high speeds

to record lake bottom profiling and other data. Recently, other systems have been sold to private sector clients for similar marine applications and to customers who record data from a magnetometer in an airborne situation.

Although the system has yet to be MIL tested, the military has expressed a great deal of interest for a variety of applications. One μC manufacturer has incorporated the OEM Cartridge Holder Interface into its military μC . The aerospace community is interested in the system as an on-board systems monitoring recorder for preventive maintenance applications. Program load and quality assurances uses have also been suggested.

Other Applications

Other harsh enviroment applications include factory Q.A., data acquisition and control, environmental monitoring, geophysical and seismic recording, robotics, and navigational buoys. Future developments will probably include increased memory capacity, broader operating specs, and user-oriented adaptation of new technology.

techtion's

DILOG makes disk controllers.. because DEC*does not live by tape alone



You know DILOG for superior tape drive controllers. What you may *not* know is how great our *disk* controllers are too.

DILOG offers you unmatched quality, ease of installation and economical operation for DEC emulating disk controllers. They'll interface with your favorites too—over 50 disk drive manufacturers in all.

And when you install DILOG, you'll be investing in your computer's future. Because DILOG controller boards include Universal Formatting.™ All drive

*DEC is a registered-trademark of Digital Equipment Corporation



parameters are programmed onto the header in each sector of the drive—instead of into components of the controller itself.

So you can add new drives without having to replace PROMs or reprogram.

Our catalog tells you all about DILOG's extensive line of disk controllers to emulate DEC. Send for it. Then the next time you're wondering how to satisfy your disk drives and your computer at the same time, just give them a good helping of DILOG.

Corporate Headquarters

12800 Garden Grove Blvd., Garden Grove, CA 92643 (714)534-8950, Telex: 681 399 DILOG GGVE, FAX: (714)534-3662

Eastern Regional Sales Office

64-A White Street, Red Bank, New Jersey 07001 (201) 530-0044

European Sales/Service Office

12 Temple Street, Aylesbury, Buckinghamshire, England 44-296-34319 Telex: 837 038 DILOGI G, FAX:(296) 25133




Photo courtesy Racal-Milgo

LSI Circuit Design Gives Modems More Capabilities

by Racal-Milgo Staff

The field of data communications has expanded tremendously as a result of advancements in LSI circuit design and its partnership with μP development. One of the product areas most affected is modem development. New offerings show an ever-increasing variety of modem products ranging from integral to stand-alone devices. Common to each of these products are enhanced features and options, making them suitable for many specialized applications.

A total network environment, where each component supports and complements the other—the modem meeting the needs of all network components—is the objective of the 'system approach' to modem design. Other primary design considerations include ease of operation and maintenance, product life, and cost.

The first modem in the Omnimode series served as a model for the design and development of the firmware-based line. This 4800 bit/sec. modem operates over 3002 type of M1040 (international) lines without special line conditioning and supports switched/constant car-

rier and dedicated/dial backup operations. It can be configured for compatibility with earlier 4800 bit/sec. Racal-Milgo modems, such as the MPS 48 (CCITT V.27) or MPS 4827 (CCITT V.27 bis). Additional proprietary training sequences and lengths can be selected for specialized applications.

LSI circuit design,
modular
construction and
firmware-controlled
functions simplify
upgrading and
integration of
options.

Two major options are available: intelligent multiport (two or four port versions), and remote modem control (RMC) options. LSI circuit design, modular construction and firmware-controlled functions simplify upgrading and integration of options while supporting reduced maintenance, improved reliability

and easier fault diagnosis. Each major function and its associated features is built on a single PC board. These functions—the main modem, intelligent multiport option and remote modem control option—are interconnected by a high speed common data bus managed by the option control processor. The block diagram in **Figure 1** represents the signal management and option integration of the design.

Each block in Figure 1 signifies a modem function and its activity in the overall functional operation. The analog circuits and converters control the analog/digital and digital/analog conversions in conjunction with the transmit and receive line levels and receive sensitivity and filtering. The LSI circuit design used for the signal processor element can simultaneously perform two real-time functions, i.e. the complete modulation/demodulation processes for both transmit and receive. The control processor and option control processor also belong to the main modem function.

The control processor provides the signal processor with sequencing information for training elements in response to the interface signals. All communication between the main modem, multiport option, RMC option and modem front panel is managed by the op-

Racal-Milgo, 8600 N.W. 41st Street, Miami, FL 33166.

tion control processor (OCP). The OCP governs all modem operating parameters, such as data rate, soft-strap (software strapping) program and option configurations.

The OCP integrates the functions of the multiport and RMC options with the main modem functions via the common data bus managed by the OCP. The multiport option, fully contained on its own PC board, provides time-division multiplexing for two or four port rate combination (depending on option selection) totalling the aggregate channel rate. The RMC board contains the test and control processor which generates and interprets all commands to and from the network controller or a controlling front panel, depending on how the RMC option is selected to function. The RMC option also provides direct access to the analog circuits and converters for secondary channel operations.

The combination of firmware-based functions form the frame-work for the design of the modem. Data rate selection monitoring, testing and soft-strapping to select modem operating are all activated from the front panel. An eight-digit display screen acts as the interface between the operator and the modem, providing all information in an easy to interpret manner.

The soft-strapping feature eliminates traditional hardware strapping and its restrictions, allowing the operator to reconfigure the mo-



The backplane assembly of a Racal-Milgo modem.

dem operating parameters from the front panel for special network requirements. For many end users this eliminates the field service calls generally required to make adjustments of modem operating parameters.

The first step in designing the product for future flexibility was selecting the ICs to comprise the signal processing element. A custom chip set was chosen, since a bipolar bit slice approach would have been too power-consumptive and area-intensive. This led to the development of the custom signal processor with a primary constraint of providing external memory and rewrite memory. With these provisions met, the same custom chip set can be used for a wide variety of products and a large selection of

modulators/demodulators within a single architecture, as well as providing reliability and improved thermal performance.

The logic of the custom signal processor is partitioned into a memory control unit (MCU), arithmetic logic unit (ALU) and interface analog/digital chip (IAD). The ALU and MCU are organized into a two-bus architecture with an address bus and data bus. Both instructions and data are formatted into 16-bit words. Instructions are further organized into operand/operation fields, so that for each operation there is a fetch rule for locating the associated operand.

Figure 2 represents the signal processing flow as implemented with the custom chip set. The IAD (Interface Analog and Digital) chip provides the interface between the transmitter digital/analog circuits, the receiver digital/analog circuits, the MCU (memory control unit) and a standard μP . It also generates the transmitter and receiver bit rate and baud rate clocks. Its primary responsibilities are determining the location of the next instruction and data word and providing the control for intermixing and pipelining the data fetches and instruction fetches. The IAD also interfaces with the control processor via the μP memory of the IAD chip. The data is then shifted to the MCU via the serial output port.

The MCU provides buffering on the serial port from the IAD. It also generates the memory location (address) of the next command to




Figure 1: Overview of signal paths and function management in Omnimode.




Figure 2: Simplified block diagram of Signal Processing Flow by Omnimode Custom Chip Set.

be executed or the next data which can be used by the MCU and ALU chips. The timing control signals for the ALU chip are also generated via the MCU. Decisions such as jumps and go to subroutines as well as performance of loops are accomplished by the MCU. The loop controller, located in the MCU, allows inner loops of routines to be performed without software overhead.

The third chip of the custom set is the ALU, which performs all arithmetic and logic functions on the data. It is organized with dual accumulators, which facilitates complex arithmetic operations. The ALU also provides input stacks on both the instructions and the data; this allows the elasticity for both to be efficiently pipelined.

An Option Control Processor provides the pivot for the system design architecture. All options interact via the common data bus through the OCP. The design is based on a master/slave approach. This approach was particularly viable since an OCP was already required for management of the front panel and non-volatile memory.

Each major option as managed by the option control processor includes a group of specialized features to support its operation. The multiport option, available in two port or four port configurations, includes the Control Signal Simulation feature and Dynamode. The CSS feature has two aspects: Request to Send—Data Carrier Detect Signal Simulation, and Switched Network Remoting adapter. RTS-DCD simulation imitates controlled line carrier when required by the DTE. The switched Network Remoting Adapter allows a remote modem to be switched into the public network. Dynamode provides automatic internal adjustment of active ports and their assigned rates by the Omnimode to achieve maximum data throughput.

The RMC option is a major advancement in the control offered by modem products. It establishes complete front panel control from a central point over remote Omnimode modems. This option may be exercised in two ways: without an external controller (from the front panel of a controlling modem), or with an external network controller such as the Racal-Milgo CMS controller. With the inclusion of this option, all monitoring, testing and selection of modem operating parameters for remote units is managed from a central control point.

From the product's earliest stages,


manufacturing took an active part in its development while design engineering kept in mind the production cost. One of the first design features that reduced manufacturing costs was the use of a standard size case for the entire series as well as for other products. The standard size circuit boards used in the series also eliminate much of the retooling generally involved in the manufacturing process. The PC boards of the Omnimode design were 98% auto-inserted, which reduced manufacturing time more than 300%. Three different pieces of manufacturing equipment, a Dual-In-Line Package (DIP) Inserter, a Variable Center Distance (VCD) Axial Lead Inserter and a Pin Machine were used to perform the auto-insertion. This computercontrolled equipment inserts integrated circuits, diodes, capacitors, resistors, and pins.

With the modular design of the product, the reduction of interconnects required between the option boards was a consideration of vital importance. A decision for ribbon interconnect resulted in significant cost savings by eliminating much of the chassis hardware.

The touch-pad assembly of the front panel offers multiple manufacturing advantages. There was a significant reduction in manufacturing labor costs, since there was little of the standard mechanical assembly usually required for indicators and switches.

Both engineering and manufacturing departments also worked to develop a system of automated product testing. Not only do the testing procedures reduce manufacturing costs (reducing man-hours spent testing by more than onehalf), they also streamline testing for field service representatives. The aim of continuous testing throughout the manufacturing process, from initial incoming chips to final test, was to provide a product of high reliability. With the increasing demands on today's data communications networks, the need for flexibility and reliability can only be met with continued advancements in LSI design and efficient implementation of those designs.

Incubation Complete



neration

(Pictured above)

A Z80 based microcomputer board with memory and I/O functions

· Fully complies with IEEE 696 Standard

 4/6/8 MHz Z80 A/B/H Supports CP/M® Plus

Operates as bus master/slave for multi-user, multi-processor architecture.

64K on board memory, dual ported, parity checked
2 serial ports, 1 full SASI port

All I/O drivers on board

Memory management

Full 24 bit address capability

3-16 bit CTC's



Expandor AM IV—Random access memory board utilizing 64K or 256K NMOS RAM chips

Fully complies with IEEE 696 Standard

256K capacity with 64K chips

1024K capacity with 256K chips

Error checking and correction (2 bit detection, 1 bit correction)

On board refresh

Supports both 8 and 16 bit data transfers

24 bit addressing



SD300—A new series of compact yet expandable S-100 microcomputers.

Compact size approximately 4" × 14" × 17"

6 Slot motherboard

Rugged metal enclosure

Supports up to 5 users

OEM Version: Designed for ease of integration and maximum flexibility

• Z80 CPU

256K RAM

Versafloppy II with free CP/M Plus™

Discless Version: An ideal high performance system for disk intensive applications. Eliminates disk wait states for spread sheets, spelling checkers, and network operation. Utilizes SDSystems RAMDisc and ROMDisc modules.

FW-3: A single board controller for floppy and Winchester disk drives

• Fully complies with IEEE 696 Standard • Free copy of CP/M PlusTM included • Up to 4 floppies and three Winchester drives may be controlled by VFW-3 • Data transfers to and from board under DMA or programmed I/O control • Supports 24 bit address space.

CP/M Plus™:high performance single user operating system.

• CP/M® 2.2. compatible—no modification! • When • CP/M® 2.2. compatible—no modification! • When used with SDSystems 256K memory board speeds are up to 7 times faster than CP/M® 2.2. • High performance file system • MP/M® II file password protection • Time and date stamps on files • Support for 1 to 16 banks of RAM • Support for 1 to 16 drives of up to 512 MB each • Easy to use system utilities with HELP facility • Powerful batch facility • Sophisticated programmer utilities

RAM DISC 256: A solid state disk emulator that greatly increases system performance by eliminating disk waits in disk intensive applications. Excellent for spreadsheets, spelling checkers and software development.

• 256K capacity • 1 mb total bus capacity • CP/M® 2.2, PLUS TM compatible • I/O port addresses user selectable • Storage locations addressed by on board 20 bit counter • On board refresh.


DISC 128: An EPROM board that replaces a floppy disk drive for the purposes of booting CP/M® and loading application programs.

 Provides non volatile, permanent storage of programs and data • Utilizes 2732 or 2764 EPROMS, (16 max) • 128K capacity per board • 512K system capacity Use with SDSystems RAMDisc to configure a stand alone or network discless system • CP/M Plus™ available in eproms • Serial port provided

CP/M® 2.2 and CP/M PlusTM are registered trademarkes of Digital Research, Inc. *Z80 product of Zilog Corp

A Syntech Company

10111 Miller Road • Dallas, Texas • (214) 340-0303 • TLX-682 9016



Digital Scene Simulation by Digital Productions, Los Angeles, CA. Copyright 1983. All rights reserved.

by Edward W. Kozdrowicki

In 1974, a study on the first generation of supercomputers had two models and a total of eleven installations to consider. These first large-scale computers to concentrate on efficient pipeline array processing and take advantage of the parallelism available when processing vectors, or numerical arrays, in scientific work were Control Data Corporation's Star-100 (String Array processor) and Texas Instruments' ASC (Advanced Scientific Computer). Four Star-100s and seven ASC systems had been installed before the first generation of supercomputers gave way to the second.

Ed Kozdrowicki is a Member of the Technical Staff of the Computer Architecture Department at the Mission Information Systems Division of The Aerospace Corporation, 2350 East El Segundo Blvd., El Segundo, CA 90009.

Supercomputers of today are still basically uniprocessors; in the 1990s, they may involve as many as 16,000 processors operating in parallel on a problem.

The Cray Computer

The second generation of vector supercomputers began in 1975 when Cray Research, Inc. announced the Cray-1. It was widely billed as the world's biggest computer, but there was initial skepticism. Little software was available at first and it required a large mainframe such as a Univac 1108 or IBM 3033 as a front-end computer.

In 1977, Auerbach Publishers suggested that the Cray computer would be limited initially to a small circle of scientific users in nuclear research, seismic analysis and weather modeling. Now, models for

aerodynamics, computer-assisted tomography, human organ modeling, fusion power and such exotic ideas as artificial intelligence experimentation have been prepared for execution on supercomputers.

Since the first installation in 1976, the Cray-1 has demonstrated reliability, high-speed secondary storage and interfacing to many front-end computers; extensive software support has also become available. As of September 1980, there were 20 Cray-1 machines at user facilities, and there are now over 50 installations. The original Cray-1 has been updated to the

Supercomputers

Cray-1S and to the Cray X-MP/22, a dual CPU system announced in April, 1982.

The most obvious architectural improvement of second-generation supercomputers over first is the inclusion of a scalar processor for nonvector operations. These second generation machines do well for scalar operation benchmarks. In fact, the Cray-1 was the world's fastest scalar computer throughout the 1970s, with a basic cycle time of 12.5 ns. This is a distinction it will hold for some time before newer versions of supercomputers become established in the 1980s. The Cray-1's closest competitor for the 1970s was the CDC 7600 or the Cyber 176, with a 27.5 ns cycle time.

The Cray-1 was a new architecture developed by Seymour Cray when he started his own company. Since Cray was the principal architect of the CDC 6600 and CDC 7600, the Cray-1 has evolutionary similarities to those designs. Cray-1 extends the pipeline concepts of those CDC architectures and adds vector processing. Figure 1 is a block diagram of the Cray-1S. The fully integrated, segmented functional units needed for scalar and vector processing at the 12.5 ns clock rate are accomplished with 225 operation codes. These codes are either 16-bit or 32-bit instructions.

The CPU has 13 functional units which can chain operation codes. By chaining, the results are available for another unit in the next clock period. A large number of internal CPU registers store the intermediate results of the units as they operate in parallel.

The Cray-1 can be used standalone, but use of a front-end IBM 370, CDC Cyber or Univac 1100 is recommended. A channel adaptor is required between the front-end computer channel and the Cray main memory. The main memory is 4K ECL Fairchild or Motorola chips and can hold up to 4M 64-bit words.

The I/O subsystem is two, three or four Cray-designed 16-bit minicomputer processor stations. These processors have a 50 ns cycle time (bipolar memory) and up to 64K 16-bit word capacity. There is a

Complex color graphics are a chief application for supercomputers (photo courtesy Air Force Weapons Lab, Kirtland AFB, New Mexico, 87117).

large buffer memory between the I/O subsystem and the main memory ports of the Cray-1; each port has up to 850 Mbits/sec. bandwidth.

The device control unit uses one of 12 bidirectional standard 50 Mbits/sec. channels for CDC 819 disk memory. Using eight controllers, a large Cray-1 system can handle up to 32 double-density, 600 Mbyte capacity 819 on-line disks.


The Cyber 205


A fierce competitor to the Cray supercomputer is the highly successful Control Data Corporation Cyber 205. In 1976, the Cyber 203 was introduced; only one was delivered. The Cyber 205, a significantly improved version of the Cyber 203, was announced in 1980. It is an all-LSI version of the 203 that also uses newer technology to upgrade CDC's Star-100 architecture. To date, Control Data has 14 of its Cyber Series 200 computer systems installed.

The University of Manchester in the United Kingdom has ordered a Cyber 205 supercomputer, to be installed in April 1983. It will serve some 30 universities, polytechnics and research institutions. This is the second leading European university to install a Cyber 205; one was installed at the University of Bochum, Germany, earlier in 1982. It is interesting that these supercomputers are now making their way into universities, since in the 1970s they were only used in advanced research institutions.


Building on the architecture of the 203, the Cyber 205 includes a scalar processor unit that provides instructions that are fully compatible with the vector stream processor unit but independent of parallel operations (**Figure 2**).


All instructions from central memory are received and decoded by the scalar processor; decoded vector and string instructions are sent to their respective processors for execution. The scalar processor also provides buffering and execution of load and store instructions.


















Figure 1: The Cray-1 extends CDC's early pipeline concepts.




Figure 2: CDC's Cyber 205 utilizes a scalar processor unit.


The scalar processor instruction stack accommodates eight virtually addressed (64-bit) words, which consist of 64 64-bit instructions, 128 32-bit instructions or a combination of both. The instruction issue pipe can issue one instruction every 20 ns. With independent vector and scalar instruction controls operating on a single stream, the scalar processor can execute scalar instructions in parallel with most vector instructions if there are no memory references generated by the scalar instruction. The scalar processor has five pipelined floating-point functional units capable of accepting operands every 20 ns.

The vector processor contains two floating-point pipeline arithmetic units. The stream unit manages the data streams between central memory and the vector pipelines. Pipelined arithmetic units provide vector addition, subtraction, multiplication, division or square root with one 64-bit or two 32-bit results. The 205 system has two pipelines with 20 ns clocking per 64-bit result without chaining or linking, and an option of two additional pipes. The string unit processes the control vectors during streaming operations.

The Cyber 205 has 16 16-bit input/output channels. The I/O sys-

	MPP	Cyber 205	Cray 1
Instruction Word Lengths	32-bits, 64-bits	32-bits, 64-bits	16-bits, 32-bits
Clock Period	100 ns	20 ns	12.5 ns
Programmable Addressable Registers	(5) 16,384-bits (1) 491,520-bits	(256) 64-bits	(72) 24-bits (584) 64-bits
Instruction Stack	16 vector calls	64 words	64 words
Hardware Look-ahead/Overlap	Vector/Scalar/IO overlap	16-32 instructions	256 instructions
Functional (e.g.)	1 unit (16,384 bit-serial PEs)	14 (6 vector: 2 FL PT, 1 String; 5 Scalar: ADD/SUB, MULT, LOG, SHIFT, DIV/SQ)	13
Pipeline Segments	none	Up to 26	Up to 14 segments with a result every clock
Maximum Vector Results Rate	2500/16,384 = .153 ns (8-bit addition)	20/2 = 10 ns (2 pipes)	12.5 ns

Table 1: Comparison of CPU organizations.



Smart Graphics™ GX-100

The Modgraph **GX-100** is the first low cost graphics terminal to offer multi-page high resolution graphics and alphanumerics. Designed to be compatible with Plot-10® (4010/4014) and DEC's VT-100 and VT-52. We call it **Smart Graphics™** and with good reason — powerful graphics, multipage alphanumerics and more.

GRAPHICS

As a graphics tool the **GX-100** is the smart choice; TWO pages of 768 x 585 viewable resolution on a 15" screen. Information from one graphics screen can be added and subtracted to the other with the

push of a key. Circle, Rectangle, Vectors, Points, Patterns, Complex Area Fill and of course Plot-10® (4010/4014) compatibility.

ALPHANUMERICS

The independent alphanumeric plane allows alphanumeric overlay without overwriting graphics. Two independent pages store a total of 6 scrollable screens in 80 x 24 format with selectable scrolling methods including window scroll. This and VT-100, VT-52 compatibility, all designed to help you work smarter not harder.

 Direct access of microprocessor via host allows downloading of code for stand alone use. Optional Floppy Disc Drive with CP/M O/S.

To fully appreciate the Modgraph **GX-100** you have to see it in action. Drop us a line, or give us a call. We'll arrange for a demonstration and show you how powerful graphics can be yours with **Smart Graphics**TM

Plot-10 Trademark Tektronix
 VT-100 Trademark Digital Equip. Corp.

Modgraph, Inc., 1393 Main Street, Waltham, MA 02154 (617) 890-5764

Modgraph

Boost Micro's Ego

This Single Board Array Processor Will Have Your Micro Thinking Like a Mainframe

It's fast enough for real-time perform almost any algorithm.

cessor. From Marinco.

It's Multibus* compatible. With other bus versions soon to follow. for 20, 30, 50 MFLOPS or more.

To the host, it simply looks like extra memory.

and settles in a mapped memory that can represent integer, floating point and complex numbers. Yet both program memory and data talk to. Especially in FORTRAN. memory are always accessible to the host

analysis. Small enough to fit in a tions in 100 nsecs. Which adds up single slot. And flexible enough to to 10 million floating point operations per second. For instance, a That's the APB-3000 array pro- 1024 point complex FFT is processed in 4.1 msecs. Start to finish. And extra boards can be linked

Standard routines include FFTs, power spectral density, cor-Data flows through dual ports relation, digital filtering and deconvolution.

Or create your own.

Order the board with standard ROM. Or with RAM for develop- count.


The APB-3000 executes instruc- ment. If you wish, Marinco will back you up with extensive engineering and software support.

> While the board may inflate your micro's ego, it won't inflate your budget. The cost: \$4250. Complete. And quantity discounts are available.

So call us today.

But remember. When your micro suddenly begins acting like It's simple. The board is easy to a mainframe, don't worry. A strong ego is healthy.

And besides-it's results that



Write 52 on Reader Inquiry Card



11760 Sorrento Valley Road. San Diego, CA 92121 (619) 453-5203

Telex 69-7901



Figure 3: Cray-2 Technology involves the immersion of the computer in a clear, inert fluorocarbon liquid to provide cooling for the system.

tem consists of 16-bit word minicomputers; up to 10 disk stations can be put on the 205. Each station can accommodate eight disk drives; the system now uses CDC 819 double-density 600 MByte disks.

Japanese Supercomputers

In Japan, Hitachi Ltd. has announced the "S-810/10 and S-810/20 Array Processor Systems," new supercomputers that will be marketed only in Japan for the next four years. They claim that the S-810/10 has an execution rate of 315 million floating operations per sec-




Figure 4: Goodyear Aerospace's MPP comprises four hardware components.

ond (Mflops), while the S-810/20 model executes 630 Mflops and has up to 32 channels rated at 96 Mbytes/sec. Their main storage capacity is 128 Mbytes.

Fujitsu Ltd., also in Japan, has unveiled their intention to produce two new supercomputer models, the "Vector Processor 200" and the "Vector Processor 100," with shipments in Japan to begin in the fall of 1983. According to the company, the VP-200 is available with 64 Mbytes of main memory, upgradable to 256 Mbytes. It has a maximum of 32 channels with a speed of 48 Mbytes/sec. They have also claimed that the processing rate (in Mflops) will outperform both the Cray and Cyber machines. Appar-

ently Nippon Electric Corp. of Japan also plans to introduce a supercomputer in the near future.

The Cray-2

Seymour Cray's ingenuity and dedication was demonstrated again on November 19, 1981, with the announcement of technology that will allow development of the Cray-2 computer system. The Cray-2 is predicted to be six to 12 times faster than the Cray-1. It will have a 32 million word memory and a CPU cycle time of 4 ns, as compared to the Cray-1's four million word memory and 12.5 ns cycle. It will be a 4-processor multiprocessing system.

The technological breakthrough involved immersing the computer in a bath of clear, inert fluorocarbon cooling liquid (**Figure 3**). The liquid will be approximately room temperature (72° F) and flow amongst the densely packed circuit elements to cool the unit.

The fluorocarbon liquid is normally quite clear with the consistency of salad oil and becomes turbulent due to heat generation; the turbulence indicates hot spots in the computer and has also been described as "quite beautiful to watch." For these two reasons, the company may enclose the Cray-2 in a clear frame.

The Cray-2 CPU will be onetenth the size of the Cray-1, stand-

	MPP	Cyber 205	Cray-1
8-bit Operands			
Addition	6553×10^{6} /s	<u> </u>	_
Multiplication	$1861 \times 10^{6}/s$		_
Division	$1531 \times 10^6/s$		
32-bit Operands			
Addition	$470 \times 10^{6}/s$	$200 \times 10^{6}/s$	$80 \times 10^{6}/s$
Multiplication	$291 \times 10^{6}/s$	$200 \times 10^{6}/s$	$80 \times 10^{6}/s$
Division	$149 \times 10^{6}/s$	$25 \times 10^{6}/s$	$25 \times 10^{6}/s$
		(square root also)	(reciprocal approx.)
64-bit Operands			
Addition	<u> </u>	$100 \times 10^{6}/s$	$80 \times 10^{6}/s$
Multiplication	_	$100 \times 10^{6}/s$	$80 \times 10^{6}/s$
Division	_	$12.5 \times 10^{6}/s$	$25 \times 10^{6}/s$
		(square root also)	(reciprocal approx.)

Table 2: Computation rates of the various CPUs.

	MPP	Cyber 205	Cray-1
Memory Word Length	Programmable Word Length (e.g., 8, 16, 32, 64 etc. bits)	64 bits (+7 bits SECDED /32 bit Half Word)	64 bits (+8 bits SECDED)
Memory Access Increment (i.e., Effective Data Path Width)	16,384 words (1 bit from each) (plus 2048 parity bits)	512 bits (i.e., Sword = 8 Words)	64 bits
Address Field	16 bits	48 bits	24 bits
Standard Working Hardware (capacity) Configuration	16M bits	1M Words	1M Words
Incremental Hardware Additions	16M bits, 48M bits	½M, 1M, 2M Words	1/4, 1/2, 1M Words
Maximum Hardware Capacity	1 × 10 ⁹ bits	4M Words	4M Words
Maximum Virtual Capacity	Not Used	4×10^{12} Words (2 ⁴² Words) ,	16 × 10 ⁶ Words (2 ²² Words)

Table 3: Central memory organization of the MPP, Cyber 205 and Cray-1.

ing 26 inches high and 38 inches long. The eight layer modules for the Cray-2 will be closely packed in three dimensions, to reduce the lengths of the connecting wires and take advantage of the greater potential speed with shorter interconnects. The longest wire in the Cray-2 will be 16", as compared to 4 ft. in the Cray-1.

The Fifth Generation

MITI and six Japanese mainframers have set 1989 as a target date for the development of a new supercomputer able to perform 10 billion floating point operations per second. In the US, the Defense Advanced Research Projects Agency (DARPA) is seeking congressional approval for a plan to spur development of a new generation of supercomputers.

DARPA Chief Dr. Robert Cooper has said that the aim will be to take developing technologies like artificial intelligence, multiprocessor architectures, gallium arsenide semiconductors and machine-generated software and integrate them into single systems. "The goals are something like the Japanese fifthgeneration computer program, but theirs is meant for commercial applications. Ours is targeted at military applications," he said.

Developers in both the US and Japan believe that architectures combining up to 10,000 individual

processors will have to be developed. The successful supercomputers of today, including the Hitachi S-810/20, Fujitsu VP-200 and the Cray-2 are still basically uniprocessor architectures, even though as many as four CPUs may cooperate on a problem.

Massively Parallel Processor

Under contract to NASA/Goddard Space Flight Center (GSFC), the Goodyear Aerospace Corporation is developing the Massively Parallel Processor (MPP). Delivery was set for April 1983; in June, 1983, a fully operational MPP is to be delivered to the NASA/GSFC for multi-

agency algorithm development. This machine has 16,384 (16K) processors operating in parallel and can perform over six billion 8 bit additions or 1.8 billion multiplies per second. There have been continuing attempts to build machines with parallel processors, but 16,384 processors operating in parallel is certainly the most ever contemplated.

MPP was originally and principally intended for ultra-high speed ground-based processing of two dimensional imagery. However, preliminary studies indicate that it can support such diverse applications as general image processing, weather

	MPP	Cyber 205	Cray-1
Memory Cycle Time	100 ns	80 ns	50 ns
N-way Interleave	None in central memory	32 Banks	16 Banks
Maximum Bandwidth (Words/sec)	2500×10^6 (for 64-bit Words)	400×10^6 (64-bit Words) with 4 MW Capacity	320×10^6 (64-bit Words) (80 \times 10 6 per Ban \times 4 Banks)
Maximum Bandwidth	163.0 × 10 ⁹	25.6 × 10 ⁹	20.48 × 10 ⁹ (4 × 80 MW/s × 64 bit Words)

NOTE: CYBER 205. The memory is bipolar, 80-nanosecond cycle time with 4-word interleave resulting in 20-nanosecond effective cycle times. It has the provision for more memory banks.

Table 4: Characteristics of the central memories.

Parallelism And Mflops

To better understand parallelism, one must consider the definition for computational speed scientific programmers now accept for numerical analysis work: millions of floating point operations per second, or Mflops. Consider the following program segment:

DO I = 1, 1000 Y (I) = A(I)*B(I) + C(I)END DO

Each pass through this DO loop accomplishes two useful floating point operations. Therefore, any computer that could execute this DO loop one thousand times in 1 ms would be computing at a rate of two million floating point operations per second, or 2 Mflops. This measurement refers to accomplished useful operations.

Clearly, more work is done in each pass through this DO loop than one multiplication and one addition. The operands must be fetched from main memory storage and inserted into intermediate registers before they can be fed to the units that perform the floating point operation. The index, labeled I, must be incremented, and some procedure must determine completion of the entire DO loop. About five individual operations must generally take place to complete one useful floating point operation.

In early machines, each of these operations took place individually and in sequence. Later machines, such as the CDC 6600, introduced some simultaneity. Current supercomputers can execute all five operations concurrently and sustain parallel operation for

large percentages of the total time. It is this performance of many operations in parallel that makes the second generation of supercomputers powerful.

Consider the following DO loop for parallel instruction execution:

DO I = 1, 64 Y(I) = A(I)*B(I)END DO

On the Cray-1, this DO loop would be executed and actually produce one answer every 12.5 ns or each clock period. This rate would be sustained from the time the first answer is produced until the 64th answer is produced. For this period of time, the Cray would be computing at a rate of

1000/12.5 ns/answer = 80 Mflops.

For the Cyber 205, the corresponding figure would be 1000/20 ns/answer = 50 Mflops,

although, in some instances, it can operate two pipes to give a 100 Mflop rate.

Note that these are burst rates measured from the time the first answer appears until the 64th answer appears. It takes extra time to set up the operation, and if the length of the DO loop if greater than 64, the entire operation must be grouped in successive segments, since 64 is the maximum vector length on the Cray and the Cyber 205. This procedure does not apply to the MPP. The tables comparing architectures show what each manufacturer did to implement parallel capabilities. They have achieved from tens to over a hundred million floating point operations per second.

simulation/forecasting, aerodynamic simulation/analyses, radar signal processing, reactor diffusion analysis, numerical analysis and matrix processing.

The arithmetic units contain a 128-by-128 array of bit-serial µPs with basic cycle rates of 100 ns and, to support its high computation rate, the MPP has an I/O rate of 320 Mbytes/sec. Two-by-four subarrays of processors are packaged in a custom VLSI HCMOS chip.

The MPP comprises four principal hardware components (**Figure 4**). Its architecture comprises an array unit (ARU) that processes arrays of data; an array control unit (ACU) that controls the operation of the ARU and performs scalar arithmetic; a program and data management unit (PDMU) that controls the flow of data; and a unique staging memory (SM) that buffers and permutes data.

The array unit contains a 128-by-128 array of bit-serial processing elements (PEs). The staging memory is a large multidimensional-access memory that performs a "corner-turning" operation which converts data stored in convention-

al format to the bit plane format required for the 16,384 processing elements.

A fully-implemented main stager would hold 67 Mbytes of data. A

	MPP	Cyber 205	Cray-1
Plug-in Modules	190	1760	1700 (× 2 DIES)
Module/Card Types	22	8	115
PC Cards (Boards)	6-9 Layers	15 Layers (150 chips/BD)	5 Layers
Circuitry (equiv. no. of Transistors)	16M (ARU only) 8000 Transistors/ Chip	10.5M (1420 Transistors/ Chip	2.5M
Chip Types	1 custom chip plus many others	26 (7303 chips total)	4
Logic	ECL	ECL, 6 picojoules 168 gate chips 600 Picoseconds gate delay	ECL, 1 ns per gate delay
High Density Logic	VLSI	LSI-20 ns	SSI

Table 5: Physical hardware/electronics of the various supercomputers.

32-bank main stager can accept and present data at the 160 MByte/sec rate of the Array Unit I/O ports (128 bits every 100 ns). This machine is completely programmable. Both the basic applications programs and the micro-coded routines that drive the processing elements for arithmetic, logic and data manipulation operations are programmable.

The Illiac IV and The BSP

One of the best known attempts at parallel processing is the ill-fated Illiac IV, which was an attempt to make 64 processors operate in parallel. The only Illiac IV ever put into production was at the Ames NASA Research Center at Moffet Field, CA. Its reliability was such that it had difficulty maintaining itself long enough to get to the end of a problem solution. Nonetheless, it worked well enough to be considered a valuable experiment.

Possibly one of the most significant parallel processing experi-

ments ever attempted was the Burroughs Scientific Processor (BSP). The BSP was an advanced array architecture that evolved from Burroughs' significant experience in designing and building the Illiac IV and the PEPE (parallel elements of processing ensemble) machine for the Army's Advanced Ballistic Missile Program.

The BSP, with its 160 ns clock cycle, was to be a more manageable 16-processor system than the 64-processor Illiac IV. The basic arithmetic instruction execution times are 320 ns. (two machine cycles) times 16 arithmetic elements for a maximum rate of 50 Mflops when all 16 processors execute synchronously.

It would be unfair to look at these figures, however, and conclude that the BSP is 25.6 times slower than the Cray. In fact, Burroughs intended to use slower logic, to allow effective use of parallelism.

The BSP was to be direct compe-

tition to the Cray-1 and the Cyber 205. With its 64M word solid state file memory for secondary memory, it would have been one of the first computers to handle programs with data spaces in the tens of millions of words. In 1981, Burroughs had actually taken orders for 1981 deliveries of their machines when they decided to drop its production.

Element Processor

The Heterogenous Element Processor (HEP) developed by Denelcor, Inc. (Denver, CO) is a supercomputer system that can have up to 16 element processors operating in parallel. Each processor can execute one instruction every 100 ns (10 MIPS) and their claim is that 16 units could, therefore, perform at 160 MIPS. It is a 64-bit machine with a maximal system containing 1024 Mbytes of data memory and 8 Mbytes of program memory per processor. At least seven Element Processors were actually installed by the end of 1982.

\$296.25* FOR A COMPLETE PRINTER?



Yes, Hecon's 40 column, dot matrix, AO 543 complete tabletop printer is only \$296.25*! The AO 543 is plug compatible with the Eaton Model 7000+**, uses the full 96 character upper and lower case ASCII set, and has enhanced print, low paper sensor, top of form, and much more as standard features! Current options include time and date, sprocket feed (for use with paper and labels), and 230 VAC/50 Hz input. Write or call for further information.

It's got to be good. It's a Hecon.

HECON

31 Park Road, Tinton Falls, N.J. Phone (201) 542-9200 Zip 07724

**When using Hecon cable

*OEM price for 1000 pieces—suggested list price \$395.00.

DCS High Reliability Multibus Microcomputer Systems for Industry



DCS/86L 16-bit (8086) microcomputer

removable cartridge disk.

(DCS/86 system prices start

at \$6900.00).

DCS

Distributed Computer Systems is a manufacturer of high reliability, rugged Multibus systems for industrial control, factory and laboratory automation, data communications and software development. Since 1979 DCS has been praised by hundreds of customers for its systems reliability and rugged design. DCS offers the best industrial microcomputer system value in the industry and we welcome your comparison.

Software

The DCS/86 utilizes standard operating systems such as CPM/86, MPM/86 (multi-user, multi-tasking), Concurrent CPM/86 (single user, multi-tasking), MS-DOS (original operating system selected for IBM PC), Xenix (UNIX) and iRMX86 (Intel multi-tasking DOS). High level languages include Fortran, Basic, Pascal, PL/1 (subset G), PLMX, Cobol, "C" and ADA. DCS offers the largest selection of software available for 16-bit microcomputer systems and a staff to provide customer support.

Field Proven

Hundreds of DCS systems are in use throughout the United States and Western Europe in demanding industrial applications. Whether it is a complete system or OEM components, please be assured that DCS is first in quality, support and price/performance.

Distributed Computer Systems

223 Crescent Street, Waltham, Ma. 02154 617 899-6619 Toll Free 1-800-225-4589 TWX 710-324-6476

Write 54 on Reader Inquiry Card

Conclusion

A supercomputer is generally characterized by three features: high computational speed, large main memory and fast and large secondary memory. Tables 1-5 compare the characteristics of some of the supercomputers available today.

The high computational speed is obviously desirable. A large main memory is useful in processing large amounts of data as units and in operating large, complicated programs without time-consuming overlay procedures.

Secondary memory is important in many scientific applications because the data simply will not fit in main memory. In such cases, secondary storage may be regarded as an overflow of main memory. Many scientific programmers spend the bulk of their effort in optimizing such data transfers between memories—i.e., on input/output. Cray and CDC have solved their secondary memory problem with sophisticated disk systems. Vector supercomputers have very fast scalar computation speeds, but their success is directly related to the execution of very large programs with a high degree of parallelism.

The Goodyear MPP, with its 16,384 arithmetic processors, has major architectural differences from the more conventional and relatively similar Cyber 205 and Cray-1, with their combined vector and scalar CPU organizations. Yet the Cray and Cyber have demonstrated marvelous strides in parallel computation due to effective use of pipelining and chaining. It now appears that these machines may face competition from the Japanese

The new generation of supercomputers, both in the US and in Japan, may involve a very large number of processors operating in parallel. Several developments with many parallel processors (Illiac IV, BSP, etc.) have failed over the last two decades. The MPP may be one of the first systems with this form of parallel processing to be successful.

Demonstrated success may pave the way for supercomputing in the 1990s. Meanwhile, more conventional innovations such as Cray-2 development assure steady prog-

References

- (1) J. L. Potter, "Image Processing on the Massively Parallel Processor," Computer, Vol. 16, No. 1, January 1983, pp. 62-67.
- (2) Ronald D. Levine, "Supercomputers," Scientific American, Jan. 1982.
- (3) Edward W. Kozdrowicki and Douglas J. Theis, "Second Generation of Vector Supercomputers," Computer, Nov. 1980.
- (4) D. J. Theis, "Special Tutorial: Vector Supercomputers," Computer, Vol. 7, No. 4, April 1974, pp. 52-61.

RS232 OR 8 BIT PARALLEL MINI CASSETTE SYSTEM



LOW COST — \$388.00 @ 100 UNITS* (BASIC DRIVE WITH R/W ELECTRONICS \$150*)

- MICROPROCESSOR CONTROLLED
- MICROPROCESSOR CONTROLLED
 >200K BYTES FORMATTED/TAPE
 VARIABLE BAUD RATE (110-9600)
 DOUBLE BUFFERED I/O
 MANUAL OR COMPUTER CONTROL
 ERROR RATE 1 IN 10 TO THE 9TH
 SMALL 3" x 3.5" x 5" W/O CASE'
 PHILIPS DRIVE 5000 HOUR MTBF

- FOR APPLICATIONS IN -

Program Loading Paper Tape Replacement Store and Forward

Peripheral Storage Software Distribution Daw Logging

Computer Program Storage and Back-Up

Also, Mini Cartridge, Cassette, Cartridge & Floppy Disk Systems to 12 Megabytes, also Bar Code Readers

ANALOG & DIGITAL PERIPHERALS, INC.



815 Diana Dr. - Troy, Ohio 45373 513/339-2241 - TWX 810/450-2685 Branch Office: Oklahoma City, OK Factory: Yucca Valley, CA


NCC @ BOOTH S5600

Write 55 on Reader Inquiry Card

Solid-State Disc Replacement

Dramatic increases in throughput. Outstanding reliability.

- Capacities to 80 megabytes
- 10 megabytes in 7-inch chassis
- · Interfaces to most minicomputers
- · Battery back-up



Let us show you how the MegaRam can enhance the performance of your computer while providing outstanding



Imperial Technology, Inc.

831 S. Douglas Street · El Segundo, California 90245 • Telephone: (213) 679-9501

Write 56 on Reader Inquiry Card

Off-The-Shelf ICs Simplify Modem Design

by Stephen J. Durham

Only recently in modem design has it become possible to use integral components rather than the more traditional custom printed circuit boards. Now, design engineers can use new monolithic modem ICs to design modems into products easily, because all critical analog functions are provided for them in IC form. Data terminal equipment designers only need to extend the design of their serial I/O port past the Universal Synchronous/Asynchronous Receiver Transmitter (UART or USART) to include a modem. They needn't consider separate PCBs or cables.

There are several key reasons why integrated components are preferred over custom boards. There is no need for RS-232C type drivers/receivers, connectors and cables; therefore system integration is increased. There is no need for an external modem power supply since the integral unit takes its power from the host. Since power

Stephen J. Durham, Cermetek Microelectronics, Inc., 1308 Forregas Ave., Sunnyvale, CA 94086.

Designing with integrated modem components may very well make the difference between the success and failure of a product.

supplies are typically a system's greatest weak point, reliability is better. Integral modems can extend a product's features beyond their intended scope and open an entirely new market. For example, a CAD workstation with an integral modem can add remote diagnostic and electronic mail features. Using integrated component modems can also result in a 66% profit margin since the modem's cost is only 33% of the market value.

Integral Component-Based Modems

Nearly all low-to-medium speed modems (300-1200 bits/sec) may be

described as shown in the block diagram of **Figure 1**. The modem spans the functional distance from the system μP bus to the telephone line. At the bus, a compatible UART or USART serializes the parallel data bus for transmission through the modem. At the other end the data coupler connects the modem to the telephone line.

Acoustic and direct connect are the two most practical data couplers. The acoustic method uses audio data carriers generated by the modem and couples them onto the telephone through the phone handset. The direct connect method couples the data carriers directly on the phone line through a Direct Access Arrangement (DAA).

Modem Signal Processor

Figure 2 shows the five fundamental jobs that the modem signal processor performs: modulation, demodulation, transmit and receive carrier filtration, and carrier energy detection.

The modulator for most low-tomedium speed modems is a frequency shift keyed (FSK) type which transmits one frequency for a serial one (mark) and another frequency for a serial zero (space).




Figure 1: Integrated modem block diagram.




Figure 2: Modem signal processor operation.

Switching from one frequency to another is done phase coherently to minimize generation of needless carrier sidebands.

The modulated carrier is then passed through a transmit filter which rejects modulator signal components outside the transmit signaling band. It is important to limit the transmit carrier energy in the local receiver's frequency band and also in the frequency range above 4 KHz to meet the FCC's Part 68 requirement for out of band energy.

Potential performance level of a modem is determined by the receive filter. It selects the receive carrier signal off the telephone line while rejecting all other frequency bands. The local transmit carrier band, often reflected back by the phone line interface at relatively high levels, is typically rejected using high Q notch filter stages.

The group delay of the transmit and receive filters is also very important. Group delay relates to the propagation time difference for a mark frequency to pass through the filter as compared with a space frequency. Group delay time should be kept small as compared with the modem's baud rate to lessen the effect of bias jitter.

The signal processor's demodulator monitors the extracted receive carrier to decode the amount of mark or space energy in the receive carrier. Its serial data output reflects the outcome of this weighting function.

The carrier detector monitors the receive carrier's signal strength and sequencing. When an inadequate receive carrier is detected, the demodulated serial data line is clamped to a "1" or a "mark" level. This guards against random or spurious transitions on the receive data line during signal fade-outs or complete carrier loss.

When adequate receive mark energy is detected continuously over a specified period (usually around 150 ms), the carrier detector unclamps the receive data line. If initial space energy is received, the receive data line will remain clamped. Only after initial mark energy carrier detection will the carrier detector consider space frequencies as valid energy. This form of initial OFF to ON carrier detect sequencing is called "mark before space turn ON." The loss of carrier is considered valid only after a specified time of continuous carrier loss (usually 17 ms).

Modem Signal Processors

There are eight monolithic signal processing chips currently on the market. Motorola's MC6860 and MC14412, Advanced Micro Devices' AMD7910, Texas Instru-

ments' TMS99532 and TCM3101, and National Semiconductor's TP3320 and 3321. The Motorola devices have been available for many years, while the AMD and TI chips have been sampled only recently by key customers. The Cermetek CH1760 is a Bell 212A compatible modem component that incorporates the complete modem function, including the direct connect telephone line interface. Many semiconductor manufacturers—Synertek, Mostek, Harris and AMIare planning to introduce second generation devices this year. Those devices, because they are not yet finalized, are not included in the Signal Processor Summary (Table 1).

Modem Handshaking

When a data telephone connection is set up, set sequence or handshaking protocol must be followed. Most Bell and CCITT compatible modems follow similar sequences.

Modem control can be done with dedicated hardware or with software. In the integrated modem, software control is readily available via the μP bus, but this implies a level of understanding of the telephone system that the software designer does not always have.

For this reason, modem sequencing is usually provided in hardware and often included in the monolithic modem IC (see **Table 1**). In any

Device		2nd		Modem	Include	d Function	ns		
P/N	Mfg.	Source	Technology	Type	Mod/Demod	Filters	Control	Power	Comments
MC6860	Motorola	No	NMOS	103	X		X	+5	Filters supplied by Cermetek's Hybrid Filters.
MC11412	Motorola	Yes	CMOS	103, V.21	X			+5	Filters supplied by Cermetek's Hybrid Filters.
AMD7910	AMD	No	NMOS	103, V.21	X	×		+5 -5	Partial auto answer control supplied.
TMS99532	TI	No	NMOS	103	X	X		+5 -5 +12	
TCM3101	TI	No	CMOS	202, V.23	×	X		+5 -5	
TP3320/ 3321	NSC	No	CMOS	203, V.23	X	X		+ 5 - 5 + 12	
CH1760	CERME- TEK	No	CMOS, HYBRID	212A	X	X	X	+5 +12 -12	Complete 212A Modem 30011200 BPS with phone line interface and auto- dial/auto-answer.

Table 1: Summary of modem signal processor features.

case, the hardware necessary to provide this function is minimal. Typical modem handshaking is shown in **Figure 3**.

Modem Idle

The integrated modem is idle when the telephone line has not been seized or is ON HOOK. The modem is forced out of its ON HOOK state when it detects a telephone line ringing signal for auto-answer or a transition of the telephone DATA exclusion KEY.

Originate Mode

Originate mode is begun after telephone dialing is completed. Dialing can be done via an external dataphone or by an internal auto-dialer. In either case the integral modem begins its sequencing when an initialing DATA KEY signal is received. This signal could come from a manually operated button (dialing through an exclusion keytype telephone) or through the auto-dialer. After dialing, the modem must direct the telephone line to go OFF HOOK and wait for the far end modem to return answer tone. At that time it may unsquelch its modulator and transmit a data carrier, thereby entering the DATA MODE.

Answer Mode

On integrated modems where autoanswer is necessary, the detection of ringing on the telephone line places the modem in the ANSWER MODE. The natural response to this is to take the modem OFF HOOK or seize the telephone line, but the modem should wait for the inter-ringing interval before going OFF HOOK. The wait prevents needless contact degradation of the Direct Connect Protective Hybrid's (DCPH) OFF HOOK relay caused by high ringing voltage line transients.

After going OFF HOOK, the integrated modem's transmitter must be silent for a minimum of 2 seconds to comply with the FCC Part 68 silent billing delay period. After that delay, ANSWER TONE may be sent to the calling or originating modem and a transition to the DATA MODE may be made.




Figure 3: Typical modem handshaking.

Data Mode

In DATA MODE, the modem's signal processor does all the work. Its primary function is to modulate and demodulate frequency shift keyed (FSK) data. DATA MODE continues until conditions indicate that data communications have ended. For full duplex modems like the Bell 103 or Bell 212A, two primary conditions signal the end of a data link: loss of receive FSK carrier, and the host controller's software command to disconnect.

On half-duplex modems such as the Bell 202, loss of receive FSK carrier cannot be used as a disconnect signal because this condition exists normally during periods while communication direction changes. For this reason, it is the host command that forces half-duplex modems to disconnect. At that point, the modem control asserts an ON HOOK condition to the telephone line and returns its sequencing to the start, or ON HOOK mode.

Telephone Line Interface

The modem data coupler joins the transmit and receive data carriers

onto the telephone line either acoustically, or metallically by an FCC Part 68 registered Direct Access Arrangement (DAA).

Acoustic coupling uses the telephone handset (usually through tightly fitting rubber caps) to send and receive data through the handset's speaker and carbon microphone. The major advantages of this technique are that it does not require Part 68 registration and that it is portable. In places where direct telephone line connection is not possible, such as a phone booth, you can couple through the telephone handset.

Unfortunately, the conveniences of acoustic coupling are often outweighed by the disadvantages. The standard telephone handset was never intended to transmit data. Its carbon microphone is fine for voice but presents signal distortion problems for data. But more importantly, the acoustic technique does not allow auto-answer and auto-dial operations which are a desired feature when the modem is integrated within the host data terminal equipment.

Direct connect coupling eliminates the non-linear telephone

Feature	CH 1810	CH 1812
1. FCC Registered	Yes	On Users PCB
2. Small Size	2" × 2"	1" × 2"
3. Lighting Surge, Isolation, And		
Hazardous Voltage Protection	Yes	Yes
4. Ringing Detect	Yes	Yes
5. On/Off Hook Control	Yes	Yes
6. Line Powered	No	Yes
7. Xmit Level Squelch	Yes	No
8. Xmit Band Limiting	Yes	No
9. Billing Silence	Yes	No
10. Price (1K)	\$50	\$15

handset, allows clear data transmission, and also permits two key functional modem operations: auto-answer and auto-dial. FCC rules and regulations covering direct connect links to the public telephone network require careful design and selection of discrete components to be connected to the phone lines. In addition, a fairly complex FCC application must be filed and *approved* before the interface is certified by the FCC for legal direct connection to the telephone network.

Cermetek provides a family of DAA components to meet FCC requirements and simplify the coupling. The family of Direct Connect Protective Hybrids (DCPH) consists of two DAA devices, the CH1810 and CH1812 (**Figure 4**).

The key differences between the DAA interfaces is FCC registration and cost. The CH1810 is Part 68 registered and conveys that registration to the host modem and data system, provided that the Cermetek-supplied registration label is displayed on the outside of the host data system. The CH1810 necessarily duplicates many of the FCC required functions typically found in a modem in order to convey its FCC registration. Examples are transmit level and billing delay control. The minimal cost of the function duplication is more than outweighed in low-to-medium volume applications by the savings gained in avoiding the lengthy FCC registration cycle.

In high-volume use where cost is a key factor to the success of the product, the CH1812 DAA is a better choice than the CH1810. It is more cost effective because it is tailored to the modem application with no modem feature duplication.

However, the data system must go through Part 68 registration with the CH1812 integrated onto the host printed circuit board.

In the long run the expense and costly time delays associated with FCC registration are not major concerns, but the two to six month registration cycle may prove to be prohibitively long and seriously af-

The CH1810 may be used initially as the host's DAA, enabling immediate registered product introduction.

fect product sales. For this reason the CH1810 also serves well in high-volume applications. The CH1810 may be used initially as the host's DAA, enabling immediate registered product introduction. When time permits, the CH1810 can be replaced with the CH1812 at less cost and without concern for registration delay times.

Integrated Auto-Dialing

A fundamental feature of an integral modem is auto-dialing. This

Figure 4: Features of the Direct Connect Protective Hybrids (DCPH) family DAA devices.

enables the host machine to use its communication facilities with or without an operator.

Five major circuit elements are needed to design an auto-dialer into an integral modem: a pulse dial generator, a DTMF generator, a call progress tone detector, telephone number storage, and a controller that sequences the dialing process. Cermetek's CH1820 Automatic Call Processing Unit provides all these functions on one IC (Table 2).

CH1820 Application

Figure 5 shows how the CH1820 integrates easily into typical modem architecture. The IC obtains its digits to be dialed over the same serial data lines that the host uses to transmit and receive modem data. This simplifies the interface with the host since it eliminates additional ports required to communicate with the auto-dialer. The CH1820 uses the serial data lines (TXD, RXD) to receive commands and return status only when the modem's clear to send (CTS) line is OFF. This indicates that the modem is not ready to transmit data over the telephone line and, therefore, transmit and receive data lines are not in use. When the modem's CTS line is ON, the CH1820 no longer monitors the serial data lines and becomes transparent to modem operation.

The modem's CTS line is looped through the CH1820 enroute to the host UART. When the modem is IDLE (its ON HOOK, OH, line low, and its CTS line is OFF) the CH1820 asserts CTS to the host UART ON to enable dialer communication. After auto-dialing is complete and remote modem answer tone is detected, the CH1820 simply loops the logic state of the CTS line from modem to UART. The modem is given indication to begin its originate call sequencing at this time by the assertion of COS (Call Originate Status).

Pulse or DTMF dialing is accom-

P/N	Mfg.	Pulse Dial	DTMF Dial	Number Storage	Call Progress Tone Detect	Dialing Sequencer
CH1820	Cermetek	Yes	Yes	Yes (7)	Yes Dial Busy Ring Back Modem Answer Voice	Yes
TMS 99531	TI	Yes	Yes	No	No	No
MM5393	National	Yes	No	Yes (1)	No	No
MM5395	National	No	Yes	No	No	No
MK5494	MOSTEK	No	Yes	Yes (1)	No	No
MK50981	MOSTEK	Yes	No	Yes (1)	No	No
S2560A	AMI	Yes	No	No	No	No
S2860	АМІ	No	Yes	No	No	No

Table 2: Comparison of auto-dialer features of various devices.

plished simply by allowing the CH1820 to respectively pulse the DAA's OH (ON HOOK) line or assert DTMF tones on the DAA's TRXCAR (Transmit Carrier) line. The CH1820 gains access to both of these signal lines by looping them through itself. When the CH1820 is not dialing, the looped modem signals are passed unaltered.

CH1820 Call Sequencing

The CH1820 takes its dialing commands serially from the host UART. These commands are decoded in ASCII as indicated in **Table 3**. Before these commands are accepted, however, the auto-dialer must be prompted or awakened. This is done by transmitting two consecutive Carriage Returns (CRs) to the CH1820. The CH1820 responds by entering the DIAL mode and returning the serial ASCII status:

DIAL: Once a dial command has been given, the CH1820 sets up to dial the number as referenced in the command or as addressed in on-chip memory. Call dialing is initiated by seizing the telephone line (asserting ON HOOK, OH, HIGH) and waiting for dial tone.

Failure to receive dial tone within 2 seconds causes the CH1820 to issue the status: No Dial Tone. It will then continue to try and dial the number anyway. This enables the CH1820 to be used in areas where dial tone does not match the

US domestic standard. If this is not desired, the host may issue a quit command; Q, to terminate dialing.

Automatic Dial Mode

The CH1820 supports the feature

of Automatic Dial Mode Selection between pulse and DTMF dialing (**Figure 6**).

Once the dialing mode is selected, dialing continues without further evaluation until the end of the

Figure 5: General CH1820 auto-dial configuration.





Figure 6: Autodial mode selection.



COMMAND SYNTAX	RESPONSE		
1. D: NUMBER ^[1] CR	Dial (Number)		
2. D L	Dial Last Number Dialed		
3. D R N	Dial from Memory Location N		
4. D R N M	Dial from Memory Location N, M Times or Until Answered		
5. S N NUMBER[1] CR	Store NUMBER in Location N		
6. L	List all stored Numbers		
7. Q	Quit Dialing Process		
8. (Null Line) CR	Exit Dialing Environment		
9. H	Help, List Command Summary		

Table 3: CH1820 command summary.

telephone number is reached or until a ">" pause detector is encountered while dialing. If a ">" is decoded within the dial NUMBER string, the dial mode is re-evaluated (Figure 6). Dial mode re-evaluation during dialing can be useful for carrier facility access from a pulse only subscriber exchange. Valueadded carriers like MCI and SPRINT require that after a user dials into their access trunk and waits for a secondary dial tone, the user's ID and called number be entered via DTMF. Without midstream dial mode re-evaluation this would not be possible.

Dial Wait Characters

The host may insert wait characters within the telephone NUMBER string to slow down or control the dialing sequence. This is typically done to wait for a secondary dial tone, as is found when dialing through a PABX, to get an outside line or when accessing SPRINT, MCI or similar systems.

The CH1820 supports two wait character types as shown in **Table 3**. The first (>) inserts a 2 second dial tone wait. After receiving dial tone it then auto-selects DIAL MODE. The second (=) simply inserts a 2 second pause in the dialing process. No dial mode alteration or

dial tone monitoring is done.

Call Progress Tone Monitoring

After the actual dialing process is over, the auto-dialer must monitor the telephone line for such indications as BUSY, RINGING, QUIET LINE, MODEM ANSWER and VOICE, and then act.

The CH1820 uses digital signal

The CH1810 may be used initially as the host's DAA, enabling immediate registered product introduction.

processing techniques to detect the call progress tones found throughout North America and many other locals. Since the tone detection characteristics are microcoded on the CH1820, simple code changes can result in compatible detection characteristics for other locals, such as are found in Europe and Asia.

No Tones: If, after dialing, no call progress tones are detected for

17 seconds, the auto-dialer assumes a mis-dial happened or there is a telephone line-related problem and terminates the call with the status message: Try Again.

Ring-Back Tone: After each detected ringing tone, the CH1820 returns the messages: Ringing. If after 6 rings there is no answer, the CH1820 hangs up and returns the message: No Answer.

Busy Tone: If busy tone is detected, the CH1820 hangs up and returns: Busy.

Voice: If, after the 2nd ring, a human instead of a modem answers the dialed number and speaks, the CH1820 detects the syllable nature of the audio and returns a disconnect tone to the human caller, then hangs up and returns the status message: Voice, Try Again.

Modem Answer Tone

When modem answer tone is detected, the modem transfers the call to the companion modem by asserting COS low. The auto-dialer then goes to sleep, ignoring all serial UART commands until the data call is over, indicated by the modem's CTS signals becoming false. Status is returned with the message: Answered-Data Mode.

Conclusion

In the early 1980s we are seeing a trend toward integral modems made of components, which integrate easily into the host data system. This step forward in the efficient use of LSI technology will produce lower communication system costs and higher reliability.

The trend for second generation modem IC manufacturers will be to include the modem handshaking control on board with the signal processing and, eventually, the auto-dialer as well. These modems will continue to be connected to the telephone line with DAA components.

In the mid-'80s third generation monolithic modem ICs should appear and will include the DAA on the chip as well. The chip will also be able to support the high voltage necessary for the DAA to control the telephone line interface.

Tektronix Introduces Color Graphics Products

In an attempt to widen their customer base, Tektronix has just introduced a group of very low cost color graphics products of considerable interest to graphics system designers. They include a high performance color raster display terminal for \$19,950, a family of color desk top display terminals starting at \$3995, a local graphics processing unit based around Intel's 8086 and 8087 processors for \$5500, and a desk-top ink jet color copier for \$1950.

Ergonomics and speed were primary concerns in the design of the Model 4115 high performance display. High resolution greatly enhances the terminal's display quality: graphic images stored in the terminal's 32-bit coordinate space are displayed at a resolution of 1280 × 1024 pixels. In addition to this large number of displayed pixels, the 4115's 60Hz non-interlaced display greatly reduces flicker, thus allowing the user to work at the terminal with less eye fatigue.

Writing rates in excess of 50,000 vectors per second are achieved through the use of a bipolar bitslice graphics processor operating in tandem with the 4115's 8086/ 8087 CPU. The display list coordinate space is user selectable, ranging from 12 to 32 bits on 12 or 32 bit coordinate space, providing an optimum match to the application. The display list is then traversed by the graphics processor which applies two-dimensional transformations (translate, rotate, scale and clip) and the resultant image is presented to the user on the 1280×1024 color display. The features of pan and true zoom provide the user with fast access to any part of the locally stored graphics data, always displayed with maximum resolution.

The 4100 family of color desktop terminals, starting at \$3995, range in display size from 13" to 19". Each terminal incorporates a 60 Hz non-interlaced raster-scan display and an anti-glare screen. The terminals can display graphics of up to eight colors at one time from a palette of 64 colors. Resolutions range from 480×360 pixels to 640×480 pixels.

The 4170 Local Graphics Processing Unit converts any one of the 4100 series terminals into a standalone computer specialized for graphics tasks. The unit is designed to bring distributed processing to a host environment. Host data is downloaded to the terminal for interactive graphics, accessing graphic firmware features, and controlling peripherals connected to the terminal.

The 4170 consists of two Intel processors, the 8086 and the 8087 numeric co-processor for data intensive functions, 256 Kbytes of RAM, two 51/4" floppy disks, four RS-232C interface ports with data rates adjustable to 19.2K baud, and three circuit board option slots. The unit is housed in a compact cabinet which fits beneath a bench or alongside a desk.

Using on-demand ink-jet technology, the 4695 color copier produces eight-color copies from computer graphics displays. The 4695 is intended for such applications as data analysis, presentation graphing, and CAD previewing.

The copier can place 120 dots per inch in both horizontal and vertical directions, allowing up to 1280 × 960 dots per A-size (8.5" × 11") image. Ink is supplied from separate cartridges containing yellow, cyan and magenta which can be mixed to also print red, green and blue. A separate black ink supply provides a true, dense black. In addition to the standard colors, up to 125 halftones are available under program control.

A variety of media can be used: A/A4 cut-sheet paper, paper rolls, and, available in September, overhead transparency media. Copy



Figure 1: The Model 4115 computer display terminal features a high performance color raster scan display which displays 1280×1024 pixels at a 60 Hz non-interlaced refresh rate.



Figure 2: The Model 4105 computer display terminal and the 4695 color graphics copier provide a personal graphics tool to technical and professional users.

speed is about 2.5 minutes/page for a typical copy. Cost per copy will be less than 20 cents. The unit also allows functions as a bi-directional printer at speeds of 20 cps. The Tektronix-designed ASCII font uses a 12×6 dot matrix to form each character. Write 237

COLOR GRAPHICS

For Distributed Processing Environment

The 8600 is a raster scan color graphics computer that will operate as a stand-alone system or as an intelligent



TERAK 8510 Computer Graphics System



TERAK 8600 Color Graphics Display System

workstation in a distributed processing environment. Its high-quality monitor, standard at $640 \times 480 \times 3$, upgradable to $640 \times 480 \times 6$, offers up to 64 displayable colors from a display palette of 512. A compact unit, the system comprises four components. The color processor contains a 16-bit Intel 8086 μP, raster scanner and frame buffer. The 13" cathode ray tube (CRT) monitor features an inline color gun, and the keyboard is a 128 ASCII set, with function keys, cursor control group and numeric keypad. The heart of the system is the DEC LSI-11 CPU memory with communication and auxiliary storage, including 2.4 Mbytes of 8" floppy disk storage and four standard RS-232C serial ports. Terak, 13444 N. 32nd St., Suite 19, Phoenix, AZ 85032.

Write 126

STANDALONE CAD SYSTEMS

With Vector Refresh

Information Displays, Inc. has introduced a family of standalone CAD systems. CADalyst employs seven independent processing sub-systems, each with their own local program

and data storage facilities. Each unit supports up to 16 Mbytes of addressable memory, features both vector refresh and color raster displays, light pen or data tablet, streaming mag tape drive, and Winchester technology disk with fixed/removable media. Each CADalyst system supports peripherals such as plotters, printers, and telecommunications equipment. CADalyst can be configured in a network that allows it to communicate with other computers and commonly pooled peripherals. On-screen command menus speed task execution on the system. The floating keyboard can be positioned in either a flat or tilt setting and features ergonomically designed keys and functionally placed key pads. Instantaneous response to the light pen and data tablet allows the operator to interactively position, rotate, and scale graphic entities in a continuous stream of motion, facilitating throughput and productivity. Price is \$100,000. Information Displays, Inc., 28 Kaysal Ct., Armonk, NY 10504. Write 127

ROBOT

For Electronics Assembly

The Model 605 is programmable through a PC and is based on a number of industry standard components. The Intelledex Model 605 Robot consists of the robot arm and end-effector, a control computer, a separate




safety computer and an optional, fully integrated vision system. Because vision is integrated into both the hardware and software of the Model 605 the optional vision capability can be plugged into the robot. Features in-

clude software and proprietary stepper-motor control technology, a cpu that addresses one million bytes of system memory, and a design that blends into the automated environment. Price is \$48,000. Intelledex, Inc., 33840 Eastgate Circle, Corvallis, OR 97333. Write 130

APPLE II SOFTWARE

Industrial Control And Monitoring

In this program package the Apple is the controlling computer in a network



using Wintek's 6801 Micro Control System. The MCS is a SBC incorporating both analog and power I/O on a $4.5'' \times 6.5''$ card. The software can be customized to fit a wide variety of applications. Price is \$198. Wintek Corp., 1801 Lafayette, IN 47904.

Write 145

CAD WORKSTATION

Produces Publication Quality Documents

The Qubix system is designed as a CAD workstation, and has software that merges text with graphics and interactively produces fully composed pages ready for publication. The resolution of the monitor allows system users to see fonts on the screen in exact size from 4.5 to 120 point in size. The number of font styles available to the user is unlimited. The workstation produces composed pages with text and graphics which are output on high and medium resolution devices. Qubix, 18835 Cox Ave., Saratoga, CA 95070. Write 131

New Products • COMPUTERS/SYSTEMS

SUPERMINICOMPUTER SYSTEM

With Library Of Application Software Packages

Applications of the Edition VII Workbench include generalized software development, office automation



including word and text processing, timesharing, software configuration management, networking, and applications development and testing. A library of application software packages, developed under Unix, is also available to the user. The system includes a processor with ½MB of memory, 65MB of disc memory, eight communications lines, a Model 550B console terminal, and an 8-port Edition VII Workbench license. Price is \$49,950. Perkin Elmer, 2 Crescent Pl, Oceanport, NJ 07757. Write 135

NETWORK BUILDING BLOCKS

Flexible Remote Access

The NETWAY family can be configured as a multiplexor data concentrator, protocol converter, cluster controller, packet processor and nodal processor. It includes distributed communications-oriented hardware and a proprietary communications operating system. Features include a communications processor, local network interface, device interface processor, and a network interface processor. The networking software provides automatic alternate routing, on-line configuration from any workstation and allows any workstation to communicate with any host on the network. Price is \$11,040. Tri-Data, 505 E. Middlefield Rd., Mountain View, CA 94043. Write 143

MINICOMPUTER SYSTEM

For Vax-11 Users

ULTRAVAX systems substitute firmware-driven controllers on each Unibus, CMI-bus or SBI-bus for the more traditional, discrete logic-driven controllers used in DEC's standard configurations. These µP-based controllers permit integration of peripherals with large capacities. The controllers comprise bipolar, bit-slice µP designs incorporated onto singleboard or single-board-extended packages that fit into available VAX backplane slots without modifications. All basic control, status and data transfer operations are implemented by microcode. ULTRAVAX controllers are software-transparent to VAX/VMS, UNIX and DEC diagnostics. California Computer Group, Inc., 3303 Harbor Blvd., Costa Mesa, CA 92626.

Write 128

1/4" STREAMING TAPE SYSTEM

Extended Storage Capacity

The 1/4" streaming tape system operates at a speed of 90 inches/sec and at a maximum data-transfer rate of up



to 72 kbytes/sec. Called the Streamer 410, the cartridge-based system stores a minimum of 45 Mbytes of formatted data on a standard DC300XL cartridge.

Designed to provide backup storage for Winchester disks of 30 Mbytes and greater capacity, the Model 410's storage capacity increases to 60 Mbytes when equipped with a 600 ft. DC600A cartridge in place of the standard 450ft. DC300XL. The drive's two-channel bidirectional tape head with its separate erase bar records data on eight tracks.

The Streamer 410 is controlled by two separate μ Ps—one for the tape drive, the other for the controller. μ P control permits features such as an automatic tape reference to ensure cartridge interchange, automatic identification of cartridge type, and a se-

ries of automatic diagnostic tests at power-up and cartridge insertion. Diagnostic tests include a RAM and ROM check, exercising of the tape drive, locating the edge of the tape and track identification. A standard command allows the tape to run from end-to-end to initialize the cartridge. Price is \$1,625. Qantex Div., North Atlantic Industries, Inc., 60 Plant Ave., Hauppauge, NY 11788. Write 203

TURNKEY WORKSTATION

For Automated Custom IC Design

The ZyPAWS workstation uses the 32-bit virtual memory Prime 2250 computer, which supports 20 users. It is a front-end workstation used for logic simulation, circuit simulation and test-program generation and is a fully integrated workstation with color graphics capability for performing automatic cell placement and routing. ZySPICE is a circuit simulation program based on SPICE version 2.E and modified by ZyMOS to include enhanced small-geometry transistor models. ZyPSIM is a proprietary event-driven logic simulator. ZyTEST is a suite of proprietary ZyMOS software modules that converts to the output of the ZyPSIM simulator into Sentry series compatible automatic



test programs. ZyPART, available with ZyPAWS II, is a collection of proprietary ZyMOS programs which automatically generate a cell placement and routing directly from the ZyPSIM network file. Price is \$100 to \$150. Zymos, 477 N. Mathilda Ave., Sunnyvale, CA 94088 Write 136

IBM-COMPATIBLE COMPUTER SYSTEM

Customizing Ability

The Raytronics computer system enables the user to customize a system to individual needs. Called an IBM

New Products • COMPUTERS/SYSTEMS



PC "work-alike" computer system, it is fully compatible with the IBM Personal Computer. The chassis contains a plug-in 8088 CPU board, a 12-slot bus for expansion, and a hevy-duty 80W power supply. The front panel cutout accepts two thinline, 51/4" floppy disk drives or Winchesters. When the CPU board is removed, the cabinet can be used as an expansion chassis. It will accept all IBM PC-compatible circuit boards. The computer system can be configured with both its manufacturer's expansion and interface cards and those from other third-party vendors. Vitek, 930-G Boardwalk Ave., San Marcos, CA 92069 Write 149

COLOR GRAPHICS SYSTEM

Interfaces with IBM, DEC, And PE

The System 1500 provides a full range of interactive features. The controller supports from one to four workstations. When configured with a communications controller, it can support up to 64 workstations. It is offered with 32-bit parallel interfaces for IBM, Perkin-Elmer, and Digital Equipment Corp. host processors. It can accommodate graphic applications such as: CAD/CAM, Signal Processing, Seismic Interpretation, Command and Control, Simulation, and Mapping. Price is \$19,900. Spectragraphics, 10260 Sorrento Valley Rd., San Diego, CA 92121. Write 209

COMPUTER-AIDED-ENGINEERING WORKSTATION

For Design And Analysis

TEGAStation, a digital design work station, is intended for the design and analysis of digital electronic circuits and systems. The workstation provides design capture, simulation and analysis software, all of which can be used at the designer's workplace. Price is \$60,000. CGIS, 7701 North Lamar Blvd., Austin, TX 78752

Write 208

IMAGE DISPLAY AND ENHANCEMENT SYSTEM

For High Speed Graphics

The Model 280-62 Graphics Image Display and Image Enhancement System is a member of the newly introduced Series 2800 family of raster scan image processing, image display, and computer graphics peripheral equipment. It is a 1024 × 1024 resolution system for the display and enhancement of digital images, the generation of computer graphics, or the merging of graphics information with digital images. The system can handle up to three banks of 1024×1024 by 8-bit memory, each bank with up to four overlays. The configuration is programmable and permits four bit greyscale, eight bit greyscale, 10×12 pseudo-color or 24 × 24 full color displays. Features include memory

Engineering

Discover the Difference

DIGITAL DESIGN ENGINEERS

At Teledyne Electronics, you'll discover a dynamic engineering environment unmatched in the industry. We are a leading manufacturer of microprocessor controlled avionics and identification systems, and our explosive growth has created several opportunities for experienced Digital Design Engineers.

To qualify, you should have background in Digital Design, including worst case analysis and TTL. Microprocessor experience and ability to write military specifications and procedures is also desireable.

We offer an excellent salary and benefits program, a comprehensive relocation package and a growth positon with a winner. Please send your resume (with salary history) to:

TELEDYNE ELECTRONICS

649 Lawrence Dr., Dept. DD Newbury Park, CA 91320 (805) 498-3621 • (213) 889-3590

Equal Opportunity Employer M/F/H • U.S. Citizenship required

TELEDYNE ELECTRONICS

Write 57 on Reader Inquiry Card



Totally new polyurethane timing belts — only from Albany.

With no plasticizers to break down, near-perfect hydrolytic stability, and the ability to withstand extremes in temperature, these new timing belts outperform every other belt.

You get greater stability, flexibility, repeatability, fewer problems, longer life. And you don't pay more! From now on, specify timing belts from Albany International. With us, timing is everything. Precision Components Division, 150 Industrial Park Road, Middletown, CT 06457.

For nearest representative call TOLL FREE: 1-800-243-8160. In CT: 1-800-842-0225.



Precision Components
Division

Timing is everything.

Write 58 on Reader Inquiry Card

Product Index

To help you find the products you need, we've compiled a subject index of the ads and new products that appear in this issue. Organized by general product area, the listings include the name of the manufacturer, the page on which the product appears and a write number for additional information on that product. Bold type indicates advertised products.

	Page #	Write #		Page #	Write #		Page #	Write #
Mini/Supermini Sy	stem	ıs	Everest Electronic			Controllers/Interface	ce	
			Equipment Inc.	6	8		00	
Pro-Log Corp.	C4	67	Methode Electronics Inc.	15	18	Boards		
DCS	102	54	Mupac	125	64	John Bell Engineering	123	62
Invention Marketing	123	00	Pick Computing Machinery	28	25	Cosmos	77	45
Sigma Sales	8,9	32	Renco	21	22	Data Translation	46	33
Cadtrak	119	129	Summagraphics	41	24	Distributed Logic Corp.	89	49
California Computer Group,	110	100	Teledyne Electric	113	57	MDB Systems Inc.	2	3,5
Inc.	112	128 208	The Mouse House	31	27	Metacomp Inc.	11	16
CGIS Grippoll Systems	113	210	Advanced Control Systems			Monitek Inc.	10	13
Grinnell Systems		127	Corp.	122	144	Greco Systems	122	140
Information Displays Inc.	111	135	Intelledex, Inc.	111	130	Intel	121	205
Perkin Elmer	112	131	Methode Electronics Inc.	122	137	Mostek	121	139
Qubix	111	149	D C 1: /TID	C/T				
Vitek	112		Power Supplies/UP	'S/L1	ne	CPU Boards		
Zymos	112	136	Conditioners				101	100
Microprocessor Sy	ctom	C		100	040	Alloy Computer Products	121	192
Microprocessor Sy	Stem	5	CEAG Electric Corp.	122	210	Inner Access Corp	121	195
Marinco	98	52	Mass Ctonage/Duive			Intercontinental Micro	100	101
Universal Semiconductor	67	43	Mass Storage/Drive	es		Systems	123	194
			ADPI	103	55	Matrox	123	142
Integrated Circuits			Control Data	24,25	10	61 6 11 5		
(μPs, A/D's, Multip		()	Flagstaff	65	41	Color Graphics Ter	rmin	ials
			Genisco Technology	37	38	Florida Computer		
Electronic Trends	80	46	Kennedy	C2	1	Graphics	17	4
Hughes Solid State	13	50	Imperial Technology	103	56	Lenco	4	6
International Microcircuits			Memodyne	119	59	Lundy	7	9
Inc.	58	39	Moya	121	60	Raster Technologies	83	47
Interdesign	62	40	Teac	124	63	Spectragraphics	113	
The second secon	68,69	44	Pertec Peripherals Corp.	120	189	Terak	111	126
Tecmar	48	35	Quantex	112	203	Torak	111	120
NEC Electronics	122	138	D : . /Dl			Data Terminals		
Application Softwa	aro		Printers/Plotters			Scherers	10	15
			Amdek	51	12	IBM	10	
Forth Inc.	38	68	California Computer			Megatek	120	
BBN Research Systems	119	148		84,85	48	Zenith Data Systems	120	
Wintek	111	145	Hecon	102	53	Zeriiti Data Systems	120	130
Test Fauinment			Nicolet Zeta Corp.	39	29	Dugges		
Test Equipment			Porelon	73	11	Busses		
Kaman Instrumentation	40	30	Versatec	5	7	dy-4 Systems Inc.	14	17
Brikon	119	187	6			Monolithic Systems Corp.	1	2,20
Gould Inc.	120	191	Communications			Thomas Engineering	40	31
STEP		206	Equipment					
				0.5	40	Displays (Led, Vac	uum	1.
Hardware/Backpla	nes.		Scherers	65	42			-,
	illos,		Tri-Data	112	143	Fluorescent, Etc.)		
Packaging,			Add In Momony De	and		Audiotronics	18	34
Electromechanical			Add-In Memory Bo	Jaru	5	Cognex	121	61
			Central Data Corp.	57	37	Digital Electronic Corp.	23	23
Components			Dataram	45	28	Intelligent Systems	70	
Albany International	113	58	Quadram	52,53	36	Modgraph	97	14
Albany International	110	00	- audurum	,		mougiapi.		
Cermetek	43	26	SD Systems	93	51	Peritek	19	

This index is provided as an additional service. The publisher assumes no liability for errors or ommissions.

New Products • COMPUTERS/SYSTEMS

boards equipped with a 10-bit input by a 12-bit output video lookup table. Price is \$27,000. **Grinnell Systems Corp.**, 6410 Via Del Oro Dr., San Jose, CA 95119. **Write 132**

CAD SYSTEM

For Process Plants

The Design Station I combines computer graphics with local plant design intelligence. Plant views appear in color and can be interactively moved, rescaled, and viewed from several directions at the same time. The DS1 offers the designer hidden line plant



views in color, which can involve the routing of 1,000,000 individual components. The workstation also has a multiple viewport facility which allows the user to look at several different views of a design simultaneously. Price is \$89,500. Cadtrak, 823 Kifer Rd., Sunnyvale, CA 94086. Write 129

DATA MANAGEMENT SYSTEM

3-D Graphics Capabilities

In addition to its data management, statistics, and modeling features, the RS/1 has two and three dimensional graphics capabilities. These graphics include plotting of data points, control over rotation and perspective, terminal and plotter independence, and are completely integrated with the rest of the system. As a research system the RS/1 gives the user access to data entry and retrieval, data transformation and analysis, statistical analysis, and curve filling. It has a list of RPL functions and analytic capabilities. Price is \$13,400-\$32,500. BBN Research Systems, 10 Moulton St., Cambridge, MA 02238. Write 148

New Products • PERIPHERALS

LARGE-SCREEN DISPLAY

Gas Panel Technology

The IBM 3290 information panel uses a state-of-the-art flat gas panel to display up to 9,920 characters of data on a distortion-free screen that is 10.7"



by 13.4". The 3290 can simultaneously display text in various character fonts, line drawings, charts and sketches. The large viewing area can be divided into quadrants to provide access to four different applications or data bases in one or more computers. The 3290 attaches to IBM System/370,

30XX, and 4300 series computers, and to the 8100 information system, via an IBM 3274 control unit. Price \$7,100. IBM, 900 King St., Rye Brook, NY 10573. Write 188

AUTOMATIC TESTER/ EXERCISER

Counts Passes And Errors

Designated the Brikon 723S, the test-er/exerciser is aimed at field maintenance, production-test and quality-control applications, and can simultaneously handle up to eight diskette drives. It incorporates a Z80µP tied to 4K bytes of (RAM) and 16K bytes of (EPROM).





(MODEL 201 SHOWN)

Memodyne Low Power Recorders Are Still Doing The Damndest Jobs!

On ocean buoys . . . on weather balloons . . . on off-shore oil rigs . . . unmanned spacecraft. Our low power incremental digital cassette recorders end up doing the damndest jobs in the damndest places.

We've got thousands of them everywhere you can imagine. On the ocean floor. In the atmosphere. Even on ice floes. They're doing boring, unexciting jobs like measuring underwater currents, wind velocities, and all kinds of other activity.

And they stay there unattended for days, weeks, even months, reliably acquiring data in digital form from transducers, converters, computers and all kinds of automated specialized devices. Once it's collected, you can transmit it, process and analyze it or store it for future use.

So, if you have to measure and collect data in some god-forsaken place, or even in your lab, you will find it worthwhile to write for our literature about low power, high density incremental recorders. Also request our brochures on data loggers, high speed microprocessor controlled recorders and thermal printers. By the way, our name's Memodyne . . . just for the record!



220 Reservoir Street
Needham Hgts., MA 02194

Tel. (617) 444-7000 Telex 92-2537

New Products • PERIPHERALS

When connected to one of the drives, the 723S will automatically verify R/W functions using random worst-case data patterns, depending on the recording format (FM/MFM), or using optional 15-byte patterns entered manually by the operator. The tester counts passes and errors, and will display error information such as date pattern, byte number, error byte and expected byte. The 723S can also operate in a read-only mode using diskettes previously recorded with worst-case patterns. Price is \$4195. Brikon, Inc., 22981 Alcalde Dr., Laguna Hills, CA 92653. Write 187

LOGIC ANALYZER

Built-In Data Reduction

Gould Biomation's K105-D is an upto-72-input logic analyzer intended for digital system design and develop-



ment, including software analysis, hardware analysis and hardware and software integration. Slots in the analyzer's chassis accommodate boards to expand or reconfigure its capabilities. Menu-driven screens enable the user to easily set up the logic analyzer. System activity can be sampled synchronously by using eight external clock inputs that can be combined into four Boolean expressions. The K105-D also includes optional disassemblers for the 68000, 8086, 8088, Z80, 8085 and 8080 µPs. The storage system provides additional memory through two formatted 328 Kbyte, 51/4" floppy disk drives. The Storage System can store up to 70 setup and measurement data files for more than one user or for later reuse or reference. Price is \$8,995. Gould Inc., 4600 Old Ironsides Dr., Santa Clara, CA. Write 191

DESKTOP TERMINAL

High Pixel Resolution


The Whizzard 1645 is a monochrome engineering desktop terminal that

provides high resolution interactive graphics concurrent with alphanumeric capability. Digital VT-100/52 compatibility allows users to perform a full range of graphic design functions as well as software development, documentation and report generation. The 1645 is the black and white version of the 1650 color terminal, and it features higher pixel resolution—1280 × 980—and is well-suited for intricate design applications. **Megatek Corp.**, 3187C Airway Ave., Costa Mesa, CA 92626. **Write 157**

INTERACTIVE TOUCH DISPLAY

Evaluation Kits

The 256 and 480-character models are featured with options and accessories for the needs of the evaluating engineer. PEP utilizes DC plasma technology with an invisible optoelectronic switch matrix system,



sequential or random data loading, and both on-board refresh and character generating memories. Each model is available with a choice of four interfaces (parallel, serial RS232, differential TTL or 20mA loop). The 256-PEP measures 11.8"W \times 6.64"H \times 3.5"D and the 480 measures 10.2"W \times 7"H \times 3.75"D. IEE Special Products Division, 7740 Lemona Ave., Van Nuys, CA 91405. Write 185

1/2" STREAMING TAPE DRIVE

Extended Gap

The Vindicator ½" streaming tape drive has auto-loading, drawer mount transport and is engineered with extended gap start/stop performance. Its extended gap feature is front panel selectable, and allows for the optimi-



zation of throughput and capacity. The gap is selectable from 0.6" to 10". Designed for traditional and backup applications, the Vindicator provides either 46 or 92 Mbyte unformatted capacity. Other front panel selectable features are auto-power restart and load on-line commands which bring the drive back to ready state after a power failure without operator intervention. Price is \$2,825.Pertec Peripherals Corp., 3151 Airway Ave., Costa Mesa, CA 92626. Write 189

COMPUTER TERMINAL

Menu Driven Configurations

The Z-29 terminal features on-screen, menu-driven configurations for user-defined parameter settings to meet desired specifications such as even/odd parity, baud rates, and even handshaking. The Z-29 is compatible with ANSI protocol units and the DEC-VT 52. In addition, it can emulate the majority of DEC-VT 100 functions (in the 80-character mode), Lear Siegler ADM-3A and the Hazeltine 1500. The keyboard has 77 type-writer-style keys (including nine special function keys) and a separate 14-



key numeric keypad to simplify mathematical data entry. On-screen editing includes character or line insertion and deletion, erase functions, tab sets and protected fields. Price is \$849. **Zenith Data System**, 1000 Milwaukee Ave., Glenview IL 60025.

Write 190

New Products • COMPONENTS

CLUSTER CONTROLLER

For Dealers and OEM's


The Z-80 based cluster controller with 16K to 64K of dynamically allocated RAM, is capable of handling a variety of interfaces and protocol translation duties. The Diplomat is a multichannel interface switch box that allows a cluster of up to four devices of different protocols or interfaces to be linked together for intercommunication and co-sharing of printers. Any configuration can be accommodated, whether it be multiple µCs and modems with one printer, or one micro and a variety of peripherals. In addition, the Diplomat contains an internal printer driver, capable of driving a Qume or Diablo-style printer directly. Price is \$595.-\$895. Intel, 780 Charcot Ave., San Jose, CA 95131.

Write 205

8- AND 16-BIT CP/M BOARD

For PDP-11 and VAX

The UCP-11 is a board that allows DEC PDP-11 and VAX computers to run CP/M programs. The UCP-11 plugs into the back of a VAX or PDP-11 computer and transforms users' terminals into CP/M workstations ca-



pable of interacting with the DEC computer's peripherals. The UCP-11 acts as a co-processor, operating in parallel with the DEC processor without degrading the latter's performance. The PCP-11 or VAX is called upon only to perform CP/M requested I/O activities. The UCP-11 can be activated from any terminal already attached to a DEC mini network. It is available under RT, TSX-Plus and RSX11 M-Plus. Alloy Computer Products, 12 Mercer Rd., Natick, MA 01760. Write 192

68000 BASED S-100 PROCESSOR BOARD

With FORTH Based Monitor

The MC68000L-based processor board runs at 12MHz but 16, 12MHz




also available. It can address 16 Mbytes of RAM. It features 3 16-bit interval timers that can be used as watch-dog or task switching timers in a multitasking environment. It can accommodate 8K of ROM and is supplied with a powerful FORTH based monitor called bug-FORTH. The onboard language is suitable for many applications and allows the user to write ROMable code. Features include an 8 MHz MC68000L, 16 bit data transfers, and 8 vectored interrupt lines. It supports the standard 246 I/O mapped ports plus an extended 64K of I/O mapped port capability. An extended vectored ID interrupt capability is also available as a jumper option. Price is \$695 in single units, \$349 in OEM quantities. Inner Access Corp., 517-K Marine View, Belmont, CA 94002. Write 195

VIDEO TERMINAL BOARD

μP Based

The Mostek CRT-80E video terminal board is a µP-based video terminal controller system which emulates the DEC VT100 video terminal. The Mostek CRT-80E card features a printer channel, protected fields, seven separate European character sets plus a built-in ASCII character set, 16 user-defined characters and a 120 × 132-point graphics standard. The board also supports both the RS170 composite video and discrete video/ sync formats. The CRT-80E board also includes features such as a programmable-font PROM for up to 768 characters, keyboard-programmable user options stored in EAROM, and five programmable attributes on a per-character basis. Price is \$456. Mostek, 1215 W. Crosby Rd., Carrollton, TX 75006. Write 139



DC100 CARTRIDGE DRIVE HAS SMART I/O

MicroDrive/OEM now features a micro processor based I/O. This unit performs all control and formatting for quick systems integration. A high level command set (22 commands) allows full peripheral status for the model 125I/O. Serial and parallel options are available priced as low as \$400 in OEM qty.

MOYA CORPORATION

9001 Oso, Unit B Chatsworth, Ca. 91311 Tel: (213) 700-1200

Write 60 on Reader Inquiry Card

CONSIDERING A VISION SYSTEM FOR ROBOTICS OR MATERIALS HANDLING?

If so, discuss your systems needs, free of charge, with an expert vision engineer.

Call us (617) 254-1231

COGNEX

COGNEX CORP. 1505 Commonwealth Ave. Boston, MA 02135

Write 61 on Reader Inquiry Card

New Products • COMPONENTS

VME 68000-BASED SBC

No Wait-State 12 MHz Operation

The IV-1600 is a SBC suitable for applications such as industrial robotics, data processing, and high resolution graphics. The system features dual port RAM, which allows access to other CPUs and DM controllers. EE-PROMS in its memory sockets make chip removal and system shut down unnecessary. Price is \$2995.—\$8995. Ironics Inc., 117 Eastern Heights Dr., Ithaca, NY 14850. Write 199

ONE MBIT CMOS ROM

For Speech Synthesis


Applications for the CMOS ROM range from speech synthesis products to language processing devices and hand-held translators. The one M-bit ROM is organized 128K-words by 8bits and uses two-micron technology. Operating on a single five-volt power supply with a ± 10 percent supply tolerance, it has a maximum access time of three usecs. Power dissipation is 60 milliwatts. It draws 12 mAs maximum power when active, and 10 µA in standby mode. The CMOS ROM is available in a 52-pin flat pack (D731000G) and a 40-pin DIP package (D731000C). The 52-pin package, for high-density applications, interfaces directly with industry standard CMOS 8-bit µPs. Price is \$70. NEC Electronics U.S.A. Inc., 550 E. Middlefield Rd., Mountain View, CA 94043.

Write 138

FLOPPY DISK INTERFACE

Duplicates DEC TU-58 Cassette Drive

The Z2800 is a single card floppy disk interface featuring a Z80A processor with 2K RAM and 4K ROM, a floppy disk port and a RS-232C port. It is supplied with firmware to duplicate the DEC TU-58 Cassette Drive protocol and a jumper selectable execu-




tive program to enable users to develop their own customer interface. It is designed to provide storage in applications including: program storage for numeric controls, robotics and process controls, data logging, remote processing, and data entry. The Z2800 memory is expandable to a total of 40K RAM/ROM and a second RS-232C port is available. Baud rates and stop bits for the RS-232C port are selectable. The disk port can accommodate single or double sided, single or double density floppy disks from Shugart and other manufacturers. IBM 3740 and IBM 40 formats are standard. Price is \$195.00. Greco Systems, 10020 Prospect Ave., Suite A15, Santee, CA 92071 Write 140

STEPPING MOTOR DRIVES PACKAGE

Eight Axis

Step-Pak, Model MDU-8 can drive eight stepping motors, currents up to six Amp per motor phase, and occupies only 10.5" of standard 19" rack space. Bi-level driver design offers high performance and efficiency.




Eight connectors on the back panel provide motor connections and limit inputs. The other features are: forced air cooling, internal logic power supply, eight motor current cut-off switches, and three power status LEDs. MDU-8 requires step and direction input signals for each channel and dual motor power supply 10 VDC and 36 VDC. Current requirements depend on the assortment of motors being used. Price is \$3,600. Advanced Control Systems Corp., 24 Teed Dr., Randolph, MA 02368.

Write 144

WRAPPABLE LOGIC BOARD

JEDEC Type "A" Chip Carrier Socket.

The new series 2200 wrappable logic board is specifically designed for the Intel Multibus and features a universal layout for .300", .400", .600" and



.900" spaced devices, plus a 68 pin JEDEC type "A" leadless chip carrier socket with wrappable pin-out. The series 2200 board has an IC field of 28 columns of 53 pins. Board capacity is forty-eight 16 pin IC's, plus 4 columns of .600" spaced devices (or 36 additional 16 pin IC's). Additional I/O includes three 50 pin wrappable headers for female ribbon cable connectors including 25 grounded contacts for twisted pair terminations. Additional features are a common ground plane on both sides in socket area, alternate ground terminals for twisted-pair terminations and hollow terminals for inter-device connections. There are locations for 12 plane-committed electrolytic capacitors. Methode Electronics, Inc., 7447 W. Wilson Ave., Chicago, IL 60656. Write 137

5 OUTPUT SWITCHING POWER SUPPLY

5 DC Output Voltages

The model M7935 is a 240W power supply with 5 DC output voltages. The output, 5VDC at 15 A; +12VDC at 4A; +15VDC at 2A; -15VDC at 2A are developed using CEAG's modular construction system.

The input voltage is 115VAC at 400Hz. The operating temperatures are -40° C to $+85^{\circ}$ C; maximum cold plate temp of $+75^{\circ}$ C using conduction cooling. The size is $10.00'' \times 8'' \times 2V/2''$ high and weight is 9 pounds. Its packaging density is 5 W/in³ and it is 75% efficient.

Model M7935 uses as its main rail the 5V output, and the auxillary outputs achieve high efficiency and synchronization to the main rail through the use of a magnetic amplifier post regulated module. There are no high power switching or linear pass transistors used. The unit is manufactured to MIL-T-28800B and MIL-STD-454. **CEAG Electric Corp.**, 1324 Motor Pkwy, Hauppauge, NY 11788.

Write 210

BIT-SLICE/MICROCODE DEVELOPMENT STATION

Emulates High-Speed Memory

The STEP-7/FITS Firmware Integration and Test Station, an engineering design tool, supports all microprogrammed designs—bit-slices, high speed controllers and digital signal



processing circuits. In addition, any high-performance µP designs get realtime support (to 36nsec access times) from the memory and ROM emulation capabilities of the STEP FITS. The STEP-7 emulates high-speed memory, controls the target system clock and analyzes the logic state of the target. The station is a single unit supported by a full sized CRT terminal and includes 6 slots (expandable to 10) for memory emulation and logic state analyzer boards. Two floppy disk drives and the CP/M operating system provide the instrument with over 1.5 Mbytes of storage for code files, command files, machine state definitions and an on-line command summary. Price is \$8,500. to \$60,000. STEP, 757 N. Pastoria Ave., PO Box 61166, Sunnyvale, CA 94086.

Write 206

HIGH-SPEED DRAM MODULE

For Multibus Systems

A high-density, Multibus-compatible DRAM module with 197 nsec access times and 303-nsec cycle times is offered with up to 512K bytes of onboard RAM, and provides cost-effective, reliable memory expansion for all Intel iSBC80 and iSBC86 systems. Moreover, it is designed to allow even denser on-board memory-it can be upgraded to 2 Mbytes using compatible 256K DRAM chips, when these become available. The TMM40020 operates in an address space of up to 16MB and supports word transfers, as well as high, swap, and low-byte transfers. The lower and upper memory addresses are independently selectable in 4K-byte sections. It features a control-status register with selectable I/O address. Other features include LEDs which indicate an error, as well as the bank of the failing DRAM chip. The module also permits the use of a battery backup and ROM overlay. Price is \$925–\$1795.

Texas Instruments Semiconductor Group, Literature Response Ctr. (SC–404) P.O. Box 401560, Dallas, TX 75240.

Write 207

VIDEO DIGITIZER BOARDS

Includes Hardware Vector Generator

The VAF-512 and QVAF-512 cards are designed to work with the existing Matrox RGB-GRAPH and QRGB-GRAPH frame buffers to provide a complete Multibus or Q-bus 512 × 512 × 8 bit imaging system. The VAF-512 board provides two features




over the video I/O conversion. A high speed (800 sec pixel) hardware vector generator is provided for drawing graphics in the frame buffer memory. The VAF-512 contains an on-board 10MHz A/D flash converter for "grabbing" entire fields of video data with a spatial resolution of 512×512 dots. A contrast control circuit allows the user to focus the digitizing range of the A/D converter to that part of the vde signal which contains most of the useful information. The VAF-512 also contains an on-board hardware vector generator. Price is \$2150. Matrox, 5800 Andover Ave., T.M.R., Que., H4T 1H4, Canada. Write 142

S-100 SLAVE

Available In Four Versions

The CPS-MX features memory transfer rates of 517 Kbytes/sec, DMA, memory mapping and host to slave requests via interrupt control. Fully compatible with Turbo-DOS, the slaves are available in four versions, synchronous or asynchronous serial




port, 4MHz or 6MHz. The CPS-MX also allows the bus master to utilize slave memory at the user's discretion. part, 4MHz or 6MHz. The CPS-MX also allows the bus master to utilize slave memory at the user's discretion. The slave then acts as a 65K RAM card. The CPS-MX integrates with Intercontinental's line of S-100 products: CPZ-48000SBC with 64K on board RAM, 4 I/O channels, memory management; on board floppy controller, DMA and vectored priority interrupts; and 256K bank selectable or contiguous memory. A complete line of personality boards allows interface to a wide body of peripherals. Price is \$475.00. Intercontinental Micro Systems, 1733 S. Douglass Rd., Anaheim, CA 92806. Write 194

RANDOM ACCESS MEMORY

Buffer Storage Applications

The 1024-bit Random Access Memory is organized as 1024 words by 1 bit. Called the MCM10415/10415A, it is designed with a separate data in line, a non-inverting data output and an active-low chip select. **Motorola**, P.O. Box 20912, Phoenix, AZ 85036. Write 197



VIDEO TERMINAL BOARD

This board uses a 6502 Microprocessor and a 6545-1 CRT controller. It displays 80 columns by 25 lines of UPPER and lower case characters. Data is transferred by RS232 at rates of 110 baud to 9600 baud. Assembled and tested #82-018A \$199.95 We have a complete line of Industrial Control Products. 0EM Pricing Available.

JOHN BELL ENGINEERING, INC. 1014 Center St., San Carlos, CA 94070 (415) 592-8411

Write 62 on Reader Inquiry Card



AT 15/8" HIGH, TEAC FD-55 SERIES 5 1/4" FLOPPY DISK

drives use half the space and run cool at half the power of conventional drives. High-reliability, lownoise brushless DC motors provide an MTBF of over 10,000 hours, backed by a one-year parts and labor warranty.

FD-55A • 48tpi

FD-55B

• 48tpi

FD-55E • 96tpi

FD-55F

• 96tpi

 40 track • 250KB

• 40 track • 500KB

• 80 track • 500KB

• 80 track

double side

single side

double side
 single side

• 1MB

Power Requirements:

DC +12V \pm 5% 0.3A typical, 0.7A max.

DC + 5V \pm 5% 0.5A typical, 0.7A max.

Phone, write or wire TEAC Corporation of America for complete technical data, price and delivery.



TEAC Corporation of America Industrial Products Division 7733 Telegraph Road Montebello, CA 90640 213/726-0303

> © 1982 TEAC Corp. MP82501M

New Literature



Response System Brochure. The pamphlet describes RESPONSE, an information processing system which provides data entry, word processing, data base management, and distributed data processing at remote sites. The system allows network communication to continue when the host CPU is down and is designed for business applications. All peripherals and terminals appear as locally attached devices to any processor in the network. Write 263 Paradyne

Computer Supplies. The 4-page brochure describes retail merchandiser displays and starter packs of computer supplies. The merchandisers require no computer expertise by the sales personnel. All displays include restocking information.

Write 262 National Systems Corp.





DC Power Supplies. Different types of HP-IB (IEEE-488) power supplies are highlighted in the brochure which features products for the automatic test-system designer. It is a guide for selecting HP-IB power supplies, which are organized into three major categories; general-purpose, precision, and bipolar-system supplies.

Hewlett Packard

Write 255



New Power Conditioners Catalog. The catalog features power conditioners intended to guard voltage-sensitive equipment, including micro/minicomputers, POS and data terminals, process control systems and mainframe computers. Voltage transformers offer voltage regulation and two types of Solatron/Acuvolt Line Conditioners are also described. Write 257 Sola Electric

The Profitable Resale Telephone Network, Defined.



Telephone Network Brochure. The pamphlet details de-regulation in the telecommunications industry which now permits entrepreneurs, interconnect companies, the hotel industry, and others to profitably re-sell the services of common carriers, satellite networks, AT&T, and others. The publication highlights features of tandem switching systems, automatic route selection and station message accounting. Harris Corp. Write 260

Computer Accessory Catalog. The product/manufacturer catalog contains products, price reductions, and editorials on computer products and maintenance. Featured are two security devices; Inmac's new Station II for Apple II computers, and a locking diskette file for floppies as well as business accounting forms in continuous feed mini-packs.

Inmac

Write 259

New Literature

IC Packaging Systems Catalog. A 28 page catalog detailing Multibus compatible IC packaging systems includes 11 card rack sizes for packaging up to 26 boards, and sideplate kits for mounting racks into cabinets. New Multibus backplane features are GND/GND/GND bus lines and resistors of equal value at both ends of the busses. Data sheets contain information on accessory items.

Mupac

Write 266

μP-Based Programmable Controllers. The brochure gives benefits, application information and specifications for three EPTAK PCs, the EPTAK 210, 220 and 240. There is a portable programmer common to all three models that retains programs for 10 years without an external power source, has I/O tracks, I/O modules and a DAD/M.

Eagle Signal Controls

Write 254

Euro-Connector Catalog. Methode Electronics, Inc., describes the firm's line of Din-41612 Euro-connectors in a 12-page catalog. DIN-41612 types R, B, C, D, F, G, and H on .100" (2.54 mm) centers with 2, 3, and 4 row pin and socket configurations are presented with specifications, dimensional drawings and application data. Featured in the catalog is the new type "R (inverted)" version for backplanes and pressfit applications.

Methode Electronics Inc.

Write 253

Laboratory Tape System. Honeywell Test Instruments high density digital laboratory tape system, HD-96, is detailed in a brochure containing diagrams of its capstan drive and illustrations of components. Also covered are the panel and transport controls and indicators, record/reproduce heads, reproduce amplifier/bit synchronizer, and balanced tension transport

Honeywell

Write 252

Digital Storage Bulletin. The subject of this eight-page bulletin from Gould Inc. is a dual-trace digital storage oscilloscope. Features include 25% pre-trigger viewing, split-trace facility, maximum sensitivity of 100 uV/cm, and high vertical and horizontal resolution via a 10-bit × 4K store. The scope is capable of selecting stored waveform portions and expanding them to X10 vertically and X50 horizontally.

Gould Inc.

Write 251

Communications Systems Brochure. The RCS-10 Nurse Call Communications System is explained in a 6-page brochure from Bunting. The RCS-10 addresses, scans, receives, stores, displays and transmits information throughout the hospital. Included are automatic staff locators which emit an inaudible high frequency signal that allows the central console operator to scan and locate the entire nursing staff

Bunting Inc.

Write 250













Cube

Standard

ULTIB

ERYTHING YOU NEED FOR MULTIBUS COMPATIBLE PACKAGING IN ONE RELIABLE PRODUCT FAMILY

Mupac's family of Multibus compatible card racks offers you the most flexible, compact and reliable Multibus packaging system available today. Card racks and expanders provide 19 different configurations for 2 to 26 active boards. Other parts of the system include wire wrap panels for prototyping and interface applications plus IVO panels for bus extension.

We'll be happy to send you complete details along with our latest catalog. Please write or call toll free 800-225-3998. (In Massachusetts 588-6110.) TWX (710) 345 8458. Mupac Corporation, 10 Mupac Drive, Brockton, Massachusetts 02401.



Mupac Corporation, 10 Mupac Drive, Brockton, Massachusetts 02401

Write 64 on Reader Inquiry Card


THE OEM SHAFT ENCODER

With Over 12 Years Of Manufacturing Excellence

- Special 1 day delivery available
 - Standard, heavy duty and explosion-proof housings
 - 1 to 2,540 pulses per shaft revolution
 - Costs less than any comparable line
 - Over 25 models

(208) 263-8541

WRITE OR PHONE FOR OUR FREE COMPLETE SPECIFICATION CATALOG



1601B Dover Road • Sandpoint, ID 83864 TWX 510-776-1595

Write 65 on Reader Inquiry Card

New Literature



DEC Terminal Brochure. The pamphlet provides specifications on the ANSI-conforming terminal and uses full-color product photography and schematic art. It describes features of the AVT Terminal which include four pages of memory standard, 43 programmable functions, switchable 80/132-column format; windowing, and multiple computer capabilities.

Write 273 **Human Designed Systems**



Short Form Catalog. The 12-page illustrated catalog covers MICOM's data communications equipment. The booklet includes brief descriptions of most product lines—data concentrators, data PABXs, local networking equipment, modems, multiplexors, and local datasets, as well as complete U.S. pricing for all currentlyavailable products. MICOM Systems, Inc.

IC Publications. Four publications are available to assist the design engineer in developing gate array and semi-custom ISO-CMOS or silicon-on-sapphire LSI circuits. The literature presents an analysis and description of the various routes available to the designer. If desired, CTI will design, verify, fabricate, test and deliver a packaged IC to MIL-STD-883B. The customer can supply "black box" requirements or his own created logic.

Circuit Tech. Inc.



Engineering Manual and Purchasing Guide. Allied Electronics' edition is a guide for anyone who uses or specifies electronic parts. Its 320 pages include "best values" throughout the book on lines of components. It contains illustrations, dimensions, technical data and specifications, descriptions and prices (as well as bulk pricing for large-quantity buyers).

Write 272 **Allied Electronics**

Computer Graphics Pamphlet. The bro-

chure describes computer graphics services

in the mechanical design field. Listed are

applications such as machine design and

numerical control, product design, HVAC

systems, instrumentation, and plant lay-

out. Included are examples of experiences

in software development. Additional ex-

amples include 2-D to 3-D conversions

and generation of parts lists and bills of

Write 271

materials from drawings.

Minigraph, Inc.



1983 Product Selection Guide. The catalog includes basic specifications and performance data for standard PMI products. The reference guide contains information about the following product groups: operational amplifiers, voltage comparators and PCM repeater amplifiers. Additionally, selection charts show the matrices of primary characteristics of operational amplifiers and digital-to-analog converters.

Precision Monolithics Write 264

Advertiser Index

Analog & Digital Peripherals .103 Albany International .113 Amdek .51 ATE East .78 Audiotronics .18
John Bell Engineering123
CalComp 84,85 Central Data 57 Cermetek 43 Cognex 121 Control Data 24,25 Cosmos Systems 77
Dataram.45Data Translation.46Digital Electronics.23Distributed Logic.89Distributed Computer Systems102DY4.14
Electronic Trend Publications .80 Encoder Products
Flagstaff Engineering

Genisco
Hecon102
Hughes13
Imperial Technology103
Intelligent Systems70
Interdesign 62
International Microcircuits 58
Invention Marketing123
Kaman Instrumentation40
Kennedy
Lenco
Lundy
Marinco
Matra Design Systems 68,69
MDB Systems2
Memodyne119
Metacomp
Methode Electronics
Modgraph
Monitek
Monolithic Systems
Mouse House
Moya
Mupae

Nicolet Zeta39
Peritek
Quadram
Raster Technologies83Reference Magazine20Renco21
Scherer's Mini Computer Mart
Teac124Tecmar48Teledyne Electronics113Thomas Engineering40
Universal Semiconductor 67
Versatec 5



NOW A 150-NS 16K CMOS STATIC RAM IN 3 POPULAR PIN-OUTS

Part No.	Organization	Access	Curre	Supply Voltage	
SRM2016C15	2Kx8	150ns	50uA	35mA	5V
SRM2017C15	2Kx8	150ns	50µA	35mA	5V
SRM2018C15	2Kx8	150ns	50µA	35mA	5V
SRM2016C20	2Kx8	200ns	100uA	35mA	5V
SRM2017C20	2Kx8	200ns	100uA	35mA	5V
SRM2018C20	2Kx8	200ns	100uA	35mA	5V
SRM2016C25	2Kx8	250ns	100µA	35mA	5V
SRM2017C25	RM2017C25 2Kx8		100uA	35mA	5V
SRM2018C25	2Kx8	250ns	100uA	35mA	5V

Get the best of both worlds — CMOS power at near NMOS speeds. And get the total commitment to quality that has made the name of Epson a byword for performance and reliability around the world.

If speed isn't that critical, 200-ns and 250-ns versions of these same $2K \times 8$ RAMS are available to meet your production

schedules. And for applications where power conservation is truly critical, ask about our family of 1.5V 4K RAMS which draw only 3uA (standby) and .03mA (operating).

Call or write today for complete technical and pricing information.

EPSON

EPSON AMERICA, INC.

OEM Products Division
Semiconductor Group
3415 Kashiwa Street, Torrance,
CA 90505 (213) 534-0360

AND 16 LOCAL REPS TO SERVE YOU ● AL, Remco (205) 533-3763 **● AZ,** Relcom (602) 893-1209 **● CA,** Abbot (415) 968-2265, Relcom (213) 340-9143 **● CO,** Wescom (303) 422-7619 **● FL,** Askland (305) 987-1074 **● IL,** Tech. Sls. (312) 991-6600 **● MA,** Marathon (617) 435-6984 **● MI,** Jensen (313) 643-0506 **● MN,** Furber-Smith (612) 881-3620 **● MO,** CF Elect. (314) 946-8500 **● NY,** JMR Sls. (201) 727-5335 **● OH,** Baier (216) 461-6161 **● PA,** Knowles (215) 947-5641 **● TX,** Delta (214) 358-4288 **● VA,** Boyle (703) 620-9558 **● VA,** Venture (206) 454-4594.

