

DMC11

FREE RUNNING TESTS
MD-11-DZDMH-B

EP-DZDMH-B-DL-A
COPYRIGHT © 76-77
FICHE 1 OF 1

AUG 1977
digital
MADE IN USA

The microfiche card contains a grid of frames. The first column on the left contains small, illegible text, likely identifying information for each frame. The subsequent columns contain test data, including numerical values, waveforms, and other graphical representations. The data is organized into a grid of approximately 10 columns and 15 rows. The right half of the card is mostly blank, with a few small, illegible markings.

ECP:0ZDMGCSE0
PCP10 PAGE: 0001

00010000

770712

PCP10 411

2:H0R1DZDMHBSE0

00010000

770712

IDENTIFICATION

PRODUCT CODE: MAINDEC-11-DZDMH-B-D
PRODUCT NAME: DMC11 FREE RUNNING TESTS
DATE: MAY 1977
MAINTAINER: DIAGNOSTICS
AUTHOR: FAY BASHAW

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may only be used or copied in accordance with the terms of such license.

Digital Equipment Corporation assumes no responsibility for the use or reliability of its software on equipment that is not supplied by Digital.

Copyright (C) 1976, 1977 by Digital Equipment Corporation

1. ABSTRACT

The function of the DMC11 diagnostics is to verify that the option operates according to specifications. The diagnostics verify that there are no malfunctions and that all operations of the DMC11 are correct in its environment.

Parameters must be set up to alert the diagnostics to the DMC11 configuration. These parameters are contained in the STATUS TABLE and are generated in two ways: 1) Manual Input - the operator answers questions. 2) Autosizing - the program determines the parameters automatically.

DZDMH tests the DMC11-AR and DMC11-AL micro-processors (M8200-YA and M8200-YB), or the KMC11 micro-processor (M8204). Free running tests are performed. A line unit (M8201 or M8202) must be installed. DZDMH can be used as a heat test diagnostic by manufacturing.

Currently there are five off line diagnostics that are to be run in sequence to insure that if an error should occur it will be detected at an early stage.

NOTE: Additional diagnostics may be added in the future.

The five diagnostics are:

1. DZDMC [REV] Basic W/R and Micro-processor tests
2. DZDME [REV] DDCMP Line unit tests
3. DZDMF [REV] BITSTUFF Line unit tests
4. DZDMG [REV] CROM and Jump tests
5. DZDMH [REV] Free-running tests (Heat test tape)

2. REQUIREMENTS

2.1 EQUIPMENT

Any PDP11 family CPU (except an LSI-11) with minimum 8k memory
ASR 33 (or equivalent)
DMC11-AR with DMC11-DA or DMC11-FA or
DMC11-AL with DMC11-MA or DMC11-MD

2.2 STORAGE

Program will use all 8k of memory except where ABL and BOOTSTRAP LOADER reside. Locations 1500 to 1640; contain the "STATUS TABLE" information which is generated at start of diagnostics by manual input (questions) or automatically (auto-sizing). This area is an overlay area and should not be altered by the operator.

3. LOADING PROCEEDURE

3.1 METHOD

All programs are in absolute format and are loaded using the ABSOLUTE LOADER. NOTE: if the diagnostics are on a media such as DISK, MAGTAPE, DECTAPE, or CASSETTE; follow instructions for the monitor which has been provided on that specific media.

ABSOLUTE LOADER starting address *500

MEMORY * SIZE

4k	17
8k	37
12k	57
16k	77
20k	117
24k	137
28k	157

- 3.1.1 Place address of ABS loader into switch register.
(also place 'HALT' SW up)
- 3.1.2 Depress 'LOAD ADDRESS' key on console and release.
- 3.1.3 Depress 'START KEY' on console and release (program should now be loading into CPU)

4. STARTING PROCEDURE

- a. Set switch register to 000200
- b. Depress 'LOAD ADDRESS' key and release
- c. Set SWR to zero for 'AUTO SIZING' or SWR bit0=1 for manual input (questions) or SWR bit7=1 to use existing parameters set up by a previous start or a previously run DMC11 diagnostic.
- d. Depress 'START KEY' and release. The program will type Maindec Name and program name (if this was the first start up of the program) and also the following:

MAP OF DMC11 STATUS

PC	CSR	STAT1	STAT2	STAT3
---	---	-----	-----	-----
001500	160010	145310	177777	000000
001510	160020	145320	177777	000000

The program will type 'R' and proceed to run the diagnostic. The above is only an example. This would indicate the status table starting at add. 1500 in the program. In this example the table contains the information and status of two DMC11'S. THE STATUS TABLE MUST BE VERIFIED BY THE USER IF AUTO SIZING IS DONE. For information of status table see section 8.4 for help.

If the diagnostic was started with SW00=1 indicating manual parameter input then the following shows an example of the questions asked and some example answers:

HOW MANY DMC11'S TO BE TESTED?1

01
 CSR ADDRESS?160010
 VECTOR ADDRESS?310
 BR PRIORITY LEVEL? (4,5,6,7)?5
 DC'S MICRO-PROCESSOR HAVE CRAM? (Y OR N)N
 WHICH LINE UNIT? IF NONE TYPE "N". IF MB201 TYPE "1", IF MB202 TYPE "2"?1
 IS THE LOOP BACK CONNECTOR ON?Y
 SWITCH PAC#1 (DDCMP LINE#)?377
 SWITCH PAC#2 (BMB73 BOOT ADD)?377

Following the questions the status map is printed out as described above. the information in the map reflects the answers to the questions. If the diagnostic was started with SW00=0 and SW07=0 (AUTO-SIZING) then no questions are asked and only the status-map is printed out. If AUTO-SIZING is used the status information must be verified to be correct (match the hardware). if it does not match the hardware the diagnostic must be restarted with SW00=1 and the questions answered.

4.1 CONTROL SWITCH SETTINGS

SW 15 Set: Halt on error
SW 14 Set: Loop on current test
SW 13 Set: Inhibit error print out
SW 12 Set: Inhibit type out/abell on error.
SW 11 Set: Inhibit iterations. (quick pass)
SW 10 Set: Escape to next test on error
SW 09 Set: Loop with current data
SW 08 Set: Catch error and loop on it
SW 07 Set: Use previous status table.
SW 06 Set: Halt in ROMCLK routine before clocking
micro-processor
SW 05 Set: Reserved
SW 04 Set: Reserved
SW 03 Set: Reselect DMC11's desired active
SW 02 Set: Lock on selected test
SW 01 Set: Restart program at selected test
SW 00 Set: Build new status table from questions. (If SW07=0
and SW00=0 a new status table is built by
auto-sizing)

Switch 06 and 08-15 are dynamic and can be changed as needed while the diagnostic is running. Switches 00-03 and switch 07 are static, and are used only on starting or restarting the diagnostic.

4.1.2 SWITCH REGISTER OPTIONS (at start up)

SW 01 RESTART PROGRAM AT SELECTED TEST. It is strongly suggested that at least one pass has been made before trying to select a test, the reason being is that the program has to clear areas and set up parameters. When this switch is used the diagnostic will ask "TEST NO.?" Answer by typing the number of the test desired and carriage return to begin execution at the selected test.

SW 02 LOCK ON SELECTED TEST. This switch when used with SW01 will cause the program to constantly loop on the selected test. Hitting any key on the console will let it advance to the next test and loop until a key is hit again. If SW02=0 when SW01 is used. The program will begin at the selected test and continue normal operations.

SW 03 RESELECT DMC11'S DESIRED ACTIVE. Please note that a message is typed out for setting the switch register equal to DMC11's active. this means if the system has four DMC11s; bits 00,01,02,03 will be set in loc 'DMACTV' from the switch register. Using this switch(SW00) alters that location; therefore if four DMC11s are in the system ***DO NOT*** set switches greater than SW 03 in the up position. this would be a fatal error. do not select more active DMC11s than there is information on in the status table.

METHOD: A: Load address 200
 B: Start with SW 00=1
 C: Program will type message
 D: Set a switch for each DMC desired active.
 EXAMPLE: If you have 4 DMC's but only want to run the first and the last set SWR bits 0 and 3 = 1. PRESS CONTINUE
 E: Number (IF VALID) will be in data lights (excluding 11/05)
 F: Set with any other switch settings desired. PRESS CONTINUE.

4.1.3 DYNAMIC SWITCHES

ERROR SWITCHES

1. SW 12 Delete print out/bell on error.
2. SW 13 Delete error printout.
3. SW 15 Halt on the error
4. SW 08 Goto beginning of the test(on error).
5. SW 10 Goto next test(on error).

SCOPE SWITCHES

1. SW06 Halt in ROMCLK routine before clocking micro-processor instruction. This allows the operator to scope a micro-processor instruction in the static state before it is clocked. Hit continue to resume running.
2. SW09 (if enabled by 'SCOPI') on an error; If an '*' is printed in front of the test no. (ex. *TEST NO. 10) SW09 is incorporated in that test and therefore SW09 is usually the best switch for the scope loop (SW14=0, SW10=0, SW09=1, SW08=0). If SW09 is not enabled; and there is a HARD error (constant); SW08 is best. (SW14=1,0, SW10=0, SW09=0, SW08=1). for intermittent errors; SW14=1 will loop on test regardless of error or not error. (SW14=1, SW10=0, SW09=0, SW08=1,0)
3. SW11 Inhibit iterations.
4. SW14 Loop on current test.

4.2 STARTING ADDRESS

Starting address is at 000200 there are no other starting addresses for the DMC11 diagnostics. (See Section 4.0)

NOTE: If address 000042 is non-zero the program assumes it is under ACT11 or XXDP control and will act accordingly after all available DMC11's are tested the program will return to 'XXDP' or 'ACT-11'.

5. OPERATING PROCEDURE

When program is initially started messages as described in section 4.0 will be printed, and program will begin running the diagnostic:

5.2 PROGRAM AND/OR OPERATOR ACTION

The typical approach should be

1. Halt on error (via SW 15=1) when ever an error occurs.
2. Clear SW 15.
3. Set SW 14: (loop on this test)
4. Set SW 13: (inhibit error print out)

The TEST NUMBER and PC will be typed out and possibly an error message (this depends on the test) to give the operator an idea as to the source of the problem. If it is necessary to know more information concerning the error report; LOOK IN THE LISTING for that TEST NUMBER which was typed out and then NOTE THE PC of the ERROR REPORT this way the EXACT FUNCTION of the test CAN BE DETERMINED.

6. ERRORS

As described previously there will always be a TEST NUMBER and PC typed out at the time of an error (providing SW 13=0 and SW 12=0). In most cases additional information will be supplied in the the error message to give the operator an indication of the error.

6.2 ERROR RECOVERY

If for some reason the DMC11 should 'HANG THE BUS' (gain control of bus so that console manual functions are inhibited) an init or power down/up is necessary for operator to regain control of cpu. If this should happen; look in location 'TSTNO' (address 1226) for the number of the test that was running at the time of the catastrophic error. In this way the operator will have an idea as to what the DMC11 was doing at the time of the error.

7. RESTRICTIONS

7.1 STARTING RESTRICTIONS

See section 4. (PLEASE)
Status table should be verified regardless of how program was started. Also it is important to use this listing along with the information printed on the TTY to completely isolate problems.

7.2 OPERATING RESTRICTIONS

The first time a DMC11 diagnostic is loaded into core and run the STATUS TABLE must be set up. This is done by manual input (SW00=1) or by autosizing (SW00=0 and SW07=0). Thereafter however the status table need not be setup by subsequent restarts or even loading the next DMC diagnostic because the STATUS TABLE is overlayed. The current parameters in the STATUS TABLE are used when SW07=1 on start up.

7.3 HARDWARE CONFIGURATION RESTRICTIONS

DMC11(MB200)- Jumper W1 must be in, and switch 7 of E76 must be in the OFF position.

KMC(MB204)- Jumper W1 must be in.

LINE UNIT(MB201)- Jumpers W1, W2, and W4 must be IN. Jumpers W3 and W5 must be OUT. SW8 of E26 must be in the ON POSITION.

LINE UNIT (MB202)- Jumper W1 must be in. SW8 of E26 must be in the OFF position.

8. MISCELLANEOUS

8.1 EXECUTION TIME

All DMC11 device diagnostics will give an 'END PASS' message (providing no errors and sw12=0) within 4 mins. This is assuming SW11=1 (DELETE ITERATIONS) is set to give the fastest possible execution. The actual execution time depends greatly on the PDP11 CPU configuration and the amount of memory in the system.

8.2 PASS COMPLETE

NOTE: EVERY time the program is started; the tests will run as if SW11 (delete iterations) was up (=1). This is to 'VERIFY NO HARD ERRORS' as soon as possible. Therefore the first pass -EACH TIME PROGRAM IS STARTED- will be a 'QUICK PASS' until all DMC11's in system are tested. When the diagnostic has completed a pass the following is an example of the print out to be expected.

```
END PASS DZDMH CSR: 175000 VEC: 0300 PASSES: 000001
ERRORS: 000000
```

NOTE: The pass count and error counts are cumulative for each DMC11 that is running, and are set to zero only when the diagnostic is started. Therefore after an overnight run for example, the total passes and errors for each DMC11 since the diagnostic was started are reflected in PASSES: and ERRORS:.

9.4 KEY LOCATIONS

RETURN (1214) Contains the address where program will return when iteration count is reached or if loop on test is asserted.

NEXT (1216) Contains the address of the next test to be performed.

TSTNO (1226) Contains the number of the test now being performed.

RUN (1316) The bit in 'RUN' always points to the DMC11 currently being tested. EXAMPLE: (RUN) 1302/0000000001000000 Means that DMC11 no.06 is the DMC11 now running.

DMCROO-DMCR17
DMSTOC-DMST17
(1500)-(1640)

These locations contain the information needed to test up to 16 (decimal) DMC11s sequentially. they contain the CSR, VECTOR and STATUS concerning the configuration of each DMC11.

DMACTV (1306) Each bit set in this location indicates that the associated DMC11 will be tested in turn. EXAMPLE: (DMACTV) 1276/0000000000011111 means that DMC11 no. 00,01,02,03,04 will be tested. EXAMPLE: (DMACTV) 1276/0000000000010001 Means that DMC11 no. 00,04 will be tested.

DMCSR (1404) Contains the CSR of the current DMC11 under test.

9.4A 'STATUS TABLE' (1500-1640)

The table is filled by AUTO SIZING or by the manual parameter input (questions) as described previously. Also if desired by user; the locations may be altered by hand (toggled in) to suit the specific configuration.

The example status map shown below contains information for two DMC11'S. the table can contain up to 16 DMC11'S. Following the map is a description of the bits for each map entry

MAP OF DMC11 STATUS

PC	CSR	STAT1	STAT2	STAT3
001500	160010	145310	177777	000000
001510	160020	016320	000000	000000

Each map entry contains 4 words which contain the status information for 1 DMC11. The PC shows where in core memory the first of the 4 words is. In the example above the first DMC'S status is in locations, 1500, 1502, 1504, and 1506. The second DMC status is located at 1510, 1512, 1514, and 1516. The information contained in each 4 word entry is defined as follows:

CSR: Contains DMC11 CSR address

STAT1: BITS 00-08 IS DMC11 VECTOR ADDRESS
BIT15=1 MICRO-PROCESSOR HAS CROM
BIT15=0 MICRO-PROCESSOR HAS CROM
BIT14=1 TURNAROUND CONNECTOR IS ON
BIT14=0 NO TURNAROUND CONNECTOR
BIT13=0 LINE UNIT IS AN M8201
BIT13=1 LINE UNIT IS AN M8202
BIT12=1 NO LINE UNIT
BITS 09-11 IS DMC11 BR PRIORITY LEVEL

STAT2: LOW BYTE IS SWITCH PAC#1 (DDCMP LINE NUMBER)
HIGH BYTE IS SWITCH PAC#2 (BM873 BOOT ADD)

STAT3: BIT0=1 PERFORM FREE RUNNING TESTS ON KMC
(MUST BE SET MANUALLY. SEE TEST 1)
BIT1=0 DMC11-AR (LOW SPEED)
BIT1=1 DMC11-AL (HIGH SPEED)

8.5 METHOD OF AUTO SIZING

8.5.1 FINDING THE CONTROL STATUS REGISTER.

The auto-sizing routine finds a DMC11 as follows: It starts at address 160000 and tests all address in increments of 10 up to and including address 167760. If the address does not time out, the following is done, the first CROM address is written to a 125252 then it is read back. If it contains a -1 or 125252 or a 626 or 16520 a DMC11 or KMC11 has been found, if not, the address is updated by 10 and the search continues. A -1 indicates a DMC11 with no CROM, a 125252 indicates a KMC11 with CROM, a 626 indicates a DMC11-AL and a 16520 indicates a DMC11-AR. Further tests are performed at this point to determine which line unit, if any, is installed, if a loop-back connector is installed and various switch settings on the line unit. THIS IS WHY THE STATUS TABLE MUST BE VERIFIED BY THE USER AND IF ANY OF THE INFORMATION DOES NOT AGREE WITH THE HARDWARE THE DIAGNOSTIC MUST BE RESTARTED AND THE QUESTIONS MUST BE ANSWERED. All DMC11's in the system will be found by the auto-sizer. If it does not find a DMC11 the diagnostic must be restarted and the questions answered.

8.5.2 FINDING THE VECTOR AND BR LEVEL

The vector area (address 300-776) is filled with the instruction IOT and '+2' (next address). The processor status is started at 7 and the DMC is programmed to interrupt. The PS is lowered by 1 until the DMC interrupts, a delay is made and if no interrupt occurs at PS level 3 (because of a bad DMC11) the program assumes vector address 300 at BR level 5 and the problem should be fixed in the diagnostic. Once the problem is fixed; the program should be re-setup again to get correct vector. If an interrupt occurred; the address to which the DMC11 interrupted to is picked up and reported as the vector. NOTE: if the vector reported is not the vector set up by you; there is a problem and AUTO SIZING should not be done.

8.5 SOFTWARE SWITCH REGISTER

If the diagnostic is run on an 11/04 or other CPU without a switch register then a software switch register is used to allow user the same switch options as described previously. If the hardware switch register does not exist or if one does and it contains all ones (177777) this software switch register is used.

Control:

To obtain control at any allowable time during execution of the diagnostic the operator types a CTRL G on the console terminal keyboard. As soon as the CTRL G is recognized, by the diagnostic, the following message will be displayed:

SWR=XXXXXX NEW?

Where XXXXXX is the current contents of the software switch register in octal. The software control routine will then await operator action. At which time the operator is required to type one or more of the legal characters: 1) 0 - 7, 2) line feed(<LF>), 3) carriage return(<CR>), or 4) control-U (CTRL U). No check is made for legality. If the input character is not a <LF>, <CR>, or CTRL U it is assumed to be an octal digit.

To change the contents of the SSR the operator simply types the new desired value in octal - leading zeros need not be typed. And terminates the input string with a <CR> or <LF> depending on the program action desired as described below. The input value will be truncated to the last 6 digits typed. At least one digit must be typed on any given input string prior to the terminator before a change to the SSR will occur.

When the input string is terminated with a <CR> the diagnostic will continue execution from the point at which it was interrupted. If a <CR> is the only thing typed the program will continue without changing the SSR. The <LF> differs from the <CR> by restarting the program as if it were restarted at address 200.

If a CTRL U is typed at any point in the input string prior to the terminator the input value will be disregarded and the prompt displayed (SWR = XXXXXX NEW?).

To set the SSR for the starting switches, first load the diagnostic, then hit CTRL G, then start the diagnostic.

DZDMH LST

B02

DECDOC VER 00.04 11-JUL-77 12:36 PAGE 01 PAGE: 0014

DOCUMENT

DZDMH LST

COPYRIGHT 1977
DIGITAL EQUIPMENT CORPORATION
MAYNARD, MASS. 01754

6 MAINDEC-11-DZDMH-B DMC11 FREE RUNNING TESTS
 COPYRIGHT 1976, DIGITAL EQUIPMENT CORP., MAYNARD, MASS. 01754

1666 ***** TEST 1 *****
 FREE RUNNING FLAG MODE DATA TEST
 TRANSMIT A MESSAGE AND VERIFY THE RECEIVED DATA
 LINE UNIT LOOP IS SET FOR THIS TEST.
 ALL FOLLOWING TESTS ARE FREE RUNNING AND ARE PERFORMED
 ONLY ON DMC'S WITH LINE UNITS. IF YOU WISH TO PERFORM
 THESE FREE RUNNING TESTS ON A KMC (NORMALLY THE FREE RUNNING TESTS
 WILL FAIL ON A KMC, THE TIMER IS TOO FAST) THEN YOU MUST
 MANUALLY SET BIT0 OF STAT3 IN THE STATUS MAP. ALSO THE KMC
 MUST HAVE THE MICRO-CODE LOADED BY PREVIOUSLY RUNNING
 DZDMG TEST 2 AND THEN LOADING AND STARTING DZDMH
 WITH SWITCH 7 = 1

1857 ***** TEST 2 *****
 OVERUN TEST
 IN FREE RUNNING MODE SEND MESSAGE WITH NO RECEIVE
 BUFFER AVAILABLE, VERIFY THAT AN OVERRUN ERROR OCCURS

1937 ***** TEST 3 *****
 LOST DATA TEST
 IN FREE RUNNING MODE SEND A MESSAGE LONGER THAN THE RECEIVE
 BUFFER, VERIFY THAT A LOST DATA ERROR OCCURS.

2003 ***** TEST 4 *****
 TRANSMIT NON-EXISTENT MEMORY TEST
 IN FREE RUNNING MODE, LOAD A TRANSMIT BA THAT WILL TIME OUT
 VERIFY THAT A NON-EXISTENT MEMORY ERROR OCCURS

2066 ***** TEST 5 *****
 RECEIVE NON-EXISTENT MEMORY TEST
 IN FREE RUNNING MODE, LOAD A RECEIVE BA THAT WILL TIME OUT
 VERIFY THAT A NON-EXISTENT MEMORY ERROR OCCURS

2132 ***** TEST 6 *****
 PROCESSOR ERROR TEST
 IN FREE RUNNING MODE, DO A BASE TRANSFER REQUEST AFTER A
 BASE HAS BEEN SET UP, VERIFY THAT A PROCESSOR ERROR OCCURS.

2192 ***** TEST 7 *****
 PROCESSOR ERROR TEST
 IN FREE RUNNING MODE DO A RQI WITH AN ILLEGAL IO CODE
 VERIFY THAT A PROCESSOR ERROR OCCURS

2252 ***** TEST 10 *****
 HALF DUPLEX TEST
 IN FREE RUNNING MODE, SET HALF DUPLEX AND L U LOOP
 SEND A MESSAGE AND VERIFY THAT THERE ARE NO DONES

2291 ***** TEST 11 *****

RESUME TEST
THIS TEST SENDS AND RECEIVES A BUFFER AND SHUTS DOWN THE
DMC. THEN A MASTER CLEAR IS ISSUED AND A BASE WITH RESUME
BIT SET IS GIVEN, ANOTHER BUFFER IS SENT AND RECEIVED.
DATA IS CHECKED.

2380 ***** TEST 12 *****

FREE RUNNING DATA TEST (INTERRUPT DRIVEN EXERCISER)
THIS TEST REPEATEDLY QUEUES UP 7 RECEIVE BUFFERS AND
7 TRANSMIT BUFFERS AND CHECKS DATA WHEN ALL 7 BUFFERS
ARE RECEIVED. TRANSMIT COUNTS RANGE FROM 2 TO 104.
DATA IS A BINARY COUNT PATTERN. THE RESUME FUNCTION
IS CHECKED IN THIS TEST. THIS TEST USES THE TURNAROUND CONNECTOR
IF IT IS PRESENT. OTHERWISE LINE UNIT LOOP IS SET.

100000
040000
020000
010000
004000
002000
001000
000400
000200
000100
000040
000020
000010
000004
000002
000001

:*MAINDEC-11-DZDMH-B DMC11 FREE RUNNING TESTS
:*COPYRIGHT 1976, DIGITAL EQUIPMENT CORP., MAYNARD, MASS. 01754
*-----

:STARTING PROCEDURE
:LOAD PROGRAM
:LOAD ADDRESS 000200
:SWR=0 AUTOSIZE DMC11
:SW07=1 USE CURRENT DMC11 PARAMETERS
:SW00=1 INPUT NEW DMC11 PARAMETERS
:PRESS START
:PROGRAM WILL TYPE "MAINDEC-11-DZDMH-B DMC11 FREE RUNNING TESTS"
:PROGRAM WILL TYPE STATUS MAP
:PROGRAM WILL TYPE "R" TO INDICATE THAT TESTING HAS STARTED
:AT THE END OF A PASS, PROGRAM WILL TYPE PASS COMPLETE MESSAGE
:AND THEN RESUME TESTING
:SUBSEQUENT RESTARTS WILL NOT TYPE PROGRAM TITLE

:SWITCH REGISTER OPTIONS
:-----

100000
040000
020000
010000
004000
002000
001000
000400
000200
000100
000040
000020
000010
000004
000002
000001

SW15=100000 :=1, HALT ON ERROR
SW14=40000 :=1, LOOP ON CURRENT TEST
SW13=20000 :=1, INHIBIT ERROR TYPEOUT
SW12=10000 :=1, DELETE TYPEOUT/BELL ON ERROR.
SW11=4000 :=1, INHIBIT ITERATIONS
SW10=2000 :=1, ESCAPE TO NEXT TEST ON ERROR
SW09=1000 :=1, LOOP WITH CURRENT DATA
SW08=400 :=1, LOOP ON ERROR
SW07=200 :=1, USE CURRENT DMC11 PARAMETERS, =0, AUTOSIZE DMC11
SW06=100 :=1, HALT BEFORE CLOCKING MICRO-PROCESSOR INSTRUCTION
SW05=40
SW04=20
SW03=10 :=RESELECT DMC11'S TO BE TESTED (ACTIVE)
SW02=4 :=LOCK ON TEST SELECT
SW01=2 :=RESTART PROGRAM AT SELECTED TEST
SW00=1 :=INPUT DMC11 PARAMETERS

46
45
44
43
42
41
40
39
38
37
36
35
34
33
32
31
30
29
28
27
26
25
24
23
22
21
20
19
18
17
16
15
14
13
12
11
10
9
8
7
6
5
4
3
2
1

;REGISTER DEFINITIONS
:-----

000000	RO=%0	: GENERAL REGISTER
000001	R1=%1	: GENERAL REGISTER
000002	R2=%2	: GENERAL REGISTER
000003	R3=%3	: GENERAL REGISTER
000004	R4=%4	: GENERAL REGISTER
000005	R5=%5	: GENERAL REGISTER
000006	SP=%6	: PROCESSOR STACK POINTER
000007	PC=%7	: PROGRAM COUNTER

;LOCATION EQUIVALENCIES
:-----

177776	PS=177776	: PROCESSOR STATUS WORD
001200	STACK=1200	: START OF PROCESSOR STACK

;INSTRUCTION DEFINITIONS
:-----

005746	PUSH1SP=5746	: DECREMENT PROCESSOR STACK 1 WORD
005726	POP1SP=5726	: INCREMENT PROCESSOR STACK 1 WORD
010046	PUSHRO=10046	: SAVE RO ON STACK
012600	POPPO=12600	: RESTORE RO FROM STACK
024646	PUSH2SP=24646	: DECREMENT STACK TWICE
022626	POP2SP=22626	: INCREMENT STACK TWICE
	.EQUIV EMT,HLT	: BASIC DEFINITION OF ERRCA CALL

;BIT DEFINITIONS
:-----

100000	BIT15=100000
040000	BIT14=40000
020000	BIT13=20000
010000	BIT12=10000
004000	BIT11=4000
002000	BIT10=2000
001000	BIT9=1000
000400	BIT8=400
000200	BIT7=200
000100	BIT6=100
000040	BIT5=40
000020	BIT4=20
000010	BIT3=10
000004	BIT2=4
000002	BIT1=2
000001	BIT0=1

98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142

000000

000024 005336
000026 000340
000030 004750
000032 000340
000034 004716
000036 000340

000040 000000
000042 000000
000044 000000
000046 003522
000052 000000

000174 000000
000176 000000

000200 000137 002002

001000 005377 040515 047111
001025 104 041515 030461

001200

001200 177570
001202 177570

```
*****
-----
:TRAPCATCAER FOR ILLEGAL INTERRUPTS
:THE STANDARD "TRAP CATCHER" IS PLACED
:BETWEEN ADDRESS 0 TO ADDRESS 776.
:IT LOOKS LIKE "PC+2 HALT".
-----
*****

.=0
:STANDARD INTERRUPT VECTORS
-----

.=24
.PFAIL          :POWER FAIL HANDLER
340             :SERVICE AT LEVEL 7
.HLT            :ERROR HANDLER
340             :SERVICE AT LEVEL 7
.TRPSPV        :GENERAL HANDLER DISPATCH SERVICE
340             :SERVICE AT LEVEL 7

.=40
0              :SAVE FOR ACT-11 OF XXDP
0              :RETURN ADDRESS IF UNDER ACT-11 OR XXDP
0              :SAVE FOR ACT-11 OF XXDP
$ENDC         :FOR USE WITH ACT-11 OR XXDP

.=52
0              :ACT-11 PROGRAM CHARACTERISTICS

.=174
DISPREG:0      :SOFTWARE DISPLAY REGISTER
SWREG: 0       :SOFTWARE SWITCH REGISTER

.=200
JMP .START     :GO TO START OF PROGRAM

.=1000
MTITLE: .ASCII (377)(12) 'MAINDEC-11-DZDMH-B'(377)
        .ASCIIZ 'DMC11 FREE RUNNING TESTS'(377)

.=1200
:INDIRECT POINTERS TO SWITCH REGISTER AND LIGHT DISPLAY
-----

DISPLAY:177570
SWP: 177570
```

```

144
145
146
147
148 001204 177560 TKCSR: 177560 : TELETYPE KEYBOARD CONTROL REGISTER
149 001206 177562 TKDBR: 177562 : TELETYPE KEYBOARD DATA BUFFER
150 001210 177564 TPCSR: 177564 : TELEPRINTER CONTROL REGISTER
151 001212 177566 TPDBR: 177566 : TELEPRINTER DATA BUFFER
152
153 :PROGRAM CONTROL PARAMETERS
154 :-----
155
156 001214 000000 RETURN: 0 : SCOPE ADDRESS FOR LOOP ON TEST
157 001216 000000 NEXT: 0 : ADDRESS OF NEXT TEST TO BE EXECUTED
158 001220 000000 LOCK: 0 : ADDRESS FOR LOCK ON CURRENT DATA
159 001222 000003 ICOLNT: 3 : NUMBER OF ITERATIONS THAT CURRENT TEST WILL BE
160 001224 000000 LPCNT: 0 : NUMBER OF ITERATIONS COMPLETED
161 001226 000000 TSTNO: 0 : NUMBER OF TEST IN PROGRESS
162 001230 000000 PASCNT: 0 : NUMBER OF PASSES COMPLETED
163 001232 000000 ERRCNT: 0 : TOTAL NUMBER OF ERRORS
164 001234 000000 LSTERR: 0 : PC OF LAST ERROR CALL
165
166 :PROGRAM VARIABLES
167 :-----
168
169 001236 000000 STRISW: 0 : SWITCHES AT START OF PROGRAM
170 001240 000000 STAT: 0 : DM STATUS WORD STORAGE
171 001242 000000 CLKX: 0
172 001244 000000 MASKX: 0
173 001246 000000 TEMP1: 0 : TEMPORARY STORAGE
174 001250 000000 TEMP2: 0 : TEMPORARY STORAGE
175 001252 000000 TEMP3: 0 : TEMPORARY STORAGE
176 001254 000000 TEMP4: 0 : TEMPORARY STORAGE
177 001256 000000 TEMPS: 0 : TEMPORARY STORAGE
178 001260 000000 SAVR0: 0 : R0 STORAGE
179 001262 000000 SAVR1: 0 : R1 STORAGE
180 001264 000000 SAVR2: 0 : R2 STORAGE
181 001266 000000 SAVR3: 0 : R3 STORAGE
182 001270 000000 SAVR4: 0 : R4 STORAGE
183 001272 000000 SAVR5: 0 : R5 STORAGE
184 001274 000000 SAVSP: 0 : STACK POINTER STORAGE
185 001276 000000 SAVPC: 0 : PROGRAM COUNTER STORAGE
186 001300 000000 ZERO: 0
187 001302 000001 ONE: 1
188 001304 000000 MEMLIM: 0 : HIGHEST LOCATION FOR NFR'S
189 001306 000001 DMACTV: .BLKW 1 : DMC11'S SELECTED ACTIVE.
190 001310 000001 DMNUM: .BLKW 1 : OCTAL NUMBER OF DMC11'S.
191 001312 000001 SAVACT: .BLKW 1 : ORIGINAL ACTV DEVICES
192 001314 000001 SAVNUM: .BLKW 1 : WORKABLE NUMBER
193 001316 000000 RUN: 0 : POINTER TO RUNNING DEVICE.
194
195 001320 001472 .EVEN : TABLE POINTER.
196 001322 001676 CREAM: DM.MAP-6 : TABLE POINTER
MILK: CNT.MAP-4

```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247

001324 000
001325 000
001326 000
001327 000

001330 104400
001330 003576
001332 104401
001332 003736
001334 104402
001334 003766
001336 104403
001336 004050
001340 104404
001340 004154
001342 104405
001342 004174
001344 104406
001344 004374
001346 104407
001346 004434
001350 104410
001350 004466
001352 104411
001352 004472
001354 104412
001354 005466
001356 104413
001356 005436
001360 104414
001360 005504
001362 104415
001362 005552
001364 104416
001364 005616

PROGRAM CONTROL FLAGS

INIFLG: .BYTE 0 ;PROGRAM INITIALIZATION FLAG
ERRFLG: .BYTE 0 ;ERROR OCCURED FLAG
LOKFLG: .BYTE 0 ;LOCK ON CURRENT TEST FLAG
QV.FLG: .BYTE 0 ;QUICK VERIFY FLAG.
;ON FIRST PASS OF EACH DMC11 ITERATIONS WILL BE
.EVEN

;DEFINITIONS FOR TRAP SUBROUTINE CALLS
;POINTERS TO SUBROUTINES CAN BE FOUND
;IN THE TABLE IMMEDIATLY FOLLOWING THE DEFINITIONS

TRPTAB:
SCOPE=TRAP+0 ;CALL TO SCOPE LOOP AND ITERATION HANDLER
SCOPI=TRAP+1 ;CALL TO LOOP ON CURRENT DATA HANDLER
TYPE=TRAP+2 ;CALL TO TELETYPE OUTPUT ROUTINE
INSTR=TRAP+3 ;CALL TO ASCII STRING INPUT ROUTINE
INSTER=TRAP+4 ;CALL TO INPUT ERROR HANDLER
PARAM=TRAP+5 ;CALL TO NUMERICAL DATA INPUT ROUTINE
SAVOS=TRAP+6 ;CALL TO REGISTER SAVE ROUTINE
RESOS=TRAP+7 ;CALL TO REGISTER RESTORE ROUTINE
CONVRT=TRAP+10 ;CALL TO DATA OUTPUT ROUTINE
CNVRT=TRAP+11 ;CALL TO DATA OUTPUT ROUTINE WITHOUT CR/LF.
MSTCLR=TRAP+12 ;CALL TO ISUE A MASTER CLEAR
DELAY=TRAP+13 ;CALL TO DELAY
ROMCLK=TRAP+14 ;CALL TO CLOCK ROM ONCE
DATACLK=TRAP+15 ;CALL TO CLK DATA
TIMER=TRAP+16 ;CALL TO DELAY A CLOCK TICK
.TIMER

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

```

248 ;DMC11 CONTROL INDICATORS FOR CURRENT DMC11 UNDER TEST
249 ;-----
250
251 001366 000000 STAT1: 0
252 001370 000000 STAT2: 0
253 001372 000000 STAT3: 0
254
255 ;DMC11 VECTOR AND REGISTER INDIRECT POINTERS
256 ;-----
257
258 001374 000000 DMRVEC: 0 ; POINTER TO DMC11 RECEIVER INTERRUPT VECTOR
259 001376 000000 DMRLVL: 0 ; POINTER TO DMC11 RECEIVER INTERRUPT SERVICE PS
260 001400 000000 DMTVEC: 0 ; POINTER TO DMC11 TRANSMITTER INTERRUPT VECTOR
261 001402 000000 DMTLVL: 0 ; POINTER TO DMC11 TRANSMITTER INTERRUPT SERVICE PS
262 001404 000000 DMCSR: 0 ; POINTER TO DMC11 CONTROL STATUS REGISTER
263 001406 000000 DMCSRH: 0 ; POINTER TO DMC11 CONTROL STATUS REGISTER HIGH BYTE.
264 001410 000000 DMCTL: 0 ; POINTER TO DMC11 CONTROL OUT REGISTER
265 001412 000000 DMFO4: 0 ; POINTER TO DMC11 PORT REGISTER (SEL 4)
266 001414 000000 DMPO6: 0 ; POINTER TO DMC11 PORT REGISTER (SEL 6)
267
268 ;TEMP STORAGE
269 ;-----
270
271 001416 000000 TEMP: 0
272 001460 . = +40
273
274 ;DMC11 STATUS TABLE AND ADDRESS ASSIGNMENTS
275 ;-----
276
277 . = 1500
278 001500 DM.MAP:
279 001500 000001 DMC00: .BLKW 1 ; CONTROL STATUS REGISTER FOR DMC11 NUMBER 00
280 001502 000001 DMS100: .BLKW 1 ; VECTOR FOR DMC11 NUMBER 00
281 001504 000001 DMS200: .BLKW 1 ; DDCMP LINE# FOR DMC11 NUMBER 00
282 001506 000001 DMS300: .BLKW 1 ; 3RD STATUS WORD
283
284 001510 000001 DMC01: .BLKW 1 ; CONTROL STATUS REGISTER FOR DMC11 NUMBER 01
285 001512 000001 DMS101: .BLKW 1 ; VECTOR FOR DMC11 NUMBER 01
286 001514 000001 DMS201: .BLKW 1 ; DDCMP LINE# FOR DMC11 NUMBER 01
287 001516 000001 DMS301: .BLKW 1 ; 3RD STATUS WORD
288
289 001520 000001 DMC02: .BLKW 1 ; CONTROL STATUS REGISTER FOR DMC11 NUMBER 02
290 001522 000001 DMS102: .BLKW 1 ; VECTOR FOR DMC11 NUMBER 02
291 001524 000001 DMS202: .BLKW 1 ; DDCMP LINE# FOR DMC11 NUMBER 02
292 001526 000001 DMS302: .BLKW 1 ; 3RD STATUS WORD
293
294 001530 000001 DMC03: .BLKW 1 ; CONTROL STATUS REGISTER FOR DMC11 NUMBER 03
295 001532 000001 DMS103: .BLKW 1 ; VECTOR FOR DMC11 NUMBER 03
296 001534 000001 DMS203: .BLKW 1 ; DDCMP LINE# FOR DMC11 NUMBER 03
297 001536 000001 DMS303: .BLKW 1 ; 3RD STATUS WORD
298
299 001540 000001 DMC04: .BLKW 1 ; CONTROL STATUS REGISTER FOR DMC11 NUMBER 04
300 001542 000001 DMS104: .BLKW 1 ; VECTOR FOR DMC11 NUMBER 04
301 001544 000001 DMS204: .BLKW 1 ; DDCMP LINE# FOR DMC11 NUMBER 04
302 001546 000001 DMS304: .BLKW 1 ; 3RD STATUS WORD
303
    
```

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

304	001550	000001	DMCR05: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 05
305	001552	000001	DMS105: .BLKW	1	;VECTOR FOR DMC11 NUMBER 05
306	001554	000001	DMS205: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 05
307	001556	000001	DMS305: .BLKW	1	;3RD STATUS WORD
308					
309	001560	000001	DMCR06: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 06
310	001562	000001	DMS106: .BLKW	1	;VECTOR FOR DMC11 NUMBER 06
311	001564	000001	DMS206: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 06
312	001566	000001	DMS306: .BLKW	1	;3RD STATUS WORD
313					
314	001570	000001	DMCR07: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 07
315	001572	000001	DMS107: .BLKW	1	;VECTOR FOR DMC11 NUMBER 07
316	001574	000001	DMS207: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 07
317	001576	000001	DMS307: .BLKW	1	;3RD STATUS WORD
318					
319	001600	000001	DMCR10: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 10
320	001602	000001	DMS110: .BLKW	1	;VECTOR FOR DMC11 NUMBER 10
321	001604	000001	DMS210: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 10
322	001606	000001	DMS310: .BLKW	1	;3RD STATUS WORD
323					
324	001610	000001	DMCR11: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 11
325	001612	000001	DMS111: .BLKW	1	;VECTOR FOR DMC11 NUMBER 11
326	001614	000001	DMS211: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 11
327	001616	000001	DMS311: .BLKW	1	;3RD STATUS WORD
328					
329	001620	000001	DMCR12: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 12
330	001622	000001	DMS112: .BLKW	1	;VECTOR FOR DMC11 NUMBER 12
331	001624	000001	DMS212: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 12
332	001626	000001	DMS312: .BLKW	1	;3RD STATUS WORD
333					
334	001630	000001	DMCR13: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 13
335	001632	000001	DMS113: .BLKW	1	;VECTOR FOR DMC11 NUMBER 13
336	001634	000001	DMS213: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 13
337	001636	000001	DMS313: .BLKW	1	;3RD STATUS WORD
338					
339	001640	000001	DMCR14: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 14
340	001642	000001	DMS114: .BLKW	1	;VECTOR FOR DMC11 NUMBER 14
341	001644	000001	DMS214: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 14
342	001646	000001	DMS314: .BLKW	1	;3RD STATUS WORD
343					
344	001650	000001	DMCR15: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 15
345	001652	000001	DMS115: .BLKW	1	;VECTOR FOR DMC11 NUMBER 15
346	001654	000001	DMS215: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 15
347	001656	000001	DMS315: .BLKW	1	;3RD STATUS WORD
348					
349	001660	000001	DMCR16: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 16
350	001662	000001	DMS116: .BLKW	1	;VECTOR FOR DMC11 NUMBER 16
351	001664	000001	DMS216: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 16
352	001666	000001	DMS316: .BLKW	1	;3RD STATUS WORD
353					
354	001670	000001	DMCR17: .BLKW	1	;CONTROL STATUS REGISTER FOR DMC11 NUMBER 17
355	001672	000001	DMS117: .BLKW	1	;VECTOR FOR DMC11 NUMBER 17
356	001674	000001	DMS217: .BLKW	1	;DDCMP LINE# FOR DMC11 NUMBER 17
357	001676	000001	DMS317: .BLKW	1	;3RD STATUS WORD
358					
359	001700	000000	DM.END: 000000		

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

Line	Code	Value	Label	Description
360			;DMC11 PASS COUNT AND ERROR COUNT TABLE	
361			-----	
362				
363				
364	001702		CNT.MAP:	
365	001702	000000	PACT00: 0	;PASS COUNT FOR DMC11 NUMBER 00
366	001704	000000	ERCT00: 0	;ERROR COUNT FOR DMC11 NUMBER 00
367				
368	001706	000000	PACT01: 0	;PASS COUNT FOR DMC11 NUMBER 01
369	001710	000000	ERCT01: 0	;ERROR COUNT FOR DMC11 NUMBER 01
370				
371	001712	000000	PACT02: 0	;PASS COUNT FOR DMC11 NUMBER 02
372	001714	000000	ERCT02: 0	;ERROR COUNT FOR DMC11 NUMBER 02
373				
374	001716	000000	PACT03: 0	;PASS COUNT FOR DMC11 NUMBER 03
375	001720	000000	ERCT03: 0	;ERROR COUNT FOR DMC11 NUMBER 03
376				
377	001722	000000	PACT04: 0	;PASS COUNT FOR DMC11 NUMBER 04
378	001724	000000	ERCT04: 0	;ERROR COUNT FOR DMC11 NUMBER 04
379				
380	001726	000000	PACT05: 0	;PASS COUNT FOR DMC11 NUMBER 05
381	001730	000000	ERCT05: 0	;ERROR COUNT FOR DMC11 NUMBER 05
382				
383	001732	000000	PACT06: 0	;PASS COUNT FOR DMC11 NUMBER 06
384	001734	000000	ERCT06: 0	;ERROR COUNT FOR DMC11 NUMBER 06
385				
386	001736	000000	PACT07: 0	;PASS COUNT FOR DMC11 NUMBER 07
387	001740	000000	ERCT07: 0	;ERROR COUNT FOR DMC11 NUMBER 07
388				
389	001742	000000	PACT10: 0	;PASS COUNT FOR DMC11 NUMBER 10
390	001744	000000	ERCT10: 0	;ERROR COUNT FOR DMC11 NUMBER 10
391				
392	001746	000000	PACT11: 0	;PASS COUNT FOR DMC11 NUMBER 11
393	001750	000000	ERCT11: 0	;ERROR COUNT FOR DMC11 NUMBER 11
394				
395	001752	000000	PACT12: 0	;PASS COUNT FOR DMC11 NUMBER 12
396	001754	000000	ERCT12: 0	;ERROR COUNT FOR DMC11 NUMBER 12
397				
398	001756	000000	PACT13: 0	;PASS COUNT FOR DMC11 NUMBER 13
399	001760	000000	ERCT13: 0	;ERROR COUNT FOR DMC11 NUMBER 13
400				
401	001762	000000	PACT14: 0	;PASS COUNT FOR DMC11 NUMBER 14
402	001764	000000	ERCT14: 0	;ERROR COUNT FOR DMC11 NUMBER 14
403				
404	001766	000000	PACT15: 0	;PASS COUNT FOR DMC11 NUMBER 15
405	001770	000000	ERCT15: 0	;ERROR COUNT FOR DMC11 NUMBER 15
406				
407	001772	000000	PACT16: 0	;PASS COUNT FOR DMC11 NUMBER 16
408	001774	000000	ERCT16: 0	;ERROR COUNT FOR DMC11 NUMBER 16
409				
410	001776	000000	PACT17: 0	;PASS COUNT FOR DMC11 NUMBER 17
411	002000	000000	ERCT17: 0	;ERROR COUNT FOR DMC11 NUMBER 17
412				

413

FORMAT OF STATUS TABLE

15	14	13	12	11	10	09	08	07	06	05	04	03	02	01	00		
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	CSR
I	C	O	N	T	R	O	L		R	E	G	I	S	T	E	R	I
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	STAT1
I	*	I	*	I	*	I	*	I	*	I	*	I	*	I	*	I	
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	STAT2
I	*	B	M		A	D	D	*	I	*	L	I	N	E		*	
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	STAT3
I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	I	

DEFINITION OF FORMAT

- CSR: CONTAINS DMC11 CSR ADDRESS
- STAT1: BITS 00-08 IS DMC11 VECTOR ADDRESS
 BIT15=1 MICRO-PROCESSOR HAS CRAM
 BIT15=0 MICRO-PROCESSOR HAS CROM
 BIT14=1 ??? TURNAROUND CONNECTOR IS ON
 BIT14=0 NO TURNAROUND CONNECTOR
 BIT13=0 LINE UNIT IS AN M8201
 BIT13=1 LINE UNIT IS AN M8202
 BIT12=1 NO LINE UNIT
 BITS 09-11 IS DMC11 BR PRIORITY LEVEL
- STAT2: LOW BYTE IS SWITCH PAC#1 (DDCMP LINE NUMBER)
 HIGH BYTE IS SWITCH PAC#2 (BM873 BOOT ADD)
- STAT3: BIT0=1 DO FREE RUNNING TESTS ON KMC
 (MUST BE SET TO A ONE MANUALLY [PROGRAM DZDMI ONLY])
 KMC MUST HAVE MICRO-CODE WRITTEN FROM RUNNING
 DZDMG TEST 2 FIRST
 BIT1=1 DMC11-AL LOCAL HIGH SPEED MICRO-CODE
 BIT1=0 DMC11-AR REMOTE LOW SPEED MICRO-CODE

468						:PROGRAM INITIALIZATION
469						:LOCK OUT INTERRUPTS
470						:SET UP PROCESSOR STACK
471						:SET UP POWER FAIL VECTOR
472						:CLEAR PROGRAM CONTROL FLAGS AND COUNTS
473						:TYPE TITLE MESSAGE
474						
475						
476	002002	012737	000340	177776	.START:	MOV #340,PS ;LOCK OUT INTERRUPTS
477	002010	012706	001200			MOV #STACK,SP ;SET UP STACK
478	002014	012737	005336	000024		MOV #PFAIL,2#24 ;SET UP POWER FAIL VECTOR
479	002022	013737	001310	001314		MOV DMNUM,SANUM ;SAVE NUMBER OF DEVICES IN SYSTEM.
480	002030	005037	010016			CLR SWFLG ;CLEAR SOFT TIMEOUT FLAG
481	002034	105037	001325			CLRB ERRFLG ;CLEAR ERROR FLAG
482	002040	105037	001327			CLRB QV.FLG ;ZERO QUICK VERIFY FLAG
483	002044	012737	001470	001320		MOV #DM.MAP-10,(CREAM ;GET MAP POINTER.
484	002052	012737	001676	001322		MOV #CNT.MAP-4,MILK ;GET PASS COUNT MAP POINTER
485	002060	012737	100000	001316		MOV #BIT15,RUN ;POINT POINTER TO FIRST DEVICE.
486	002066	012700	001702			MOV #CNT.MAP,RO ;PASS COUNT POINTER TO RO
487	002072	005020			23\$:	CLR (RO)+ ;CLEAR TABLE
488	002074	022700	002002			CMP #CNT.MAP+10,RO ;DONE YET?
489	002100	001374				BNE 23\$;KEEP GOING
490	002102	005037	001234			CLR LSTERR ;CLEAR LAST ERROR POINTER
491	002106	012737	000001	001226		MOV #1,TSTNO ;SET UP FOR TEST 1
492	002114	012737	002002	001214		MOV #.START,RETURN ;SET UP FOR POWER FAIL BEFORE
493						TESTING STARTS
494	002122	013746	000006			MOV 2#6,-(SP) ;SAVE CURRENT VECTORS
495	002126	013746	000004			MOV 2#4,-(SP)
496	002132	012737	002166	000004		MOV #5,2#4 ;SET UP FOR TIMEOUT
497	002140	012737	177570	001202		MOV #177570,SWR ;SET SWR TO HARD SWR ADDRESS
498	002146	012737	177570	001200		MOV #177570,DISPLAY ;SET DISPLAY TO HARD SWR ADDRESS
499	002154	022777	177777	177020		CMP #-1,2\$SWR ;REFERENCE HARDWARE SWITCH REGISTER
500	002162	001402				BEQ 6\$+2 ;IF = -1 USE SOFT SWR ANYWAY
501	002164	000407				BR 7\$;IF IT EXISTS AND NOT = -1 USE HARD SWR
502	002166	022626			6\$:	CMP (SP)+,(SP)+ ;ADJUST STACK
503	002170	012737	000176	001202		MOV #SWREG,SWR ;POINTER TO SOFT SWR
504	002176	012737	000174	001200		MOV #DISPREG,DISPLAY ;POINTER TO SOFT DISPLAY REG
505	002204	012637	000004		7\$:	MOV (SP)+,2#4 ;RESTORE VECTORS
506	002210	012637	000006			MOV (SP)+,2#6
507	002214	105737	001324			TSTB INIFLG ;HAS INITIALIZATION BEEN PERFORMED
508	002220	001006				BNE 20\$;BR IF YES
509	002222	022737	003522	000042		CMP #SENDAD,2#42 ;IF ACT-11 AUTOMATIC MODE. DON'T TYPE ID
510	002230	001402				BEQ 20\$
511	002232	104402	001000			TYPE #MTITLE ;TYPE TITLE MESSAGE
512	002236	004737	007606		20\$:	JSR #C,CKSWR ;CHECK FOR SOFT SWR
513	002242	017737	176734	001236		MOV 2\$SWR,STRTSW ;STORE STARTING SWITCHES
514	002250	005737	000042			TST 2#42 ;IS IT RUNNING IN AUTO MODE?
515	002254	001402				BEQ .+6 ;BR IF NO
516	002256	005037	001236			CLR STRTSW ;IF YES, CLEAR SWITCHES
517	002262	032737	000001	001236		BIT #SW00,STRTSW ;IF SW00=1, QUESTIONS ARE ASKED.
518	002270	001012				BNE 17\$;BR IF SW00=1
519	002272	105737	001236			TSTB STRTSW ;BIT7=1??
520	002276	100007				BPL 17\$;BR IF SW07=0
521	002300	005737	001306			TST DMACTV ;ARE ANY DEVICES SELECTED?
522	002304	001006				BNE 16\$;BR IF YES
523	002306	104402	007154			TYPE #NOACT ;NO DEVICES SELECTED.

```

524 002312 000000          HALT          ;STOP THE SHOW
525 002314 000776          BR          ;DISQUALIFY CONTINUE SWITCH
526 002316 004737 010512 17$: JSR          PC,AUTO.SIZE ;GO DO THE AUTO SIZE
527 002322 105737 001324 16$: TSTB       INIFLG      ;FIRST TIME?
528 002326 001410          BEQ          21$      ;BR IF YES
529 002330 105737 001236  TSTB       STATSW     ;IF USING SAME PARAMETERS DONT TYPE *MAP
530 002334 100431          BMI          1$
531 002336 032737 000006 001236 BIT        #BIT1!BIT2,STATSW ;IS TEST NO. OR LOCK SELECTED
532 002344 001403          BEQ          24$      ;IF NO THEN TYPE STATUS
533 002346 000424          BR          1$
534 002350 005137 001324 21$: COM        INIFLG      ;SET FLAG
535 002354 104402 006224 24$: TYPE       ,XHEAD     ;TYPE HEADER
536 002360 012704 001500  MOV        #DM.MAP,R4     ;SET POINTER
537 002364 010437 001246 5$:  MOV        R4,TEMP1     ;SET ADDRESS
538 002370 012437 001250  MOV        (R4)+,TEMP2    ;SET CSR
539 002374 001411          BEQ          1$
540 002376 012437 001252  MOV        (R4)+,TEMP3    ;SET STAT1
541 002402 012437 001254  MOV        (R4)+,TEMP4    ;SET STAT2
542 002406 012437 001256  MOV        (R4)+,TEMP5    ;SET STAT3
543 002412 104410          CONVRT      ;TYPE OUT STATUS MAP
544 002414 007454          XSTATO
545 002416 000762          BR          5$
546 002420 012700 001500 1$:  MOV        #DM.MAP,R0   ;R0 POINTS TO STATUS TABLE

```

```

*****
*AUTO SIZE TEST
*THIS TEST VERIFYS THAT THE DMC11S AND/OR KMC11S ARE AT THE CORRECT FLOATING
*ADDRESSES FOR YOUR SYSTEM. IF THIS TEST FAILS, IT IS NOT A HARDWARE ERROR.
*CHECK THE ADDRESSES OF ALL FLOATING DEVICES (DJ,DH,DO,DU,DUP,LK,DMC,DZ,KMC).
*IF THERE ARE NO OTHER FLOATING DEVICES BEFORE THE DMC11, THE FIRST
*DMC11 ADDRESS IS 760070, KMC11 IS 760110. NO DEVICE SHOULD EVER BE AT
*ADDRESS 760000. THIS TEST MAY REQUIRE 2 OR MORE ATTEMPTS TO GET THE
*RIGHT ADDRESSES. AFTER YOU HAVE CHANGED THE ADDRESS TO WHAT IT TOLD
*YOU THE FIRST TIME, IT MAY COME BACK AND TELL YOU A DIFFERENT ADDRESS
*THE NEXT TIME YOU RUN IT. PLEASE HAVE PATIENCE, THE FINAL ADDRESS
*WILL BE CORRECT (AS LONG AS ALL DEVICES IN FRONT OF THE DMC'S ARE
*CORRECT).
*****

```

```

563 002424 013746 000004          MOV        #4,-(SP)      ;SAVE LOC 4
564 002430 013746 000006          MOV        #6,-(SP)      ;SAVE LOC 6
565 002434 005037 00000E          CLR        #6          ;CLEAR VEC+2
566 002440 005037 001252          CLR        TEMP3       ;CLEAR FLAG
567 002444 005005          CLR        R5          ;R5=0=DMC, R5=-1=KMC
568 002446 011037 001404  AUSTRT: MOV       (R0),DMCSR   ;GET NEXT DMC CSR
569 002452 001564          BEQ        AUDONE      ;BR IF DONE
570 002454 005705          TST       R5          ;DMC OR KMC?
571 002456 001005          BNE       1$          ;BR IF KMC
572 002460 032760 100000 000002 BIT        #BIT15,2(R0) ;CHECK FOR DMC CSR
573 002466 001061          BNE       SKIP        ;SKIP IF NOT DMC
574 002470 000404          BR        2$          ;ITS A DMC SO CONTINUE
575 002472 032760 100000 000002 1$: BIT        #BIT15,2(R0) ;CHECK FOR KMC CSR
576 002500 001454          BEQ        SKIP       ;SKIP IF NOT KMC
577 002502 012737 002674 000004 2$: MOV        #NODEV,#4   ;SET UP FOR TIMEOUT
578 002510 005705          TST       R5          ;DMC OR KMC?
579 002512 001003          BNE       3$          ;BR IF KMC

```

580	002514	012703	000006		MOV	#6,R3	:R3 IS COUNT OF DEVICES BEFORE DMC
581	002520	000402			BR	4\$:GO ON
582	002522	012703	000010	3\$:	MOV	#10,R3	:R3 IS COUNT OF DEVICES BEFORE KMC
583	002526	012702	003010	4\$:	MOV	#DEVTAB,R2	:R2 IS DEVICE TABLE POINTER
584	002532	012701	160010		MOV	#160010,R1	:START WITH ADDRESS 160010
585	002536	005711		FLOAT:	TST	(R1)	:CHECK ADDRESS IN R1
586	002540	111204			MOVB	(R2),R4	:IF NO TIMEOUT, GET NEXT ADDRESS
587	002542	060401			ADD	R4,R1	:IN R1
588	002544	005201			INC	R1	:
589	002546	040401			BIC	R4,R1	:
590	002550	005703			TST	R3	:ANY MORE DEVICES TO CHECK FOR?
591	002552	001371			BNE	FLOAT	:BR IF YES
592	002554	012737	002700	000004	MOV	#ERR,2#4	:OK ONLY DMC'S ARE LEFT, SET UP FOR TIMEOUT
593	002562	010137	003022		MOV	R1,XLOC	:SAVE FIRST DMC/KMC ADDRESS
594	002566	005705		FY:	TST	R5	:DMC OR KMC?
595	002570	001005			BNE	1\$:BR IF KMC
596	002572	032760	100000	000002	BIT	#BIT15,2(R0)	:CHECK FOR DMC CSR
597	002600	001014			BNE	SKIP	:SKIP IF NOT DMC
598	002602	000404			BR	2\$:ITS A DMC SO CONTINUE
599	002604	032760	100000	000002	1\$:	BIT	#BIT15,2(R0)
600	002612	001407			BEQ	SKIP	:CHECK FOR KMC CSR
601	002614	005711			2\$:	TST	(R1)
602	002616	020137	001404		CMP	R1,DMCSR	:CHECK DMC ADDRESS
603	002622	001411			BEQ	OK	:DOES IT MATCH
604	002624	062701	000010		ADD	#10,R1	:BR IF YES
605	002630	000756			BR	FY	:GET NEXT DMC ADDRESS
606	002632	062700	000010		3\$:	ADD	#10,R0
607	002636	011037	001404	SKIP:	MOV	(R0),DMCSR	:DO IT AGAIN
608	002642	001470			BEQ	AUDONE	:SKIP TO NEXT CSR IN TABLE
609	002644	000750			BR	FY	:GET NEXT CSR
610	002646	062700	000010		OK:	ADD	#10,R0
611	002652	062737	000010	003022	ADD	#10,XLOC	:BR IF DONE
612	002660	011037	001404		MOV	(R0),DMCSR	:ELSE CONTINUE
613	002664	001457			BEQ	AUDONE	:SKIP TO NEXT DMC CSR
614	002666	013701	003022		MOV	XLOC,R1	:UPDATE EXPECTED DMC/KMC ADDRESS
615	002672	000735			BR	FY	:GET NEXT DMC/KMC CSR
616	002674	122243			NODEV:	CMPB	(R2)+,-(R3)
617	002676	000002			RTI		:BR IF DONE
618	002700	005737	001252		ERR:	TST	TEMP3
619	002704	001014			BNE	1\$:ON TIMEOUT, INC R2, DEC R3
620	002706	104402			TYPE		:RETURN
621	002710	007223			CONERR		:CHECK FLAG IF = 0 TYPE HEADER
622	002712	012737	002700	001276	MOV	#ERR,SAVPC	:SKIP HEADER
623	002720	104411			CONVRT		:TYPEOUT HEADER MESSAGE
624	002722	002770			ERRPC		:CONFIGURATION ERROR!!!!
625	002724	104402			TYPE		:SAVE PC FOR TYPEOUT
626	002726	007277			CNERR		:TYPE OUT ERROR PC
627	002730	012737	177777	001252	1\$:	MOV	#-1,TEMP3
628	002736	010137	001262		MOV	R1,SAVR1	:TYPE REST OF HEADER
629	002742	104410			CONVRT		:SET FLAG SO IT ONLY GETS TYPED ONCE
630	002744	002776			CONTAB		:SAVE R1 FOR TYPEOUT
631	002746	005705			TST	R5	:TYPE CSR VALUES
632	002750	001003			BNE	3\$:DMC OR KMC ?
633	002752	104402			TYPE		:BR IF KMC
634	002754	007320			DMCM		:
635	002756	000402			BR	4\$:CONTINUE

```

636 002760 104402      3$:  TYPE
637 002762 007330      KCM
638 002764 022626      4$:  CMP      (SP)+,(SP)+  ;ADJUST STACK
639 002766 000727      BR      OK      ;BR TO GET OLT
640 002770 000001      ERRPC: 1
641 002772 006      002      .BYTE 6,2
642 002774 001276      SAVPC
643 002776 000002      CONTAB: 2
644 003000 006      004      .BYTE 6,4
645 003002 003022      XLOC
646 003004 006      002      .BYTE 6,2
647 003006 001404      DMCSR
648 003010 007      DEVTAB: .BYTE 7      :DJ
649 003011 017      .BYTE 17     :DH
650 003012 007      .BYTE 7      :DQ
651 003013 007      .BYTE 7      :DU
652 003014 007      .BYTE 7      :DJP
653 003015 007      .BYTE 7      :LK
654 003016 007      .BYTE 7      :DMC
655 003017 007      .BYTE 7      :DZ
656 003020 007      .BYTE 7      :KMC
657      003022      .EVEN
658 003022 000000      XLOC: 0
659 003024 005705      AUDONE: TST      R5      :DMC?
660 003026 001005      BNE      1$      :BR IF KMC AND ALL DONE
661 003030 012705 177777      MOV      #-1,R5  :SET R5 TO -1 (KMC)
662 003034 012700 001500      MOV      #DM.MAP,RO :RESET RO TO START OF TABLE
663 003040 000602      BR      AUSTRT   :GO DO KMC'S
664 003042 012637 000006      1$:  MOV      (SP)+,2#6  :RESTORE LOC 6
665 003046 012637 000004      MOV      (SP)+,2#4  :RESTORE LOC 4
666 003052 032737 000010 001236      BIT      #SW03,STRTSW :SELECT SPECIFIC DEVICES??
667 003060 001422      BEQ      3$      :BR IF NO.
668 003062 104402 006144      TYPE     MNEW    :TYPE THE MESSAGE.
669 003066 005000      CLR      RO      :ZERO DATA LIGHTS
670 003070 000000      HALT     :WAIT FOR USER TO TELL WHAT DEVICES TO RUN
671 003072 027737 176104 001312      CMP      2$SWR,SAVACT :IS THE NUMBER VALID?
672 003100 101404      BLOS     2$      :BR IF NUMBER IS OK.
673 003102 104402 006005      TYPE     ,MERR3   :TELL USER OF INVALID NUMBER.
674 003106 000000      HALT     :STOP EVERY THING.
675 003110 000776      BR      -2      :RESTART THE PROGRAM AGAIN.
676 003112 017737 176064 001306      2$:  MOV      2$SWR,DMACTV :GET NEW DEVICE PATTERN
677 003120 013700 001306      MOV      DMAC+V,RO  :SHOW THE USER WHAT HE SELECTED.
678 003124 000000      HALT     :CONTINUE DYNAMIC SWITCHES.
679 003126 012700 000300      3$:  MOV      #300,RO   :PREPARE TO CLEAR THE FLOATING
680 003132 012701 000302      MOV      #302,R1   :VECTOR AREA. 300-776
681 003136 010120      4$:  MOV      R1,(RO)+  :START PUTTING "PC+2 - HALT"
682 003140 005021      CLR     (R1)+      :IN VECTOR AREA.
683 003142 022021      CMP     (RO)+,(R1)+ :POP POINTERS
684 003144 022700 001000      CMP     #1000,RO   :ALL DONE??
685 003150 001372      BNE     4$      :BR IF NO.
686
687
688
689
690 003152 012706 001200      :TEST START AND RESTART
691 003156 013746 000000      -----
        .BEGIN: MOV      #STACK,SP      :SET UP STACK
        MOV      2#6,-(SP)      :SAVE LOC 6

```

692	003162	013746	000004		MOV	2#4, -(SP)	:SAVE LOC 4	
693	003166	005000			CLR	RO	:START AT 0	
694	003170	012737	003234	000004	MOV	2#5, 2#4	:SET UP FOR TIME OUT	
695	003176	005037	000006		CLR	2#6	:TO AUTOSIZE MEMORY	
696	003202	005720		5\$:	TST	(RO)+	:CHECK ADDRESS IN RO	
697	003204	022700	157776		CMP	157776, RO	:IS IT AT LEAST 28K	
698	003210	001374			BNE	6\$:BR IF NO	
699	003212	162700	007776		SUB	7776, RO	:SAVE 2K FOR MONITORS	
700	003216	010037	001304	7\$:	MOV	RO, MEM LIM	:STORE MEMORY LIMIT	
701	003222	012637	000004		MOV	(SP)+, 2#4	:RESTORE LOC 4	
702	003226	012637	000006		MOV	(SP)+, 2#6	:RESTORE LOC 6	
703	003232	000413			BR	10\$:CONTINUE	
704	003234	022626		2\$:	CMP	(SP)+, (SP)+	:ADJUST STACK	
705	003236	162700	000004		SUB	4, RO	:GET LAST GOOD ADDRESS	
706	003242	162700	007776		SUB	7776, RO	:SAVE 2K FOR MONITORS	
707	003246	022700	030000		CMP	30000, RO	:IS IT 8K?	
708	003252	001361			BNE	7\$:BR IF NO	
709	003254	012700	037400		MOV	37400, RO	:IF 8K DON'T SAVE 2K	
710	003260	000756			BR	7\$:	
711	003262	012737	000340	177776	10\$:	MOV	340, PS	:LOCK OUT INTERRUPTS
712	003270	032737	000004	001236	BIT	BIT2, STRTSW	:CHECK FOR LOCK ON TEST	
713	003276	001411			BEQ	1\$:BR IF NO LOCK DESIRED.	
714	003300	104402	00604J		TYPE	, MLOCK	:TYPE LOCK SELECTED.	
715	003304	012737	00024J	003612	MOV	NOPI, TTST	:ADJUST SCOPE ROUTINE.	
716	003312	012737	000240	003614	MOV	NOPI, TTST+2	:SET UP TO LOCK	
717	003320	000406			BR	3\$:CONTINUE ALONG.	
718	003322	013737	003730	003612	1\$:	MOV	BRW, TTST	:PREPARE NORMAL SCOPE ROUTINE
719	003330	013737	003732	003614	MOV	BRX, TTST+2	:LOCK NOT SELECTED, SET UP FOR NORMAL SCOPE LOOP	
720	003336	012737	010060	001214	3\$:	MOV	CYCLE, RETURN	:START AT "CYCLE" FIND WHICH DEVICE TO TEST
721	003344	032737	000002	001236	4\$:	BIT	SW01, STRTSW	:IS TEST NO. SELECTED?
722	003352	001002			BNE	5\$:BR IF YES	
723	003354	104402	005755		TYPE	, MR	:TYPE R	
724	003360	000177	175630		5\$:	JMP	RETURN	:START TESTING

```

726                                     :END OF PASS
727                                     :TYPE NAME OF TEST
728                                     :UPDATE PASS COUNT
729                                     :CHECK FOR EXIT TO ACT-11
730                                     :RESTART TEST
731 003364 000005 .EOP: RESET                                     :MAKE THE WORLD CLEAN AGAIN.
732 003366 005037 001234 CLR LSTERR                               :CLEAR LAST ERROR PC
733 003372 105037 001325 CLR ERRFLG                             :CLEAR ERROR FLAG
734 003376 005237 001230 INC PASCNT                             :UPDATE PASS COUNT
735 003402 013777 001230 175570 MOV PASCNT, @DISPLAY      :DISPLAY PASS COUNT
736 003410 104402 005733 TYPE .MEPASS                    :TYPE END PASS
737 003414 104402 006072 TYPE .MCSRX                      :TYPE CSR
738 003420 104411 003546 CNVRT .XCSR                          :SHOW IT
739 003424 104402 006100 TYPE .MVECX                       :TYPE VECTOR
740 003430 104411 003554 CNVRT .XVEC                          :SHOW IT
741 003434 104402 006106 TYPE .MPASSX                       :TYPE PASSES
742 003440 104411 003562 CNVRT .XPASS                       :SHOW IT
743 003444 104402 006117 TYPE .MERRX                       :TYPE ERRORS
744 003450 104411 003570 CNVRT .XERR                          :SHOW IT
745 003454 013700 001322 MOV MILK, RO                    :GET POINTER TO PASS COUNT
746 003460 013720 001230 MOV PASCNT, (RO)+                :STORE PASS COUNT FOR THIS DMC1!
747 003464 013720 001232 MOV ERRCNT, (RO)+                :STORE ERROR COUNT FOR THIS DMC1!
748 003470 005337 001314 DEC SAVNUM                          :ARE ALL DEVICES TESTED?
749 003474 001017 001017 BNE RESTR                               :BR IF NO.
750 003476 112737 000377 001327 MCVB #377, QV.FLG             :SET THE QUICK VERIFY FLAG.
751 003504 013737 001310 001314 MOV DMNUM, SAVNUM          :RESTORE THE COUNT
752 003512 013701 000042 MOV #42, R1                    :CHECK FOR ACT-11 OR DDP
753 003516 001406 BEQ RESTR                               :IF NOT, CONTINUE TESTING
754 003520 000005 RESET                                     :STOP THE SHOW--CLEAR THE WORLD
755 003522 SENDAC: JSR PC, (R1)
756 003522 004711 NOP
757 003524 000240 NOP
758 003526 000240 NOP
759 003530 000240 NOP
760 003532 000240 NOP
761 003534 012737 010060 001214 RESTR: MOV #CYCLE, RETURN
762 003542 000137 010060 JMP CYCLE
763 003546 000001 XCSR: 1
764 003550 006 002 .BYTE 6,2
765 003552 001404 DMCSR
766 003554 000001 XVEC: 1
767 003556 004 002 .BYTE 4,2
768 003560 001374 DMRVEC
769 003562 000001 XPASS: 1
770 003564 006 002 .BYTE 6,2
771 003566 001230 PASCNT
772 003570 000001 XERR: 1
773 003572 006 002 .BYTE 6,2
774 003574 001232 ERRCNT
775
776                                     :SCOPE LOOP AND ITERATION HANDLER
777 -----
778
779 003576 004737 007606 .SCOPE: JSR PC, CKSWR          :CHECK FOR SOFT SWR
780 003602 010016 MOV RO, SP                    :SAVE RO ON THE STACK

```

GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

```

781 003604 032777 040000 175370
782 003612 001407
783 003614 000437
784 003616 005737 003734
785 003622 001434
786 003624 005037 003734
787 003630 000415
788 003632 032777 004000 175342
789 003640 001011
790 003642 105737 001327
791 003646 001406
792 003650 005237 001224
793 003654 023737 001224 001222
794 003662 101414
795 003664 105037 001325
796 003670 005037 001224
797 003674 005037 001220
798 003700 012737 000020 001222
799 003706 013737 001216 001214
800 003714 011600
801 003716 022626
802 003720 013701 001404
803 003724 000177 175264
804 003730 001407
805 003732 000437
806 003734 000000
807
808
809
810
811 003736 004737 007606
812 003742 032777 001000 175232
813 003750 001405
814 003752 005737 001220
815 003756 001402
816 003760 013716 001220
817 003764 000002
818
819
820
821
822 003766 010546
823 003770 017605 000002
824 003774 062766 000002 000002
825 004002 005737 010016
826 004006 001004
827 004010 032777 010000 175154
828 004016 001012
829 004020 105715
830 004022 100002
831 004024 104402 005672
832 004030 105777 175154
833 004034 100375
834 004036 112577 175150
835 004042 001357
836 004044 012605

TTST: BIT #BIT14,2SWR ;"LOOP ON THIS TEST"?
      BEQ 1$ ;BR IF NO. (IF LOCK SW01=1; THIS LOC =240;
      BR 3$ ;GOTO 3$ (IF LOCK SW01=1; THIS LOC =240;
      TST DONE ;WAS TKCSR DONE SET?
      BEQ 3$ ;BR IF NO (LOCKED ON TEST)
      CLR DONE ;YES, CLEAR FLAG
      BR 2$ ;GO TO NEXT TEST
1$: BIT #SW11,2SWR ;DELETE ITERATION? (QUICK PASS,
   BNE 2$ ;BR IF YES
   TSTB QV.FLG ;HAVE PASSES BEECOMPLETED?
   BEQ 2$ ;BR IF QUICK PASS.
   INC LPCNT ;UPDATE ITERATION COUNTER
   CMP LPCNT,ICOUNT ;ARE ALL ITERATIONS DONE??
   BLOS 3$ ;BR IF NOT YET
2$: CLRB ERRFLG ;PREPARE FOR NEW TEST
   CLR LPCNT ;START ICOUNTER AT 0
   CLR LOCK
   MOV #20,ICOUNT ;RESET ITERATIONS
   MOV NEXT,RETURN ;GET NEXT TEST
3$: MOV (SP),RO ;POP RO OFF OF THE STACK
   POP2SP ;FAKE AN "RTI"
   MOV DMCSR,R1 ;R1 CONTAINS BASE DMC ADDRESS
   JMP @RETURN ;GO DO THE TEST

BRW: 1407
BRX: 437
DONE: 0

;CHECK FOR FREEZE ON CURRENT DATA
-----
.SCOPE1: JSR PC,CKSWR ;CHECK FOR SOFT SWR
          BIT #SW09,2SWR ;IS SW09=1(SET)?
          BEQ 1$ ;BR IF NOT SET.
          TST LOCK
          BEQ 1$
          MOV LOCK,(SP) ;GOTO THE ADDRESS IN LOCK.
1$: RTI ;GO BACK.

;TELETYPE OUTPUT ROUTINE
-----
TYPE: MOV R5,-(SP) ;SAVE R5 ON THE STACK.
      MOV @2(SP),R5 ;GET ADDRESS OF MESSAGE.
      ADD #2,2(SP) ;POP OVER ADDRESS.
4$: TST SWFLG ;SOFT SWR MESSAGE?
   BNE 1$ ;IF YES TYPE IT OUT REGARDLESS OF SW12
   BIT #SW12,2SWR ;INHIBIT ALL PRINT OUT??
   BNE 3$ ;BR IF NO PRINT OUT WANTED (SW12=1)
   TSTB (R5) ;IS NUMBER MINUS? (MSB=1(BIT7))
   BPL 2$ ;BR IF NUMBER IS PLUS
   TYPE MCRLF ;TYPE A CR/LF!
   TSTB @TPCSR ;TTY READY?
   BPL 2$ ;BR IF NO.
   MOVB (R5)+,@TPCSR ;PRINT CURRENT CHAR.
   BNE 4$ ;IF NOT ZERO KEEP PRINTING!
3$: MOV (SP)+,R5 ;END OF OUTPUT. RESTORE R5
    
```

GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

```

837 004046 000002          RTI          ;GO HOME
838          :-----:
839
840 004050 010346          .INSTR: MOV      R3,-(SP)          ;SAVE R3 ON STACK
841 004052 010446          MOV      R4,-(SP)          ;SAVE R4 ON STACK
842 004054 017637 000004 004072  MOV      24(SP),MSG
843 004062 062766 000002 000004  ADD      #2,4(SP)
844 004070 104402          .INST1: TYPE
845 004072 000000          .MSG: 0
846 004074 012704 007502          MOV      #INBUF,R4
847 004100 012703 000007          MOV      #7,R3
848 004104 105777 175074          1$: TSTB     2TKCSR
849 004110 100375          BPL      1$
850 004112 117714 175070          MOV      2TKDBR,(R4)
851 004116 142714 000200          BICB     #200,(R4)
852 004122 122427 000015          CMPB     (R4)+,#15
853 004126 001417          BEQ      INSTR2
854 004130 105777 175054          2$: TSTB     2TPCSR
855 004134 100375          BPL      2$
856 004136 017777 175044 175046          MOV      2TKDBR,2TPDBR
857 004144 005303          DEC      R3
858 004146 001356          BNE      1$
859 004150 012604          MOV      (SP)+,R4
860 004152 012603          MOV      (SP)+,R3
861 004154 104402 005566          .INSTE: TYPE  MQM
862 004160 010346          MOV      R3,-(SP)
863 004162 010446          MOV      R4,-(SP)
864 004164 000741          BR       .INST1
865 004166 012604          INSTR2: MOV     (SP)+,R4          ;RESTORE R4
866 004170 012603          MOV     (SP)+,R3          ;RESTORE R3
867 004172 000002          RTI
868
869          :CONVERT ASCII STRING TO OCTAL
870          :-----:
871
872 004174 010546          .PARAM: MOV     R5,-(SP)
873 004176 010446          MOV     R4,-(SP)
874 004200 016605 000004          MOV     4(SP),R5
875 004204 012537 004364          MOV     (R5)+,LOLIM
876 004210 012537 004366          MOV     (R5)+,HILIM
877 004214 012537 004370          MOV     (R5)+,DEVADR
878 004220 112537 004372          MOV     (R5)+,LOBITS
879 004224 112537 004373          MOV     (R5)+,AORCNT
880 004230 010566 000004          MOV     R5,4(SP)
881 004234 005005          PARAM1: CLR     R5
882 004236 012704 007502          MOV     #INBUF,R4
883 004242 122714 000015          CMPB     #15,(R4)
884 004246 001420          BEQ      PARERR
885 004250 121427 000060          1$: CMPB     (R4),#60
886 004254 002415          BLT      PARERR
887 004256 121427 000067          CMPB     (R4),#67
888 004262 003012          BGT      PARERR
889 004264 142714 000060          BICB     #60,(R4)
890 004270 152405          BISB     (R4)+,R5
891 004272 122714 000015          CMPB     #15,(R4)
892 00427E 00140E          BEQ      LIMITS

```

893	004300	006305			ASL	R5	
894	004302	006305			ASL	R5	
895	004304	006305			ASL	R5	
896	004306	000760			BR	IS	
897	004310	104404			PARERR: INSTER		
898	004312	000750			BR	PARAM1	
899							
900							
901							
902							
903	004314	020537	004366		LIMITS: CMP	R5, HILIM	
904	004320	101373			BHI	PARERR	
905	004322	020537	004364		CMP	R5, LOLIM	
906	004326	103770			BLO	PARERR	
907	004330	133705	004372		BITB	LOBITS, R5	
908	004334	001365			BNE	PARERR	
909							
910							
911							
912	004336	013704	004370				
913	004342	010524			IS: MOV	DEVADR, R4	
914	004344	062705	000002		MOV	R5, (R4)+	
915	004350	105337	004373		ADD	#2, R5	
916	004354	001372			DECB	ADRCNT	
917	004356	012604			BNE	IS	
918	004360	012605			MOV	(SP)+, R4	
919	004362	000002			MOV	(SP)+, R5	
920	004364	000000			RTI		
921	004366	000000			LOLIM: 0		
922	004370	000000			HILIM: 0		
923	004372	000000			DEVADR: 0		
924		004373			LOBITS: 0		
925					ADRCNT=LOBITS+1		
926							
927							
928							
929	004374	016637	000004	001276	.SAV05: MOV	4(SP), SAVPC	:SAVE R7 (PC)
930							
931							
932							
933	004402	010537	001272		SV05: MOV	R5, SAVR5	:SAVE R5
934	004406	010437	001270		MOV	R4, SAVR4	:SAVE R4
935	004412	010337	001266		MOV	R3, SAVR3	:SAVE R3
936	004416	010237	001264		MOV	R2, SAVR2	:SAVE R2
937	004422	010137	001262		MOV	R1, SAVR1	:SAVE R1
938	004426	010037	001260		MOV	R0, SAVR0	:SAVE R0
939	004432	000002			RTI		:LEAVE.
940							
941							
942							
943	004434	013700	001260		.RES05: MOV	SAVR0, R0	:RESTORE R0
944	004440	013701	001262		MOV	SAVR1, R1	:RESTORE R1
945	004444	013702	001264		MOV	SAVR2, R2	:RESTORE R2
946	004450	013703	001266		MOV	SAVR3, R3	:RESTORE R3
947	004454	013704	001270		MOV	SAVR4, R4	:RESTORE R4
948	004460	013705	001272		MOV	SAVR5, R5	:RESTORE R5

GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

```

949 004464 000002 RTI ;LEAVE
950 ;
951 ; CONVERT OCTAL NUMBER TO ASCII AND OUTPUT TO TELEPRINTER
952 ;
953 -----
954 004466 104402 005672 .CONVR: TYPE MCRLF
955 004472 010046 .CNVRT: MOV R0,-(SP)
956 004474 010146 MOV R1,-(SP)
957 004476 010346 MOV R3,-(SP)
958 004500 010446 MOV R4,-(SP)
959 004502 010546 MOV R5,-(SP)
960 004504 017601 000012 MOV @12(SP),R1
961 004510 062766 000002 000012 ADD #2,12(SP)
962 004516 012137 004710 MOV (R1)+,WROCNT
963 004522 112137 004712 1$: MOVB (R1)+,CHRCNT
964 004526 112137 004713 MOVB (R1)+,SPACNT
965 004532 013137 004714 MOV @2(R1)+,BINWRD
966 004536 122737 000003 004712 CMPB #3,CHRCNT
967 004544 001003 BNE 2$
968 004546 042737 177400 004714 BIC #177400,BINWRD
969 004554 013704 004714 2$: MOV BINWRD,R4
970 004560 113705 004712 MOVB CHRCNT,R5
971 004564 012700 001416 MOV #TEMP,R0
972 004570 010403 3$: MOV R4,R3
973 004572 042703 177770 BIC #177770,R3
974 004576 062703 000060 ADD #060,R3
975 004602 110320 MOVB R3,(R0)+
976 004604 000241 CLC
977 004606 006004 ROR R4
978 004610 000241 CLC
979 004612 006004 ROR R4
980 004614 000241 CLC
981 004616 006004 ROR R4
982 004620 005305 DEC R5
983 004622 001362 BNE 3$
984 004624 012703 007544 MOV #MDATA,R3
985 004630 114023 4$: MOVB -(R0),(R3)+
986 004632 105337 004712 DECB CHRCNT
987 004636 001374 BNE 4$
988 004640 105737 004713 TSTB SPACNT
989 004644 001405 BEQ 6$
990 004646 112723 000040 5$: MOVB #040,(R3)+
991 004652 105337 004713 DECB SPACNT
992 004656 001373 BNE 5$
993 004660 105013 6$: CLRB (R3)
994 004662 104402 007544 TYPE #MDATA
995 004666 005337 004710 DEC WROCNT
996 004672 001313 BNE 1$
997 004674 012605 MOV (SP)+,R5
998 004676 012604 MOV (SP)+,R4
999 004700 012603 MOV (SP)+,R3
:000 004702 012601 MOV (SP)+,R1
:001 004704 012600 MOV (SP)+,R0
:002 004706 000002 RTI
:003 004710 000000 WROCNT: 0
:004 004712 000000 CHRCNT: 0

```

```

1005          004713      004713      SPACNT=CHRCNT+1
1006 004714      000000      BINWRD: 0
1007
1008
1009
1010          :TRAP DISPATCH SERVICE
1011          :ARGUMENT OF TRAP IS EXTRACTED
1012          :AND USED AS OFFSET TO OBTAIN POINTER
1013          :TO SELECTED SUBROUTINE
1014 004716      011646      .TRPSR: MOV      (SP), -(SP)      :GET PC OF RETURN
1015 004720      162716      000002      SUB      #2, (SP)      :PC OF TRAP
1016 004724      017616      000000      MOV      2(SP), (SP)   :GET TRP
1017 004730      006316      TRPOK: ASL      (SP)      :MULTIPLY TRAP ARG BY 2
1018 004732      042716      177001      BIC      #177001, (SP)  :CLEAR UNWANTED BITS
1019 004736      062716      001330      ADD      #.TRPTAB, (SP) :POINTER TO SUBROUTINE ADDRESS
1020 004742      017616      000000      MOV      2(SP), (SP)   :SUBROUTINE ADDRESS
1021 004746      000136      JMP      2(SP)+        :GO TO SUBROUTINE
1022
1023          :ERROR HANDLER
1024          :-----
1025
1026 004750      004737      007606      .HLT: JSR      PC, CKSWR      :CHECK FOR SOFT SWR
1027 004754      032777      010000      174220  BIT      #SW12, 2SWR     :BELL ON ERROR?
1028 004762      001406      BEQ      XBX           :BR IF NO BELL
1029 004764      105777      174220      TSTB    2TPCSR        :TTY READY.
1030 004770      100003      BPL      XBX           :DON'T WAIT IF TTY NOT READY.
1031 004772      112777      000207      174212  MOVB    #207, 2TPDBR   :PUSH A BELL AT THE TTY.
1032 005000      032777      020000      174174  XBX: BIT      #SW13, 2SWR     :DELETE ERROR PRINT OUT?
1033 005006      001105      BNE      HALTS        :BR IF NO PRINT OUT WANTED.
1034 005010      021637      001234      CMP      (SP), LSTERR  :WAS THIS ERROR FOUND LAST TIME?
1035 005014      001404      BEQ      1$           :BR IF YES
1036 005016      011637      001234      MOV      (SP), LSTERR  :RECORD BEING HERE
1037 005022      105037      001325      CLRB    ERRFLG        :PREPARE HEADER
1038 005026      104406      1$: SAVOS           :SAVE ALL PROC REGISTERS
1039 005030      011605      MOV      (SP), R5      :GET THE PC OF ERROR
1040 005032      162705      000002      SUB      #2, R5        :GET ADDRESS OF TRAP CALL
1041 005036      011504      MOV      (R5), R4      :GET HLT INSTRUCTION
1042 005040      006304      ASL      R4            :MULT BY TWO
1043 005042      061504      ADD      (R5), R4      :DOUBLE IT
1044 005044      006304      ASL      R4            :MULT AGAIN
1045 005046      042704      177001      BIC      #177001, R4    :CLEAR JUNK
1046 005052      062704      023414      ADD      #.ERRTAB, R4  :GET POINTER
1047 005056      012437      005172      MOV      (R4)+, ERMSG  :GET ERROR MESSAGE
1048 005062      012437      005204      MOV      (R4)+, DATAH :GET DATA HEADER
1049 005066      011437      005216      MOV      (R4), DATABP  :GET DATA TABLE
1050 005072      105737      001325      TSTB    ERRFLG        :TYPE HEADREER
1051 005076      001403      BEQ      TYPMSG        :BR IF YES
1052 005100      005737      005216      TST      DATABP        :DOES DATA TABLE EXIST?
1053 005104      001040      BNE      TYPDAT        :BR IF YES.
1054 005106      104402      005672      TYPMSG: TYPE      ,MCRLF
1055 005112      104402      005672      TYPE      ,MCRLF
1056 005116      005737      001220      TST      LOCK
1057 005122      001402      BEQ      1$
1058 005124      104402      006142      TYPE      ,MASTEK
1059 005130      104402      006130      1$: TYPE      ,MTSTN
1060 005134      104411      005330      CNVRT    ,XTSTN      :SHOW IT

```

GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

1061	005140	104402	006217		TYPE	,MERRPC	:TYPE PC.
1062	005144	104411	005322		CNVRT	,ERTABO	:SHOW IT
1063	005150	104402	005672		TYPE	,MCRLF	:GIVE A CR/LF
1064	005154	112737	177777	001325	MOVB	#-1,ERRFLG	:NO MORE HEADER UNLESS NO DATA TABLE.
1065	005162	005737	005172		TST	ERRMSG	:IS THERE AN ERROR MESSAGE?
1066	005166	001402			BEQ	WRKO.FM	:BR IF NO.
1067	005170	104402			TYPE		:TYPE
1068	005172	000000			ERRMSG: 0		: ERROR MESSAGE
1069	005174				WRKO.FM:		
1070	005174	005737	005204		TST	DATAHD	:DATA HEADER?
1071	005200	001402			BEQ	TYPDAT	:BR IF NO
1072	005202	104402			TYPE		:TYPE
1073	005204	000000			DATAHD: 0		: DATA HEADER
1074	005206	005737	005216		TYPDAT: TST	DATABP	:DATA TABLE?
1075	005212	001402			BEQ	RESREG	:BR IF NO.
1076	005214	104410			CONVRT		:SHOW
1077	005216	000000			DATABP: C		: DATA TABLE
1078	005220	104407			RESREG: RES05		:RESTORE PROC REGISTERS
1079	005222	022737	003522	000042	HALTS: CMP	#SENDAD,2#42	:IF ACT-11 AUTOMATIC MODE, HALT!!
1080	005230	001403			BEQ	1\$	
1081	005232	005777	173744		TST	JSWR	:HALT ON ERROR?
1082	005236	100005			BPL	EXITER	:BR IF NO HALT ON ERROR
1083	005240	010046			1\$: PUSHRO		:SAVE RO
1084	005242	016600	000002		MOV	2(SP),RO	:SHOW ERROR PC IN DATA LIGHTS
1085	005246	000000			HALT		:HALT
1086	005250	012600			POPPO		:GET RO
1087	005252	005237	001232		EXITER: INC	ERRCNT	:UPDATE ERROR COUNT
1088	005256	032777	000400	173716	BIT	#SW08,JSWR	:GOTO TOP OF TEST?
1089	005264	001007			BNE	1\$:BR IF YES
1090	005266	032777	002000	173706	BIT	#SW10,JSWR	:GOTO NEXT TEST?
1091	005274	001411			BEQ	2\$:BR IF NO
1092	005276	013737	001216	001214	MOV	NEXT,RETURN	:SET FOR NEXT TEST
1093	005304	012706	001200		1\$: MOV	#STACK,SP	:RESET SP
1094	005310	013701	001404		MOV	DMCSR,R1	:SET UP R1
1095	005314	000177	173674		JMP	2RETURN	:GOTO SPECIFIED TEST
1096	005320	000002			2\$: RTI		:RETURN
1097	005322	000001			ERTABO: 1		
1098	005324	006	002		.BYTE	6,2	
1099	005326	001276			SAVPC		
1100	005330	000001			XTSTN: 1		
1101	005332	003	002		.BYTE	3,2	
1102	005334	001226			TSTNO		
1103					:ENTER HERE ON POWER FAILURE		
1104					-----		
1105							
1106							
1107	005336				.PFAIL:		
1108	005336	012737	005350	000024	MOV	#RESTART,24	:SET JP FOR POWER UP TRAP
1109	005344	000000			HALT		:HALT ON POWER DOWN NORMAL
1110	005346	000777			BR	.	
1111							
1112							:PROCESSOR WILL TRAP HERE WHEN POWER IS RESTORED
1113							
1114	005350				RESTAR:		
1115	005350	012737	005336	000024	MOV	#.PFAIL,24	:SET UP FOR POWER FAILURE
1116	005356	012706	001200		MOV	#STACK,SP	:RESET THE STACK POINTER

```

1117 005362 013701 001404      MOV      DMCSR,R1      ;RESTORE R1
1118 005366 005037 001416      CLR      TEMP         ;READY FOR TIMER
1119 005372 005237 001416      INC      TEMP         ;PLUS ONE TO THE TIMER!
1120 005376 001375          BNE     -4            ;BR IF MORE TO GO
1121 005400 104402 005675      TYPE    ,MPFAIL      ;TYPE THE MESSAGE
1122 005404 104411 005430      CNVRT   PFTAB        ;TELL WHAT TEST TO RETURN TO.
1123 005410 105037 001325      CLRB    ERRFLG       ;START CLEAN
1124 005414 005037 001234      CLR     LSTERR       ;.....
1125 005420 005011          CLR     (R1)         ;CLEAR MAINT BITS
1126 005422 104412          MSTCLR ;START CLEAN UP OF DEVICE
1127 005424 000177 173564      JMP     @RETURN      ;START DOING THAT TEST AGAIN.
1128 005430 000001          PFTAB: 1
1129 005432 003      002      .BYTE  3,2
1130 005434 001226          TSTNO
1131
1132 005436          .DELAY:
1133 005436 012777 000020 173746      MOV     #20,@DMP04
1134 005444 104414          ROMCLK ;NEXT WORD IS INSTRUCTION. ROMCLK PC=5304
1135 005446 121111          121111 ;POKE CLOCK DELAY BIT
1136 005450          1$:
1137 005450 104414          ROMCLK ;NEXT WORD IS INSTRUCTION. ROMCLK PC=5304
1138 005452 121224          121224 ;PORT4+IBUS#11
1139 005454 032777 000020 173730      BIT    #BIT4,@DMP04 ;IS CLOCK BIT SET?
1140 005462 001772          BEQ    1$           ;BR IF NO
1141 005464 000002          RTI
1142
1143 005466          .MSTCLR:
1144 005466 152777 000100 173712      BISB   #BIT6,@DMCSRH ;SET MASTER CLEAR
1145 005474 142777 000300 173704      BICB   #BIT6!BIT7,@DMCSRH ;CLEAR MASTER CLEAR AND RUN
1146 005502 000002          RTI                ;RETURN
1147
1148 005504          .ROMCLK:
1149 005504 152777 000002 173674      BISB   #BIT1,@DMCSRH ;SET ROMI
1150 005512 013677 173676          MOV    @(SP)+,@DMP06 ;LOAD INSTRUCTION IN SEL6
1151 005516 062746 000002          ADD    #2,-(SP)      ;ADJUST STACK
1152 005522 032777 000100 173452      BIT    #SW06,@SWR    ;HALT IF SW06 =1
1153 005530 001401          BEQ    1$           ;BR IF SW06 =0
1154 005532 000000          HALT   ;HALT BEFORE CLOCKING INSTRUCTION
1155 005534 152777 000003 173644      1$:  BISB   #BIT1!BIT0,@DMCSRH ;CLOCK INSTRUCTION
1156 005542 142777 000007 173636      BICB   #BIT2!BIT1!BIT0,@DMCSRH ;CLEAR ROMO, ROMI, STEP
1157 005550 000002          RTI
1158
1159 005552          .DATACLK:
1160 005552 013637 001416          MOV    @(SP)+,TEMP    ;PUT TICK COUNT IN TEMP
1161 005556 062746 000002          ADD    #2,-(SP)      ;ADJUST STACK
1162 005562 152777 000020 173616      1$:  BISB   #BIT4,@DMCSRH ;SET STEP LU
1163 005570 027777 173610 173606      CMP    @DMCSR,@DMCSR ;WASTE TIME
1164 005576 142777 000020 173602      BICB   #BIT4,@DMCSRH ;CLEAR STEP LU
1165 005604 005337 001416          DEC    TEMP          ;DEC TICK COUNT
1166 005610 001364          BNE    1$           ;BR IF NOT DONE
1167 005612 000002          RTI                ;RETURN
1168 005614 000001          3$:  .BLKW 1
1169
1170 005616          .TIMER:
1171 005616 013637 001416          MOV    @(SP)+,TEMP    ;MOVE COUNT TO TEMP
1172 005622 062746 000002          ADD    #2,-(SP)      ;ADJUST STACK

```

```

1173 005626
1174 005626 104414
1175 005630 021364
1176 005632 032777 000002 173552
1177 005640 001772
1178 005642
1179 005642 104414
1180 005644 021364
1181 005646 032777 000002 173536
1182 005654 001372
1183 005656 005337 001416
1184 005662 001361
1185 005664 000002
1186
1187 005666 020040 000077
(2) 005672 005015 000
(2) 005675 377 053520 020122
(2) 005733 377 047105 020104
(2) 005755 377 000122
(2) 005760 047377 020117 042504
(2) 006005 377 047111 052523
(2) 006031 377 042524 052123
(2) 006043 377 047514 045503
(2) 006072 051503 035122 000040
(2) 006100 042526 035103 000040
(2) 006106 040520 051523 051505
(2) 006117 105 051122 051117
(2) 006130 042524 052123 047040
(2) 006142 000052
(2) 006144 051777 052105 051440
(2) 006217 120 035103 000040
(2) 006224 020212 020040 020040
(2) 006263 377 020040 020040
(2) 006322 020212 050040 020103
(2) 006374 026777 026455 026455
(2) 006450 044377 053517 046440
(2) 006510 041777 051123 040440
(2) 006526 053377 041505 047524
(2) 006547 377 051102 050040
(2) 006606 044777 020106 046504
(2) 006704 053777 044510 044103
(2) 007016 051777 044527 041524
(2) 007054 051777 044527 041524
(2) 007114 044777 020123 044124
(2) 007154 047377 020117 042504
(2) 007205 377 051412 051127
(2) 007215 116 053505 020077
(2) 007223 377 042377 041515
(2) 007277 377 054105 042520
(2) 007320 024040 046504 024503
(2) 007330 024040 046513 024503
(2) 007340 042377 041515 030461
(2)
(2) 007454 000005
1188 007456 006 003
1189 007460 001246

```

```

1$: ROMCLK ;NEXT WORD IS INSTRUCTION, ROMCLK PC=5304
021364 ;PORT4+IBUS* REG11
BIT #2, DMP04 ;IS PGM CLOCK BIT CLEAR?
BEQ 1$ ;BR IF YES

2$: ROMCLK ;NEXT WORD IS INSTRUCTION, ROMCLK PC=5304
021364 ;PORT4+IBUS* REG11
BIT #2, DMP04 ;IS PGM CLOCK BIT SET?
BNE 2$ ;BR IF YES
DEC TEMP ;DEC COUNT
BNE 1$ ;BR IF NOT DONE
RTI ;RETURN

MQM: .ASCIZ / ?/
MCRLF: .ASCIZ <15><12>
MPFAIL: .ASCIZ <377>/PWR FAILED. RESTART AT TEST /
MEPASS: .ASCIZ <377>/END PASS DZDMH /
MR: .ASCIZ <377>/R/
MERR2: .ASCIZ <377>/NO DEVICES PRESENT./
MERR3: .ASCIZ <377>/INSUFFICIENT DATA!/
MTSTPC: .ASCIZ <377>/TEST PC-/
MLOCK: .ASCIZ <377>/LOCK ON SELECTED TEST/
MCSRX: .ASCIZ /CSR: /
MVECX: .ASCIZ /VEC: /
MPASSX: .ASCIZ /PASSES: /
MERRX: .ASCIZ /ERRORS: /
MTSTN: .ASCIZ /TEST NO: /
MASTEK: .ASCIZ /*/
MNEW: .ASCIZ <377>/SET SWITCH REG TO DMC11'S DESIRED ACTIVE./
MERRPC: .ASCIZ /PC: /
XHEAD: .ASCII <212>/
.ASCII <377>/
.ASCII <212>/ PC CSR STAT1 STAT2 STAT3/
.ASCIZ <377>/-----
NUM: .ASCIZ <377>/HOW MANY DMC11'S TO BE TESTED?/
CSR: .ASCIZ <377>/CSR ADDRESS?/
VEC: .ASCIZ <377>/VECTOR ADDRESS?/
PRIO: .ASCIZ <377>/BR PRIORITY LEVEL? (4,5,6,7)?/
CRAM: .ASCIZ <377>/IF DMC HAS CRAM (M8204) TYPE "Y", IF CROM (M8200) TYPE "N"
MODU: .ASCIZ <377>/WHICH LINE UNIT? IF NONE TYPE "N", IF M8201 TYPE "1", IF M
LINE: .ASCIZ <377>/SWITCH PAC#1 (D0CMP LINE #)?/
BM: .ASCIZ <377>/SWITCH PAC#2 (BM873 BOOT ADD)?/
CONN: .ASCIZ <377>/IS THE LOOP BACK CONNECTOR ON?/
NOACT: .ASCIZ <377>/NO DEVICES ARE SELECTED/
SWMES: .ASCIZ <377><12>/SWR= /
SWMES1: .ASCIZ /NEW? /
CONERR: .ASCIZ <377><377>/DMC11 FOUND AT NON-STANDARD ADDRESS PC: /
CNERR: .ASCIZ <377>/EXPECTED FOUND/
DMCM: .ASCIZ / (DMC) /
KMCM: .ASCIZ / (KMC) /
SPEED: .ASCIZ <377>/DMC11-AR(REMOTE,LOW SPEED) OR DMC11-AL(LOCAL,HIGH SPEED): T
.EVEN
XSTATQ: 5
.BYTE 6,3
TEMP1

```

```

1190 007462 006 003 .BYTE 6,3
1191 007464 001250 TEMP2
1192 007466 006 003 .BYTE 6,3
1193 007470 001252 TEMP3
1194 007472 006 003 .BYTE 6,3
1195 007474 001254 TEMP4
1196 007476 006 002 .BYTE 6,2
1197 007500 001256 TEMPS
1198 .EVEN
1199
1200 ;BUFFERS FOR INPUT-OUTPUT
1201
1202 007502 000000 INBUF: 0
1203 007544 .=. +40
1204 007544 000000 MDATA: 0
1205 007506 .=. +40
1206
1207
1208 ;ROUTINE USED TO CHANGE SOFTWARE SWITCH
1209 ;REGISTER USING THE CONSOLE TERMINAL
1210 -----
1211
1212 007606 022737 000176 001202 CKSWR: CMP #SWREG,SWR ;IS THE SOFT SWR BEING USED?
1213 007614 001077 BNE CKSWR5 ;BR IF NO
1214 007616 105777 171362 TSTB @TKCSR ;IS DONE SET?
1215 007622 100003 BPL 2$ ;GO ON IF NOT SET
1216 007624 012737 177777 003734 MOV #-1,DONE ;IF DONE SET, SET FLAG
1217 007632 022777 000007 171346 2$: CMP #7,@TKDBR ;WAS CTRL G TYPED? (7 BIT ASCII)
1218 007640 001404 BEQ 1$ ;BR IF YES
1219 007642 022777 000207 171336 CMP #207,@TKDBR ;WAS CTRL G TYPED? (8 BIT ASCII)
1220 007650 001061 BNE CKSWR5 ;BR IF NO
1221 007652 010246 1$: MOV R2,-(SP) ;STORE R2
1222 007654 010346 MOV R3,-(SP) ;STORE R3
1223 007656 010446 MOV R4,-(SP) ;STORE R4
1224 007660 012737 177777 010016 MOV #-1,SWFLG ;SET SOFT TYPE OUT FLAG
1225 007666 005002 CKSWR1: CLR R2 ;CLEAR NEW SWR CONTENTS
1226 007670 012704 177777 MOV #-1,R4 ;SET FLAG TO ALL ONES
1227 007674 104402 007205 TYPE .SWMES ;TYPE "SWR="
1228 007700 104411 CKSWR2: CNVRT ;TYPE OUT PRESENT CONTENTS
1229 007702 010052 SOFTSW ;OF SOFT SWITCH REGISTER
1230 007704 104402 007215 CKSWR3: TYPE .SWMES1 ;TYPE "NEW"
1231 007710 004737 010020 CKSWR4: JSR PC,INCHAR ;GET RESPONSE
1232 007714 022703 000015 CMP #15,R3 ;WAS IT A CR?
1233 007720 001424 BEQ 5$ ;BR IF YES
1234 007722 022703 000012 CMP #12,R3 ;WAS IT A LF?
1235 007726 001416 BEQ 4$ ;BR IF YES
1236 007730 022703 000025 CMP #25,R3 ;WAS IT CTRL U?
1237 007734 001754 BEQ CKSWR1 ;BR IF YES(START OVER)
1238 007736 022703 000007 CMP #7,R3 ;IF CNTL G GET NEXT CHAR
1239 007742 001762 BEQ CKSWR4
1240 007744 005004 CLR R4 ;IT MUST BE A DIGIT SO CLR FLAG
1241 007746 042703 177770 BIC #177770,R3 ;ONLY 0-7 ARE LEGAL SO MASK OFF BITS
1242 007752 006302 ASL R2 ;SHIFT R2 3 TIMES
1243 007754 006302 ASL R2
1244 007756 006302 ASL R2
1245 007760 050302 BIS R3,R2 ;ADD LAST DIGIT
    
```

GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

1246	007762	000752			BR	CKSWR4	:GET NEXT CHARACTER
1247	007764	012766	002002	000006	4S: MOV	#.START,6(SP)	:LF WAS TYPED SO GO TO START
1248	007772	005704			5S: TST	R4	:IS FLAG CLEAR?
1249	007774	001002			BNE	6S	:IF NOT DON'T CHANGE SOFT SWP
1250	007776	010277	171200		MOV	R2,2SWR	:IF YES THEN WRITE NEW CONTENTS TO SOFT SWP
1251	010002	005037	010016		6S: CLR	SWFLG	:CLEAR TYPEOUT FLAG
1252	010006	012604			MOV	(SP)+,R4	:RESTORE R4
1253	010010	012603			MOV	(SP)+,R3	:RESTORE R3
1254	010012	012602			MOV	(SP)+,R2	:RESTORE R2
1255	010014	000207			CKSWR5: RTS	PC	:RETURN
1256							
1257	010016	000000			SWFLG:	0	
1258							
1259	010020	105777	171160		INCHAR: TSTB	@TKCSR	
1260	010024	100375			BPL	-4	
1261	010026	017703	171154		MOV	@TKDBR,R3	
1262	010032	105777	171152		TSTB	@TPCSR	
1263	010036	100375			BPL	-4	
1264	010040	010377	171146		MOV	R3,@TPDBR	
1265	010044	042703	000200		BIC	#BIT7,R3	
1266	010050	000207			RTS	PC	
1267							
1268	010052	000001			SOFTSW: 1		
1269	010054	006	002		.BYTE	6.2	
1270	010056	000176			SWREG		

```

1271
1272
1273
1274
1275
1276
1277
1278
1279
1280 010060 005737 001306          CYCLE:  TST      DMACTV      ;ARE ANY DMC11'S TO BE TESTED?
1281 010064 001004                BNE      1$          ;BR IF OK.
1282 010066 104402 007154          TYPE     .NOACT     ;NO DMC11'S SELECTED!!
1283 010072 000000                HALT                    ;STOP THE SHOW.
1284 010074 000776                BR       -2          ;DISQUALIFY CONT. SW.
1285 010076 000241                1$:      CLC                    ;CLEAR PROC. CARRY BIT.
1286 010100 006137 001316          ROL                    ;UPDATE POINTER
1287 010104 005537 001316          ADC      RUN        ;CATCH CARRY FROM RUN
1288 010110 062737 000004 001322          ADD      #4,MILK     ;UPDATE POINTER
1289 010116 062737 000010 001320          ADD      #10,CREAM  ;UPDATE ADDRESS POINTER.
1290 010124 022737 001700 001320          CMP      #DM.MAP+200,CREAM
1291 010132 001006                BNE      2$          ;KEEP GOING; NOT ALL TESTED FOR.
1292 010134 012737 001500 001320          MOV      #DM.MAP,CREAM ;RESET ADDRESS POINTER.
1293 010142 012737 001702 001322          MOV      #CNT.MAP,MILK ;RESET PASS COUNT POINTER
1294 010150 033737 001316 001306          2$:      BIT      RUN,DMACTV ;IS THIS ONE ACTIVE?
1295 010156 001747                BEQ      1$          ;BR IF NO
1296 010160 013700 001320          MOV      CREAM,R0    ;GET ADDRESS POINTER
1297 010164 013702 001322          MOV      MILK,R2     ;GET PASS COUNT POINTER
1298 010170 012037 001404          MOV      (R0)+,DMCSR ;LOAD SYSTEM CTRL. REG
1299 010174 011037 001374          MOV      (R0),DMRVEC ;LOAD VECTOR
1300 010200 042737 177000 001374          BIC      #177000,DMRVEC ;CLEAR UNWANTED BITS
1301 010206 012037 001366          MOV      (R0)+,STAT1 ;LOAD STAT1
1302 010212 012037 001370          MOV      (R0)+,STAT2 ;LOAD STAT2
1303 010216 012037 001372          MOV      (R0)+,STAT3 ;LOAD STAT3
1304 010222 012237 001230          MOV      (R2)+,PASCNT ;LOAD PASS COUNT
1305 010226 012237 001232          MOV      (R2)+,ERRCNT ;LOAD ERROR COUNT
1306 010232 012700 000002          MOV      #2,R0      ;SAVE CORE THIS WAY!
1307 010236 013737 001404 001406          MOV      DMCSR,DMCSRH
1308 010244 005237 001406          INC      DMCSRH
1309 010250 013737 001406 001410          MOV      DMCSRH,DMCTL
1310 010256 005237 001410          INC      DMCTL
1311 010262 013737 001410 001412          MOV      DMCTL,DMP04
1312 010270 060037 001412          ADD      R0,DMP04
1313 010274 013737 001412 001414          MOV      DMP04,DMP06
1314 010302 060037 001414          ADD      R0,DMP06
1315
1316 010306 013737 001374 001376          MOV      DMRVEC,DMRLVL ;PTY LVL
1317 010314 060037 001376          ADD      R0,DMRLVL
1318 010320 013737 001376 001400          MOV      DMRLVL,DMTVEC ;TX VEC
1319 010326 060037 001400          ADD      R0,DMTVEC
1320 010332 013737 001400 001402          MOV      DMTVEC,DMTLVL ;TX LVL
1321 010340 060037 001402          ADD      R0,DMTLVL
1322
1323 010344 032737 000002 001236          BIT      #SW01,STATSW ;IS TEST NO. SELECTED
1324 010352 001450                BEQ      7$          ;BR IF NO
1325 010354
1326 010354 005737 000042          4$:      TST      #42          ;RUNNING IN ALTO MODE?

```

```

1327 010360 001045          BNE      7$          ;BR IF YES
1328 010362 104402 005672  TYPE      .MCRLF
1329 010366 104403          INSTR
1330 010370 006130          MTSTN          ;GET TEST NO.
1331 010372 104405          PARAM
1332 010374 000001          1
1333 010376 001000          1000
1334 010400 001226          TSTNO
1335 010402          000          .BYTE 0
1336 010403          001          .BYTE 1
1337 010404 012700 012320  MOV      #TST1,RO
1338 010410 022710 5$:  CMP      (PC)+,(RO)      ;CMP FIRST WORD TO 12737
1339 010412 012737  MOV      (PC)+,2(PC)+
1340 010414 001020          BNE      6$          ;BR IF NOT SAME
1341 010416 023760 001226 000002  CMP      TSTNO,2(RO)      ;DOES TSTNO MATCH?
1342 010424 001014          BNE      6$          ;BR IF NO
1343 010426 022760 001226 000004  CMP      #TSTNO.4(RO)      ;IS LAST WORD OK?
1344 010434 001010          BNE      6$          ;BR IF NO
1345 010436 010037 001214  MOV      RO,RETURN      ;IT IS A LEGAL TEST SO DO IT
1346 010442 104402 005755  TYPE      .MR
1347 010446 042737 000002 001236  BIC      #SW01,STRTSW
1348 010454 000412          BR      8$
1349 010456 005720 6$:  TST      (RO)+          ;POP RO
1350 010460 020027 016224  CMP      RO,#TLAST+10      ;AT END YET?
1351 010464 001351          BNE      5$          ;BR IF NO
1352 010466 104402 005666  TYPE      .MQM          ;YES ILLEGAL TEST NO.
1353 010472 000730          BR      4$          ;TRY AGAIN
1354
1355 010474 012737 012320 001214 7$:  MOV      #TST1,RETURN      ;PREPARE RETURN ADDRESS
1356 010502 013701 001404 8$:  MOV      DMC1R,R1          ;R1 = BASE DMC11 ADDRESS
1357 010506 000177 170502  JMP      @RETURN          ;GO START TESTING.
1358
1359
1360          ;ROUTINE USED TO "AUTO SIZE" THE DMC11
1361          ;CSR AND VECTOR.
1362          ;NOTE: THE CSR MAY BE ANY WHERE IN THE FLOATING
1363          ;ADDRESS RANGE (160000:164000)
1364          ;AND THE VECTOR MAY BE ANY WHERE IN THE
1365          ;FLOATING VECTOR RANGE (300:770)
1366          ;
1367          ;
1368          AUTO.SIZE:
1369 010512 000005          RESET          ;INSURE A BUS INIT.
1370 010514 012702 001500  CSRMAP: MOV      #DM.MAP,R2      ;LOAD MAP POINTER.
1371 010520 005022 1$:  CLR      (R2)+          ;ZERO ENTIRE MAP
1372 010522 022702 001700  CMP      #DM.END,R2          ;ALL DONE?
1373 010526 001374          BNE      1$          ;BR IF NO
1374 010530 005037 001310  CLR      DMNUM          ;SET OCTAL NUMBER OF DMC11'S TO C
1375 010534 012702 001500  MOV      #DM.MAP,R2          ;R2 POINTS TO DMC MAP
1376 010540 005037 001306  CLR      DMACTV          ;CLEAR ACTIVE
1377 010544 032737 000001 001236  BIT      #SW00,STRTSW      ;QUESTIONS?
1378 010552 001002          BNE      .+6          ;BR IF YES
1379 010554 000137 011252  JMP      7$          ;IF NO SKIP QUESTIONS
1380 010560 012737 000001 001256  MOV      #1,TEMPS          ;START WITH 1
1381 010566 104403          INSTR
1382 010570 006450          NUM

```

F04

1383	010572	104405			PARAM		
1384	010574	000001			1		
1385	010576	000020			16.		
1386	010600	001252			TEMP3		
1387	010602	000			.BYTE	0	
1388	010603	001			.BYTE	1	
1389	010604	013737	001252	001310	MOV	TEMP3,DMNUM	:DMNUM = HOW MANY
1390	010612	104402	005672		TYPE	,MCRLF	
1391	010616	104410		12\$:	CONVRT		:TYPE WHICH DMC IS BEING DONE
1392	010620	012002			WHICH		:TEMPS IS WHICH DMC
1393	010622	005237	001256		INC	TEMPS	
1394	010626	104403			INSTR		
1395	010630	006510			CSR		
1396	010632	104405			PARAM		
1397	010634	160000			160000		
1398	010636	164000			164000		
1399	010640	001254			TEMP4		
1400	010642	000			.BYTE	0	
1401	010643	001			.BYTE	1	
1402	010644	013722	001254		MOV	TEMP4,(R2)+	:STORE CSR IN MAP
1403	010650	104403			INSTR		
1404	010652	006526			VEC		
1405	010654	104405			PARAM		
1406	010656	000000			0		
1407	010660	000776			776		
1408	010662	001254			TEMP4		
1409	010664	000			.BYTE	0	
1410	010665	001			.BYTE	1	
1411	010666	013712	001254		MOV	TEMP4,(R2)	:STORE VECTOR IN MAP
1412	010672	104402		10\$:	TYPE		
1413	010674	006547			PRIC		:ASK WHAT BR LEVEL
1414	010676	004737	012266		JSR	PC,INTTY	:GET RESPONSE
1415	010702	022703	000024		CMP	#24,R3	
1416	010706	101014			BHI	50\$:BR IF LESS THAN 4
1417	010710	022703	000027		CMP	#27,R3	
1418	010714	103411			BLO	50\$:BR IF GREATER THAN ?
1419	010716	012704	000011		MOV	#11,R4	:R4 = NUMBER OF SHIFTS
1420	010722	006303			ASL	R3	:SHIFT R3 LEFT
1421	010724	005304			DEC	R4	:DEC SHIFT COUNT
1422	010726	001375			BNE	.-4	:BR IF NOT DONE
1423	010730	042703	170777		BIC	#170777,R3	:BIC UNWANTED BITS
1424	010734	050312			BIS	R3,(R2)	:PUT BR LEVEL IN STATUS MAP
1425	010736	000403			BR	8\$:CONTINUE
1426	010740	104402		50\$:	TYPE		:RESPONSE IS OUT OF LIMITS
1427	010742	005666			MQM		
1428	010744	000752			BR	10\$:TRY AGAIN
1429	010746	104402		8\$:	TYPE		
1430	010750	006606			CRAM		:DOES DMC HAVE CRAM?
1431	010752	004737	012266		JSR	PC,INTTY	:GET REPLY
1432	010756	022703	000131		CMP	#131,R3	
1433	010762	001427			BEQ	9\$:YES
1434	010764	022703	000116		CMP	#116,R3	:NO
1435	010770	001403			BEQ	40\$:NOT A Y OR N
1436	010772	104402			TYPE		
1437	010774	005666			MQM		:TYPE ""
1438	010776	000763			BR	8\$:ASK AGAIN

1439	011000	104402		40\$:	TYPE			
1440	011002	007340			SPEED		:DMC11-AR OR DMC11-AL'	
1441	011004	004737	012266		JSR	PC,INTTY	:GET RESPONSE	
1442	011010	022703	000122		CMP	#122,R3	:IS IT R	
1443	011014	001414			BEQ	16\$:BR IF REMOTE	
1444	011016	022703	000114		CMP	#114,R3	:IS IT L	
1445	011022	001403			BEQ	41\$:BR IF LOCAL	
1446	011024	104402			TYPE			
1447	011026	005666			MQM			
1448	011030	000763			BR	40\$:TRY AGAIN	
1449	011032	052762	000002	000004	41\$:	BIS	#BIT1,(R2)	:SET BIT1 IN STAT3
1450	011040	000402			BR	16\$:CONTINUE	
1451	011042	052712	100000		3\$:	BIS	#BIT15,(R2)	:SET BIT 15 IF CRAM
1452	011046	104402			16\$:	TYPE		
1453	011050	006704			MODU		:ASK WHICH LINE UNIT	
1454	011052	004737	012266		JSR	PC,INTTY	:GET REPLY	
1455	011056	022703	000021		CMP	#21,R3	: "1"	
1456	011062	001417			BEQ	30\$		
1457	011064	022703	000022		CMP	#22,R3	: "2"	
1458	011070	001412			BEQ	31\$		
1459	011072	022703	000116		CMP	#116,R3	: "N"	
1460	011076	001403			BEQ	32\$		
1461	011100	104402			TYPE			
1462	011102	005666			MQM		: IF NOT A 1,2 OR N TYPE ""	
1463	011104	000760			BR	16\$:TRY AGIAN	
1464	011106	052722	010000		32\$:	BIS	#BIT12,(R2)+	:SET BIT 12 IN STAT2 IF NO _J
1465	011112	022222			CMP	(R2)+,(R2)+	:POP OVER STAT2 AND STAT3	
1466	011114	000447			BP	33\$		
1467	011116	052712	020000		31\$:	BIS	#BIT13,(R2)	:SET BIT 13 IN STAT2 IF M8202
1468	011122	104402			30\$:	TYPE		
1469	011124	007114			CONN		:ASK IF LOOP-BACK IS ON	
1470	011126	004737	012266		JSR	PC,INTTY	:GET REPLY	
1471	011132	022703	000131		CMP	#131,R3	:Y	
1472	011136	001406			BEQ	17\$		
1473	011140	022703	000116		CMP	#116,R3	:N	
1474	011144	001406			BEQ	18\$		
1475	011146	104402			TYPE			
1476	011150	005666			MQM		: IF NOT Y OR N TYPE ""	
1477	011152	000763			BR	30\$:TRY AGAIN	
1478	011154	052722	040000		17\$:	BIS	#BIT14,(R2)+	:TURNAROUND IS CONNECTED
1479	011160	000402			BP	19\$		
1480	011162	042722	040000		18\$:	BIC	#BIT14,(R2)+	:NO TURNAROUND
1481	011166				19\$:			
1482	011166	104402			INSTR			
1483	011170	007016			LINE			
1484	011172	104405			PARAM			
1485	011174	000000			0			
1486	011176	000377			377			
1487	01:200	001254			TEMP4			
1488	011202	000			.BYTE	0		
1489	011203	001			.BYTE	1		
1490	011204	113722	001254		MOV8	TEMP4,(R2)+	:STORE SWITCH PAC IN MAP	
1491	011210	104403			INSTR			
1492	011212	007054			BM			
1493	011214	104405			PARAM			
1494	01:216	000000			0			

1495	011220	000377			377		
1496	011222	001254			TEMP4		
1497	011224	000			.BYTE	0	
1498	011225	001			.BYTE	1	
1499	011226	113722	001254		MOVB	TEMP4,(R2)+	
1500	011232	005722			TST	(R2)+	
1501	011234	005337	001252	33\$:	DEC	TEMP3	
1502	011240	001402			BEQ	34\$	
1503	011242	000137	010612		JMP	12\$	
1504	011246	000137	011702	34\$:	JMP	13\$	
1505	011252	012701	160000	7\$:	MOV	#160000,R1	
1506	011256	012737	011774	000004	MOV	#6\$,R4	
1507	011264	005011		2\$:	CLR	(R1)	
1508	011266	005711			TST	(R1)	
1509	011270	001172			BNE	3\$	
1510	011272	005061	000006		CLR	6,(R1)	
1511	011276	005761	000006		TST	6,(R1)	
1512	011302	001165			BNE	3\$	
1513	011304	012711	002000		MOV	#BIT10,(R1)	
1514	011310	005061	000004		CLR	4(R1)	
1515	011314	012761	125252	000006	MOV	#125252,6(R1)	
1516	011322	052711	020000		BIS	#BIT13,(R1)	
1517	011326	022761	125252	000004	CMP	#125252,4(R1)	
1518	011334	001004			BNE	21\$	
1519	011336	052762	100000	000002	BIS	#BIT15,2(R2)	
1520	011344	000431			BR	22\$	
1521	011346	012711	001000	21\$:	MOV	#BIT9,(R1)	
1522	011352	012761	100417	000006	MOV	#100417,6(R1)	
1523	011360	012711	001400		MOV	#BIT9!BIT8,(R1)	
1524	011364	012711	002000		MOV	#BIT10,(R1)	
1525	011370	022761	000626	000006	CMP	#626,6(R1)	
1526	011376	001411			BEQ	23\$	
1527	011400	022761	016520	000006	CMP	#16520,6(R1)	
1528	011406	001410			BEQ	22\$	
1529	011410	022761	177777	000006	CMP	#-1,6(R1)	
1530	011416	001404			BEQ	22\$	
1531	011420	000516			BR	3\$	
1532	011422	052762	000002	000006	23\$:	BIS	#BIT1,6(R2)
1533					AT THIS POINT IT IS ASSUMED THAT	R1 HOLDS A DMC11 CSR ADDRESS.	
1534	011430	010122			22\$:	MOV	R1,(R2)+
1535	011432	012711	001000		15\$:	MOV	#BIT9,(R1)
1536	011436	005061	000004		CLR	4(R1)	
1537	011442	012761	122113	000006	MOV	#122113,6(R1)	
1538	011450	052711	000400		BIS	#BIT8,(R1)	
1539	011454	012761	021264	000006	MOV	#021264,6(R1)	
1540	011462	052711	000400		BIS	#BIT8,(R1)	
1541	011466	122761	000377	000004	CMPB	#377,4(R1)	
1542	011474	001003			BNE	+.10	
1543	011476	052712	010000		BIS	#BIT12,(R2)	
1544	011502	000436			BR	20\$	
1545	011504	032761	000002	000004	BIT	#BIT1,4(R1)	
1546	011512	001403			BEQ	+.10	
1547	011514	052712	060000		BIS	#BIT13!BIT14,(R2)	
1548	011520	000427			BR	20\$	
1549	011522	032761	000010	000004	BIT	#BIT3,4(R1)	
1550	011530	001023			BNE	20\$	

```

:STORE SWITCH PAC IN MAP
:POP OVER STAT3
:DEC DMC COUNT
:BR IF DONE
:JUMP IF NOT
:CONTINUE
:SET FOR FIRST ADDRESS TO BE TESTED
:SET FOR NON-EXISTANT DEVICE TIME OUT
:CLEAR SEL0
:IF DMC11 DMC5R 5/8 0
:IF NO DEV : TRAP TO 4. IF NO BIT 9 THEN NO DMC1
:CLEAR SEL6
:IF DMC11 THEN DMC10 5/8 =0!
:BR IF NOT DMC1!
:SET ROM0
:CLEAR SEL4
:WRITE THIS TO SEL6
:WRITE IT!
:WAS IT WRITTEN?
:IF NO IT IS NOT CROM
:SET BIT15 IF CROM
:SET ROM1
:PUT INSTRUCTION IN SEL6
:CLOCK INSTRUCTION (MICRO PROC PC TO 0)
:SET ROM0
:IS IT LOCAL CROM
:BR IF YES
:IS IT REMOTE CROM?
:BR IF YES
:NO CROM?
:BR IF YES
:NOT A DMC
:SET BIT 1 IN STAT3
:STORE CSR IN CORE TABLE.
:CLEAR LINE UNIT LOOP
:CLEAR PORT4
:LOAD INSTRUCTION (CLR CTR)
:CLOCK INSTRUCTION
:LOAD INSTRUCTION
:CLOCK INSTRUCTION
:IS IT ALL ONES?
:BR IF NO
:IF YES, NO LINE UNIT, SET STATUS BIT
:IS SWITCH A ONE?
:BR IF M8201
:M8202 ASSUME CONNECTOR
:CONNECTOR ON)
:IS M8201 SET
:BR IF M8201 NO CONNECTOR ON LINE

```

```

1551 011532 012761 000100 000004      MOV      #BIT6,4(R1)      ;LOAD PORT4
1552 011540 012761 122113 000006      MOV      #122113,6(R1)   ;LOAD INSTRUCTION
1553 011546 052711 000400              BIS      #BIT8,(R1)      ;CLOCK INSTRUCTION(SET STR)
1554 011552 012761 021264 000006      MOV      #021264,6(R1)   ;LOAD INSTRUCTION
1555 011560 052711 000400              BIS      #BIT8,(R1)      ;CLOCK INSTRUCTION(READ MODEM REG.)
1556 011564 032761 000010 000004      BIT      #BIT3,4(R1)     ;IS MRDY SET NOW?
1557 011572 001402              BEQ      20$             ;BR IF NO CONNECTOR
1558 011574 052712 040000              BIS      #BIT14,(R2)    ;SET STATUS BIT FOR CONNECTOR
1559 011600 005722              20$: TST      (R2)+          ;POP POINTER
1560 011602 012761 021324 000006      MOV      #021324,6(R1)   ;PUT INSTRUCTION IN PORT6
1561 011610 012711 001400              MOV      #BIT9!BIT8,(R1) ;PORT4+LU IS
1562 011614 156122 000004              BISH    4(R1),(R2)+      ;STORE ODCMP LINE # IN TABLE
1563 011620 012761 021344 000006      MOV      #021344,6(R1)   ;PORT6+INSTRUCTION
1564 011626 012711 001400              MOV      #BIT8!BIT9,(R1) ;CLOCK INSTR.
1565 011632 156122 000004              BISH    4(R1),(R2)+      ;STORE BM873 ADD IN TABLE
1566 011636 005722              TST      (R2)+          ;POP OVER STAT3
1567 011640 005011              CLR      (R1)           ;CLEAR ROMI
1568 011642 005237 001310              INC      DMNUM          ;UPDATE DEVICE COUNTER
1569 011646 022737 000020 001310      CMP      #20,DMNUM      ;ARE MAX. NO. OF DEV FOUND?
1570 011654 001412              BEQ      13$            ;YES DON'T LOOK FOR ANY MORE.
1571 011656 005011              3$: CLR      (R1)       ;CLEAR BIT 10
1572 011660 005061 000006              CLR      6(R1)         ;CLEAR SEL 6
1573 011664 062701 000010              14$: ADD      #10,R1    ;UPDATE CSR POINTER ADDRESS
1574 011670 022701 164000              CMP      #164000,R1
1575 011674 001402              BEQ      13$            ;BR IF DONE
1576 011676 000137 011264              JMP      2$             ;JUMP IF NOT
1577 011702 005037 001306              13$: CLR      DMACTV    ;WERE ANY DMC11'S FOUND AT ALL?
1578 011706 005737 001310              TST      DMNUM          ;ERROR AUTO SIZER FOUND NO DMC11'S IN THIS SYS.
1579 011712 001423              BEQ      5$             ;
1580 011714 013701 001310              MOV      DMNUM,R1
1581 011720 010137 001314              MOV      R1,SAVNUM     ;SAVE NUMBER OF DEVICES
1582 011724 000241              4$: CLC              ;GENERATE ACTIVE REGISTER OF DEVICES.
1583 011726 006137 001306              ROL      DMACTV        ;SET THE BIT
1584 011732 005237 001306              INC      DMACTV
1585 011736 005301              DEC      R1
1586 011740 001371              BNE      4$            ;BR IF MORE TO GENERATE
1587 011742 012737 000006 000004      MOV      #6,2#4        ;RESTORE TRAP VECTOR
1588 011750 013737 001306 001312      MOV      DMACTV,SAVACT ;SAVE ACTIVE REGISTER
1589 011756 000137 012010              JMP      VECMAP        ;GO FIND THE VECTOR NOW.
1590 011762 104402 005760              5$: TYPE      MERR2    ;NOTIFY OPR THAT NO DMC11'S FOUND.
1591 011766 005000              CLR      R0            ;MAKE DATA LIGHTS ZERO
1592 011770 000000              HALT                    ;STOP THE SHOW
1593 011772 000776              BR      -2             ;DISABLE CONT. SW.
1594 011774 012716 011664              6$: MOV      #14$,(SP) ;ENTERED BY NON-EXISTANT TIME-OUT.
1595 012000 000002              RTI                    ;RETURN TO MAINSTREAM
1596
1597 012002 000001              WHICH: 1
1598 012004          002          002          .BYTE 2,2
1599 012006 001256              *EMPS
1600
1601 012010 032737 000001 001236      VECMAP: BIT      #SW00,STRSW
1602 012016 001114              BNE      5$            ;
1603 012020 012737 000340 000022      MOV      #340,2#22     ;SET IOT TRAP PRIO TO 7
1604 012026 012737 012202 000020      MOV      #4$,(2#20)    ;SET IOT TRAP VECTOR
1605 012034 012702 001500              MOV      #DM.MAP,R2   ;SET SOFTWARE POINTER
1606 012040 012700 000300              MOV      #300,R0      ;FLOATING VECTORS START HERE.

```

1607	012044	012701	000302		MOV	#302,R1	:PC OF IOT INSTR
1608	012050	010120		15:	MOV	R1,(R0)+	:START FILLING VECTOR AREA
1609	012052	012721	000004		MOV	#4,(R1)+	:WITH .+2; IOT
1610	012056	022021			CMP	(R0)+(R1)+	:ADD 2 TO R0 +R1
1611	012060	020127	001000		CMP	R1,#1000	
1612	012064	101771			BLOS	15	:BR IF MORE TO FILL
1613	012066	013737	001306	001246	MOV	DMACTV,TEMP1	:STORE TEMPORALLY
1614	012074	006037	001246	25:	ROR	TEMP1	:BRING OUT A BIT
1615	012100	103063			BCC	55	:BR IF ALL DONE
1616	012102	012704	000012		MOV	#12,R4	:R4 IS INDEX REGISTER
1617	012106	016437	012252	177776	MOV	BRLVL(R4),PS	:SET PS TO 7
1618	012114	011201			MOV	(R2),R1	
1619	012116	012761	000200	000004	MOV	#200,4(R1)	
1620	012124	012711	001000		MOV	#BIT9,(R1)	:SET ROMI
1621	012130	012761	121111	000006	MOV	#121111,6(R1)	:PUT INSTRUCTION IN PCRT6
1622	012136	012711	001400		MOV	#BIT9!BIT8,(R1)	:FORCE AN INTERRUPT
1623	012142	105200		75:	RO		:STALL
1624	012144	001376			BNE	.-2	:FOR TIME TO INTERRUPT
1625	012146	162704	000002		SUB	#2,R4	:GET NEXT LOWEST PS LEVEL
1626	012152	001404			BEQ	65	:BR IF R4 = 0
1627	012154	016437	012252	177776	MOV	BRLVL(R4),PS	:MOVE NEXT LOWER LEVEL IN PS
1628	012162	000767			BR	75	:BR TO DELAY
1629	012164	052762	005300	000002	65:	BIS	#5300,2(R2)
1630	012172	005011		35:	CLR	(R1)	:NO INTERRUPT ASSUME 300 AT LEVEL 5 AND FIX DMC11
1631	012174	062702	000010		ADD	#10,R2	:CLEAR ROMI
1632	012200	000735			BR	25	:POP SOFTWARE POINTER
1633	012202	051662	000002		45:	BIS	(SP),2(R2)
1634	012206	042762	000007	000002	BIC	#7,2(R2)	:KEEP GOING
1635	012214	016405	012254		MOV	BRLVL+2(R4),R5	:GET VECTOR ADDRESS
1636	012220	006305			ASL	R5	:CLEAR JUNK
1637	012222	006305			ASL	R5	:GET BR LEVEL OF DMC11
1638	012224	006305			ASL	R5	:SHIFT LEVEL 4 PLACES
1639	012226	006305			ASL	R5	:TO THE LEFT FOR THE
1640	012230	042705	170777		BIC	#170777,R5	:STATUS TABLE
1641	012234	050562	000002		BIS	R5,2(R2)	:CLEAR UNWANTED BITS
1642	012240	022626			CMP	(SP)+(SP)+	:PUT BR LEVEL IN STATUS TABLE
1643	012242	012716	012172		MOV	#35,(SP)	:POP IOT JUNK OFF STACK
1644	012246	000002			RTI		:SET FOR RETURN
1645	012250	000207		55:	RTS	PC	:ALL DONE WITH "AUTO SIZING"
1646							
1647	012252	000000		BR_LVL:	0		:LEVEL 0
1648	012254	000000			0		:LEVEL 0
1649	012256	000200			200		:LEVEL 4
1650	012260	000240			240		:LEVEL 5
1651	012262	000300			300		:LEVEL 6
1652	012264	000340			340		:LEVEL 7
1653							
1654							
1655	012266	105777	166712	INTTY:	TSTB	@TKCSR	:WAIT FOR DONE
1656	012272	100375			BPL	.-4	
1657	012274	017703	166706		MOV	@TKDBR,R3	:PUT CHAR IN R3
1658	012300	105777	166704		TSTB	@TPCSR	:WAIT UNTIL PRINTER IS READY
1659	012304	100375			BPL	.-4	
1660	012306	010377	166700		MOV	R3,@TPDBR	:ECHO CHAR
1661	012312	042703	000240		BIC	#BIT7!BITS,R3	:MASK OFF LOWER CASE
1662	012316	000207			RTS	PC	:RETURN

K04

DZDMH MACY11 30(1046) 11-JUL-77 12:32 PAGE 34
DZDMH.P11 16-MAY-77 09:54 GENERAL UTILITIES (TYPEOUT, ERROR, SCOPE, ETC)

PAGE: 0049

1663

1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719

012320 012737 000001 001226
012326 012737 013404 001216
012334 032737 100000 001366
012342 001406
012344 032737 000001 001372
012352 001002
012354 000137 013402
012360 032737 010000 001366
012366 001372
012370 013700 021370
012374 062700 000002
012400 012702 021372
012404 105022
012406 005300
012410 001375
012412 005037 021316
012416 005037 021320
012422 012711 040000
012426 032737 100000 001366
012434 001402
012436 012711 100000
012442 105227 000000
012446 001375
012450 005037 001416
012454 005711
012456 100405
012460 005237 001416
012464 001373
012466 104014
012470 000771
012472 052711 004043
012476 005037 001416
012502 105711
012504 100404
012506 005237 001416
012512 001373
012514 104014

```
***** TEST 1 *****  
*FREE RUNNING FLAG MODE DATA TEST  
*TRANSMIT A MESSAGE AND VERIFY THE RECEIVED DATA  
*LINE UNIT LOOP IS SET FOR THIS TEST.  
*ALL FOLLOWING TESTS ARE FREE RUNNING AND ARE PERFORMED  
*ONLY ON DMC'S WITH LINE UNITS. IF YOU WISH TO PERFORM  
*THESE FREE RUNNING TESTS ON A KMC (NORMALLY THE FREE RUNNING TESTS  
*WILL FAIL ON A KMC, THE TIMER IS TOO FAST) THEN YOU MUST  
*MANUALLY SET BIT0 OF STAT3 IN THE STATUS MAP. ALSO THE KMC  
*MUST HAVE THE MICRO-CODE LOADED BY PREVIOUSLY RUNNING  
*DZDMG TEST 2 AND THEN LOADING AND STARTING DZDMH  
* WITH SWITCH 7 = 1  
*****  
: TEST 1  
-----  
*ST1: MOV #1,TSTNO  
MOV #TST2,NEXT ;R1 CONTAINS BASE DMC11 ADDRESS  
BIT #BIT15,STAT1 ;IS IT A DMC?  
BEQ .+16 ;BR IF YES  
BIT #BIT0,STAT3 ;KMC WITH BIT0 SET?  
BNE .+6 ;BR IF YES  
JMP 14$ ;SKIP TEST  
BIT #BIT12,STAT1 ;LU PRESENT?  
BNE .-12 ;BR IF NO  
MOV RCOUNT,RO ;CLEAR RECEIVER BUFFER  
ADD #2,RO ;CLEAR 2 MORE LOCATIONS  
MOV #RBUF,R2 ;CLEAR OUT RECEIVE BLFFEP  
10$: CLRB (R2)+ ;CLEAR BUFFER  
DEC RO ;DONE YET!  
BNE 10$ ;NO  
CLR TFLAG ;SET TFLAG TO 0  
CLR RFLAG ;SET RFLAG TO 0  
MOV #BIT14,(R1) ;MASTER CLEAR  
BIT #BIT15,STAT1 ;CRAM?  
BEQ .+6 ;BR IF NO  
MOV #BIT15,(R1) ;IF CRAM SET RUN  
INCB #0 ;DELAY  
BNE .-4 ;DELAY  
CLR TEMP ;GET SET TO DELAY  
1$: TST (R1) ;RUN SET?  
BMI .+14 ;BR IF YES  
INC TEMP ;INC DELAY  
BNE 1$ ;BR IF NOT DONE  
HLT 14 ;ERROR RUN NOT SET  
BR 1$ ;TRY AGAIN  
BIS #4043,(R1) ;BASE I, LU LOOP  
CLR TEMP ;GET SET TO DELAY  
2$: TSTB (R1) ;RDI SET?  
BMI .+12 ;BR IF YES  
INC TEMP ;INC DELAY  
BNE 2$ ;BR IF NOT DONE  
HLT 14 ;ERROR,RDI NOT SET
```

1720	012516	012761	021440	000004	MOV	#BASE,4(R1)	;SET UP BASE ADDRESS
1721	012524	005061	000006		CLR	6(R1)	;CLEAR COUNT
1722	012530	142711	000040		BICB	#40,(R1)	;CLEAR RQI
1723	012534	005037	001416		CLR	TEMP	;GET SET TO DELAY
1724	012540	105711		3\$:	TSTB	(R1)	;IS RDI GONE?
1725	012542	100020			BPL	8\$;BR IF YES
1726	012544	005237	001416		INC	TEMP	;INC DELAY
1727	012550	001373			BNE	3\$;BR IF NOT DONE
1728	012552	105761	000002		TSTB	2(R1)	;IS THERE A CNTL 0 ERROR
1729	012556	100011			BPL	18\$;BR IF NO
1730	012560	016137	000004	001252	MOV	4(R1),TEMP3	;SAVE SEL4 FOR TYPEOUT
1731	012566	016137	000006	001254	MOV	6(R1),TEMP4	;SAVE SEL6 FOR TYPEOUT
1732	012574	104016			HLT	16	;CNTL 0 ERROR
1733	012576	000137	013402		JMP	14\$;FATAL ERROR STOP
1734	012602	104014		18\$:	HLT	14	;ERROR RDI STILL SET
1735	012604			8\$:			
1736	012604	152711	000041		BISB	#41,(R1)	;ASK FOR CNTL I
1737	012610	105711		64\$:	TSTB	(R1)	;WAIT FOR RDI
1738	012612	100376			BPL	64\$;BR IF NOT SETY
1739	012614	005061	000006		CLR	6(R1)	;SET FULL DUPLEX
1740	012620	142711	000040		BICB	#40,(R1)	;CLEAR RQI
1741	012624	105711		65\$:	TSTB	(R1)	;RDI UP?
1742	012626	100776			BMI	65\$;BR IF YES
1743	012630	152711	000044		BISB	#44,(R1)	;REC BA/CC
1744	012634	005037	001416		CLR	TEMP	;GET SET TO DELAY
1745	012640	105711		4\$:	TSTB	(R1)	;IS RDI SET?
1746	012642	100404			BMI	.+12	;BR IF YES
1747	012644	005237	001416		INC	TEMP	;INC DELAY
1748	012650	001373			BNE	4\$;BR IF DELAY NOT DONE
1749	012652	104014			HLT	14	;ERROR RDI NOT SET
1750	012654	012761	021372	000004	MOV	#RBUF,4(R1)	;LOAD REC BA
1751	012662	013761	021370	000006	MOV	RCOUNT,6(R1)	;LOAD REC COUNT
1752	012670	142711	000040		BICB	#40,(R1)	;CLEAR RQI
1753	012674	005037	001416		CLR	TEMP	;GET SET TO DELAY
1754	012700	105711		5\$:	TSTB	(R1)	;RDI GONE?
1755	012702	100004			BPL	.+12	;BR IF YES
1756	012704	005237	001416		INC	TEMP	;INC DELAY
1757	012710	001373			BNE	5\$;BR IF NO DONE
1758	012712	104014			HLT	14	;ERROR RDI STILL SET
1759	012714	152711	000040		BISB	#40,(R1)	;XMIT BA/CC
1760	012720	005037	001416		CLR	TEMP	;GET SET TO DELAY
1761	012724	105711		6\$:	TSTB	(R1)	;RDI SET?
1762	012726	100404			BMI	.+12	;BR IF YES
1763	012730	005237	001416		INC	TEMP	;INC DELAY
1764	012734	001373			BNE	6\$;BR IF NOT DONE
1765	012736	104014			HLT	14	;ERROR RDI NOT SET
1766	012740	012761	021324	000004	MOV	#TBUF,4(R1)	;LOAD XMIT BUFFER
1767	012746	013761	021322	000006	MOV	TCOUNT,6(R1)	;LOAD COUNT
1768	012754	142711	000040		BICB	#40,(R1)	;CLEAR RQI
1769	012760	005037	001416		CLR	TEMP	;GET SET TO DELAY
1770	012764	105711		7\$:	TSTB	(R1)	;RDI GONE?
1771	012766	100004			BPL	.+12	;BR IF YES
1772	012770	005237	001416		INC	TEMP	;INC DELAY
1773	012774	001373			BNE	7\$;BR IF NOT DONE DELAY
1774	012776	104014			HLT	14	;ERROR RDI STILL SET
1775	013000	005037	001416	16\$:	CLR	TEMP	;GET SET TO DELAY

1776	013004	012737	000022	001246		MOV	#22,TEMP1	:GET SET FOR LONG DELAY
1777	013012	105761	000002		11\$:	TSTB	2(R1)	:RDO SET?
1778	013016	100407				BMI	17\$:BR IF YES
1779	013020	005237	001416			INC	TEMP	:INC DELAY
1780	013024	001372				BNE	11\$:BR IF DELAY NOT DONE
1781	013026	005337	001246			DEC	TEMP1	:DEC DELAY COUNT
1782	013032	001367				BNE	11\$:BR IF NOT DONE DELAY
1783	013034	104014				HLT	14	:ERROR RDO NOT SET
1784	013036	016137	000002	001250	17\$:	MOV	2(R1),TEMP2	:SAVE SEL2
1785	013044	001001				BNE	+.4	:BR IF OK
1786	013046	104014				HLT	14	:ERROR!!! SEL2 = 0!!!!!!
1787	013050	032761	000004	000002		BIT	#BIT2,2(R1)	:REC OR XMIT?
1788	013056	001032				BNE	13\$:BR IF REC
1789	013060	005737	021316		12\$:	TST	TFLAG	:FIRST TIME HERE?
1790	013064	001401				BEQ	+.4	:BR IF YES
1791	013066	104014				HLT	14	:ERROR MULTIPLE XMIT DONES
1792	013070	012737	177777	021316		MOV	#-1,TFLAG	:SET TFLAG TO -1
1793	013076	132761	000001	000002		BITB	#BIT0,2(R1)	:IS IT CONTROL 0
1794	013104	001401				BEQ	+.4	:BR IF NO
1795	013106	104014				HLT	14	:XMIT ERROR
1796	013110	022761	021324	000004		CMP	#TBUF,4(R1)	:XMIT BA CORRECT?
1797	013116	001401				BEQ	+.4	:BR IF YES
1798	013120	104014				HLT	14	:XMIT BA ERROR
1799	013122	023761	021322	000006		CMP	Tcount,6(R1)	:COUNT OK?
1800	013130	001401				BEQ	+.4	:BR IF YES
1801	013132	104014				HLT	14	:XMIT COUNT ERROR
1802	013134	142761	000207	000002		BICB	#207,2(R1)	:CLEAR RDO AND BITS 0-2
1803	013142	000453				BR	15\$:CONTINUE
1804	013144	005737	021320		13\$:	TST	RFLAG	:FIRST TIME HERE?
1805	013150	001401				BEQ	+.4	:BR IF YES
1806	013152	104014				HLT	14	:ERROR MULTIPLE REC DONES
1807	013154	012737	177777	021320		MOV	#-1,RFLAG	:SET RFLAG TO -1
1808	013162	132761	000001	000002		BITB	#BIT0,2(R1)	:IS IT CNTL 0
1809	013170	001401				BEQ	+.4	:BR IF NO
1810	013172	104014				HLT	14	:RECEIVE ERROR
1811	013174	022761	021372	000004		CMP	#RBUF,4(R1)	:REC BA CORRECT?
1812	013202	001401				BEQ	+.4	:BR IF YES
1813	013204	104014				HLT	14	:REC BA ERROR
1814	013206	023761	021370	000006		CMP	Rcount,6(R1)	:COUNT OK?
1815	013214	001401				BEQ	+.4	:BR IF YES
1816	013216	104014				HLT	14	:REC COUNT ERROR
1817	013220	013700	021370			MOV	Rcount,R0	:GET SET TO CHECK DATA
1818	013224	012732	021324			MOV	#TBUF,R2	:R2 POINTS TO GOOD DATA
1819	013230	012703	021372			MOV	#RBUF,R3	:R3 POINTS TO RECEIVE DATA
1820	013234	010337	001252		9\$:	MOV	R3,TEMP3	:SAVE ADDRESS FOR TYPEOUT
1821	013240	112205				MOVB	(R2)+,R5	:R5 = XMIT DATA
1822	013242	112304				MOVB	(R3)+,R4	:R4 = RECEIVE DATA
1823	013244	120504				CMPB	R5,R4	:CHECK DATA
1824	013246	001401				BEQ	+.4	:BR IF OK
1825	013250	104013				HLT	13	:DATA ERROR
1826	013252	005300				DEC	R0	:DEC COUNT
1827	013254	001367				BNE	9\$:BR IF NOT DCNE
1828	013256	005713				TST	(R3)	:THIS SHOULD BE 0, ELSE
1829	013260	001401				BEQ	+.4	:IT RECEIVED TO MUCH!!
1830	013262	104014				HLT	14	:ERROR
1831	013264	142761	000207	000002		BICB	#207,2 R1)	:CLEAR RDC AND BITS 0-2

```

1832 013272 005737 021320      15$: TST RFLAG ;REC DONE?
1833 013276 001640              BEQ 16$ ;BR IF NO
1834 013300 005737 021316      TST TFLAG ;XMIT DONE?
1835 013304 001635              BEQ 16$ ;BR IF NO
1836 013306 004737 022502      JSR PC,SHUTDOWN ;SHUTDOWN DMC
1837 013312 012700 013340      MOV #25$,R0 ;POINTER TO EXPECTED SOFT COUNTS
1838 013316 012701 021443      21$: MOV #BASE+3,R1 ;POINTER TO ACTUAL COUNTS
1839 013322 012702 000010      MOV #10,R2 ;COUNT
1840 013326 122021              22$: CMPB (R0)+,(R1)+ ;COMPARE SOFT ERROR COUNTS
1841 013330 001007              BNE 23$ ;IF ERROR BR 23$
1842 013332 005302              DEC R2 ;DEC COUNT
1843 013334 001374              BNE 22$ ;CONTINUE CHECKING IF NOT DONE
1844 013336 000421              BR 24$ ;ALL COUNTS OK, GET OUT
1845 013340 000 000 000      25$: .BYTE 0,0,0,0,0,0,0,0 ;EXPECTED ERROR COUNTS
1846 013343 000 000 000
1847 013346 000 000 000
1848 013350 113737 021443 001250      23$: MOVB BASE+3,TEMP2
1849 013356 113737 021445 001252      MOVB BASE+5,TEMP3
1850 013364 113737 021447 001254      MOVB BASE+7,TEMP4
1851 013372 113737 021451 001256      MOVB BASE+11,TEMPS
1852 013400 104017              HLT 17
1853 013402              24$:
1854 013402 104400      14$: SCOPE ;SCOPE THIS TEST
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864

```

```

:***** TEST 2 *****
: *OVERUN TEST
: *IN FREE RUNNING MODE SEND MESSAGE WITH NO RECEIVE
: *BUFFER AVAILABLE, VERIFY THAT AN OVERRUN ERROR OCCURS
:*****

```

: TEST 2

```

1865 013404 012737 000002 001226      *ST2: MOV #2,TSTNO
1866 013412 012737 013754 001216      MOV #TST3,NEXT
1867
1868 013420 032737 100000 001366      BIT #BIT15,STAT1 ;RI CONTAINS BASE DMC! ADDRESS
1869 013426 001406              BEQ .+16 ;IS IT A DMC?
1870 013430 032737 000001 001372      BIT #BIT0,STAT3 ;BR IF YES
1871 013436 001002              BNE .+6 ;KMC WITH BIT0 SET?
1872 013440 000137 013736              JMP 10$ ;BR IF YES
1873 013444 032737 010000 001366      BIT #BIT12,STAT1 ;SKIP TEST
1874 013452 001372              BNE .-12 ;LU PRESENT?
1875 013454 004737 022040      JSR PC,BASELD ;BR IF NO
1876 013460 004537 022450      JSR R5,XFRELD ;LOAD DMC BASE ADDRESS
1877 013464 021324              TBUF ;LOAD XMIT BA/CC
1878 013466 000044              +4 ;BA
1879 013470 012700 000010      MOV #10,R0 ;CC
1880 013474 012703 000015      MOV #15,R3 ;RO = RETRANSMISSION COUNT
1881 013500 005037 001416      CLR TEMP ;DELAY COUNT
1882 013504 105761 000002      1$: TSTB 2(R1) ;CLEAR DELAY COUNTER
1883 013510 100407              BMI .+20 ;IS RDY 0 SET?
1884 013512 005237 001416      INC TEMP ;BR IF SET
1885 013516 001372              BNE 1$ ;INC DELAY COUNTER
1886 013520 005303              DEC R3 ;BR IF NOT DONE DELAY
1887 013522 001372              BNE 1$ ;DEC DELAY COUNT
;BR IF DELAY NOT DONE

```

```

1888 013524 104014          HLT      14          ;ERROR, RDY C NOT SET
1889 013526 000503          BR       10$        ;GET OUT
1890 013530 132761 000001 000002 BITB     #BIT0,2(R1) ;IS IT CNTL 0?
1891 013536 001002          BNE     11$        ;BR IF YES
1892 013540 104014          HLT      14          ;ERROR, NOT CNTL 0
1893 013542 000475          BR       10$        ;CONTINUE
1894 013544 012705 000004 11$:     MOV     #BIT2,R5    ;PUT "EXPECTED" IN R5
1895 013550 016104 000006          MOV     6(R1),R4    ;PUT "FOUND" IN R4
1896 013554 020504          CMP     R5,R4      ;IS ORUN SET?
1897 013556 001404          BEQ     12$        ;BR IF YES
1898 013560 022704 000001          CMP     #1,R4      ;DATA CK ERROR?
1899 013564 001465          BEQ     13$        ;BR IF YES
1900 013566 104015          HLT      15          ;ERROR, ORUN NOT SET
1901 013570 042761 000207 000002 12$:     BIC     #207,2(R1)  ;CLEAR RDO
1902 013576 005037 001416          CLR     TEMP       ;RESET DELAY
1903 013602 005300          DEC     R0         ;DEC RETRANS COUNT
1904 013604 001337          BNE     1$         ;CONTINUE
1905 013606 004737 022502          JSR     PC,SHUTDOWN ;SHUTDOWN DMC
1906 013612 032737 020000 001366 BIT      #BIT13,STAT1 ;IS IT AN M8201?
1907 013620 001446          BEQ     10$        ;SKIP BASE CHECK IF YES
1908 013622 012700 013664          MOV     #25$,R0    ;POINTER TO EXPECTED SOFT COUNTS (LOW SPEED)
1909 013626 032737 000002 001372 BIT      #BIT1,STAT3 ;IS IT HIGH OR LOW
1910 013634 001402          BEQ     21$        ;BR IF LOW
1911 013636 012700 013674          MOV     #26$,R0    ;POINTER TO EXPECTED SOFT COUNTS (HIGH SPEED)
1912 013642 012701 021443 21$:     MOV     #BASE+3,R1 ;POINTER TO ACTUAL COUNTS
1913 013646 012702 000010          MOV     #10,R2     ;COUNT
1914 013652 122021 22$:     CMPB   (R0)+,(R1)+ ;COMPARE SOFT ERROR COUNTS
1915 013654 001013          BNE     23$        ;IF ERROR BR 23$
1916 013656 005302          DEC     R2         ;DEC COUNT
1917 013660 001374          BNE     22$        ;CONTINUE CHECKING IF NOT DONE
1918 013662 000425          BR      24$        ;ALL COUNTS OK, GET OUT
1919 013664          000          000          000 25$:     .BYTE 0,0,0,100,0,0,0,0 ;EXPECTED ERROR COUNTS (LOW SPEED)
1920 013667          100          000          000
1921 013672          000          000          000
1922 013674          000          000          077 26$:     .BYTE 0,0,77,100,0,0,0,0 ;EXPECTED ERROR COUNTS (HIGH SPEED)
1923 013677          100          000          000
1924 013702          000          000          000
1925 013704 113737 021443 001250 23$:     MOVB   BASE+3,TEMP2
1926 013712 113737 021445 001252          MOVB   BASE+5,TEMP3
1927 013720 113737 021447 001254          MOVB   BASE+7,TEMP4
1928 013726 113737 021451 001256          MOVB   BASE+11,TEMP5
1929 013734 104017          HLT      17
1930 013736          24$:
1931 013736 104400          10$:     SCOPE ;SCOPE THIS TEST
1932 013740 042761 000207 000002 13$:     BIC     #207,2(R1) ;IGNOR THIS ERROR
1933 013746 005037 001416          CLR     TEMP       ;RESET DELAY
1934 013752 000654          BR      1$         ;CONTINUE
1935
1936
1937
1938 ;***** TEST 3 *****
1939 ;*LOST DATA TEST
1940 ;*IN FREE RUNNING MODE SEND A MESSAGE LONGER THAN THE RECEIVE
1941 ;*BUFFER, VERIFY THAT A LOST DATA ERROR OCCURS.
1942 ;*****
1943 ; TEST 3

```


Address	Hex 1	Hex 2	Hex 3	Hex 4	Label	Instruction	Comments
2000	014234	104400			10\$:	SCOPE	;SCOPE THIS TEST
2001							
2002							
2003							***** TEST 4 *****
2004							*TRANSMIT NON-EXISTENT MEMORY TEST
2005							*IN FREE RUNNING MODE, LOAD A TRANSMIT BA THAT WILL TIME OUT
2006							*VERIFY THAT A NON-EXISTENT MEMORY ERROR OCCURS
2007							*****
2008							
2009							; TEST 4
2010							-----
2011	014236	012737	000004	001226	TST4:	MOV #4,TSTNO	
2012	014244	012737	014510	001216		MOV #TSTS,NEXT	
2013							;R1 CONTAINS BASE DMC11 ADDRESS
2014	014252	104412				MSTCLR	;MASTER CLEAR DMC11
2015	014254	032737	100000	001366		BIT #BIT15,STAT1	;IS IT A DMC?
2016	014262	001406				BEQ .+16	;BR IF YES
2017	014264	032737	000001	001372		BIT #BIT0,STAT3	;KMC WITH BIT0 SET?
2018	014272	001002				BNE .+6	;BR IF YES
2019	014274	000137	014506			JMP 10\$;SKIP TEST
2020	014300	032737	010000	001366		BIT #BIT12,STAT1	;LU PRESENT?
2021	014306	001372				BNE .-12	;BR IF NO
2022	014310	004737	022040			JSR PC,BASELD	;LOAD DMC BASE ADDRESS
2023	014314	004537	022450			JSR RS,XFRELD	;LOAD XMIT BA/CC
2024	014320	177320				177320	;BA
2025	014322	140044				140044	;CC
2026	014324	012703	000015			MOV #15,R3	;DELAY COUNT
2027	014330	005037	001416			CLR TEMP	;CLEAR DELAY COUNTER
2028	014334	105761	000002		1\$:	TSTB 2(R1)	;IS RDY 0 SET?
2029	014340	100407				BMI .+20	;BR IF SET
2030	014342	005237	001416			INC TEMP	;INC DELAY COUNTER
2031	014346	001372				BNE 1\$;BR IF NOT DONE DELAY
2032	014350	005303				DEC R3	;DEC DELAY COUNT
2033	014352	001370				BNE 1\$;BR IF DELAY NOT DONE
2034	014354	104014				HLT 14	;ERROR, RDY 0 NOT SET
2035	014356	000453				BR 10\$;GET OUT
2036	014360	132761	000001	000002		BITB #BIT0,2(R1)	;IS IT CNTL 0?
2037	014366	001002				BNE 11\$;BR IF YES
2038	014370	104014				HLT 14	;ERROR, NOT CNTL 0
2039	014372	000445				BR 10\$;CONTINUE
2040	014374	012705	000400		11\$:	MOV #BIT8,R5	;PUT "EXPECTED" IN R5
2041	014400	016104	000006			MOV 6(R1),R4	;PUT "FOUND" IN R4
2042	014404	020504				CMP R5,R4	;IS NON-EX-MEM SET?
2043	014406	001401				BEQ .+4	;BR IF YES
2044	014410	104015				HLT 15	;ERROR NON-EX-MEM NOT SET
2045	014412	004737	022502			JSR PC,SHUTDOWN	;SHUTDOWN DMC
2046	014416	012700	014444			MOV #25\$,R0	;POINTER TO EXPECTED SOFT COUNTS
2047	014422	012701	021443		21\$:	MOV #BASE+3,R1	;POINTER TO ACTUAL COUNTS
2048	014426	012702	000010			MOV #10,R2	;COUNT
2049	014432	122021			22\$:	CMPB (R0)+,(R1)+	;COMPARE SOFT ERROR COUNTS
2050	014434	001007				BNE 23\$;IF ERROR BR 23\$
2051	014436	005302				DEC R2	;DEC COUNT
2052	014440	001374				BNE 22\$;CONTINUE CHECKING IF NOT DONE
2053	014442	000421				BR 24\$;ALL COUNTS OK, GET OUT
2054	014444	000	000	000	25\$:	.BYTE 0,0,0,0,0,0,0,0	;EXPECTED ERROR COUNTS
2055	014447	000	000	000			


```

2168 015130 016104 000006      MOV      6(R1),R4      ;PUT "FOUND" IN R4
2169 015134 020504              CMP      R5,R4        ;IS PROC ERROR SET?
2170 015136 001401              BEQ      .+4          ;BR IF YES
2171 015140 104015              HLT      15           ;ERROR, PROC ERROR NOT SET
2172 015142 012700 015170      MOV      #255,R0      ;POINTER TO EXPECTED SOFT COUNTS
2173 015146 012701 021443 215:  MOV      #BASE+3,R1   ;POINTER TO ACTUAL COUNTS
2174 015152 012702 000010      MOV      #10,R2      ;COUNT
2175 015156 122021 225:  CMPB     (R0)+,(R1)+   ;COMPARE SOFT ERROR COUNTS
2176 015160 001007              BNE      235         ;IF ERROR BR 235
2177 015162 005302              DEC      R2          ;DEC COUNT
2178 015164 001374              BNE      225         ;CONTINUE CHECKING IF NOT DONE
2179 015166 000421              BR       245         ;ALL COUNTS OK, GET OUT
2180 015170          000      000      000 255:  .BYTE   0,0,0,0,0,0,0 ;EXPECTED ERROR COUNTS
2181 015173          000      000      000
2182 015176          000      000
2183 015200 113737 021443 001250 235:  MOVB     BASE+3,TEMP2
2184 015206 113737 021445 001252      MOVB     BASE+5,TEMP3
2185 015214 113737 021447 001254      MOVB     BASE+7,TEMP4
2186 015222 113737 021451 001256      MOVB     BASE+11,TEMP5
2187 015230 104017              HLT      17
2188 015232 245:
2189 015232 104400 105:  SCOPE      ;SCOPE THIS TEST
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201 015234 012737 000007 001226  TST7:  MOV      #7,TSTNO
2202 015242 012737 015776 001216      MOV      #TST10,NEXT
2203
2204 015250 104412              MSTCLR                    ;R1 CONTAINS BASE DMC11 ADDRESS
2205 015252 032737 100000 001366      BIT      #BIT15,STAT1    ;MASTER CLEAR DMC1
2206 015260 001406              BEQ      .+16          ;IS IT A DMC?
2207 015262 032737 000001 001372      BIT      #BIT0,STAT3    ;BR IF YES
2208 015270 001002              BNE      .+6          ;KMC WITH BIT0 SET?
2209 015272 000137 015474              JMP      105          ;BR IF YES
2210 015276 032737 010000 001366      JMP      105          ;SKIP TEST
2211 015304 001372              BNE      .-12         ;LU PRESENT?
2212 015306 004737 022040              JSR      PC,BASELD     ;BR IF NO
2213 015312 152711 000046              BISB     #46,(R1)      ;LOAD DMC BASE ADDRESS
2214 015316 105711              TSTB    (R1)          ;RQI AND ILLEGAL CODE
2215 015320 100376              RPL      .-2          ;WAIT FOR RDI
2216 015322 142711 000040              BICB     #40,(R1)     ;BR IF NO RDI
2217 015326 005037 001416              CLR      TEMP        ;CLEAR RQI
2218 015332 105761 000002 15:  TSTB    2(R1)        ;CLEAR COUNTER
2219 015336 100405              BMI      .+14         ;RDY 0 SET?
2220 015340 005237 001416              INC      TEMP        ;BR IF YES
2221 015344 001372              SNE      15          ;BUMP COUNTER DELAY
2222 015346 104014              HLT      14          ;BR IF NOT DONE
2223 015350 000770              BR       15          ;ERROR NO RDY 0
2224 015352 132761 000001 000002      BITB     #BIT0,2,R1   ;TRY AGAIN
2225
2226
2227
2228
2229
2230
2231
2232
2233

```

```

2224 015360 001002      BNE      11$      ;BR IF YES
2225 015362 104014      HLT      14      ;ERROR, NOT CNTL C
2226 015364 000443      BR       10$      ;CONTINUE
2227 015366 012705 001000 11$: MOV     #BIT9,R5 ;PUT "EXPECTED" IN R5
2228 015372 016104 000006 MOV     6(R1),R4 ;PUT "FOUND" IN R4
2229 015376 020504      CMP     R5,R4    ;IS PROC ERROR SET?
2230 015400 001401      BEQ     .+4      ;BR IF YES
2231 015402 104015      HLT     15      ;ERROR PROC ERROR NOT SET
2232 015404 012700 015432 MOV     #25$,R0 ;POINTER TO EXPECTED SOFT COUNTS
2233 015410 012701 021443 21$: MOV     #BASE+3,R1 ;POINTER TO ACTUAL COUNTS
2234 015414 012702 000010 MOV     #10,R2   ;COUNT
2235 015420 122021 22$: CMPB   (R0)+,(R1)+ ;COMPARE SOFT ERROR COUNTS
2236 015422 001007      BNE     23$     ;IF ERROR BR 23$
2237 015424 005302      DEC     R2      ;DEC COUNT
2238 015426 001374      BNE     22$     ;CONTINUE CHECKING IF NOT DONE
2239 015430 000421      BR      24$     ;ALL COUNTS OK, GET OUT
2240 015432      000      000      000 25$: .BYTE 0,0,0,0,0,0,0,0 ;EXPECTED ERROR COUNTS
2241 015435      000      000      000
2242 015440      000      000
2243 015442 113737 021443 001250 23$: MOVB   BASE+3,TEMP2
2244 015450 113737 021445 001252 MOVB   BASE+5,TEMP3
2245 015456 113737 021447 001254 MOVB   BASE+7,TEMP4
2246 015464 113737 021451 001256 MOVB   BASE+11,TEMP5
2247 015472 104017      HLT     17
2248 015474      24$:
2249 015474 104400 10$: SCOPE ;SCOPE THIS TEST

```

```

:***** TEST 10 *****
: *HALF DUPLEX TEST
: *IN FREE RUNNING MODE, SET HALF DUPLEX AND L U LOOP
: *SEND A MESSAGE AND VERIFY THAT THERE ARE NO DONES
:*****

```

: TEST 10

```

2260 015476 012737 000010 001226 15$: MOV     #10,TSTNO
2261 015504 012737 015632 001216 MOV     #TST11,NEXT
2262 015512 104412      M$TCLR ;R1 CONTAINS BASE DMC11 ADDRESS
2264 015514 032737 100000 001366 BIT     #BIT15,STAT1 ;MASTER CLEAR DMC11
2265 015522 001406      BEQ     .+16    ;IS IT A DMC?
2266 015524 032737 000001 001372 BIT     #BIT0,STAT3 ;BR IF YES
2267 015532 001002      BNE     .+6     ;KMC WITH BITC SET?
2268 015534 000137 015624      JMP     10$     ;BR IF YES
2269 015540 032737 010000 001366 BIT     #BIT12,STAT1 ;SKIP TEST
2270 015546 001372      BNE     .-12    ;LU PRESENT?
2271 015550 004737 022156      JSR    PC,BASELH ;BR IF NO
2272 015554 004537 022416      JSR    R5,RFRELD ;LOAD BASE AND HALF DUPLEX
2273 015560 021372      RBUF   ;LOAD RECEIVE BUFFER
2274 015562 000044      44     ;BA
2275 015564 004537 022450      JSR    R5,XFRELD ;CC
2276 015570 021324      TBUF   ;LOAD TRANSMIT BUFFER
2277 015572 000044      44     ;BA
2278 015574 012703 000003      MOV    #3,R3   ;CC
2279 015580 005037 001416      CLR    TEMP    ;LOAD DELAY COUNT
                ;CLEAR DELAY

```

```

2280 015604 105761 000002      4$:  TSTB  2(R1)      : IS DONE SET?
2281 015610 100406              BMI  5$          : BR IF YES ERROR
2282 015612 005237 001416      INC  TEMP        : INC DELAY
2283 015616 001372              BNE  4$          : BR IF DELAY NOT DONE
2284 015620 005303              DEC  R3          : DEC DELAY COUNT
2285 015622 001370              BNE  4$          : BR IF DELAY NOT DONE
2286 015624 104400      10$: SCOPE        : SCOPE THIS TEST
2287 015626 104014      5$:  HLT  14        : ERROR DONE WITH HALF-DUPLEX
2288 015630 000775              BR   10$        : GET OUT

```

```

:***** TEST 11 *****
:RESUME TEST
:THIS TEST SENDS AND RECEIVES A BUFFER AND SHUTS DOWN THE
:DMC. THEN A MASTER CLEAR IS ISSUED AND A BASE WITH RESUME
:BIT SET IS GIVEN. ANOTHER BUFFER IS SENT AND RECEIVED.
:DATA IS CHECKED.
:*****

```

: TEST 11

```

2300
2301 015632 012737 000011 001226  TST11: MOV  #11,TSTNC
2302 015640 012737 016214 001216  MOV  #TS+12,NEXT
2303
2304 015646 104412              MSTCLR          : R1 CONTAINS BASE DMC11 ADDRESS
2305 015650 032737 100000 001366  BIT  #BIT15,STAT1 : MASTER CLEAR DMC11
2306 015656 001406              BEQ  .+16        : IS IT A DMC?
2307 015660 032737 000001 001372  BIT  #BIT0,STAT3  : BR IF YES
2308 015666 001002              BNE  .+6         : KMC WITH BIT0 SET?
2309 015670 000137 016212              JMP  10$        : BR IF YES
2310 015674 032737 010000 001366  BIT  #BIT12,STAT1 : SKIP TEST
2311 015702 001372              BNE  .-12        : LU PRESENT?
2312 015704 005037 020060              CLR  RESUME     : BR IF NO
2313 015710 005737 020060      1$:  TST  RESUME     : CLR RESUME FLAG
2314 015714 001003              BNE  2$         : FIRST OR SECOND PASS
2315 015716 004737 022040              JSR  PC,BASELD  : BR IF SECOND
2316 015722 000402              BR   3$         : BASE
2317 015724 004737 022276      2$:  JSR  PC,RESJM   : CONTINUE
2318 015730 004537 022416      3$:  JSR  R5,RFRELD : BASE WITH RESUME BIT
2319 015734 021372              RBUF          : RECEIVE BUFFER
2320 015736 000044              44           : BR
2321 015740 004537 022450              JSR  R5,XFRELD : CC
2322 015744 021324              *BUF         : XMIT BUFFER
2323 015746 000044              44           : BR
2324 015750 012703 000030              MOV  #30,R3     : CC
2325 015754 012700 000002              MOV  #2,R0     : DELAY COUNT
2326 015760 005037 001416              CLR  TEMP      : NEED TWO DONES
2327 015764 105761 000002      4$:  TSTB  2(R1)    : CLEAR DELAY COUNTER
2328 015770 100407              BMI  .+20      : IS RDY 0 SET?
2329 015772 005237 001416      INC  TEMP      : BR IF SET
2330 015776 001372              BNE  4$        : INC DELAY COUNTER
2331 016000 005303              DEC  R3        : BR IF NOT DONE DELAY
2332 016002 001370              BNE  4$        : DEC DELAY COUNT
2333 016004 104014              HLT  14        : BR IF DELAY NOT DONE
2334 016006 000501              BR   10$      : ERROR, RDY 0 NOT SET
2335 016010 042761 000207 000002  BIC  #207,2 R1) : GET OUT
                : CLEAR DONE

```

2336	016016	005300				DEC	R0	: TWO DONES YET?
2337	016020	001361				BNE	4\$: BR IF NOT
2338	016022	012702	021324			MOV	#TBUF,R2	: ADDRESS OF GOOD DATA
2339	016026	012703	021372			MOV	#RBUF,R3	: ADDRESS OF RECEIVED DATA
2340	016032	012700	000044			MOV	#44,R0	: COUNT
2341	016036	112205			6\$:	MOVB	(R2)+,R5	: LOAD GOOD DATA
2342	016040	112304				MOVB	(R3)+,R4	: LOAD FOUND DATA
2343	016042	120504				CMPB	R5,R4	: COMPARE DATA
2344	016044	001401				BEQ	7\$: BR IF OK
2345	016046	104012				HLT	12	: DATA ERROR
2346	016050	005300			7\$:	DEC	R0	: DONE YET?
2347	016052	001371				BNE	6\$: BR IF NOT
2348	016054	004737	022502			JSR	PC,SHUTDOWN	: SHUTDOWN DMC
2349	016060	005737	020060			TST	RESUME	
2350	016064	001004				BNE	8\$: BR IF ALL DONE
2351	016066	012737	177777	020060		MOV	#-1,RESUME	: SET FLAG FOR SECOND PASS
2352	016074	000705				BR	1\$: CONTINUE
2353	016076				9\$:			
2354	016076	012700	016140			MOV	#25\$,R0	: POINTER TO EXPECTED SOFT COUNTS (LOW SPEED)
2355	016102	032737	000002	001372		BIT	#BIT1,STAT3	: IS IT HIGH OR LOW
2356	016110	001402				BEQ	21\$: BR IF LOW
2357	016112	012700	016150			MOV	#25\$,R0	: POINTER TO EXPECTED SOFT COUNTS (HIGH SPEED)
2358	016116	012701	021443		21\$:	MOV	#BASE+3,R1	: POINTER TO ACTUAL COUNTS
2359	016122	012702	000010			MOV	#10,R2	: COUNT
2360	016126	122021			22\$:	CMPB	(R0)+,(R1)+	: COMPARE SOFT ERROR COUNTS
2361	016130	001013				BNE	23\$: IF ERROR BR 23\$
2362	016132	005302				DEC	R2	: DEC COUNT
2363	016134	001374				BNE	22\$: CONTINUE CHECKING IF NOT DONE
2364	016136	000425				BR	24\$: ALL COUNTS OK, GET OUT
2365	016140	000	000	000	25\$:	.BYTE	0,0,0,0,0,0,1,1	: EXPECTED ERROR COUNTS (LOW SPEED)
2366	016143	000	000	000				
2367	016146	001	001					
2368	016150	000	000	000	26\$:	.BYTE	0,0,0,0,0,0,0,0	: EXPECTED ERROR COUNTS (HIGH SPEED)
2369	016153	000	000	000				
2370	016156	000	000					
2371	016160	113737	021443	001250	23\$:	MOVB	BASE+3,TEMP2	
2372	016166	113737	021445	001252		MOVB	BASE+5,TEMP3	
2373	016174	113737	021447	001254		MOVB	BASE+7,TEMP4	
2374	016202	113737	021451	001256		MOVB	BASE+11,TEMP5	
2375	016210	104017				HLT	17	
2376	016212				24\$:			
2377	016212	104400			10\$:	SCOPE		: SCOPE THIS TEST

```

:***** TEST 12 *****
: *FREE RUNNING DATA TEST (INTERRUPT DRIVEN EXERCISER)
: *THIS TEST REPEATEDLY QUEUES UP 7 RECEIVE BUFFERS AND
: *7 TRANSMIT BUFFERS AND CHECKS DATA WHEN ALL 7 BUFFERS
: *ARE RECEIVED TRANSMIT COUNTS RANGE FROM 2 TO 104.
: *DATA IS A BINARY COUNT PATTERN. THE RESUME FUNCTION
: *IS CHECKED IN THIS TEST. THIS TEST USES THE TURNAROUND CONNECTOR
: *IF IT IS PRESENT, OTHERWISE LINE UNIT LOOP IS SET.
:*****

```

```

: TEST 12
:-----

```

2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391

2392	016214	012737	000012	001226	TST12:	MOV	#12,TSTNO	
2393	016222	012737	003364	001216		MOV	#.EOP,NEXT	
2394								:R1 CONTAINS BASE DMC11 ADDRESS
2395	016230	104412				MSTCLR		:MASTER CLEAR DMC11
2396	016232	032737	100000	001366		BIT	#BIT15,STAT1	:IS IT A DMC?
2397	016240	001406				BEQ	+.16	:BR IF YES
2398	016242	032737	000001	001372		BIT	#BIT0,STAT3	:KMC WITH BIT0 SET?
2399	016250	001002				BNE	+.6	:BR IF YES
2400	016252	000137	017044			JMP	ENDEX1	:SKIP TEST
2401	016256	032737	010000	001366		BIT	#BIT12,STAT1	:LU PRESENT?
2402	016264	001372				BNE	-.12	:BR IF NO
2403	016266	012737	000340	177776		MOV	#340,PS	:LOCK OUT INTERRUPTS
2404	016274	013700	001366			MOV	STAT1,RO	:GET BR LEVEL
2405	016300	001700				ASR	RO	:SHIFT RIGHT 4 TIMES
2406	016302	006200				ASR	RO	
2407	016304	006200				ASR	RO	
2408	016306	006200				ASR	RO	
2409	016310	042700	177437			SIC	#177437,RO	:PUT BR LEVEL IN RO
2410	016314	012777	017132	163052		MOV	#IISR,DMRVEC	:LOAD INPUT VECTOR
2411	016322	010077	163050			MOV	RO,DMRLVL	:LOAD LEVEL
2412	016326	012777	017422	163044		MOV	#OISR,DMTVEC	:LOAD OUTPUT VECTOR
2413	016334	010077	163042			MOV	RO,DMTLVL	:LOAD LEVEL
2414								
2415								:INITIALIZE ALL BUFFER LISTS AND COUNT LISTS
2416								
2417	016340	012737	000104	021316		MOV	#104,TFLAG	:TFLAG CONTAINS COUNT
2418	016346	012700	020064			MOV	#XMITBA+2,RO	:RO POINTS TO BA LIST
2419	016352	012703	020356			MOV	#RBUF,R3	:R3 CONTAINS BUFFER ADDRESS
2420	016356	010320			1\$:	MOV	R3,(RO)+	:LOAD BA LIST WITH REC BA
2421	016360	062703	000104			ADD	#104,R3	:UPDATE BUFFER ADDRESS
2422	016364	022700	020102			CMP	#XMITBA+20,RO	:END OF REC BUFFERS?
2423	016370	001372				BNE	1\$:NO LOAD NEXT ONE
2424	016372	012720	020120		2\$:	MOV	#TBUF,(RO)+	:LOAD BA LIST WITH XMIT BA
2425	016376	022700	020120			CMP	#XMITBA+36,RO	:END OF XMIT BUFFERS?
2426	016402	001373				BNE	2\$:NO LOAD NEXT BUFFER
2427	016404	012700	020232			MOV	#RCNTAB+2,RO	:RO POINTS TO COUNT LIST
2428	016410	013720	021316		3\$:	MOV	TFLAG,(RO)+	:LOAD COUNT OF 104
2429	016414	022700	020250			CMP	#RCNTAB+20,RO	:END OF REC COUNT LIST?
2430	016420	001373				BNE	3\$:BR IF NO
2431	016422	012737	000005	021314		MOV	#5,FLAG ; LOOP COUNT	
2432	016430	012711	040000			MOV	#BIT14,(R1)	:SET MASTER CLEAR
2433	016434	032737	100000	001366		BIT	#BIT15,STAT1	:IOP?
2434	016442	001402				BEQ	+.6	:BR IF NO
2435	016444	012711	100000			MOV	#BIT15,(R1)	:SET RUN ON IOP
2436	016450	012700	177777			MOV	#-1,RO	:RO IS INPUT DONE COUNTER
2437	016454	005037	020060		CLRTAB:	CLR	RESUME	:CLEAR RESUME FLAG
2438	016460	012705	020266			MOV	#RONTAB,R5	:GET READY TO CLEAR ALL RECEIVE
2439	016464	005025			2\$:	CLR	(R5)+	:BUFFERS
2440	016466	022705	021312			CMP	#RBUFE,R5	:END OF BUFFER?
2441	016472	001374				BNE	2\$:BR IF NO
2442	016474	012704	020250			MOV	#XCNTAB,R4	:R4 POINTS TO XMIT COUNT LIST
2443	016500	013724	021316		4\$:	MOV	TFLAG,(R4)+	:LOAD XMIT CHAR COUNT
2444	016504	022704	020266			CMP	#XCNTAB+16,R4	:DONE?
2445	016510	001373				BNE	4\$:BR IF NO
2446	016512	005002			5\$:	CLR	R2	:R2 IS OUTPUT DONE COUNTER
2447	016514	005004				CLR	R4	:R4 IS USED AS INDEX IN CISR

2448	016516	005711				IST	(R1)	: IS RUN SET?
2449	016520	100376				BPL	.-2	: WAIT FOR RUN
2450	016522	152761	000100	000002		BISB	#BIT6,2(R1)	: SET IE0
2451	016530	032737	040000	001366		BIT	#BIT14,STAT1	: LOOP BACK CONNECTOR?
2452	016536	001002				BNE	+.6	: BR IF YES
2453	016540	052711	004000			BIS	#BIT11,(R1)	: SET LINE UNIT LOOP
2454	016544	022737	000005	021314		CMP	#5,FLAG	: FIRST TIME?
2455	016552	001003				BNE	1\$: BR IF NOT
2456	016554	052711	000143			BIS	#143,(R1)	: SET IEI,RQI,BASE I
2457	016560	000402				BR	3\$: CONTINUE
2458	016562	052711	000144		1\$:	BIS	#144,(R1)	: SET IEI,RQI,REC BA/CC
2459	016566	005037	001416		3\$:	CLR	TEMP	: SET UP FOR DELAY COUNT
2460	016572	012737	000022	001250		MOV	#22,TEMP2	: GET SET FOR DELAY
2461	016600	005037	177776			CLR	PS	: ALLOW INTERRUPTS
2462	016604	022700	000020		SCAN:	CMP	#20,R0	: INPUT DONE?
2463	016610	001402				BEQ	SCAN2	: BR IF YES
2464	016612	000137	017102			JMP	SCAN1	: BR IF NO
2465	016616	022702	000034		SCAN2:	CMP	#34,R2	: XMIT DONE FOR ALL MESSAGES?
2466	016622	001402				BEQ	8\$: BR IF YES
2467	016624	000137	017102			JMP	SCAN1	: BR IF NO
2468	016630	022704	000034		8\$:	CMP	#34,R4	: REC DONE FOR ALL MESSAGES?
2469	016634	001402				BEQ	9\$: BR IF YES
2470	016636	000137	017102			JMP	SCAN1	: BR IF NO
2471	016642				9\$:			
2472	016642	012700	020266			MOV	#RONTAB,R0	: GET FIRST REC BUFFER
2473	016646	012002			5\$:	MOV	(R0)+,R2	: R2 POINTS TO BUFFER
2474	016650	005005				CLR	R5	: R5=EXPECTED
2475	016652	005003				CLR	R3	: R3 = COUNT
2476	016654	010237	001252		6\$:	MOV	R2,TEMP3	: SAVE ADDRESS FOR TYPEOUT
2477	016660	112204				MOVB	(R2)+,R4	: GET RECEIVE DATA
2478	016662	120504				CMPB	R5,R4	: IS IT CORRECT?
2479	016664	001401				BEQ	+.4	: BR IF YES
2480	016666	104013				HLT	13	: DATA ERROR
2481	016670	005205				INC	R5	: NEXT CHARACTER
2482	016672	005203				INC	R3	: INC COUNT
2483	016674	021003				CMP	(R0),R3	: DONE YET?
2484	016676	001366				BNE	6\$: BR IF NO
2485	016700	062700	000002			ADD	#2,R0	: GET NEXT REC BUFFER
2486	016704	022700	020322			CMP	#RONTAB+34,R0	: DONE YET?
2487	016710	001356				BNE	5\$: BR IF NO
2488	016712	012700	000001			MOV	#1,R0	: SET R0 TO 1
2489	016716	032737	000001	021314	4\$:	BIT	#BIT0,FLAG	: CHANGE CHAR COUNT FOR NEXT LOOP
2490	016724	001003				BNE	1\$: BR TO SUB 40
2491	016726	005337	021316			DEC	TFLAG	: DEC BY ONE
2492	016732	000403				BR	2\$: CONTINUE
2493	016734	162737	000040	021316	1\$:	SUB	#40,TFLAG	: SUBTRACT 40 FROM XMIT COUNT
2494	016742	005337	021314		2\$:	DEC	FLAG	: DEC LOOP COUNT
2495	016746	001242				BNE	CLRTAB	: GO DO IT AGAIN
2496	016750	152711	000146		ENDEX:	BISB	#146,(R1)	: SHUT DOWN DMC
2497	016754	005737	021314		1\$:	TST	FLAG	: HAS INTERRUPT OCCURED?
2498	016760	001775				BEQ	1\$: BR IF NO
2499	016762	012700	017024			MOV	#10\$,R0	: R0 POINTS TO LO SPEED COUNTS
2500	016766	032737	000002	001372		BIT	#BIT1,STAT3	: IS IT LO SPEED?
2501	016774	001402				BEQ	2\$: BR IF YES
2502	016776	012700	017034			MOV	#11\$,R0	: R0 POINTS TO HI COUNTS
2503	017002	012701	021443		2\$:	MOV	#BASE+3,R1	: POINTER TO ACTUAL COUNTS

```

2504 017006 012702 000010          MOV      #10,R2          ;10 COUNTS TO CHECK
2505 017012 122021          3$:    CMPB     (R0)+,(R1)+      ;CHECK COUNT
2506 017014 103414          BLO     ENDEX2          ;BR IF ERROR
2507 017016 005302          DEC     R2              ;DEC COUNT
2508 017020 001374          BNE     3$              ;BR IF NOT DONE
2509 017022 000410          BR      ENDEX1          ;ALL OK GET OUT
2510 017024          000      000          10$:   .BYTE    0,0,0,0,0,0,5,5 ;EXPECTED LO SPEED COUNTS
2511 017027          000      000      000
2512 017032          005      005
2513 017034          000      000      005
2514 017037          000      000      000
2515 017042          005      005          11$:   .BYTE    0,0,5,0,0,0,5,5 ;EXPECTED HI SPEED COUNTS
2516 017044 104400          ENDEX1: SCOPE          ;SCOPE THIS TEST
2517 017046 113737 021443 001250          ENDEX2: MOVB    BASE+3,TEMP2 ;SAVE ALL ODD ADDRESSES
2518 017054 113737 021445 001252          MO 'B    BASE+5,TEMP3      ;FOR TYPEOUT
2519 017062 113737 021447 001254          MOVB    BASE+7,TEMP4
2520 017070 113737 021451 001256          MOVB    BASE+11,TEMP5
2521 017076 104017          HLT     17              ;NON ZERO ERROR COUNT
2522 017100 000761          BR      ENDEX1          ;GET OUT
2523 017102 005337 001416          SCAN1: DEC     TEMP        ;DECREMENT DELAY COUNTER
2524 017106 001402          BEQ     1$              ;BR IF ZERO
2525 017110 000137 016604          JMP     SCAN            ;BR IF NOT DONE DELAY
2526 017114 005337 001250          1$:    DEC     TEMP2      ;DEC DELAY COUNT
2527 017120 001402          BEQ     2$              ;BR IF DONE DELAY
2528 017122 000137 016604          JMP     SCAN            ;BR IF NOT DONE
2529 017126 104001          2$:    HLT     1          ;ERROR HUNG
2530 017130 000745          BR      ENDEX1          ;GET OUT
2531
2532          ;INPUT INTERRUPT SERVICE ROUTINE
2533
2534 017132 022700 000017          IISR:  CMP     #17,R0      ;PROC. ERROR DONE?
2535 017136 001421          BEQ     12$             ;BR IF YES
2536 017140 005737 020060          TST    RESUME          ;IS THIS A RESUME INTERRUPT
2537 017144 001432          BEQ     8$              ;BR IF NO
2538 017146 032711 000002          BIT    #BIT1,(R1)      ;CNTL OR BASE?
2539 017152 001407          BEQ     13$            ;BR IF CNTL I
2540 017154 012761 021440 000004          MOV    #BASE,4(R1)     ;LOAD BASE ADDRESS
2541 017162 012761 010000 000006          MOV    #BIT12,6(R1)   ;WITH RESUME BIT SET
2542 017170 000404          BR      12$            ;CONTINUE
2543 017172 005061 000006          13$:   CLR     6(R1)        ;SELECT FULL DUPLEX
2544 017176 005037 020060          CLR    RESUME          ;CLEAR RESUME FLAG
2545 017202 142711 000040          12$:   BICB   #40,(R1)      ;CLEAR RQI
2546 017206 105711          TSTB   (R1)            ;IS RDI GONE?
2547 017210 100776          BMI    -2              ;BR IF NO
2548 017212 005737 020060          TST    RESUME          ;BASE OR CNTL I?
2549 017216 001403          BEQ    14$             ;BR IF IT WAS CNTL I
2550 017220 152711 000041          BISB   #41,(R1)       ;ASK FOR CNTL I
2551 017224 000002          RTI                      ;RETURN
2552 017226 105011          14$:   CLRB   (R1)        ;CLEAR BSEL 0
2553 017230 000002          R* I                      ;RETURN
2554 017232 005700          8$:    TST    R0          ;FIRST TIME HERE?
2555 017234 100006          BPL    7$              ;LOAD BASE IF MINUS
2556 017236 012761 021440 000004          MOV    #BASE,4(R1)     ;SET UP BASE ADDRESS
2557 017244 005061 000006          CLR    6(R1)           ;CLEAR COUNT
2558 017250 000434          BR      3$              ;CONTINUE
2559 017252 001003          7$:    BNE    1$          ;CNTL I FULL DUPLEX IF 0

```

2560	017254	005061	000006		CLR	6(R1)	:SELECT FULL DUPLEX	
2561	017260	000430			BR	3\$:CONTINUE	
2562	017262	032700	000010	1\$:	BIT	#BIT3,RO	:XMIT?	
2563	017266	001013			BNE	2\$:BR IF YES	
2564	017270	000241			CLC		:CLEAR CARRY	
2565	017272	006100			ROL	RO	:MAKE RO EVEN	
2566	017274	016061	020062	000004	MOV	RECBA(RO),4(R1)	:LOAD REC BUFFER	
2567	017302	016061	020230	000006	MOV	RCNTAB(RO),6(R1)	:LOAD COUNT	
2568	017310	000241			CLC		:CLEAR CARRY	
2569	017312	006000			ROR	RO	:GET RO BACK	
2570	017314	000412			BR	3\$:CONTINUE	
2571	017316	000241		2\$:	CLC		:CLEAR CARRY	
2572	017320	006100			ROL	RO	:MAKE IT EVEN	
2573	017322	016061	020062	000004	MOV	XMITBA(RO),4(R1)	:LOAD XMIT BUFFER	
2574	017330	016061	020230	000006	MOV	RCNTAB(RO),6(R1)	:LOAD COUNT	
2575	017336	000241			CLC		:CLEAR CARRY	
2576	017340	006000			ROR	RO	:PUT IT BACK	
2577	017342	142711	000040	3\$:	BICB	#40,(R1)	:CLEAR RQI	
2578	017346	105711			TSTB	(R1)	:WAIT FOR	
2579	017350	100776			BMI	-2	:RDI TO GO AWAY	
2580	017352	005200			INC	RO	:INC COUNT	
2581	017354	001003			BNE	6\$:IF 0 ASK FOR CNTL I	
2582	017356	152711	000041		BISB	#41,(R1)	:ASK FOR CNTL I	
2583	017362	000002			RTI		:RETURN	
2584	017364	022700	000017	6\$:	CMP	#17,RO	:DONE YET?	
2585	017370	001411			BEQ	4\$:BR IF YES	
2586	017372	032700	000010		BIT	#BIT3,RO	:XMIT?	
2587	017376	001003			BNE	5\$:BR IF YES	
2588	017400	152711	000044		BISB	#44,(R1)	:ASK FOR REC BA/CC	
2589	017404	000002			RTI		:RETURN	
2590	017406	152711	000040	5\$:	BISB	#40,(R1)	:ASK FOR XMIT BA/CC	
2591	017412	000002			RTI		:RETURN	
2592	017414	152711	000046	4\$:	BISB	#46,(R1)	:FORCE PROC. ERROR	
2593	017420	000002			RTI		:RETURN	
2594								
2595							:OUTPUT INTERRUPT SERVICE ROUTINE	
2596								
2597	017422	032761	000001	000002	OISR:	BIT	#BIT0,2(R1)	:IS THIS AN ERROR?
2598	017430	001467			BEQ	1\$:BR IF NO	
2599	017432	005737	021314		TST	FLAG	:IS THIS SHUT DOWN INTERRUPT?	
2600	017436	001006			BNE	9\$:BR IF NO	
2601	017440	005237	021314		INC	FLAG	:YES MAKE FLAG NON-ZERO	
2602	017444	022761	001000	000006	CMP	#BIT9,6(R1)	:SHUT DOWN BIT SET?	
2603	017452	001531			BEQ	10\$:YES ALL IS OK	
2604	017454	022700	000017	9\$:	CMP	#17,RO	:RESUME INTERRUPT?	
2605	017460	001041			BNE	11\$:BR IF NO	
2606	017462	022761	001000	000006	CMP	#BIT9,6(R1)	:PROC. ERROR BIT SET?	
2607	017470	001035			BNE	11\$:BR IF NO	
2608	017472	005200			INC	RO	:BUMP COUNTER (TO 20)	
2609	017474	012711	040000		MOV	#BIT14,(R1)	:MASTER CLEAR DEVICE	
2610	017500	032737	100000	001366	BIT	#BIT15,STAT1	:DMC OR KMC?	
2611	017506	001405			BEQ	+14	:BR IF DMC	
2612	017510	012711	100000		MOV	#BIT15,(R1)	:SET RUN ON KMC	
2613	017514	105227	000000		INCB	#0	:DELAY ON KMC	
2614	017520	001375			BNE	-4		
2615	017522	012737	177777	020060	MOV	#-1,RESUME	:SET RESUME FLAG	

2616	017530	005711			TST	(R1)	:RUN SET?	
2617	017532	100376			BPL	.-2	:BR IF NO	
2618	017534	012761	000100	000002	MOV	#BIT6,2(R1)	:SET IEO	
2619	017542	032737	040000	001366	BIT	#BIT14,STAT1	:LOOP BACK CONNECTOR?	
2620	017550	001002			BNE	.+6	:BR IF YES	
2621	017552	052711	004000		BIS	#BIT11,(R1)	:SET LINE UNIT LOOP	
2622	017556	052711	000143		BIS	#143,(R1)	:ASK FOR PORT (BASE REQUEST)	
2623	017562	000002			RTI		:RETURN	
2624	017564	016137	000004	001252	11\$:	MOV	4(R1),TEMP3	:SAVE FOR ERROR TYPEOUT
2625	017572	016137	000006	001254	MOV	6(R1),TEMP4	:SAVE FOR ERROR TYPEOUT	
2626	017600	104016			HLT	16	:CNTL 0 ERROR	
2627	017602	022626			CMP	(SP)+,(SP)+	:ADJUST STACK	
2628	017604	000137	017044		JMP	ENDEX1	:GET OUT	
2629	017610	032761	000004	000002	1\$:	BIT	#BIT2,2(R1)	:RECEIVE?
2630	017616	001053			BNE	2\$:BR IF YES	
2631	017620	022761	020120	000004	CMP	#TBUF,4(R1)	:IS XMIT BA CORRECT?	
2632	017626	001412			BEQ	4\$:BR IF OK	
2633	017630	022761	020121	000004	CMP	#TBUF+1,4(R1)	:IS XMIT BA CORRECT?	
2634	017636	001406			BEQ	4\$:BR IF YES	
2635	017640	012705	020120		MOV	#TBUF,R5	:R5 = EXPECTED	
2636	017644	016137	000004	001252	MOV	4(R1),TEMP3	:SAVE FOUND FOR TYPEOUT	
2637	017652	104002			HLT	2	:XMIT BA ERROR	
2638	017654	005005			4\$:	CLR	R5	:R5 IS INDEX REG
2639	017656	026561	020250	000006	5\$:	CMP	XCNTAB(R5),6(R1)	:IS CHAR COUNT OK?
2640	017664	001406			BEQ	6\$:BR IF YES	
2641	017666	062705	000002		ADD	#2,R5	:INC INDEX	
2642	017672	022705	000016		CMP	#16,R5	:DONE LIST YET?	
2643	017676	001367			BNE	5\$:BR IF NO	
2644	017700	104003			HLT	3	:XMIT COUNT ERROR	
2645	017702	016162	000004	020322	6\$:	MOV	4(R1),XCNTAB(R2)	:STORE XMIT DONE BA
2646	017710	062702	000002		ADD	#2,R2	:INC INDEX	
2647	017714	016162	000006	020322	MOV	6(R1),XCNTAB(R2)	:STORE XMIT DONE CC	
2648	017722	062702	000002		ADD	#2,R2	:INC INDEX	
2649	017726	142761	000207	000002	BICB	#207,2(R1)	:CLEAR R00	
2650	017734	000002			RTI		:RETURN	
2651	017736	105011			10\$:	CLRB	(R1)	:CLEAR SEL0
2652	017740	105061	000002		CLRB	2(R1)	:CLEAR SEL2	
2653	017744	000002			RTI		:RETURN	
2654	017746	012705	000002		2\$:	MOV	#2,R5	:SET UP R5 AS INDEX
2655	017752	026561	020062	000004	CMP	RECBA(R5),4(R1)	:COMPARE WITH LIST OF CORRECT BA'S	
2656	017760	001406			BEQ	3\$:BR IF OK?	
2657	017762	062705	000002		ADD	#2,R5	:INCREMENT R5	
2658	017766	022705	000020		CMP	#20,R5	:END OF LIST?	
2659	017772	001367			BNE	2\$+4	:BR IF NO	
2660	017774	104004			HLT	4	:REC BA ERROR	
2661	017776	005005			3\$:	CLR	R5	:R5 IS INDEX
2662	020000	026561	020250	000006	7\$:	CMP	XCNTAB(R5),6(R1)	:CHECK FOR CORRECT REC COUNT
2663	020006	001406			BEQ	8\$:BR IF YES	
2664	020010	062705	000002		ADD	#2,R5	:INCREMENT R5	
2665	020014	022705	000016		CMP	#16,R5	:END OF LIST?	
2666	020020	001367			BNE	7\$:BR IF NOT	
2667	020022	104005			HLT	5	:REC COUNT ERROR	
2668	020024	016164	000004	020266	8\$:	MOV	4(R1),RDNTAB(R4)	:STORE REC BA
2669	020032	062704	000002		ADD	#2,R4	:INC INDEX	
2670	020036	016164	000006	020266	MOV	6(R1),RDNTAB(R4)	:STORE REC DONE CC	
2671	020044	062704	000002		ADD	#2,R4	:INC INDEX	

```

2672 020050 142761 000207 000002          BICB      #207,2(R1)      ;CLEAR RDO
2673 020056 000002                                RTI          ;RETURN
2674
2675
2676                                ;BUFFERS
2677
2678 020060 000000          RESUME: 0
2679 020062                                RECBA:
2680 020062 000017          XMITBA: .BLKW 17          ;REC & XMIT BA LIST
2681
2682 020120                                TBUFF:                                ;TRANSMIT DATA
2683 020120          000          001          002          .BYTE 0,1,2,3,4,5,6,7
2684 020123          003          004          005
2685 020126          006          007
2686 020130          010          011          012          .BYTE 10,11,12,13,14,15,16,17
2687 020133          013          014          015
2688 020136          016          017
2689 020140          020          021          022          .BYTE 20,21,22,23,24,25,26,27
2690 020143          023          024          025
2691 020146          026          027
2692 020150          030          031          032          .BYTE 30,31,32,33,34,35,36,37
2693 020153          033          034          035
2694 020156          036          037
2695 020160          040          041          042          .BYTE 40,41,42,43,44,45,46,47
2696 020163          043          044          045
2697 020166          046          047
2698 020170          050          051          052          .BYTE 50,51,52,53,54,55,56,57
2699 020173          053          054          055
2700 020176          056          057
2701 020200          060          061          062          .BYTE 60,61,62,63,64,65,66,67
2702 020203          063          064          065
2703 020206          066          067
2704 020210          070          071          072          .BYTE 70,71,72,73,74,75,76,77
2705 020213          073          074          075
2706 020215          076          077
2707 020221          100          101          102          .BYTE 100,101,102,103,104,105,106,107
2708 020223          103          104          105
2709 020226          106          107
2710
2711 020230 000010          RCNTAB: .BLKW 10          ;RECEIVE COUNT TABLE
2712 020250 000007          XCNTAB: .BLKW 7          ;TRANSMIT COUNT TABLE
2713
2714 020266 000016          RDNTAB: .BLKW 16          ;RECEIVE DONE TABLE (BA CC)
2715 020322 000016          XDNTAB: .BLKW 16          ;XMIT DONE TABLE (BA CC)
2716
2717 020356                                RBUFF:                                ;RECEIVER BUFFERS
2718 020356 000104          RBUFF1: .BLKB 104
2719 020462 000104          RBUFF2: .BLKB 104
2720 020566 000104          RBUFF3: .BLKB 104
2721 020672 000104          RBUFF4: .BLKB 104
2722 020776 000104          RBUFF5: .BLKB 104
2723 021102 000104          RBUFF6: .BLKB 104
2724 021206 000104          RBUFF7: .BLKB 104
2725 021312 000000          RBUFF8: 0          ;END OF RECEIVER BUFFERS
2726
2727                                81800
                                81900

```

```

2728      82000
2729      82100      ;BUFFER AREA
2730      82200      ;-----
2731      82300
2732      021314 000000      82400 FLAG: 0
2733      021316 000000      82500 TFLAG: 0
2734      021320 000000      82600 RFLAG: 0
2735      021322 000044      82700 TCOUNT: 44
2736      021324 041101 042103 043105      82800 TBUF: .ASCII/ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789/
2737      021332 044107 045111 046113
2738      021340 047115 050117 051121
2739      021346 052123 053125 054127
2740      021354 055131 030460 031462
2741      021362 032464 033465 034470
2742
2743      021370 000044      82900 .EVEN
2744      021372 021440      83000 RCOUNT: 44
2745
2746      021440 022040      83100 RBUF: .+.46
2747
2748
2749
2750
2751
2752
2753      022040      83200 .EVEN
2754
2755
2756
2757      022040 012711 040000      83300 BASE: .+.256.
2758      022044 032737 100000 001366      00300
2759      022052 001402      00400
2760      022054 012711 100000      00500 ;SUBROUTINES
2761      022060 105227 000000      00600 ;-----
2762      022064 001375      00700
2763      022066 005711      00800
2764      022070 100376      00900 BASELD:
2765      022072 052711 004000      01000 ;THIS SUBROUTINE LOADS THE DMC WITH A BASE ADDRESS
2766      022076 152711 000043      01100 ;AND PUTS DMC INTO FULL-DUPLEX MODE
2767      022102 105711      01200
2768      022104 100376      01300 MOV #BIT14,(R1) ;MASTER CLEAR
2769      022106 012761 021440 000004      01400 BIT #BIT15,STAT1 ;CRAM?
2770      022114 005061 000006      01500 BEQ .+6 ;BR IF NO
2771      022120 142711 000040      01600 MOV #BIT15,(R1) ;IF CRAM SET RUN
2772      022124 105711      01700 INCB #0 ;DELAY
2773      022126 100776      01800 BNE .-4 ;BR IF NOT DONE DELAY
2774      022130 152711 000041      01900 1$: TST (R1) ;IS RUN SET?
2775      022134 105711      02000 BPL 1$ ;BR IF NO
2776      022136 100376      02100 BIS #BIT11,(R1) ;SET LU LOOP
2777      022140 005061 000006      02200 BISB #43,(R1) ;BASE REQUEST
2778      022144 142711 000040      02300 2$: TSTB (R1) ;RDY I SET?
2779      022150 105711      02400 BPL 2$ ;BR IF NO
2780      022152 100776      02500 MOV #BASE.4,(R1) ;LOAD BASE ADDRESS
2781      022154 000207      02600 CLR 6(R1) ;CLEAR CC
2782
2783      022156      02700 BICB #40,(R1) ;CLEAR RQI
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000

```


2840	022412	100776				BMI	655		:BR IF YES
2841	022414	000207			07900	RTS	PC		:RETURN
2842					08000				
2843	022416				08100	RFRELD:			
2844					08200				: THIS SUBROUTINE LOADS THE DMC WITH A RECEIVE BA/CC
2845					08300				
2846	022416	152711	000044		08400	BISB	#44, (R1)		:REC BA/CC REQUEST
2847	022422	105711			08500	1S: TSTB	(R1)		:RDY I SET?
2848	022424	100376			08600	BPL	1S		:BR IF NO
2849	022426	012561	000004		08700	MOV	(R5)+,4(R1)		:LOAD REC BA
2850	022432	012561	000006		08800	MOV	(R5)+,6(R1)		:LOAD REC CC
2851	022436	142711	000040		08900	BICB	#40, (R1)		:CLEAR RQI
2852	022442	105711			09000	2S: TSTB	(R1)		:IS RDY I CLEAR
2853	022444	100776			09100	BMI	2S		:BR IF NO
2854	022446	000205			09200	RTS	R5		:RETURN
2855					09300				
2856	022450				09400	XFRELD:			
2857					09500				: THIS SUBROUTINE LOADS THE DMC WITH A TRANSMIT BA/CC
2858					09600				
2859	022450	152711	000040		09700	BISB	#40, (R1)		:XMIT BA/CC REQUEST
2860	022454	105711			09800	1S: TSTB	(R1)		:RDY I SET?
2861	022456	100376			09900	BPL	1S		:BR IF NO
2862	022460	012561	000004		10000	MOV	(R5)+,4(R1)		:LOAD XMIT BA
2863	022464	012561	000006		10100	MOV	(R5)+,6(R1)		:LOAD XMIT CC
2864	022470	142711	000040		10200	BICB	#40, (R1)		:CLEAR RQI
2865	022474	105711			10300	2S: TSTB	(R1)		:IS RDY I CLEAR
2866	022476	100776			10400	BMI	2S		:BR IF NO
2867	022500	000205			10500	RTS	R5		:RETURN
2868					10600				
2869					10700				
2870	022502				10800	SHUTDOWN:			
2871					10900				: THIS SUBROUTINE FORCES THE DMC TO UPDATE THE BASE TABLE
2872					11000				
2873	022502	042761	000207	000002	11100	BIC	#207,2(R1)		:CLEAR ANY OUTPUT DONES
2874	022510	152711	000046		11200	BISB	#46, (R1)		:ASK FOR ILLEGAL REQUEST
2875	022514	105711			11300	1S: TSTB	(R1)		:RDI SET?
2876	022516	100376			11400	BPL	1S		:BR IF NO
2877	022520	142711	000040		11500	BICB	#40, (R1)		:CLEAR RQI
2878	022524	105761	000002		11600	2S: TSTB	2(R1)		:OUTPUT DONE SET?
2879	022530	100375			11700	BPL	2S		:BR IF NOT
2880	022532	000207			11800	RTS	PC		:RETURN
2881					11900				
2882					00300				
	022534	052377	040522	051516	00400	EM2:	.ASCIZ	<377>	TRANSMIT BA ERROR
	022557	377	051124	047101	00500	EM3:	.ASCIZ	<377>	TRANSMIT COUNT ERROR.
	022605	377	042522	042503	00600	EM4:	.ASCIZ	<377>	RECEIVE BA ERROR
	022627	377	042522	042503	00700	EM5:	.ASCIZ	<377>	RECEIVE COUNT ERROR.
	022654	051377	041505	044505	00800	EM11:	.ASCIZ	<377>	RECEIVE DATA ERROR
	022700	043377	042522	020105	00900	EM12:	.ASCIZ	<377>	FREE RUNNING ERROR
	022724	041777	047117	051124	01000	EM13:	.ASCIZ	<377>	CONTROL OUT ERROR
	022747	377	047111	042524	01100	EM14:	.ASCIZ	<377>	INTERNAL DDCMP ERROR COUNTS NON ZERO
					01200				
	023015	377	054105	042520	01300	DH1:	.ASCIZ	<377>	EXPECTED FOUND ADDRESS
	023047	377	054105	042520	01400	DH2:	.ASCIZ	<377>	EXPECTED FOUND
	023070	020377	042523	032114	01500	DH3:	.ASCIZ	<377>	SEL4 SEL6
	023111	377	040502	042523	01600	DH4:	.ASCIZ	<377>	BASE+3 THRU BASE+12

023137	377	046504	030503	01700	DHS:	.ASCIZ	(377)/DMC11 IS HUNG/
				01800		.EVEN	
				01900			
023156	000003			02000	DT1:	3	
023160	006	004		02100		.BYTE	6.4
023162	001264			02200		SAVR2	
023164	006	004		02300		.BYTE	6.4
023166	001270			02400		SAVR4	
023170	004	002		02500		.BYTE	4.2
023172	001260			02600		SAVR0	
023174	000003			02700	DT2:	3	
023176	006	004		02800		.BYTE	6.4
023200	001272			02900		SAVR5	
023202	006	004		03000		.BYTE	6.4
023204	001270			03100		SAVR4	
023206	004	002		03200		.BYTE	4.2
023210	001264			03300		SAVR2	
023212	000003			03400	DT3:	3	
023214	006	004		03500		.BYTE	6.4
023216	001272			03600		SAVR5	
023220	006	004		03700		.BYTE	6.4
023222	001270			03800		SAVR4	
023224	004	002		03900		.BYTE	4.2
023226	001252			04000		TEMP3	
023230	000002			04100	DT4:	2	
023232	003	007		04200		.BYTE	3.7
023234	001272			04300		SAVR5	
023236	003	002		04400		.BYTE	3.2
023240	001270			04500		SAVR4	
023242	000002			04600	DT5:	2	
023244	006	004		04700		.BYTE	6.4
023246	001272			04800		SAVR5	
023250	006	002		04900		.BYTE	6.2
023252	001270			05000		SAVR4	
023254	000003			05100	DT6:	3	
023256	003	010		05200		.BYTE	3.10
023260	001272			05300		SAVR5	
023262	003	004		05400		.BYTE	3.4
023264	001270			05500		SAVR4	
023266	004	002		05600		.BYTE	4.2
023270	021314			05700		FLAG	
023272	000003			05800	DT7:	3	
023274	003	010		05900		.BYTE	3.10
023276	001272			06000		SAVR5	
023300	003	004		06100		.BYTE	3.4
023302	001270			06200		SAVR4	
023304	004	002		06300		.BYTE	4.2
023306	001264			06400		SAVR2	
023310	000003			06500	DT10:	3	
023312	003	007		06600		.BYTE	3.7
023314	001272			06700		SAVR5	
023316	003	004		06800		.BYTE	3.4
023320	001270			06900		SAVR4	
023322	006	002		07000		.BYTE	6.2
023324	001252			07100		TEMP3	
023326	000002			07200	DT11:	2	

023330	006	004	07300	.BYTE	6.4
023332	001252		07400	TEMP3	
023334	006	002	07500	.BYTE	6.2
023336	001254		07600	TEMP4	
023340	000010		07700	DT12:	10
023342	003	002	07800	.BYTE	3,2
023344	001250		07900	TEMP2	
023346	003	002	08000	.BYTE	3,2
023350	021444		08100	BASE+4	
023352	003	002	08200	.BYTE	3,2
023354	001252		08300	TEMP3	
023356	003	002	08400	.BYTE	3,2
023360	021446		08500	BASE+6	
023362	003	002	08600	.BYTE	3,2
023364	001254		08700	TEMP4	
023366	003	002	08800	.BYTE	3,2
023370	021450		08900	BASE+10	
023372	003	002	09000	.BYTE	3,2
023374	001256		09100	TEMP5	
023376	003	002	09200	.BYTE	3,2
023400	021452		09300	BASE+12	
023402	000002		09400	DT13:	2
023404	006	004	09500	.BYTE	6,4
023406	001272		09600	SAVR5	
023410	006	002	09700	.BYTE	6,2
023412	001270		09800	SAVR4	
			09900		
023414			10000	.ERRTAB:	
023414	000000		10100	0	
023416	000000		10200	0	
023420	000000		10300	0	
023422	022700		10400	EM12	
023424	023137		10500	DH5 ;HLT	1
023426	000000		10600	0	
023430	022534		10700	EM2	
023432	023047		10800	DH2 ;HLT	2
023434	023402		10900	DT13	
023436	022557		11000	EM3	
023440	000000		11100	0 ;HLT	3
023442	000000		11200	0	
023444	022605		11300	EM4	
023446	000000		11400	0 ;HLT	4
023450	000000		11500	0	
023452	022627		11600	EM5	
023454	000000		11700	0	
023456	000000		11800	0	
023460	022605		11900	EM4	
023462	023047		12000	DH2 ;HLT	6
023464	023242		12100	DT5	
023466	022627		12200	EM5	
023470	023047		12300	DH2 ;HLT	7
023472	023230		12400	DT4	
023474	000000		12500	0	
023476	023015		12600	DH1 ;HLT	10
023500	023254		12700	DT6	
023502	000000		12800	0	

023504	023015	12900	DH1	:HLT	11
023506	023272	13000	DT7		
023510	000000	13100	0		
023512	023047	13200	DH2	:HLT	12
023514	023230	13300	DT4		
023516	022654	13400	EM11		
023520	023015	13500	DH1	:HLT	13
023522	023310	13600	DT10		
023524	022700	13700	EM12		
023526	000000	13800	0	:HLT	14
023530	000000	13900	0		
023532	022700	14000	EM12		
023534	023047	14100	DH2	:HLT	15
023536	023242	14200	DT5		
023540	022724	14300	EM13		
023542	023070	14400	DH3	:HLT	16
023544	023326	14500	DT11		
023546	022747	14600	EM14		
023550	023111	14700	DH4	:HLT	17
023552	023340	14800	DT12		
		14900			
		15000			
023554		15100	CORMAX:		
	000001	15600	.END		

DZDMH.P11 16-MAY-77 09:54 CROSS REFERENCE TABLE -- JSER SYMBOLS

AORCNT=	004373	879*	915*	924*										
AUDONE	003024	569	608	613	659*									
AUSTRT	002446	568*	663											
AUTO.S	010512	526	1368*											
BASE	021440	1720	1838	1848	1849	1850	1851	1912	1925	1926	1927	1928	1984	1994
		1995	1996	1997	2047	2057	2058	2059	2060	2113	2123	2124	2125	2126
		2173	2183	2184	2185	2186	2233	2243	2244	2245	2246	2358	2371	2372
		2373	2374	2503	2517	2518	2519	2520	2540	2555	2746*	2769	2799	2829
		2882												
BASELD	022040	1875	1356	2022	2085	2151	2211	2315	2753*					
BASELH	022156	2271	2783*											
BNWARD	004714	965*	968*	969	1006*									
BITO =	000001	95*	1155	1156	1687	1793	1808	1870	1890	1951	1973	2017	2036	2080
		2102	2146	2163	2206	2223	2266	2307	2398	2489	2597			
BIT1 =	000002	94*	531	1149	1155	1156	1449	1532	1545	1909	2355	2500	2538	
BIT10 =	002000	85*	1513	1524	2807									
BIT11 =	004000	84*	2453	2621	2765	2795	2825							
BIT12 =	010000	83*	1464	1543	1690	1873	1954	2020	2083	2149	2209	2269	2310	2401
		2541	2930											
BIT13 =	020000	82*	1467	1516	1547	1906								
BIT14 =	040000	81*	781	1478	1480	1547	1558	1700	2432	2451	2609	2619	2757	2787
		2817												
BIT15 =	100000	80*	485	572	575	596	599	1451	1519	1685	1701	1703	1868	1949
		2015	2078	2144	2204	2264	2305	2396	2433	2435	2610	2612	2758	2760
		2788	2790	2818	2820									
BIT2 =	000004	93*	531	712	1156	1787	1894	2629						
BIT3 =	000010	92*	1549	1556	2562	2586								
BIT4 =	000020	91*	1139	1162	1164	1977								
BIT5 =	000040	90*	1661											
BIT6 =	000100	89*	1144	1145	1551	2450	2618							
BIT7 =	000200	88*	1145	1265	1661									
BIT8 =	000400	87*	1523	1538	1540	1553	1555	1561	1564	1622	2040	2106		
BIT9 =	001000	86*	1521	1523	1535	1561	1564	1620	1622	216*	222*	2606	2606	
BM	007054	1187*	1492											
BRVL	012252	1617	1627	1635	1647*									
BRW	003730	718	804*											
BRX	003732	719	905*											
CHRCNT	004712	963*	966	970	986*	1004*	1005							
CKSWR	007606	512	779	811	1026	1212*								
CKSWR1	007666	1225*	1237											
CKSWR2	007700	1228*												
CKSWR3	007704	1230*												
CKSWR4	007710	1231*	1239	1246										
CKSWR5	010014	1213	1220	1255*										
CLKX	001242	171*												
CLRTAB	016454	2437*	2495											
CNERR	007277	626	1187*											
CNT.MA	001702	196	364*	484	486	488	1293							
CONVRT =	104411	233*	623	738	740	742	744	1060	1062	1122	1228			
CONERR	007223	621	1187*											
CCNN	007114	1187*	1469											
CONTAB	002776	630	643*											
CONVRT =	104410	231*	543	629	1076	1391								
CCPMAX	023554	2882*												
CFAM	006606	1187*	1430											
CFEAM	001320	195*	483*	1289*	1290	1292*	1296							

DZDMM.P11 16-MAY-77 09:54 CROSS REFERENCE TABLE -- USER SYMBOLS

EM3	022557	2882#								
EM4	022605	2882#								
EM5	022627	2882#								
ENDEX	016750	2496#								
ENDEX1	017044	2400	2509	2516#	2522	2530	2628			
ENDEX2	017046	2506	2517#							
ERCT00	001704	366#								
ERCT01	001710	369#								
ERCT02	001714	372#								
ERCT03	001720	375#								
ERCT04	001724	378#								
ERCT05	001730	381#								
ERCT06	001734	384#								
ERCT07	001740	387#								
ERCT10	001744	390#								
ERCT11	001750	393#								
ERCT12	001754	396#								
ERCT13	001760	399#								
ERCT14	001764	402#								
ERCT15	001770	405#								
ERCT16	001774	408#								
ERCT17	002000	411#								
ERR	002700	592	618#	622						
ERRCNT	001232	163#	747	774	1087*	1305*				
ERRFLG	001325	202#	481*	733*	795*	1037*	1050	1064*	1123*	
ERRMSG	005172	1047*	1065	1068#						
ERRPC	002770	624	640#							
ERTAB0	005322	1062	1097#							
EXIT =	000205	96#								
EXITER	005252	1082	1087#							
FLAG	021314	2431*	2454	2489	2494*	2497	2599	2601*	2732#	2882
FLOAT	002536	585#	591							
FY	002566	594#	605	609	615					
HALTS	005222	1033	1079#							
HILIM	004366	876*	903	921#						
ICOUNT	001222	159#	793	798*						
IISR	017132	2410	2534#							
INBUF	007502	846	882	1202#						
INCHAR	010020	1231	1259#							
INIFLG	001324	201#	507	527	534*					
INSTER=	104404	223#	897							
INSTR =	104403	221#	1329	1381	1394	1403	1482	1491		
INSTR2	004166	853	865#							
INTTY	012266	1414	1431	1441	1454	1470	1655#			
KMCM	007330	637	1187#							
LIMITS	004314	892	903#							
LINE	007016	1187#	1483							
LOBITS	004372	878#	907	923#	924					
LOCK	001220	158#	797*	814	816	1056				
LOCKLG	001326	203#								
LOLIM	004364	875*	905	920#						
LPCNT	001224	160#	792*	793	796*					
LSTERR	001234	164#	490*	732*	1034	1036*	1124*			
MASKX	001244	172#								
MASTEK	006142	1058	1187#							
MCRLF	005672	831	954	1054	1055	1063	1187#	1328	1390	

DMEND	10	725													
DMFRNT	10														
MLT	750	1711	1719	1732	1734	1749	1758	1765	1774	1783	1786	1791	1795	1798	1801
	1805	1810	1813	1816	1825	1830	1852	1888	1892	1900	1929	1971	1975	1981	1998
	2034	2038	2044	2061	2100	2104	2110	2127	2161	2165	2171	2187	2221	2225	2231
	2247	2297	2333	2345	2375	2480	2521	2529	2626	2637	2644	2660	2667		
\$AUTO	10	547													
\$BASEC	10	1837	1908	1983	2046	2112	2172	2232	2353						
\$BUFFE	10	1199													
\$BYTE	10	2683	2686	2689	2692	2695	2698	2701	2704	2707					
\$CKDAT	10	2472													
\$COMP	10														
\$CYCLE	10	1271													
\$DATAF	10	1664													
\$EOP	10	725													
\$EXER	10	2378													
\$FD	10	1736	2774	2834											
\$FINI	10	2747													
\$GETPA	10														
\$HALF	10	2250													
\$HD	10	2804													
\$HEADE	10														
\$LSTDA	10	1935													
\$MARHI	10														
\$MOCK	10														
\$MSG	10	1187													
\$NONEX	10	2001	2064												
\$ORUN	10	1855													
\$PFATL	10	1103													
\$PROC	10	2130													
\$PROC1	10	2190													
\$QUEST	10	1381	1394	1403	1482	1491									
\$RAMCL	10	1131													
\$RCLK	10	1134	1137	1174	1179										
\$RESUM	10	2289													
\$SCOPE	10	775													
\$SETUP	10	1868	1949	2015	2078										
\$SIMBC	10														
\$SKIPT	10	1685	1868	1949	2015	2078	2144	2204	2264	2305	2396				
\$SOFTC	10	1207													
\$TRPDE	10	215	217	219	221	223	225	227	229	231	233	235	237	239	241
	243														
\$TSTN	10	1680	1863	1943	2009	2072	2138	2198	2258	2299	2390				
\$VARI	10	134													
\$XZ	10	1664	1678	1855	1861	1935	1941	2001	2007	2064	2070	2130	2135	2190	2196
	2250	2256	2289	2297	2379	2388									

. ABS. 023554 000

ERRORS DETECTED: 0

DZDMH, DZDMH/SOL/CRF-IPLUTL, DZDMH
RUN-TIME: 8 12 1 SECONDS
RUN-TIME RATIO: 199/21=9.1

H07

SDMM MACY11 30.1046) 11-JUL-77 12:32 PAGE 72
SDMM.P11 16-MAY-77 09:54 CROSS REFERENCE TABLE -- MACRO NAMES
CORE USED: 24K (47 PAGES)

PAGE: 0085