

# RDOS

Instruction  
Manual

*five dollars*

# RDOS

© Copyright 1978. All Rights Reserved.



---

## Table of Contents

---

	<i>Pg. No.</i>
Introduction .....	1
Command Format	
Swath Operator	
Errors and Escapes	
Baud Rate Selection	
System Stack	
Using the RDOS Monitor	
Commands .....	2
Boot	
Display Memory	
Examine Input Port	
Go	
Initialize Baud Rate	
Kick Stack	
Move	
Output	
Read Disk	
Seek Track	
Substitute Memory	
Verify	
Write Disk	
Select Disk Drive	
An Illustrative Example.....	6
RDOS Program Listing .....	7

## Introduction

The Cromemco Resident Disk Operating System (RDOS) is a 1K-byte program supplied in ROM with each Cromemco model 4FDC disk controller card. The RDOS program is designed to execute beginning at location C000 in memory space.

RDOS includes a bootstrap loader for the Cromemco Disk Operating System (CDOS) supplied with Cromemco disk software. RDOS also includes a system monitor with over a dozen commands. Several of the RDOS monitor commands are the same as those used in the Cromemco Z-80 Monitor program. These include commands to transfer program control, display the contents of memory, change the contents of memory, move and compare blocks of memory, write data to output ports, and change the baud rate of the serial port on the 4FDC card. The RDOS monitor also has several unique commands designed specifically for disk operations. These include commands to select one of four disk drives, set the head seek rate, seek disk tracks, read blocks of data from the disk, and write blocks of data onto the disk.

To use RDOS, first be sure that the power-on jump address of your ZPU card is set to memory location C000 (see Table 1). If you wish to boot in CDOS from your disk without entering the RDOS monitor, then set Switch 3 of the 4FDC card to the ON position (this selects auto-boot mode). Once CDOS is booted in, you may return to the RDOS monitor by executing the "BYE" command in CDOS. If on power-up or reset you do wish to enter the RDOS monitor, then set Switch 3 of the 4FDC card to the OFF position (see Table 2). Once the RDOS monitor is entered, you can begin using the RDOS commands described in this manual.

ZPU Switch	Switch Position
A15	1
A14	1
A13	0
A12	0

Table 1

The power-on jump address switch on the ZPU card should be set as shown to begin automatic execution of RDOS at location C000 in memory space.

RDOS Mode	4FDC Switch 3
CDOS Bootstrap	ON
RDOS Monitor	OFF

Table 2

The setting of Switch 3 on the 4FDC card sets the RDOS mode of operation on power up. When this switch is ON, CDOS is automatically booted in from the system diskette. When this switch is OFF, the RDOS Monitor is entered.

## Command Format

The normal prompt of the monitor is a semi-colon, ';'. However, if a disk drive is selected the prompt changes in order to remind the user which drive is current. (See Select Disk Drive for details.)

The monitor is controlled by one and two-character commands from the terminal keyboard. The format is free-form with respect to spaces. All data is entered and printed in hexadecimal format.

In the following, DM is the Display Memory command and S is the Swath operator (see below). The four examples are equivalent commands. They display the contents of 100 hex bytes of memory beginning with location 1000 hex. ('(CR)' indicates carriage return).

```
;DM1000 10FF (CR)
;DM1000S100 (CR)
; D M 1000 10FF (CR)
; D M 1000 S 100 (CR)
```

When entering an address as an operand, only the last four digits typed in are retained. For example, '321000' is read as '1000'. Therefore, if a wrong digit is entered, continue typing until the last four digits are correct.

Only the last two digits typed are retained when a two-digit number such as a data byte is entered.

## Swath Operator

There are two ways to specify the address range of many commands. The first is to simply list the beginning and ending addresses (and, where appropriate, the destination address). For example, the first command displays the contents of memory between addresses E400 and E402. The second com-

mand moves (or copies) the first 1400 hex bytes of memory to memory starting at 2000 hex.

```
DM E400 E402  
M 0 13FF 2000
```

Another way to do the same thing is to use the Swath operator, S, to specify the width of the address range rather than state the ending address explicitly.

```
DM E400S3  
M 0 S1400 2000
```

## Errors and Escapes

When the monitor detects an error condition, the command is aborted and a '?' is printed followed by the prompt ';' for the next command.

Any command may be aborted from the keyboard either when the monitor is requesting further input, or during print-out, by depressing either of the ESCAPE or the ALT MODE key. (CONTROL-SEMI-COLON, CONTROL-SHIFT-'K', and '}' may also work, depending on the design of your CRT terminal.)

## Baud Rate Selection

When the monitor is entered, push carriage-return (up to four times) until the monitor responds with:

```
CROMEMCO RDOS
```

The monitor is capable of selecting 19200, 9600, 4800, 2400, 1200, 300, 150, or 110 baud. The maximum number of carriage-returns required to select any of these baud rates is four.

The baud rate can also be changed by using Initialize command. (See page 3.)

Some peripheral devices such as paper tape readers or punches may have no keyboards. The baud rate can also be set by outputting a data byte from the following table to port 0.

Baud Rates	Data Byte
110	01
150	82
300	84
1200	88
2400	90
4800	A0
9600	C0

The baud rate can be octupled by outputting 10 hex to port 2. Outputting 0 to this port brings the baud rate back to normal.

## System Stack

The RDOS stack normally resides in low memory between 40 and 80 hex. However, if it is in the way, it can be moved using the Kick Stack command. (See page 3.)

## Using the RDOS Monitor

Set the power-on jump switch on the ZPU card to C (1100 binary) and turn off DIP switch 3 on the 4FDC.

Depress carriage-return two to four times in order to set the UART on the 4FDC to the baud rate of the terminal being used.

The monitor will then respond:

```
CROMEMCO RDOS
```

followed by a prompt ';'. The monitor is then ready to accept commands from the keyboard.

## Commands

### Boot

(1) B (CR)

Boots CDOS from the diskette on drive-A. CDOS will then respond with its prompt 'A.'

### Display Memory

(2a) DM beginning-addr ending-addr (CR)  
or

(2b) DM beginning-addr S swath-width

The contents of memory are displayed in hexadecimal form. Each line of the display is preceded by the address of its first byte. For example:

```
; DM100 S3  
01 0 0 : C3 34 7F
```

### Examine Input Port

(3) E port-number (CR)

Displays the current contents of the input port identified by port-number (in hex).

### Go

(4) G starting-addr (CR)

Execution begins at starting-address.

## Initialize Baud Rate

### (5) I (CR)

After the carriage-return is typed, change the baud rate of the terminal to the desired value and then push carriage-return until the monitor responds with its prompt.

The monitor is capable of selecting 19200, 9600, 4800, 2400, 1200, 300, 150, or 110 baud. The maximum number of carriage returns required to select any of these baud rates is four.

## Kick Stack

### (6) K new-stack-location (CR)

Moves the monitor's stack from normal location at 7C hex to any convenient location in RAM memory. Remember to leave 64 (40 hex) bytes for the system stack above its new location (including 4 bytes for temporary storage above the stack proper).

## Move

### (7a) M source-addr source-end destination-addr (CR)

or

### (7b) M source-addr Sswath-width destination-addr (CR)

Move (or copy) the contents of memory beginning with source-address and ending with source-end to destination-address. After the move, the monitor verifies that source and destination are the same. This will result in a print-out of discrepancies which are not really errors after certain types of overlapping moves. However, this print-out can be terminated by depressing ESCAPE or ALT Mode.

The move command can be used to fill a block of memory with a constant. For example, to enter zeros between locations 100 and 108, use the Substitute Memory command to enter 0 at location 100, and then move 100 through 107 to 101:

M 100 107 101

or

M 100 S 8 101

Care should be taken not to overwrite the monitor's stack which resides in low memory between 40 and 80 hex unless changed with the Kick Stack command.

## Output

### (8) O data-byte port-number (CR)

Writes data to the output port identified by port-number (in hex).

## Read Disk

### (9a) RD destination-addr destination-end sector-number (CR)

or

### (9b) RD destination-addr S swath-width sector-number (CR)

Before this command will be accepted the disk drive and track number must have been specified. (See the Select Disk Drive and Seek commands.)

This command reads enough sectors from the current drive to fill the specified memory area, starting with the specified sector of the current track. The first track and sector and the last track and sector read are then displayed. However, if the last sector of the last track on the diskette is read before the memory area is filled then a question mark is printed and the command is terminated. The track and sector designations for both 5" and 8" diskettes are shown in Table 3.

The command is also terminated if an error occurs in reading a sector. In this case, a message of the following type is printed:

R-ERR nn

where nn is a hex number which indicates the status:

Bit	Indication
7	Not Ready
6	Record Type
5	Record Type
4	Record Not Found
3	CRC Error
2	Lost Data
1	Data Request
0	Busy

The number of the last track accessed can be obtained from input port 31 hex and the number of the last sector accessed from input port 32 hex. (See the Examine Input Port command.)

	8" Diskette	5" Diskette
Tracks	0-4C hex	0-27 hex
Sectors	1-1A hex	1-12 hex

Table 3

Care should be taken not to overwrite the monitor's stack which normally resides in lower RAM

between 40 and 80 hex. If it is desired to load this region of memory from the disk, first move the stack using the Kick Stack command.

## Seek Track

### (10) S track-number (CR)

Before this command will be accepted the disk drive must be specified. (See the Select Disk Drive command.)

This command seeks the specified track of the current drive.

If an error is made, a message of the following type is printed:

S-ERR nn

where nn is a hex number which indicates the status:

Bit	Indication
7	Not Ready
6	Write Protect
5	Head Engaged
4	Seek Error
3	CRC Error
2	Track 0
1	Index
0	Busy

## Substitute Memory

### (11) SM address (CR)

Substitute Memory displays the contents of address and outputs a dot, '.', as a prompt for the substituted value. If no change is desired, type a space or another dot. Otherwise, enter the new value. The monitor accepts hex digits until it gets a delimiter, such as a space, dot, or carriage-return, retaining the last two digits entered as the value. Unless the delimiter is a carriage-return, the monitor then outputs the contents of the next sequential memory location with a dot prompt. A carriage-return terminates the command.

## Verify

### (12a) V source-addr source-end destination-addr (CR) or

### (12b) VsOURCE-addr S swath-width destination-addr (CR)

This command verifies that the block of memory between source-address and source-end contains the

same values as the block beginning at destination-address. The addresses and contents are printed for each discrepancy found (unless the print-out is terminated by ESCAPE or ALT MODE).

This command works by reading bytes from the source and destination and comparing them. If a discrepancy is found, the memory is read again for print-out. Thus it can happen that a discrepancy is printed-out with the source and destination contents indicated to be the same. This is caused by a defective memory element.

## Write Disk

### (13a) WD source-addr source-end sector-number (CR) or

### (13b) WD source S swath-width sector-number (CR)

Before this command will be accepted the disk drive and track number must have been specified. (See the Select Disk Drive and Seek commands).

This command writes the contents of the specified memory area to the current drive, starting with the specified sector of the current track. The first track and sector and the last track and sector written are then displayed (see Table 3). However, if part of the memory area remains after the last sector of the last track is written, a question mark is printed and the command is terminated.

The command is also terminated if an error is made in writing a sector. In this case, a message of the following type is made:

W-ERR nn

where nn is a hex number indicating the status:

Bit	Indication
7	Not Ready
6	Write Protect
5	Write Fault
4	Record Not Found
3	CRC Error
2	Lost Data
1	Data Request
0	Busy

The last track accessed can be obtained from port 31 hex. The last sector accessed from port 32 hex. (See Examine Input command.)

## Select Disk Drive

The 4FDC will control up to four disk drives, labelled "A", "B", "C", and "D". It can handle seek speeds from the slow seek appropriate to the mini floppy to the fast seek of Cromemco's large floppy. It can also handle the medium seek of some other large floppies. To select a drive and a seek speed, type the drive label followed by one semi-colon for the fast seek, and two semi-colons for medium seek, or three semi-colons for slow seek. For example, to select drive C with slow seek, type:

C ; ; ; (CR)

To select drive A with fast seek, type:

A ; (CR)

Until the drive selection is changed the normal monitor prompt, ';', will be replaced by the disk label and speed indicator as typed, 'C ; ; ;' in the first example.

All disk commands (Seek, Read Disk, and Write Disk) refer to the drive most recently selected.

Disk selection also restores the disk drive head to home, track 0. If an error is made in doing this a message of the following type is printed:

H-ERR nn

where nn is a hex number indicating the status:

Bit	Indication
7	Not Ready
6	Write Protect
5	Head Engaged
4	Seek Error
3	CRC Error
2	Track 0
1	Index
0	Busy

## An Illustrative Example

To illustrate a specific use of the RDOS commands, consider the situation where you wish to make a copy of a diskette. If you have two disk drives this can easily be done using the CDOS command XFER. But if you have only one disk drive, you can use RDOS to read the original diskette into memory, and then write from memory to the new diskette. Since the total amount of system RAM memory is typically less than the capacity of a diskette, the procedure will have to be repeated several times — a different portion of the diskette is copied with each iteration.

The following procedure explains how to use RDOS to make a back-up mini-diskette using only one drive. This procedure assumes that there is 32K of contiguous low memory; if the user has less memory, the procedure

can easily be adapted to a smaller configuration by decreasing the swath lengths of the READS and WRITES. Note that you must also keep track of the sector numbers when changing the following procedure. This is easily done by noting the starting and stopping track and sector numbers given after the completion of a READ or WRITE.

Throughout the following, note that the commands which are typed by the user are underlined. The other prompts and messages are those issued by RDOS. The messages enclosed in brackets are parenthetical remarks and should not be typed into the terminal.

*Get into RDOS and insert the disk to be copied, or the original disk, into the drive. Then type the following RDOS commands.*

```
ASS1  
ASS1S0  
ASSRD100 SZE00 1  
0001 0D12
```

INSERT BLANK DISK WHICH HAS BEEN INITIALIZED AND  
WHICH WILL BE THE NEW BACK-UP DISK. ]

```
ASS1S0  
ASSWD100 SZE00 1  
0001 0D12
```

INSERT ORIGINAL DISK. ]

```
ASS1E  
ASSRD100 SZE00 1  
0E01 1E12
```

INSERT BACK-UP DISK. ]

```
ASS1E  
ASSWD100 SZE00 1  
0E01 1E12
```

INSERT ORIGINAL DISK. ]

```
ASS1C  
ASSRD100 S6C00 1  
1C01 2712
```

INSERT BACK-UP DISK. ]

```
ASS1C  
ASSWD100 S6C00 1  
1C01 2712  
ASS1S0  
ASS1E
```

HOME THE HEAD. ]  
SYSTEM SHOULD BOOT UP INTO CDOS FROM THE  
NEW BACK-UP DISK. TYPE THE DIRECTORY AND  
VERIFY THAT THE TRANSFER IS CORRECT AND  
COMPLETE BY TRYING SEVERAL OF THE FILES. ]

## RDOS Program Listing

```

0002 ; COPYRIGHT (C) 1977, CROMEMCO, INC.
0003 ;
0004 ;
0000      0005     ORG     0C000H ;START OF PROM
0006 ;
0007 ;
(007C)   0008 STACK: EQU    7CH    ;MUST LEAVE ROOM FOR
0009 ;        ;4 BYTES OF TEMP STORAGE
0010 ;        ;ABOVE THE STACK
0011 ;        ;(STACK) = DISK FLAGS
0012 ;        ;(STACK+1) = DISK LETTER (A - D)
0013 ;        ;(STACK+2) - (STACK+3) = ROOM FOR
0014 ;        ;UP TO 2 SEMI-COLONS AS PART OF
0015 ;        ;THE DISK PROMPT.
0016 ;
0017 ;
(0004)   0018 NDRIVES: EQU    4      ;MAX. NO. OF DISK DRIVES
0019 ;
0020 ; BIT ASSIGNMENT FOR THE DISK FLAGS
0021 ;
(0007)   0022 FASTSEEK: EQU    7
(0005)   0023 DISKMODE: EQU    5
(0004)   0024 MAXI: EQU    4
0025 ;THE DISK NUMBER (0 - 3) OCCUPIES BITS 0 & 1
0026 ;
0027 ;
(0030)   0028 DSTAT: EQU    30H    ;DISK STATUS PORT
(0030)   0029 DCOMMND: EQU    30H    ;DISK COMMAND PORT
(0032)   0030 DSEC: EQU    32H    ;DISK SECTOR PORT
(0033)   0031 DDATA: EQU    33H    ;DISK DATA PORT
(0034)   0032 DFLAGS: EQU    34H    ;DISK FLAGS PORT
(0034)   0033 DCONTR: EQU    34H    ;DISK CONTROL PORT
(0031)   0034 DTRACK: EQU    31H    ;DISK TRACK PORT
0035 ;
(0003)   0036 IMASK: EQU    3      ;INTERRUPT MASK PORT
(0000)   0037 BAUD: EQU    0      ;BAUD RATE PORT
(0004)   0038 PARREL: EQU    4      ;PARALLEL PORT
(0040)   0039 BOOTSW: EQU    40H    ;BOOT SWITCH
(0010)   0040 MAXIM: EQU    10H    ;MASK FOR MAXI DISK
(0020)   0041 HDLDM: EQU    20H    ;HEAD LOAD MASK
0042 ;
0043 ;
(0000)   0044 STAT: EQU    0      ;STATUS PORT
(0001)   0045 DATA: EQU    1      ;DATA PORT
(0002)   0046 COMMND: EQU    2      ;COMMAND PORT
(0040)   0047 DAV: EQU    40H    ;DATA-AVAILABLE MASK
(0080)   0048 TBE: EQU    80H    ;XMITTER-BUF-EMPTY MSK
0049 ;
(0000)   0050 CASE: EQU    0
0051 ;
(000D)   0052 CR: EQU    0DH
(000A)   0053 LF: EQU    0AH
(001B)   0054 ESC: EQU    1BH
(007D)   0055 ALT: EQU    7DH
0056 ;

```

```

0057 ;
0058 ;+++++;
0059 ;
C000 217C00 0060 START: LD HL,STACK
C003 F9 0061 LD SP,HL
C004 EB 0062 EX DE,HL ;DE -> TEMP STORAGE
C005 F3 0063 DI
C006 CDEEC0 0064 CALL INTBAUD ;INIT. THE SERIAL PORT
C009 97 0065 SUB A
C00A D303 0066 OUT IMASK,A ;MASK OUT 4FDC INTERRUPTS
C00C DB34 0067 IN A,DFLAGS ;READ DISK FLAGS
C00E E640 0068 AND BOOTSW ;LOOK AT BOOT SWITCH
C010 2806 0069 JR Z,BOOTDK
C012 C30BC1 0070 JP MONITR
0071 ;
0072 ;
0073 ; MONITOR COMMAND
0074 ; QUIT THE MONITOR & BOOT CDDOS IN.
0075 ;
C015 0076 BOOTMC:
C015 CD29C2 0077 CALL SKSGCR ;REQUIRE A CR
0078 ;
0079 ;
0080 ; BOOT DISK
0081 ;
C016 0082 BOOTDK:
C018 3ED0 0083 LD A,0D0H ;TERMINATE THE HOMING
C01A D330 0084 OUT DCOMMND,A ;OF THE DISK HEAD
C01C DB30 0085 BOT200: IN A,DSTAT
C01E 1F 0086 RRA
C01F 38FB 0087 JR C,BOT200
C021 F3 0088 DI
C022 3E10 0089 LD A,1 SHL MAXI ;MAXI FLAG
C024 0090 BOT300:
C024 218000 0091 LD HL,0080H ;INIT. BUFFER PNTR
C027 F9 0092 LD SP,HL ;& STACK PNTR
C028 F5 0093 PUSH AF ;SAVE MINI/MAXI FLAG
C029 44 0094 LD B,H ;0 EDISK AJ
C02A CD3FC0 0095 CALL DHOME ;HOME DISK
C02D 200B 0096 JR NZ,BOT500 ;DISK ERROR
C02F F1 0097 POP AF ;GET MINI/MAXI FLAG
C030 F5 0098 PUSH AF
C031 44 0099 LD B,H ;0 EDISK AJ
C032 1E01 0100 LD E,1 ;SECTOR 1
C034 CD8CC0 0101 CALL DREAD ;READ THE SECTOR
C037 CAB000 0102 JP Z,80H ;OK, GO EXECUTE
C03A F1 0103 BOT500: POP AF ;GET MINI/MAXI FLAG
C03B EE10 0104 XOR 1 SHL MAXT ;TOGGLE IT
C03D 18E5 0105 JR BOT300
0106 ;
0107 ;
0108 ;HOME DISK DRIVE
0109 ;
0110 ;INPUT - B CONTAINS DISK NUMBER (0,1,2,3)
0111 ; A BIT 4 CONTAINS 1 IF MAXI
0112 ;
0113 ;OUTPUT - B CONTAINS STATUS
0114 ; ZERO FLAG RESET IF ERROR
0115 ;
0116 ;REGISTERS A,F,B,C ARE CHANGED
0117 ;
0118 ;

```

C03F CDCBC0	0119 DHOME:	CALL	SELECT	;SELECT DISK
C042 D334	0120	OUT	DCONTR,A	;OUTPUT SELECT BYTE
C044 1698	0121	LD	D,98H	;ERROR MASK
C046 E610	0122	AND	MAXIM	;MAXI DISK?
C048 3E7F	0123	LD	A,7FH	;TURN OFF HIGH SPEED SEEK
C04A D304	0124	OUT	PARREL,A	
C04C 3E0F	0125	LD	A,0FH	;LOAD MINI RESTORE COMMAND
C04E 281A	0126	JR	Z,EXECUTE	;NO, ITS A MINI
C050 3E0D	0127	LD	A,0DH	;MAXI RESTORE COMMAND
C052 1816	0128	JR	EXECUTE	;EXEC COMMAND &
	0129 ;			;WAIT TIL DONE
	0130 ;			
	0131 ;			
	0132 ;SEEK TO DESIRED TRACK			
	0133 ;			
	0134 ;TRACK REGISTER MUST HAVE BEEN PREVIOUSLY LOADED			
	0135 ;(MAY BE DONE BY INITIALLY DOING A HOME)			
	0136 ;			
	0137 ;INPUT - B CONTAINS DISK DRIVE (0,1,2,3)			
	0138 ; D CONTAINS TRACK			
	0139 ; A BIT 7 = 1 FOR FAST SEEK			
	0140 ; A BIT 4 = 1 FOR MAXI			
	0141 ;			
	0142 ;OUTPUT - B CONTAINS STATUS			
	0143 ; ZERO FLAG RESET IF ERROR			
	0144 ;			
	0145 ;REGISTERS A,F,B,C,D ARE CHANGED			
	0146 ;			
C054 F5	0147 DSEEK:	PUSH	AF	;SAVE DISK FLAGS
C055 CDCBC0	0148	CALL	SELECT	;SELECT DISK
C056 D334	0149	OUT	DCONTR,A	;OUTPUT CONTROL BYTE
C05A ED51	0150	OUT	(C),D	;OUTPUT DESIRED TRACK
C05C 1698	0151	LD	D,98H	;ERROR MASK
C05E F1	0152	POP	AF	;GET FLAGS
C05F 17	0153	RLA		;FAST SEEK?
C060 3814	0154	JR	C,DSK500	
C062 E620	0155	AND	MAXIM SHL 1	;MASK FOR MINI/MAXI
C064 3E1F	0156	LD	A,01FH	;LOAD SEEK COMMAND FOR MINI
C066 2802	0157	JR	Z,EXECUTE	;MINI DISK
C068 3E1D	0158	LD	A,1DH	;LOAD COMMAND FOR MAXI
	0159 ;			
	0160 ;			
C06A	0161 EXECUTE:			
C06A D330	0162	OUT	DCOMMND,A	;OUTPUT COMMAND
	0163 ;			
C06C	0164 EXCCCHK:			
C06C DB34	0165	IN	A,DFLAGS	;WAIT FOR COMPLETION
C06E 1F	0166	RRA		
C06F 30FB	0167	JR	NC,EXCCCHK	;UNTIL INTREQD
C071	0168 EREXIT:			
C071 DB30	0169	IN	A,DSTAT	;DISK STATUS
C073 47	0170	LD	B,A	;SAVE STATUS
C074 A2	0171	AND	D	;MASK FOR ERRORS
C075 C9	0172	RET		
	0173 ;			
	0174 ;			
C076 3E6F	0175 DSK500:	LD	A,6FH	;TURN ON FAST SEEK
C078 D304	0176	OUT	PARREL,A	
C07A 3E18	0177	LD	A,18H	;SEEK COMMAND
C07C CD6AC0	0178	CALL	EXECUTE	
C07F DB04	0179 DSK540:	IN	A,PARREL	;FAST SEEK DONE?
C081 E640	0180	AND	40H	

C083 20FA	0181	JR	NZ,DSK540	
C085 3E7F	0182	LD	A,7FH	TURN OFF FAST SEEK
C087 D304	0183	OUT	PARLEL,A	
C089 97	0184	SUB	A	END ERROR CHECKING, SAY OK
C08A 47	0185	LD	B,A	
C08B C9	0186	RET		
	0187 ;			
	0188 ;			
	0189 ;READ 1 SECTOR FROM DISK			
	0190 ;			
	0191 ;INPUT - B CONTAINS DISK (0,1,2,3)			
	0192 ; E CONTAINS SECTOR			
	0193 ; A BIT 4 = 1 FOR MAXI			
	0194 ; HL CONTAINS BUFFER ADDRESS			
	0195 ;			
	0196 ;OUTPUT - B CONTAINS STATUS			
	0197 ; Z FLAG IS SET IF NO ERRORS			
	0198 ; HL PTS PAST BUFFER			
	0199 ;			
	0200 ;REGISTERS A,F,B,C,D,E,H,L ARE CHANGED			
	0201 ;			
	0202 ;			
C08C CDB6C0	0203	DREAD:	CALL	SETUP
C08F C608	0204		ADD	38H
C091	0205			ADD READ COMMAND TO
C091 169C	0206	LD	D,9CH	HEAD LOAD FLAG
	0207 ;			ERROR MASK
C093 D330	0208		OUT	DCOMMND,A
C095 DB34	0209	DRD250:	IN	A,DFLAGS
C097 1F	0210		RRA	WAIT FOR REQUEST
C098 3BD7	0211		JR	C,EREEXIT
C09A EDA2	0212		INI	END OF SECTOR OR ERROR
C09C C295C0	0213		JP	NOT DONE YET
C09F 18CB	0214		JR	WAIT FOR INTREQ
	0215 ;			
	0216 ;			
	0217 ;WRITE A SECTOR TO THE DISK			
	0218 ;			
	0219 ;INPUT - B CONTAINS DISK (0,1,2,3)			
	0220 ; E CONTAINS SECTOR			
	0221 ; A BIT 4 = 1 FOR MAXI			
	0222 ; HL CONTAINS BUFFER ADDRESS			
	0223 ;			
	0224 ;OUTPUT - B CONTAINS STATUS			
	0225 ; Z FLAG IS SET IF NO ERRORS			
	0226 ; HL PTS PAST BUFFER			
	0227 ;			
	0228 ;REGISTERS A,F,B,C,D,E,H,L ARE CHANGED			
	0229 ;			
	0230 ;			
C0A1 CDB6C0	0231	DWRITE:	CALL	SETUP
C0A4 C6A8	0232		ADD	0A8H
C0A6	0233			ADD WRITE COMMAND TO
C0A6 16FC	0234		LD	0,0FCH
C0A8 D330	0235		OUT	DCOMMND,A
C0AA DB34	0236	DWR250:	IN	A,DFLAGS
C0AC 1F	0237		RRA	WAIT FOR REQUEST
C0AD 38C2	0238		JR	C,EREEXIT
C0AF EDA3	0239		OUTI	END OF SECTOR OR ERROR
C0B1 C2AAC0	0240		JP	NOT DONE YET
C0B4 18B6	0241		JR	WAIT FOR INTREQ
	0242 ;			

```

0243 ;
0244 ;SET UP FOR READ OR WRITE
0245 ;
0246 ;INPUT - B CONTAINS DISK DRIVE (0,1,2,3)
0247 ;           E CONTAINS SECTOR
0248 ;           A BIT 4 CONTAINS 1 IF MAXI
0249 ;
0250 ;OUTPUT - D CONTAINS SELECT BYTE
0251 ;           A CONTAINS HEAD LOAD FLAG
0252 ;           B CONTAINS 128 (# OF BYTES)
0253 ;           C CONTAINS DATA PORT
0254 ;
0255 ;REGISTERS A,F,B,C,D ARE CHANGED
0256 ;
0257 ;
C0B6
C0B6 CDCBC0 0258 SETUP:
0259     CALL    SELECT      ;GET SELECT BYTE
C0B9 F680 0260     OR      30H      ;TURN ON AUTO WAIT
C0B8 57   0261     LD      D,A      ;SAVE CONTROL BYTE
C0B8 7B   0262     LD      A,E      ;SECTOR #
C0BD D332 0263     OUT     DSEC,A
0264 ;
0265 ;CHECK WHETHER DISK HEAD LOADED
0266 ;
C0BF DB34 0267     IN      A,DFLAGS ;READ FLAGS
C0C1 E620 0268     AND     HDLDM   ;HEAD LOADED?
C0C3 7A   0269     LD      A,D      ;CONTROL BYTE
C0C4 D334 0270     OUT     DCONTR,A ;THIS MUST BE DONE AFTER
0271 ;           THE INPUT FROM DFLAGS
0272 ;           BECAUSE OF AUTO WAIT
C0C6 3E04 0273     LD      A,4      ;HEAD NOT LOADED
C0C8 C8   0274     RET     Z
C0C9 97   0275     SUB     A
C0CA C9   0276     RET
0277 ;
0278 ;
0279 ;SELECT DISK DRIVE
0280 ;
0281 ;INPUT - B CONTAINS DISK DRIVE (0,1,2,3)
0282 ;           A BIT 4 CONTAINS 1 IF MAXI
0283 ;
0284 ;OUTPUT - A CONTAINS SELECT BYTE
0285 ;           B CONTAINS 128
0286 ;           C CONTAINS DATA PORT #
0287 ;
0288 ;REGISTERS A,F,B,C ARE CHANGED
0289 ;
0290 ;
C0CB E610 0291 SELECT: AND    MAXIM    ;GET MAXI FLAG ONLY
C0CD 4F   0292     LD      C,A      ;SAVE FLAG
C0CE 04   0293     INC     B
C0CF 97   0294     SUB     A
C0D0 37   0295     SCF
C0D1 17   0296 SEL300: RLA
C0D2 10FD 0297     DJNZ    SEL300
C0D4 B1   0298     OR      C      ;MAXI FLAG
C0D5 F620 0299     OR      20H      ;MOTOR ON
C0D7 010380 0300     LD      BC,8000H+DDATA
C0DA C9   0301     RET
0302 ;
0303 ;
0304 ;

```

```

0305 ; CHECK INPUT & RETURN WITH DATA IF READY.
0306 ;
C0DB DB00 0307 CHKIN: JN      A,STAT
C0DD E640 0308      AND     DAV
C0DF C8   0309      RET     Z
C0E0 DB01 0310      TN      A,DATA
C0E2 C9   0311      RET
0312 ;
0313 ;
0314 ; GET CHARACTER FROM INPUT.
0315 ;
C0E3 CDDEBC0 0316 GBYTE: CALL    CHKIN
C0E6 28FB   0317      JR      Z,GBYTE
C0E8 E67F   0318      AND     7FH
C0EA C9   0319      RET
0320 ;
0321 ;
0322 ; COMMAND
0323 ; CHANGE BAUD RATE OF THE SERIAL PORT
0324 ;
C0EB      0325 INITBR:
C0EB CD29C2 0326      CALL    SKSGCR      ;REQUIRE CR
0327 ;                                ;CONTINUE BELOW)
0328 ;
0329 ;
0330 ; INITIALIZE BAUD RATE OF THE CURRENT DEVICE.
0331 ;
0332 ; PUSH CARRIAGE-RETURN TO SELECT THE PROPER BAUD
0333 ; RATE FOR THE CURRENT TERMINAL. (THE MAXIMUM
0334 ; NUMBER OF CARRIAGE-RETURNS REQUIRED IS FOUR.)
0335 ;
0336 ; ANY OF THE FOLLOWING BAUD RATES CAN BE SELECTED:
0337 ; 19200, 9600, 4800, 2400, 1200, 300, 150, 110.
0338 ;
C0EE 21CAC3 0339 INITBAUD: LD      HL,BAUDRS
C0F1 0E00   0340      LD      C,BAUD
C0F3 3E19   0341      LD      A,19H      ;OCTUPLE THE CLOCK
C0F5 D302   0342 IT1:   OUT    COMMND,A      ;& RESET CURRENT DEVICE
C0F7 EDA3   0343      OUTI
C0F9 CDE3C0 0344      CALL    GBYTE
C0FC CDE3C0 0345      CALL    GBYTE
C0FF FE0D   0346      CP      CR
C101 3E09   0347      LD      A,9      ;SLOW THE CLOCK
C103 20F0   0348      JR      NZ,IT1
C105 C9   0349      RET
0350 ;
0351 ;
0352 ; COMMAND
0353 ; CHANGE LOCATION OF THE SYSTEM STACK
0354 ;
C106      0355 KICKSTK:
C106 CD85C2 0356      CALL    L1NCR
C109 1813   0357      JR      LOADIX      ;IX STORES INITIAL SP VALUE
0358 ;
0359 ;
0360 ;
0361 ; MONITOR ENTRY POINT
0362 ;
0363 ;
0364 ; ENTER MONITOR WITH THE STK PNTR LOADED & WITH
0365 ; DE -> THE DISK FLAGS. (THIS IS ALSO
0366 ; THE TOP OF THE STACK.)
```

C10B	0367 ;			
C10B CDF7C2	0368 MONITR:			
C10E 000D4352	0369	CALL	PMSGFOLLOWING	
4F4D454D	0370	DB	CR, CR, 'CROMEMCO RDOS', '1'+'80H	
434F2052				
444F53B1				
C11E	0371 ;			
C11E 97	0372 LOADIX:			
C11F 12	0373 SUB A			
C120 D5	0374 LD (DE), A			CLEAR DISK MODE
C121 DDE1	0375 PUSH DE			
	0376 POP IX			IX STORES INITIAL SP VALUE
C123	0377 ;			
C123 DDF9	0378 CLEANSTACK:			
	0379 LD SP, IX			PRE-INITIALIZE SP
	0380 ;			
	0381 ;			
	0382 ; GET COMMAND.			
	0383 ; RETURNS VALUE IN HL & JUMPS TO THAT ADDR.			
	0384 ;			
C125 CDA9C1	0385 CALL CRLF			
C129 2128C1	0386 CMND:	LD HL, CMND		SET-UP RETURN
C12B DDE5	0387 PUSH TX			
C12D E3	0388 EX (SP), HL			RETN ADDR ON STK
C12E 4E	0389 LD C, (HL)			HL -> DISK FLAGS
C12F CB69	0390 EXIT DISKMODE, C			
C131 23	0391 INC HL			> DISK LETTER
C132 C1ECC2	0392 CALL NZ, PMSG			DISK MODE PROMPT
C135 CDF7C2	0393 CALL PMSGFOLLOWING			
C136 BE	0394 DB '1'+'80H			THE REGULAR PROMPT
	0395 ;			
C139 CDBAC2	0396 CALL SKSG0			GET THE COMMAND
C13C 2005	0397 JR NZ, CM6			
C13E DD360000	0398 LD (IX), 0			CR, RESET DISK MODE.
C142 C9	0399 RET			
	0400 ;			
C143 D641	0401 CM6:	SUB 'A'+CASE		> < 'A'?
C145 386E	0402 JR C, ERROR			
C147 FE17	0403 CP 'W'-'A'+1			> > 'W'?
C149 306A	0404 JR NC, ERROR			
C14B 5F	0405 LD E, A			
C14C 1600	0406 LD D, 0			
	0407 ;			
C14E CDBAC2	0408 CALL SKSG0			NEXT COMMAND CHARACTER
C151 FE3B	0409 CP '1'			
C153 230D	0410 JR Z, DISKSELECT			
C155 EB	0411 EX DE, HL			
C156 29	0412 ADD HL, HL			> TIMES 2
C157 11D2C3	0413 LD DE, CMNDTEL			
C15A 19	0414 ADD HL, DE			> + TBL ADDR
C15B 5E	0415 LD E, (HL)			
C15C 23	0416 INC HL			
C15D 56	0417 LD D, (HL)			
C15E EB	0418 EX DE, HL			
C15F FEAD	0419 CP 'M'+CASE			USED IN SUBST & DISPLAY
C161 E9	0420 JP (HL)			
	0421 ;			
	0422 ;			
	0423 ; DISK SELECT			
	0424 ; ENTER WITH E CONTAINING THE DISK NUMBER			
	0425 ;			

C162	0426	DISKSELECT:		
C162 7B	0427	LD	A,E	;DTSK NUMBER
C163 FE04	0428	CP	NDRIVES	;>A THROUGH D ONLY
C165 304E	0429	JR	NC,ERROR	
C167 43	0430	LD	B,E	;>SAVE DISK #
C168 DDE5	0431	PUSH	IX	
C16A E1	0432	POP	HL	;> DISK FLAGS
C16B F6B0	0433	OR	C1 SHL DISKMODE   & C1 SHL MAXI   & E1 SHL FASTSEEK	
C16D 77	0434	LD	(HL),A	;>DISK # & FLAGS
C16E 54	0435	LD	D,H	
C16F 5D	0436	LD	E,L	
C170 13	0437	INC	DE	;> DISK LETTER
C171 78	0438	LD	A,B	
C172 C641	0439	ADD	'A'	
C174 12	0440	LD	(DE),A	;>DISK LETTER
C175 CD19C2	0441	CALL	GCHR	
C178 FE3B	0442	CP	'>'	
C17A 2010	0443	JR	NZ,DS2	
C17C CBEB	0444	RES	FASTSEEK,(HL)	;>NOT FAST SEEK
C17E 13	0445	TNC	DE	
C17F 12	0446	LD	(DE),A	;>PART OF DISKMODE PROMPT
C180 CD19C2	0447	CALL	GCHR	
C183 FE3B	0448	CP	'>'	
C185 2005	0449	JR	NZ,DS2	
C187 CBA6	0450	RES	MAXI,(HL)	;>MINI FLOPPY
C189 13	0451	INC	DE	
C18A 12	0452	LD	(DE),A	
C18B 97	0453	SUB	A	
	0454 ;			
C18C CD29C2	0455	DS2:	CALL	SKSGCR
C18F CBFE	0456	SET	Z,(HL)	;>ALSO EXCCS DE & HL
	0457 ;			;>MARK END-OF-MSG
C191 1A	0458	LD	A,(DE)	;>DISK FLAGS
C192 C03FC0	0459	CALL	DHOME	
C195 3E48	0460	LD	A,'H'	;>IN CASE OF HOME ERROR
	0461 ;			
C197	0462	DERRCK:		
C197 C8	0463	RET	Z	;>IF NO ERROR, DONE
	0464 ;			
C198	0465	PERRMSG:		
C198 CDF7C2	0466	CALL	PMSGFOLLOWING	
C19B 20455252	0467	DB	'ERR', '480H	
A0				
C1A0 CDF1C1	0468	CALL	PCHR	;>ERROR LETTER
C1A3 78	0469	LD	A,B	;>ERROR NUMBER
	0470 ;			
	0471 ;			
	0472 ;	PRINT THE 2 HEX DIGITS IN THE A-REGISTER		
	0473 ;	AND CLEAN STACK.		
	0474 ;			
C1A4	0475	P2HXCLEAN:		
C1A4 CDD4C2	0476	CALL	P2HEX	
C1A7 1810	0477	JR	CLEAN0	
	0478 ;			
	0479 ;			
	0480 ;	PRINT CRLF		
	0481 ;			
C1A7	0482	CRLF:		
C1A9 3E0D	0483	LD	A,CR	
C1AB 1844	0484	JR	PCHR	
	0485 ;			
	0486 ;			

```

0487 ; COMMAND
0488 ; EXAMINE INPUT PORT
0489 ;
C1AD 0490 EXMINPUT:
C1AD CD85C2 0491 CALL L,INCR
C1B0 4B 0492 LD C,E ;PORT #
C1B1 ED78 0493 IN A,(C)
C1B3 18EF 0494 JR P2HXCLEAN ;PRINT THE VALUE, CRLF
0495 ;
0496 ;
0497 ; ERROR & ESCAPE. RETURNS TO CMND WITH SP
0498 ; RE-INITIALIZED.
0499 ;

C1B5 0500 ERROR:
C1B5 CDF7C2 0501 CALL PMSGFOLLOWING
C1B8 BF 0502 DB '?'+80H
C1B9 0503 ESCAPE:
C1B9 0504 CLEANV:
C1B9 C323C1 0505 JP CLEANSTACK
0506 ;
0507 ;
0508 ; GET NEXT SECTOR FOR THE READ & WRITE DISK
0509 ; ROUTINES. PRESERVES HL AND, BEFORE RETURNING,
0510 ; POPS DE AND BC FROM THE STACK.
0511 ;

C1BC 0512 NEXTSC:
C1BC D9 0513 EXX
C1BD E1 0514 POP HL ;RETURN ADDR
C1BE D9 0515 EXX
C1BF D1 0516 POP DE
C1C0 2805 0517 JR Z,NS2 ;SKIP IF NO ERROR
C1C2 15 0518 DEC D ;TRY AGAIN?
C1C3 28D3 0519 JR Z,PERRMSG
C1C5 180A 0520 JR NS4 ;YES, USE OLD MEM PNTR
0521 ;
C1C7 017FFF 0522 NS2: LD BC,-81H ;NO ERROR
C1CA FD09 0523 ADD IY,BC ;BUMP THE INCREMENT
C1CC FD29 0524 INC IY
C1CE E3 0525 EX (SP),HL ;USE LATEST MEM PNTR
C1CF 160A 0526 LD D,10 ;RELOAD RETRIAL COUNTER
0527 ;
C1D1 E1 0528 NS4: POP HL ;MEM PNTR
C1D2 C1 0529 POP BC
C1D3 79 0530 LD A,C ;RELOAD DISK FLAGS
C1D4 D9 0531 EXX
C1D5 E5 0532 PUSH HL ;RETURN ADDR
C1D6 D9 0533 EXX
C1D7 C0 0534 RET NZ ;IF ERROR, DONE
0535 ;
C1D8 D4A2C3 0536 CALL NC,FTRKSC ;IF NEGATIVE, DONE!
C1D8 30DC 0537 JR NC,CLEANV ;PRINT TRK, SEC, CLEAN STK.
0538 ;
C1DD 1C 0539 INC E ;BUMP SECTOR #
C1DE CDAEC3 0540 CALL CHKSECNO
C1E1 D0 0541 RET NC ;DONE IF # OK
C1E2 DB31 0542 IN A,DTRACK ;GET TRACK #
C1E4 3C 0543 INC A ;BUMP IT
C1E5 5F 0544 LD E,A
C1E6 C5 0545 PUSH BC
C1E7 CD29C3 0546 CALL SEEKNXT ;SEEK NEXT TRACK
C1EA C1 0547 POP BC
C1EB 79 0548 LD A,C ;DISK FLAGS

```

C1EC 1E01	0549	LD	E,1	;SECTOR 1
C1EE C9	0550	RET		
	0551 ;			
	0552 ;			
	0553 ; PRINT SPACE. ALTERS A.			
	0554 ;			
C1EF 3E20	0555	SPACE: LD	A,1	;(CONTINUE BELOW)
	0556 ;			
	0557 ;			
	0558 ; PRINT THE CHARACTER IN THE A-REGISTER.			
	0559 ; (CHKS INPUT FOR ESC.) PRESERVES ALL REGS.			
	0560 ;			
C1F1 F5	0561	PCHR:	PUSH AF	;SAVE THE CHAR
C1F2 E67F	0562	PC1:	AND ZFH	
C1F4 FE1B	0563	CP	ESC	
C1F6 28C1	0564	JR	Z,ESCAPE	
C1F8 FE7D	0565	CP	ALT	;ALT MODE?
C1FA 28BD	0566	JR	Z,ESCAPE	
C1FC CDDBC0	0567	CALL	CHKIN	
C1FF 20F1	0568	JR	NZ,PC1	
	0569 ;			
C201 DB00	0570	PC2:	IN A,STAT	
C203 E680	0571	AND	TBE	
C205 28FA	0572	JR	Z,PC2	
C207 F1	0573	POP	AF	
C208 F5	0574	PUSH	AF	
C209 E67F	0575	AND	ZFH	
C20B D301	0576	OUT	DATA,A	
C20D FE0D	0577	CP	CR	
C20F 2006	0578	JR	NZ,PC3	
C211 CDF7C2	0579	CALL	FMSGFOLLOWING	
C214 0A0080	0580	DB	LF,0,80H	
C217 F1	0581	PC3:	POP AF	
C218 C9	0582	RET		
	0583 ;			
	0584 ;			
	0585 ; GET CHARACTER. RETURNS IT IN A.			
	0586 ; ALTERS F.			
	0587 ;			
C219 CDE3C0	0588	GCHR:	CBYTE	
C21C CDF1C1	0589	CALL	PCHR	
C21F FE61	0590	CP	61H	;CONVERT LOWER CASE ;TO UPPER.
C221 D8	0591	RET	C	
C222 D620	0592	SUB	20H	
C224 C9	0593	RET		
	0594 ;			
	0595 ;			
	0596 ; LOADS HL WITH SOURCE ADDR, BC & DE			
	0597 ; WITH THE INCREMENT. ENDS WITH A CRLF.			
	0598 ;			
C225 97	0599	L2NCR0:	SUB A	
	0600 ;			
C226 CD64C2	0601	L2NCR:	CALL LD2N	
	0602 ;			
	0603 ; SKIP INITIAL SPACES.			
	0604 ; IF DELIMITTER NOT A CR, ERROR			
	0605 ;			
C229 CDBBC2	0606	SKGGCR:	CALL SKGG	;WAIT FOR NON-SPACE ;IF NOT CR, ERROR
C22C 2087	0607	JR	NZ,ERROR	
C22E EB	0608	EX	DE,HL	
C22F C9	0609	RET		
	0610 ;			

```

0611 ;
0612 ; PRINT THE NUMBER IN HL, FOLLOWED BY A COLON.
0613 ; PRESERVES ALL REGISTERS EXCEPT A.
0614 ;
C230 CDA9C1 0615 PCADDR: CALL    CRLF
0616 ;
C233 CDCFC2 0617 PADDR:  CALL    PNHL
C236 3E3A   0618 LD     A, ':''
C238 18B7   0619 JR     PCHR
0620 ;
0621 ;
0622 ; COMMAND
0623 ;
C23A CD82C2 0624 VERIF:  CALL    L3NCR           ;GET 3 OPERANDS
0625 ;
0626 ; COMPARES TWO AREAS OF MEMORY. ENTER WITH
0627 ; SOURCE IN HL, DESTINATION IN DE & COUNT
0628 ; IN BC, ALTERS ALL REGISTERS.
0629 ;
C23D 0630 VRFY:
C23D 1A 0631 LD     A, (DE)          ;COMPARE TO SOURCE
C23E EDA1 0632 CPI
C240 2B 0633 DEC    HL
C241 C4CFC2 0634 CALL   NZ,PNHL          ;PRINT SOURCE ADDR
C244 C4C6C2 0635 CALL   NZ,PSNM          ;& CONTENTS
C247 EB   0636 EX    DE,HL
C248 C4C6C2 0637 CALL   NZ,PSNM          ;& DEST CONTENTS
C24B C4CCC2 0638 CALL   NZ,PSNHL         ;& DEST ADDR
C24E C4A9C1 0639 CALL   NZ,CRLF
C251 EB   0640 EX    DE,HL
C252 23  0641 INC    HL
C253 13  0642 INC    DE
C254 E0   0643 RET    PO
C255 18E6 0644 JR     VRFY           ; IF BC=0, DONE.
0645 ;
0646 ; COMMAND
0647 ;
C257 0648 MOVE:
C257 CD82C2 0649 CALL   L3NCR           ;OPERANDS
C25A E5   0650 PUSH   HL
C25B D5   0651 PUSH   DE
C25C C5   0652 PUSH   BC
C25D EDB0 0653 LDIR
C25F C1   0654 POP    BC
C260 D1   0655 POP    DE
C261 E1   0656 POP    HL
C262 18D9 0657 JR     VRFY
0658 ;
0659 ;
0660 ;
0661 ; LOAD TWO NUMBERS. LOADS DE WITH THE BEGINNING
0662 ; ADDR, N1. LOADS BC & HL WITH THE INCREMENT
0663 ; N2-N1+1 (OR WITH NZ IF THE OPR IS 'S').
0664 ; RETURNS WITH LAST DELIMITER IN A.
0665 ;
0666 ;
C264 CD8BC2 0667 LD2N:  CALL   GNHL           ;N1 TO HL, DELIM TO A
C267 EB   0668 EX    DE,HL           ;SAVE N1 IN DE
C268 CDBBC2 0669 CALL   SKSG           ;GET NEXT NON-SPACE
C26B FE53  0670 CP    'S' +CASE        ;SWATH?
C26D 2005  0671 JR     NZ,L2N1
0672 ;

```

C26F CD8AC2	0673	CALL	GNHL0	YES, INCREMENT TO HL.
C272 1807	0674	JR	L2N2	
	0675 ;			
C274 CD8BC2	0676 L2N1:	CALL	GNHL	;INCREMENT
C277 B7	0677	OR	A	;CLEAR CY
C278 ED52	0678	SEC	HL,DE	;N2-N1
C27A 23	0679	INC	HL	;INCLUDE END POINT
C27B 44	0680 L2N2:	LD	B,H	
C27C 4D	0681	LD	C,L	;BC GETS THE INCRM
C27D E5	0682	PUSH	HL	
C27E FDE1	0683	POP	IY	; & SO DOES IY.
C280 C9	0684	RET		
	0685 ;			
	0686 ;			
	0687 ; LOAD 3 OPERANDS, HL GETS THE SOURCE, BC			
	0688 ; THE INCREMENT, AND DE THE 3RD OPERAND.			
	0689 ;			
C281 97	0690 L3NCR0:	SUB	A	
	0691 ;			
C282 CD64C2	0692 L3NCR:	CALL	LD2N	
	0693 ; (CONTINUE BELOW)			
	0694 ;			
	0695 ;			
	0696 ; ENTER WITH SPACE OR THE FIRST DIGIT			
	0697 ; OF A NUMBER IN A. LOADS HL WITH			
	0698 ; WITH A NEW NUMBER & THEN EXCHANGES			
	0699 ; DE & HL. FINISHES WITH A CRLF.			
	0700 ;			
C285 CD8EC2	0701 L1NCR:	CALL	GNHL	;SKIP SPACES, LOAD HL
C288 189F	0702	JR	SKSGCR	;WAIT FOR A CR
	0703 ;			
	0704 ;			
	0705 ; CLEARS HL. IF ENTERED WITH HEX CHAR IN A,			
	0706 ; SHIFTS IT INTO HL. O/W, IGNORES LEADING			
	0707 ; SPACES. FIRST CHAR MUST BE HEX. CONTINUES			
	0708 ; SHIFT UNTIL A NON-HEX CHAR RECEIVED & THEN			
	0709 ; RETURNS WITH THE LATTER IN A.			
	0710 ; PRESERVES B,C,D,E.			
	0711 ;			
	0712 ;			
C28A 97	0713 GNHL0:	SUB	A	
	0714 ;			
C28B C5	0715 GNHL:	PUSH	BC	;SAVE
C28C 210000	0716	LD	HL,0	;CLEAR BUFFER
	0717 ; STRIP LEADING SPACES & GET CHAR			
C28F CD8BC2	0718	CALL	SKSG	
	0719 ; FIRST CHAR MUST BE HEX			
C292 CDA3C2	0720	CALL	HEXSH	;IF HEX, SHIFT INTO HL
C295 DAB5C1	0721	JP	C,ERROR	;O/W, ERROR
C298 CD19C2	0722 GN1:	CALL	GCHR	
C29B CDA3C2	0723	CALL	HEXSH	;IF HEX SHIFT INTO HL
C29E 78	0724	LD	A,B	;RESTORE CHAR
C29F 30F7	0725	JR	NC,GN1	;IF HEX, CONTINUE
C2A1 C1	0726 C	POP	BC	;IF NON-HEX, DONE
C2A2 C9	0727	RET		
	0728 ;			
	0729 ;			
	0730 ; IF A CONTAINS HEX CHAR, SHIFTS BINARY EQUIVALENT			
	0731 ; INTO HL. IF NOT HEX, RET WITH CY SET. SAVES			
	0732 ; ORIGINAL CHAR IN B			
	0733 ;			
C2A3 47	0734 HEXSH:	LD	B,A	

```

C2A4 D630      0735     SUB    '0'          ; < '0'?
C2A6 D8        0736     RET    C
C2A7 C6E9      0737     ADD    '0'-'G'+CASEJ
C2A9 D8        0738     RET    C
C2AA D6FA      0739     SUB    'A'-'G'
C2AC 3003      0740     JR     NC,HX1      ;OK IF >= 'A'
C2AE C607      0741     ADD    C-'A'+CASEJ-C-'9'+1J
C2B0 D8        0742     RET    C
C2B1 C60A      0743 HX1:   ADD    '9'+1-'0'
0744 ; THE A-REG NOW CONTAINS THE HEX DIGIT IN BINARY,
0745 ; (THE HIGH-ORDER NIBBLE OF A IS 0.)
C2B3 29        0746 HXSH4:  ADD    HL,HL      ;SHIFT 4 BITS INTO HL
C2B4 29        0747     ADD    HL,HL
C2B5 29        0748     ADD    HL,HL
C2B6 29        0749     ADD    HL,HL
C2B7 E5        0750     OR     L
C2B8 6F        0751     LD     L,A
C2B9 C9        0752     RET
0753 ;
0754 ;
0755 ; RETURNS WITH A NON-SPACE IN THE A-REG,
0756 ; IF ENTERED WITH A-REG CONTAINING A NULL
0757 ; OR A SPACE, GETS NEW CHARS UNTIL FIRST
0758 ; NON-SPACE OCCURS. ALTERS AF.
0759 ;
C2BA 97        0760 SKSG0:  SUB    A
0761 ;
C2BB E7        0762 SKSG:   OR     A          ;DOES A CONTAIN NULL?
C2BC CC19C2      0763 SK1:    CALL   Z,GCHR
C2BF FE20      0764 CP     20H      ;SPACE?
C2C1 28F9      0765 JR     Z,SK1
C2C3 FE0D      0766 CP     CR
C2C5 C9        0767 RET
0768 ;
0769 ;
0770 ;
0771 ; PRINT SPACE FOLLOWED BY THE NUMBER POINTED
0772 ; TO BY HL. ALTERS A ONLY.
0773 ;
C2C6 CDEF01      0774 PSNM:   CALL   SPACE
0775 ; (CONTINUE BELOW)
0776 ;
0777 ; PRINTS THE NUMBER POINTED TO BY HL,
0778 ; PRESERVES ALL REGISTERS BUT A.
0779 ;
C2C9 7E        0780 PNM:   LD     A,(HL)
C2CA 1808      0781     JR     P2HEX
0782 ;
0783 ;
0784 ;
0785 ; PRINT THE NUMBER IN HL,
0786 ; PRESERVES ALL BUT A.
0787 ;
C2CC CDEF01      0788 PSNHL:  CALL   SPACE
0789 ;
C2CF 7C        0790 PNHL:  LD     A,H
C2D0 CDD4C2      0791     C     CALL   P2HEX
C2D3 70        0792     LD     A,L
0793 ;           ;(CONTINUE BELOW)
0794 ;
0795 ; PRINT THE NUMBER IN THE A-REGISTER,
0796 ; PRESERVES ALL REGISTERS.

```

	0797 ;			
C2D4 CDD8C2	0798 P2HEX:	CALL	P1HEX	
C2D7 1F	0799	RRA		
C2D8 1F	0800 P1HEX:	RRA		
C2D9 1F	0801	RRA		
C2DA 1F	0802	RRA		
C2DB 1F	0803	RRA		
C2DC F5	0804	PUSH	AF	
C2DD E60F	0805	AND	0FH	;MASK
C2DF FE0A	0806	CP	10D	; <= 9?
C2E1 3802	0807	JR	C,PH1	
C2E3 C607	0808	ADD	Z	;A THRU F
C2E5 C630	0809 PH1:	ADD	30H	;ASCII BIAS
C2E7 CDF1C1	0810	CALL	PCHR	;PRINT IT
C2EA F1	0811	POP	AF	
C2EB C9	0812	RET		
	0813 ;			
	0814 ;			
	0815 ; PRINT MESSAGE. ENTER WITH ADDR OF MSG			
	0816 ; IN HL. THE MESSAGE IS TERMINATED			
	0817 ; AFTER PRINTING A CHARACTER WHOSE			
	0818 ; PARITY BIT WAS SET.			
	0819 ; PRESERVES FLAGS, INCREMENTS HL.			
	0820 ;			
	0821 ;			
	0822 ;			
C2EC F5	0823 PMSG:	PUSH	AF	;SAVE
C2ED 7E	0824 PS1:	LD	A,(HL)	
C2EE 23	0825	INC	HL	
C2EF CDF1C1	0826	CALL	PCHR	
C2F2 17	0827	RLA		;LAST CHARACTER?
C2F3 30F8	0828	JR	NC,PS1	;IF NOT, LOOP
C2F5 F1	0829	POP	AF	
C2F6 C9	0830	RET		
	0831 ;			
	0832 ;			
	0833 ; PRINTS THE MESSAGE FOLLOWING THE CALL			
	0834 ; TO THIS ROUTINE.			
	0835 ; PRESERVES ALL REGISTERS			
	0836 ;			
C2F7	0837 PMSGFOLLOWING:			
C2F7 E3	0838	EX	(SP),HL	
C2F8 CDECC2	0839	CALL	PMSG	
C2FB E3	0840	EX	(SP),HL	
C2FC C9	0841	RET		
	0842 ;			
	0843 ;			
	0844 ; COMMAND			
	0845 ;			
	0846 ; GO <ADDR>			
	0847 ; EXECUTION BEGINS AT ADDR.			
	0848 ;			
C2FD	0849 GO:			
C2FD E1	0850	POP	HL	;CLEAN STACK
C2FE CD85C2	0851	CALL	L1NCR	;GET ADDR
C301 EB	0852	EX	DE,HL	
C302 E9	0853	JP	(HL)	
	0854 ;			
	0855 ;			
	0856 ; COMMAND. DISPLAY MEMORY.			
	0857 ;			
	0858 ; DM <STARTING ADDR> <ENDING ADDR OR SWATH>			

C303	0859 ;			
C303 2036	0860 DSFM:	JR	NZ,ERRORV	;IF NOT 'M', ERROR
C305 CD25C2	0861 CALL	L2NCR0		;GET OPERANDS
C308 1610	0862 DSFM1:	LD	D,16	;BYTE COUNT
C30A CD30C2	0863	CALL	PCADDR	;ADDRESS
C30D CDC6C2	0864 DM2:	CALL	PSNM	;MEM CONTENTS
C310 EDA1	0865	CPI		;INC HL & DEC BC
C312 E2A9C1	0866 JP	PO,CRLF		
C315 15	0867 DEC	D		
C316 28F0	0868 JR	Z,DSFM1		
C318 7A	0869 LD	A,D		
C319 E403	0870 AND	3		
C31B CCEFC1	0871 CALL	Z,SPACE		
C31E 18ED	0872 JR	DM2		
	0873			
	0874 ;			
	0875 ;			
C320	0876 SHANDLER:			
C320 281C	0877 JR	Z,SUBSM		;IF 'M', SUBSM
	0878 ;			
	0879 ;			
	0880 ; DISK SEEK			
	0881 ;			
C322	0882 SEEKR:			
C322 CB69	0883 BJT	DISKMODE,C		
C324 2815	0884 JR	Z,ERRORV		
C326 CD85C2	0885 CALL	L1NCR		;E = TRACK #
C329	0886 SEEKNXT:			
C329 3E4C	0887 LD	A,76		;MAX TRACK #, MAXI DISK
C32B 1627	0888 LD	D,39		;MAX TRACK #, MINT DISK
C32D CDB2C3	0889 CALL	CHKNO		;CHECK #
C330 3809	0890 JR	C,ERRORV		
C332 53	0891 LD	D,E		;TRACK #
C333 CD54C0	0892 CALL	DSEEK		
C336 3E53	0893 LD	A,'S'		;IN CASE OF SEEK ERROR
	0894 ;			
C338 C397C1	0895 DERCKV: JP	DERRCK		;DISK ERROR CHECK
	0896 ;			
	0897 ;			
C33B C3B5C1	0898 ERRORV: JP	ERROR		
	0899 ;			
	0900 ;			
	0901 ; COMMAND. SUBSTITUTE MEMORY LOCATION.			
	0902 ;			
	0903 ; SM <ADDR>			
	0904 ;			
C33E	0905 SUBSM:			
C33E 97	0906 SUB	A		
C33F CD85C2	0907 CALL	L1NCR		
C342 EB	0908 EX	DE,HL		;HL GETS ADDR
C343 CC30C2	0909 SM1:	CALL	Z,PCADDR	
C346 CCEFC1	0910 CALL	Z,SPACE		
	0911 ; PRINT CURRENT VALUE, REQUEST NEW VALUE &			
	0912 ; PRINT IT IF GIVEN			
C349 CDC9C2	0913 CALL	PNM		;PRINT (HL)
C34C CDF7C2	0914 CALL	PMMSGFOLLOWING		
C34F AE	0915 DB	'+'+80H		;THE PROMPT
C350 CD19C2	0916 CALL	GCHR		
C353 FE2F	0917 CP	'+'+1		;IF <= '+',
C355 DCF1C1	0918 CALL	C,FCHR		;NO SUBSTITUTION.
C358 3806	0919 JR	C,SM2		
C35A EE	0920 EX	DE,HL		

C35B CD8BC2	0921	CALL	GNHL	GET NEW VALUE
C35E EB	0922	EX	DE, HL	
C35F 73	0923	LD	(HL), E	
C360 FE0D	0924	SM2:	CP	CR
C362 C4EFC1	0925	CALL	NZ, SPACE	
	0926 ;			
C365 C8	0927	RET	Z	; IF CR, DONE.
C366 23	0928	INC	HL	
C367 9E07	0929	LD	A, Z	; PRINT ADDRESS IF IT
C369 A5	0930	AND	L	IS A MULTIPLE OF 8
C36A 18D7	0931	JR	SM1	
	0932 ;			
	0933 ;			
C36C	0934	RHANDLER:		
C36C FE44	0935	CP	'D' + CASE	
C36E 20CB	0936	JR	NZ, ERRORV	
(	0937 ;			
	0938 ; READ DISK			
	0939 ;			
C370	0940	READDR:		
C370 CD94C3	0941	CALL	SECSETUP	
C373 C5	0942	RD2:	PUSH BC	
C374 E5	0943	PUSH	HL	
C375 D5	0944	PUSH	DE	
C376 CD8CC0	0945	CALL	DREAD	
C379 3E52	0946	LD	A, 'R'	; IN CASE OF READ ERROR
C37B CDBCC1	0947	CALL	NEXTSC	; NEXT SECTOR EPOPS STK, J
C37E 18F3	0948	JR	RD2	
	0949 ;			
	0950 ;			
C380	0951	WHANDLER:		
C380 FE44	0952	CP	'D' + CASE	
C382 20B7	0953	JR	NZ, ERRORV	
	0954 ;			
	0955 ; WRITE DISK			
	0956 ;			
C384	0957	WRITDR:		
C384 CD94C3	0958	CALL	SECSETUP	
C387 C5	0959	WD2:	PUSH BC	
C388 E5	0960	PUSH	HL	
C389 D5	0961	PUSH	DE	
C38A CDA1C0	0962	CALL	DWRITE	
C38D 3E57	0963	LD	A, 'W'	; IN CASE OF WRITE ERROR
C38F CDBCC1	0964	CALL	NEXTSC	; EPOPS STACK J
C392 18F3	0965	JR	WD2	
	0966 ;			
	0967 ;			
	0968 ; GET MEMORY ADDRESS, SECTOR # AND CHECK IT,			
	0969 ; AND LOAD B & C.			
	0970 ;			
C394	0971	SECSETUP:		
C394 CB69	0972	BIT	DISKMODE, C	
C395 28A3	0973	JR	Z, ERRORV	
C398 C5	0974	PUSH	BC	
C399 CD81C2	0975	CALL	L3NCR0	; BUFFER ADDRS & SEC #
C39C C1	0976	POP	BC	
C39D CDAEC3	0977	CALL	CHKSECNO	
C3A0 3899	0978	JR	C, ERRORV	
	0979 ;			
	0980 ;			
	0981 ; PRINT TRACK & SECTOR #'S			
	0982 ;			

C3A2	0983	PTRKSC:		
C3A2 DB31	0984	IN	A,DTRACK	
C3A4 57	0985	LD	D,A	
C3A5 EB	0986	EX	DE,HL	
C3A6 CDCCC2	0987	CALL	PSNHL	;PRINT TRK & SEC
C3A9 EB	0988	EX	DE,HL	
C3AA 79	0989	LD	A,C	;DISK FLAGS
C3AB 160A	0990	LD	D,10	;# OF RETRIALS
C3AD C9	0991	RET		
	0992 ;			
	0993 ;			
C3AE	0994	CHKSECNO:		
C3AE 3E1A	0995	LD	A,26	;MAX SEC #, MAXI DISK
C3B0 1612	0996	LD	D,18	;MAX SEC #, MINI DISK
	0997 ;			
	0998 ;			
C3B2	0999	CHKNO:		
C3B2 CB61	1000	BIT	MAXI,C	
C3B4 2001	1001	JR	NZ,CN2	
C3B6 7A	1002	LD	A,D	
C3B7 BB	1003	CN2:	CP	E
C3B8 D8	1004	RET	C	
C3B9 79	1005	LD	A,C	
C3BA E603	1006	AND	NDRIVES-1	
C3BC 47	1007	LD	B,A	;DISK #
C3BD 79	1008	LD	A,C	;DISK FLAGS
C3BE C9	1009	RET		
	1010 ;			
	1011 ;			
	1012 ; COMMAND			
	1013 ; OUT <DATA-BYTE> <PORT NNUMBER>			
	1014 ;			
C3BF CD8BC2	1015	OUTP:	CALL	GNHL
C3C2 EB	1016	EX	DE,HL	;E GETS DATA
C3C3 CD85C2	1017	CALL.	L1NCR	;GET PORT NUMBER
	1018 ;			
C3C6 4B	1019	LD	C,E	; TO C
C3C7 ED69	1020	OUT	(C),L	
C3C9 C9	1021	RET		
	1022 ;			
	1023 ;			
	1024 ; BAUD RATES:			
	1025 ; 19200, 9600, 4800, 2400, 1200, 300, 150, 110,			
	1026 ;			
	1027 ;			
C3CA 90C0A090	1028	BAUDRS:	DB	90H,0C0H,0A0H,90H,08H,84H,82H,1
68848201				
	1029 ;			
	1030 ;			
C3D2	1031	CMNDTBL:		
C3D2 B5C1	1032	DW	ERROR	;A
C3D4 15C0	1033	DW	BOOTMC	;BOOT CDDOS
C3D6 B5C1	1034	DW	ERROR	;C
C3D8 03C3	1035	DW	DSPM	;DISPLAY MEMORY
C3DA ADC1	1036	DW	EXMINPUT	;EXAMINE INPUT PORT
C3DC B5C1	1037	DW	ERROR	;F
C3DE FDC2	1038	DW	GO	;GO ETTRANSFER OF CONTROL ]
C3E0 B5C1	1039	DW	ERROR	;H
C3E2 EBC0	1040	DW	INITBR	;INITIALIZE BAUD RATE
C3E4 B5C1	1041	DW	ERROR	;J
C3E6 06C1	1042	DW	KICKSTK	;KICK SYSTEM STACK
C3E8 B5C1	1043	DW	ERROR	;L

C3EA 57C2	1044	DW	MOVE	MOVE A BLOCK OF MEMORY
C3EC B5C1	1045	DW	ERROR	IN
C3EE BFC3	1046	DW	OUTP	OUTPUT
C3F0 B5C1	1047	DW	ERROR	IP
C3F2 B5C1	1048	DW	ERROR	IQ
C3F4 6CC3	1049	DW	RHANDLER	READ DISK
C3F6 20C3	1050	DW	SHANDLER	SUBSTITUTE MEM SEEK TRACK
C3FB B5C1	1051	DW	ERROR	IT
C3FA B5C1	1052	DW	ERROR	IU
C3FC 3AC2	1053	DW	VERIF	VERIFY BLOCKS OF MEMORY
C3FE 80C3	1054	DW	WHANDLER	WRITER DISK
	1055 ;			
	1056 ;			
(C3FF)	1057	LASTBYTE: EQU	\$-1	
	1058 ;			

0000 ERRORS

## CROMEMCO CDOS Z80 ASSEMBLER V.1.4A

## SYMBOL TABLE

ALT	007D	BAUD	0000 .	BAUDRS	C3CA	BOOTDK	C018
BOOTMC	C015	BOOTSW	0040	BOT200	C01C	BOT300	C024
BOT500	C03A	CASE	0000	CHKIN	C0DB	CHKNO	C3B2
CHKSEC	C3AE	CLEANS	C123	CLEANV	C189	CM6	C143
CMND	C128	CMNDTB	C3D2	CN2	C3B7	COMMND	0002
CR	000D	CRLF	C1A9	DATA	0001	DAV	0040
DCOMMN	0030	DCONTR	0034	DDATA	0033	DERCKV	C338
DERRCK	C197	DFLAGS	0034	DHOME	C03F	DISKMO	0005
DTSKSE	C162	DM2	C30D	DRD250	C095	DREAD	C08C
DS2	C18C	DSEC	0032	DSEEK	C054	DSK500	C076
DSK540	C07F	DSPM	C303	DSPM1	C308	DSTAT	0030
DTRACK	0031	DWR250	C0AA	DWRITE	C0A1	EREXIT	C071
ERROR	C1B5	ERRORV	C33B	ESC	001B	ESCAPE	C1B9
EXCCCHK	C06C	EXECUT	C06A	EXMINF	C1A0	FASTSE	0007
GBYTE	C0E3	GCHR	C219	GN1	C298	GNHL	C28B
GNHL0	C28A	GO	C2FD	HOLDM	0020	HEXSH	C2A3
HX1	C2B1	HXSH4	C2B3	IMASK	0003	INITBA	C0EE
INITBR	C0EB	IT1	C0F5	KICKST	C104	L1NCR	C285
L2N1	C274	L2N2	C27B	L2NCR	C226	L2NCR0	C225
L3NCR	C282	L3NCR0	C281	LASTBY	C3FF	LD2N	C264
LF	000A	LOADIX	C11E	MAXI	0004	MAXIM	0010
MONITR	C10B	MOVE	C257	NDRIVE	0004	NEXTSC	C1BC
NS2	C1C7	NS4	C1D1	OUTP	C3EF	P1HEX	C2D8
P2HEX	C2D4	P2HXCL	C1A4	PADDR	C233	PARREL	0004
PC1	C1F2	PC2	C201	PC3	C217	PCADDR	C230
PCHR	C1F1	PERRMS	C193	PH1	C2E5	PMSG	C2EC
PMSGFO	C2F7	PNHL	C2C6	PNM	C2C9	PS1	C2ED
PSNHL	C2CC	PSNM	C2C6	PTRKSC	C3A2	RD2	C3Z3
READDR	C370	RHANDL	C36C	SECSET	C394	SEEKNX	C329
SEEKR	C3Z2	SEL300	C0D1	SELECT	C0CB	SETUP	C0B6
SHANDL	C320	SK1	C2BC	SKSG	C2BF	SKSG0	C2B4
SKSGCR	C229	SM1	C343	SM2	C360	SPACE	C1EF
STACK	007C	START	C000	STAT	0000	SUBSM	C33E
TBE	0080	VERIF	C23A	VRFY	C23D	WD2	C387
WHANDL	C380	WRITDR	C384				

## CROMEMCO CROSS REFERENCE LISTING V.1.0 FOR FILE RDOS

ALT	0055	0565
BAUD	0037	0340
BAUDRS	1028	0339
BOOTDK	0082	0069
BOOTMC	0076	1033
BOOTSW	0039	0068
BOT200	0085	0087
BOT300	0020	0105
BOT500	0103	0076
CASE	0050	0419 0670 0737 0741 0935 0952
CHKIN	0307	0316 0567
CHKNO	0999	0889
CHKSEC	0994	0510 0277
CLEANS	0378	0505
CLEANV	0504	0477 0537
CM6	0401	0397
CMND	0386	0386
CMNDTB	1031	0413
CN2	1003	1001
COMMND	0046	0342
CR	0052	0346 0370 0370 0483 0577 0766 0924
CRLF	0482	0335 0315 0639 0367
DATA	0045	0310 0576
DAV	0047	0303
DCOMMN	0029	0084 0162 0208 0235
DCONTR	0033	0120 0149 0270
DDATA	0031	0300
DERCKU	0395	
DERRCK	0462	0895
DFLAGS	0032	0067 0165 0209 0236 0267
DHOME	0119	0095 0459
DISKMO	0023	0390 0433 0803 0972
DISKSE	0426	0410
DM2	0865	0873
DRD250	0209	0213
DREAD	0203	0101 0945
DS2	0455	0443 0449
DSEC	0030	0263
DSEEK	0147	0892
DSK500	0175	0154
DSK540	0179	0181
DSFM	0860	1035
DSFM1	0863	0869
DSTAT	0028	0035 0169
DTRACK	0034	0542 0984
DWR250	0236	0240
DWRITE	0231	0962
EREEXIT	0168	0211 0238
ERROR	0500	0402 0404 0429 0607 0721 0898 1032 1034 1037 1039 1041 1043 1045 1047 1048 1051 1052
ERRORV	0898	0861 0884 0890 0936 0953 0973 0978
ESC	0054	0563
ESCAPE	0503	0564 0566
EXCCCHK	0164	0167 0214 0241
EXECUT	0161	0126 0128 0157 0178
EXMINP	0490	1036
FASTSE	0022	0433 0444

GBYTE	0316	0317	0344	0345	0589			
GCHR	0538	0441	0442	0722	0733	0916		
GN1	0722	0725						
GNHL	0715	0667	0676	0701	0921	1015		
GNHL 0	0713	0673						
GO	0849	1038						
HDLDL	0041	0268						
HEXSH	0734	0720	0723					
HX1	0743	0740						
HXSH4	0746							
IMASK	0036	0066						
INITBA	0339	0054						
INITBR	0325	1040						
IT1	0342	0348						
KICKST	0355	1042						
L1NCR	0701	0356	0491	0851	0885	0907	1017	
L2N1	0676	0671						
L2N2	0680	0674						
L2NCR	0601							
L2NCR0	0599	0862						
L3NCR	0692	0624	0649					
L3NCR0	0690	0975						
LASTBY	1057							
LD2N	0667	0601	0692					
LF	0053	0580						
LOADIX	0372	0357						
MAXI	0024	0039	0104	0133	0450	1000		
MAXIM	0040	0122	0155	0291				
MONITR	0368	0070						
MOVE	0648	1044						
NDRIVE	0018	0428	1006					
NEXTSC	0512	0947	0964					
NS2	0522	0517						
NS4	0528	0520						
OUTP	1015	1046						
P1HEX	0800	0798						
P2HEX	0793	0476	0781	0791				
P2HXCL	0475	0494						
PADDR	0617							
PARREL	0038	0124	0176	0179	0183			
PC1	0562	0568						
PC2	0570	0572						
PC3	0581	0578						
PCADDR	0615	0864	0909					
PCHR	0561	0433	0484	0589	0612	0810	0826	0918
PERRMS	0465	0519						
PH1	0809	0807						
PMSG	0823	0322	0332					
PMSGFO	0837	0369	0393	0466	0501	0579	0914	
PNHL	0790	0617	0634					
PNM	0780	0913						
PS1	0824	0828						
PSNHL	0788	0638	0987					
PSNM	0774	0635	0637	0865				
PTRKSC	0983	0536						
RD2	0942	0948						
READDR	0940							
RHANDL	0934	1049						
SECSET	0971	0941	0953					
SEEKNX	0836	0546						
SEEKR	0882							
SEL300	0226	0297						

SELECT	0291	0119	0148	0259		
SETUP	0258	0203	0231			
SHANDL	0876	1050				
SK1	0763	0765				
SKSG	0762	0606	0669	0718		
SKSG0	0760	0396	0408			
SKSGCR	0606	0077	0326	0455	0702	
SM1	0909	0931				
SM2	0924	0919				
SPACE	0555	0774	0788	0872	0910	0925
STACK	0008	0060				
START	0060					
STAT	0044	0307	0570			
SUBSM	0905	0877				
TBE	0048	0571				
VERIF	0624	1053				
VRFY	0630	0644	0657			
WD2	0959	0955				
WHANDL	0951	1054				
WRITDR	0257					