
Edison Controls Bus
Edison Ready
Diagnostic LED
Edison Monitors Bus
Edison Active
8 bits Data to from S100 Bus to Edison or INTA VECTOR FROM S100 Bus
Data IN Bus to Edison
8 Bits to S100 Bus From Edison
8 Bits from Data Out S100 Bus To Edison
Atmel JTAG-A Socket
Rocktwell JTAG Socket
Oscillator 16MHz
Edison Breakout Board Connectors (14x4)
Data IN Bus
Data OUT Bus
Card Ejector Mounting Holes
Pololu S9xit 2.5 Amp Regulator (Optional)
5V Edison Power Supply Pin for Edison J25
Chip connections are under U12
Chip connections are under U11
Chip connections are under U18
Chip connections are under U20
Chip connections are under U23
Note Chip is placed with Pin 1 on Lower RHS
LOW for To S100 Bus Control HIGH for Bus Monitoring
LOW for Bus Monitoring
(1.8V Supply from Edison)
S100Computers.com
Files s100 Edison Board.sch
Sheet: /
Title: Raspberry PI Module Board.sch
Size: User | Date: 2 Jun 2017 | Rev: V1.0
KiCad E.D.A. eeschema (2013-07-07 BZR 4022)-stable | Id: 1/1