| TITLE ASSEMBLY, PCB DATA AND INTERFACE | | | DWG NO. 200263-002 | | REV SHEET 1 OF | |
|--|---------------------------|-------|-----------------------|------|--------------------|--|
| } | MODEL 270 DOUBLE DENSITY | | PERSCI, I | | | |
| ITEM NO. | | | DWG NO. | QTY | | |
| NO. | USE BASIC BD 200263-000 | | DWG NO. | 1011 | REMARKS | |
| | LATEST REVISION AND | | | | | |
| | ADD THE FOLLOWING: | | | | | |
| | | | | | | |
| 1 | IC | 74193 | 150614 | 2 | U16,27 | |
| 2 | | | | | | |
| 3 | CAPACITOR, TANTL., 10% | 0.1UF | 150100-104 | 1 | C36 | |
| 4 | CAPACITOR, TANTL., 10% | 1UF | 150100-105 | 2 | C40,41 | |
| 5 | | | | | | |
| 6 | RESISTOR, ¼ W., 5% | 11K | 150000-113 | 2 | R88,94 | |
| 7 | | | | | | |
| 8 | WIRE, INSULATED AWG 24 | | | A/R | JUMPER FROM A TO E | |
| | | | | | JUMPER FROM D TO E | |
| | | | | | JUMPER FROM F TO (| |
| | | | | | JUMPER FROM H TO 3 | |
| | | | | | JUMPER FROM M TO F | |
| | | | | | JUMPER FROM R TO S | |
| | | | | | JUMPER FROM W TO Y | |
| | | | | | JUMPER FROM AA TO | |
| | | | | | JUMPER FROM AD TO | |
| | | | | | JUMPER FROM AH TO | |
| | | | | | JUMPER FROM AL TO | |
| | | | | | JUMPER FROM AT TO | |
| | | | | | JUMPER FROM AV TO | |
| | | | | | JUMPER FROM BA TO | |
| | | | | | JUMPER FROM BD TO | |
| | | | | | JUMPER FROM BH TO | |
| | | | | | JUMPER FROM BK TO | |
| | | | | | SECTOR "O" JUMPER | |
| | NOTE: JUMPER POINTS NOT L | ISTED | | - | SECTOR "1" JUMPER | |
| | ARE OPEN (NOT USED) | | | | CHASSIS GND W1 | |