| 2 × | PE | RSCI INC | | | MA | TER | IAL | LIST | |
|--------------------------|-------------|-----------------------|--------------|------------------------|---------|------------------------------|------------------|----------------|-----------------|
| | TITLE | ASSY., PCB DATA & INT | | | | M/L NO. REV 200263-046. A | | | |
| | 1 / | LED BY: DATE CHECKED | BY: DATE | APPROVED M. R. COOL | 3/5/80 | E RE | LEASE/ /27/80 | CHANGE DATE (| DRN 80 |
| 70. 200263-016 | NEXT / | 200131 | 1ST USED ON | 277. | DWG SI | ZE | SHEET O | | 2 |
| 0263 | ITEM NO. | DRAWING TITLE | | DWG I | ٧٥. | QTY | CODE | REMARKS | |
| | | USE BASIC BD 200263-0 | 00 LATEST | | | | | | |
| 1/W | | REVISION AND ADD THE | FOLLOWING: | | | | | | |
| | | | | | | | | | |
| | 1 | | | | | | | | |
| | 2 | · | | | | | | | |
| | 3 | | | | | | | | |
| | 4 | CAPACITOR, TANTL, 10% | 0.1UF | 150100- | 104 | 3 | | C40, 41, 36 | |
| | 5 | | | | | | | | |
| | 6 | RESISTOR, & W., 5% | 36K | 150000- | 363 | 2 | | R88, 94 | |
| . . | 7 | MODULE, SELECT | | 200288- | 005 | 1 | | ווט | |
| | 8 | WIRE, INSULATED, AWG | 24 | | | A/R | | JUMPER FROM A | (TO B |
| | | · | | | | | | JUMPER FROM J | TO Z |
| | | · | | | | | | JUMPER FROM K | (TO L |
| | | | | | | | | JUMPER FROM U | TO V |
| | | | | | | | | JUMPER FROM W | 1 TO X |
| | | | | | | | <u> </u> | JUMPER FROM A | |
| | | | | | | | | JUMPER FROM P | |
| | | | | | | | ļ. <u>.</u> | JUMPER FROM AL | TO A |
| | | | | | | | ļ | JUMPER FROM AN | 1 TO A |
| | | | | | | | ļ | JUMPER FROM AF | |
| | | | | | | | | JUMPER FROM AY | / TO A |
| | | | | | | | <u> </u> | JUMPER FROM A | / TO A |
| | | | | | | | - | JUMPER FROM BA | |
| • | - | | | | | | | JUMPER FROM BE | 2 OT C |
| | | | | | | | | JUMPER FROM BI | |
| | | | | | | | | CHASSIS GND W | |
| | | NOTE: JUMPER POINTS | NOT LISTED A | RE OPEN (N | OT USED |) | | | |

| Ø . | PE | RSCI INC | | MA | TER | IAL | LIST | | |
|------------|----------------------|--------------------|--------------------------------|--|----------------|-----------|--|-------------|---|
| | TITLE | ASSY. PCB DATA & I | M/L NO. 200263-016 | | | | | REV | |
| 016 | LIEUE | | nfallo | PPROVED BY: DATE RELEASE, M & QUEEN 3/5/80 | | | | DRI 80 | |
| 263- | NEXT ASSY. 200131 | | IST USED ON | 277 | 277 DWG SI | | SHEET | OF _ | 2 |
| 200263-016 | ITEM NO. | DRAWING | TITLE | DWG | NO. | QTY | CODE | REMARK | 5 |
| | | | | | · | | | | |
| | | | | | | ļ | | | |
| | | | | | | | | | |
| | | REWORK DATA | INTEDEAC | E PCP | | | | | |
| | | RENORK DATA | INILATAL | = [[] | | | + | | |
| | | | | V | | | + | | |
| | | | 0 | | | | <u></u> | | |
| | | : - | 000 | § ' / | CUT | TD 3 | <u>. </u> | | |
| | | | | Ŏ \ | CUT - HE | TRA RE | | | |
| | | | | T 11 | ETWE | ENU | 45-13 | | |
| | | ADD ——— JUMPER | | \mathscr{K} | & U4 | 1-8 | _ | | |
| | | U45-12 | | | | | | | |
| | | TO U45-13 | | | | | + | | |
| | | | | 1 | ··· | | + | | |
| | | | | - | | - | | | |
| | | | | | | | | | |
| | | i · | | | | | <u> </u> | | |
| | | | | | | | T | | |
| | | DELETE - | | ADD | | | I | | |
| | | | | | | | | | |
| | | 3 04100 | 13 145 | | | | 1 | | |
| | | | 12 7408 |) — | | | | · | · |
| | | | | | | | | | |
| - | | | | | | | , | | |
| | Li | | the second state of the second | eccentry M | /1 14 M | <u> </u> | | | |