



NOTES:

- UNLESS OTHERWISE SPECIFIED:
- 1. ALL RESISTORS ARE 1/2 W, 5%.
- 2. RESISTOR R1, R7, R11 AND R19 ARE 1/4 W, 5%, R12 *W, 5%.
- 3. ALL CAPACITORS ARE 0.1 MFD, 12V.
- 4. CAPACITOR C1, 100 MFD, 20V, CAPACITOR C2, 22 MFD, 15V.
- 5. ALL DIODES ARE IN4001.
- 6. J1-1 "POWER GND"
- 7. J2-1 "LOGIC GND"
- 8. PROVISIONS MADE ON PC LAYOUT FOR IN4001 DIODES MAY BE LEFT OUT IF TRANSISTOR TYPES 2N6041 & 2N6044 ARE USED.
- 9. THIS SCHEMATIC VALID FOR ASSY REV "A" PCN 0660
- 10. DESIGNATES COMPONENTS ARE NOT USED.

LAST USED
C6, R19, CR6, F1,
U5

J	K	REVISIONS AND IN CHARGE	DATE	Qume
G	H	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	1-25-77	
E	F	LINEAR RESISTOR	6/23/77	SCHEMATIC - SPRINT MICRO 3 AUX. PAPERFEED BOARD.
C	D	ANGULAR	F5	
A	B	MATERIAL SEE B/M 90702	4/21/77	SCALE 2X
REVISED		HEAT TREAT	4/24/77	SHEET 2
FIRST USED		FINISH		TOTAL 2
QUME STANDARD CA FORM 50-1 (MARCH 74)			PROPERTY INFORMATION: QUANTITY NUMBER ENCLOSURE OR USE PREVIOUS EDITIONS	90700 B

8-27