



**System Fact Sheet**

**SYSTEM**

**Introduced:** May 1995  
**Discontinued:** May 1996  
**Gestalt ID:** 67  
**Form Factor:** PM 9500  
**Weight (lbs.):** 28  
**Dimensions (inches):** 16.9 H x 7.7 W x 15.75 D

**POWER**

**Max. Watts:** 225  
**Amps:** 9.00  
**BTU Per Hour:** 769.5  
**Voltage Range:** 100-125/200-240  
**Freq'y Range (Hz):** 50-60  
**Battery Type:** 3.6V lithium  
 **Soft Power**  
 **Monitor Power Outlet**

**PORTS**

**ADB:** 1  
**Video:** none  
**Floppy:** none  
**SCSI:** DB-25  
**GeoPort Connectors:** 2  
**Ethernet:** AAUI, 10baseT  
**Microphone Port Type:** PlainTalk

**Printer**  
 **Modem**

**Speaker**  
 **Headphone**  
 **Remote Control**

**VIDEO** **Built-in Display:** none

**VRAM Speed:** n/a **VRAM Needed:** on-card module **Video Configuration:** video card (2MB) video card (4MB)

		<i>Maximum Color Bit-depth<sup>1</sup> At:</i>									
		512	640	640	640	800	832	1024	1152	1280	
<b>VRAM Speed:</b>	<b>VRAM Needed:</b>	x384	x400	x480	x870 <sup>2</sup>	x600	x624	x768	x870	x1024	
n/a	on-card module	n/a	n/a	24	8	24	24	16	16	8	
		n/a	n/a	24	8	24	24	24	24	16	

<sup>1</sup> 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions  
<sup>2</sup> The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.  
*A video card ships bundled with this system.*

**LOGIC BOARD**

**Main Processor:** 604, 120 MHz  
**PMMU:** integrated  
**FPU:** integrated  
**Data Path:** 64-bit, 40 MHz  
**L1 Cache:** 32K  
**L2 Cache:** 512K  
**Secondary Processor:** opt. PC Compatibility Card  
**Slots:** 6 PCI

*One PCI slot occupied by video card.*

**MEMORY**

**Memory on Logic Board:** none  
**Minimum RAM:** 16MB  
**Maximum RAM:** 768MB  
**RAM Slots:** 12 168-pin  
**Minimum RAM Speed:** 70 ns  
**RAM Sizes:** 8, 16, 32, 64MB  
**Install in Groups of:** 1

*128MB DIMMs can be used, but have not been tested. Two identical DIMMs installed in corresponding slots may result in increased performance.*

**SOFTWARE**  **Speech Recognition Supported**

**Addressing Modes:** 32-bit  
**Original SSW:** 7.5.2  
**Original Enabler:** System Enabler 701 v1.0

**ROM ID:** \$077D  
**ROM Version:** \$28  
**ROM Size:** 4MB  
**AppleTalk Version:** 60.0.0

*Maximum memory supported by System 7.5.2 is 1GB.*

**Supported Macintosh System Software:**

<input type="checkbox"/> <1.0	<input type="checkbox"/> 6.0	<input type="checkbox"/> 6.0.8	<input type="checkbox"/> 7.1P2	<input type="checkbox"/> 7.1.2
<input type="checkbox"/> 1.0	<input type="checkbox"/> 6.0.1	<input type="checkbox"/> 7.0	<input type="checkbox"/> 7.1P3	<input type="checkbox"/> 7.5
<input type="checkbox"/> 1.1	<input type="checkbox"/> 6.0.2	<input type="checkbox"/> 7.0.1	<input type="checkbox"/> 7.1P5	<input type="checkbox"/> 7.5.1
<input type="checkbox"/> 2.0	<input type="checkbox"/> 6.0.3	<input type="checkbox"/> 7.0.1P	<input type="checkbox"/> 7.1P6	<input checked="" type="checkbox"/> 7.5.2
<input type="checkbox"/> 2.0.1	<input type="checkbox"/> 6.0.4	<input type="checkbox"/> 7.1	<input type="checkbox"/> 7.1.1 (Pro)	<input checked="" type="checkbox"/> 7.5.3
<input type="checkbox"/> 5.0	<input type="checkbox"/> 6.0.5	<input type="checkbox"/> 7.1P	<input type="checkbox"/> 7.1.1	<input checked="" type="checkbox"/> 7.5.5
<input type="checkbox"/> 5.1	<input type="checkbox"/> 6.0.7	<input type="checkbox"/> 7.1P1	<input type="checkbox"/> 7.1.2	<input checked="" type="checkbox"/> 7.6

**SOUND**

**Built-in Microphone**

**Microphone Port Type:** PlainTalk  
**Sound In:** stereo, 16-bit  
**Sound Out:** stereo, 16-bit

**STORAGE**

**Supports Internal CD-ROM**

**Floppy Size:** 1.44MB  
**Floppy Inject:** manual  
**Internal HD Size:** 1GB  
**Internal HD Interface:** SCSI  
**Original CD-ROM Speed:** 4x