Apple
Spec Database
System Fact Sheet

Power Computing Power 100 Tower

System

Introduced: April 1995
Discontinued: January 1996
Gestalt ID:
Form Factor: Power Computing 80
Weight (lbs.): 22
Dimensions (inches): 15 H x 7 W x 16 D

Codename:
Oder Number:
KB Article #:

Power

Max. Watts: 200
Amps:
BTU Per Hour: 684
Voltage Range: 100-240 V
Freq'y Range (Hz): 50-60 Hz
Battery Type: 3.6V lithium
☐ **Soft Power**
☐ **Monitor Power Outlet**

Ports

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: AAUI-15
Microphone Port Type: PlainTalk
☐ **Printer** ☒ **Speaker**
☐ **Modem** ☒ **Headphone**
☐ **Airport** ☐ **Remote Control**

PS/2 keyboard and mouse port

Video

Built-in Display:

VRAM Speed:	VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870[2]	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
	RAM-based	2MB						16			

Maximum Color Bit-depth[1] At:

[1] 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions
[2] The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LogicBoard

Main Processor: 601, 100 MHz
PMMU: none
FPU: non
Data Path: , 33 MHz
L1 Cache: 32K
L2 Cache: 256-512K
Secondary Processor: none
Slots: 3 NuBus, 1 PDS

Memory

Memory on Logic Board: 16MB
Minimum RAM: 16MB
Maximum RAM: 200MB
RAM Slots: 8 72-pin
Minimum RAM Speed: 80 ns
RAM Sizes: 16 MB
Install in Groups of:

Software

☐ **Speech Recognition Supported**

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler:

ROM ID:
ROM Version:
ROM Size: 4MB
AppleTalk Version:

Supported Macintosh System Software:

☐ A/UX 1.0	☐ NOS 1.11	☐ ProDOS	☐
☐ A/UX 1.11	☐ NOS 1.3	☐ GS/OS	☐
☐ A/UX 2.0	☐ NOS 2.0	☐ NeXTStep 1.x	☐
☐ A/UX 3.0.1	☐ NOS 2.1	☐ NeXTStep 2.x	☐
☐ A/UX 4.1.4	☐ LOS 7/7	☐ NeXTStep 3.x	☐
☐ A/UX 4.1.4.1	☐ DOS 3.1	☐ OpenStep	☐
☐ A/UX 4.1.5	☐ SOS 1.3	☐ <1.0	☐

Sound

☐ **Built-in Microphone**

Microphone Port Type: PlainTalk
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

Storage

☒ **Supports Internal CD-ROM**

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 540MB
Internal HD Interface: IDE
Original CD-ROM Speed: 4x

History

The Power series was Power Computing's first generation Macompatible. As faster 601 CPUs became available, Power bumped this model from 80 to 100, then to 120 MHz.

Note: n/a = information not available or not applicable

Database Last Modified On: 1/7/2003