

CENTRONICS® PRODUCT REFERENCE CHART 1975

FEATURE REFERENCE CHART

FEATURE	101	101A	101AL	101S	102A	102AL	301	306	500	501
Printing Method	Impact	Impact	Impact	Impact	Impact	Impact	Impact	Impact	Impact	Impact
Print Speed (char/sec)	165	165	165	165	330	330	165	120	120	165
Lines/Minute	60 (132 char/line 200 (20-30 char)	60 (132 char/line 200 (20-30 char)	60 (132 char/line 200 (20-30 char)	60 (132 char/line 200 (20-30 char) (for .1 in char)	125	125	70 (80 char/line 180 (10 char)	60 (80 char/line 150 (20-30 char)	40 (132 char/line 150 (20-30 char)	55 (132 char/line 180 (10 char)
Characters/Line	132	132	132	132 Std. Chars	132	132	80	80	132	132
Characters/Inch (Horizontal)	10	10	10	10	10	10	10	10	10	10
Lines/Inch (Vertical)	6 8 10	Std Opt N.A.	Std Opt N.A.	N.A. N.A. Std	Std Opt N.A.	Std Opt N.A.	Std N.A. N.A.	Std N.A. N.A.	Std N.A. N.A.	Std N.A. N.A.
6,8,10 Operator Selectable	N.A.	N.A.	N.A.	Opt	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
Paper Width	Up to 14-7/8"	Up to 14-7/8"	Up to 14-7/8"	Up to 14-7/8"	Up to 14-7/8"	Up to 14-7/8"	Up to 9½"	Up to 9½"	Up to 14-7/8"	Up to 14-7/8"
Paper Slew Rate (Inches/Sec)	4	4	4	2.5	4	4	8	4	4	8
Character Structure	5 x 7	9 x 7 Std 5 x 7 Std	9 x 7 Std 5 x 7 Std	5 x 7 (Std Char) 6 x 7 (Seg. Char)	9 x 7 Std 5 x 7 Std	9 x 7 Std 5 x 7 Std	5 x 7 Std 9 x 7 Opt	5 x 7 Std 9 x 7 Opt	5 x 7 Std 9 x 7 Opt	5 x 7 Std 9 x 7 Opt
Character Set	64-ASCII	64-ASCII (Std) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)	64-ASCII & 64 or 128 Segment	64-ASCII (STD) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)	64-ASCII (Std) Up to 128 (Opt)
Data Input	7-Bit	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)	8-Bit (Std)	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)	7-Bit (Std) 8-Bit (Opt)
Character Buffer	132	132	132	132	132	132	80	80	132	132
Serial/Communications Interfaces	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
Interface Adapter	Std	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Electronic Circuitry	TTL	TTL	LSI	TTL	TTL	LSI	LSI	LSI	LSI	LSI
2-Channel VFU	Std	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Auto Motor Control	Opt	Opt	Opt	Opt	Std	Std	Opt	Opt	Opt	Opt
Audio Alarm	N.A.	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Single Character Elongation	N.A.	Opt	Opt	N.A.	N.A.	N.A.	Opt	Opt	Opt	Opt
Bottom of Form	Opt	Opt	N.A.	Opt	N.A.	N.A.	Opt	N.A.	N.A.	Opt
Elapsed Time Indicator	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt

Std - Standard
Opt - Optional
N.A. - Not Available

11/16/75

CENTRONICS® PRODUCT REFERENCE CHART 1975 (Cont.)

FEATURE	101	101A	101AL	101S	102A	102AL	301	306	500	501
Paper Runaway Inhibit	N.A.	Std	Std	Std	Std	Std	Std	Std	Std	Std
Remote Select/Deselect	N.A.	Std	Std	Std	Std	Std	Std	Std	Std	Std
Switch/Indicators:										
On/OFF	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Select	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Forms Override	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Top of Form	Std	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Line Feed	N.A.	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Paper Out	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Power Input: 115VAC [±] 10%, 60Hz	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
230VAC [±] 10%, 50Hz	Opt	Std	Std	Std	Std	Std	Opt	Opt	Opt	Opt
Multi Voltage	Opt	Std	Std	Std	Std	Std	Std	N.A.	Std	Std
Dimensions	11½" (H) 20" D 27-3/4" (W)	11½" (H) 20" D 27-3/4" (W)	11½" (H) 20" D 27-3/4" (W)	11½" (H) 20" D 27-3/4" (W)	11½" (H) 20" D 27-3/4" (W)	11½" (H) 20" D 27-3/4" (W)	12" (H) 19" (D) 23" (W)	12" (H) 19" (D) 23" (W)	13-3/4" (H) 21½" (D) 32" (W)	13-3/4" (H) 21½" (D) 32" (W)
Weight (lbs)	118	118	118	118	118	118	66	66	98	98
Temperature - Operating	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F	40° to 100°F
- Storage	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F	-40° to 160°F
Humidity - Operating	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)	5% to 90% (no condensation)
- Storage	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%	0% to 95%

Std - Standard
Opt - Optional
N.A. - Not Available

UP 0066