

CUSTOMER SERVICE BULLETIN

Radio Shack® CUSTOMER SERVICE BULLETIN

400 Atrium—One Tandy Center, Fort Worth, Texas 76102

| | |
|---------------------|------------------------|
| Bulletin No. | 1559-Ø6 (Correction 1) |
| Description | Manuf. Inv. Control |
| Model | Model I |
| Stock No. | 26-1559 All Prior 3.Ø |
| Date | March 17, 1982 |
| Page 1 of | 2 |

Problem

It has been found that a problem can occur in Finish Good Maintenance which causes the machine to lock up when updating the files if more than 3ØØ raw materials are in the finished good.

Solution

The problem is corrected by following the steps listed below.

1. Backup the diskette(s) and make the changes on the Backup copy of the program.
2. In BASIC load the program by typing LOAD"FGMAINT"
3. Make the following corrections:

CHANGES (Retype the line or refer to the Edit section of the owners manual)

Old Line:4 DEFINFI-K,F,R,W-Z:DIMW,WS,WL,WD,PT,X,Y,F1\$(8,5,4),F(7),IX\$(128),FR(1,61Ø),J(3),FG\$(25,3),FG(25),P\$(63),Q\$(63)

New Line:4 DEFINFI-K,F,R,W-Z:DIMW,WS,WL,WD,PT,X,Y,F1\$(8,5,4),F(7),IX\$(128),FR(1,61Ø),J(4),FG\$(25,3),FG(25),P\$(63),Q\$(63)

Old Line:851Ø J(1)=VARPTR(IX(1)):J(2)=VARPTR(FR(Ø,1)):J(3)=RQ

New Line:851Ø J(1)=VARPTR(IX(1)):J(2)=VARPTR(FR(Ø,1)):J(3)=RQ:J(4)=HR

Old Line:1ØØ9Ø FIELD1,146ASUS\$:GET1,285:SR\$=US\$:RETURN

New Line:1ØØ9Ø FIELD1,149ASUS\$:GET1,285:SR\$=US\$:RETURN

CUSTOMER SERVICE BULLETIN

Subject MANUFACTURING INVENTORY CONTROL 1559-06 Page 2 Of 2

4. Type SAVE"FGMAINT"
5. Type LOAD"MFGINIT" from the Initialization Disk
6. Make the following changes:

Old Line:16000 SR\$=STRING\$(146,32):FORX=1TO146:READY:MID\$(SR\$,X,1)=CHR\$(Y):
NEXT

New Line:16000 SR\$=STRING\$(149,32):FORX=1TO149:READY:MID\$(SR\$,X,1)=CHR\$(Y):NEXT

Old Line:16010 FIELD1,146ASQSS:LSETQSS=SR\$:PUT1,285:SR\$="":RETURN

New Line:16010 FIELD1,149ASQSS:LSETQSS=SR\$:PUT1,285:SR\$="":RETURN

REPLACE LINES 16030 THROUGH 16120 WITH THESE LINES:

```
16030 DATA 205,127,10,94,35,86,213,221,225,35,94,35,86,213,253
16040 DATA 225,35,94,35,86,35,78,35,70,3,19,197,213,209,193
16050 DATA 11,121,176,200,197,221,35,221,35,213,253,229,225,1,4
16060 DATA 0,27,122,179,40,67,213,221,126,0,190,35,32,69,221
16070 DATA 126,1,190,32,63,209,43,94,35,86,213,35,94,35,86
16080 DATA 213,229,209,43,62,4,245,197,213,229,237,184,225,209,193
16090 DATA 241,61,32,243,209,253,114,3,253,115,2,209,253,114,1
16100 DATA 253,115,0,253,229,225,17,4,0,25,229,253,225,209,27
16110 DATA 122,179,213,32,159,209,193,201,17,3,0,25,229,197,225
16120 DATA 19,25,229,193,225,209,27,122,179,40,138,213,24,159
```

4. Type SAVE"MFGINIT" to save the changes in the program.
5. At TRSDOS Ready, make a backup copy of the corrected diskette.